

**GEOTECHNICAL RECONNAISSANCE
TORREY PINES ROAD REALIGNMENT
SAN DIEGO, CALIFORNIA**

PREPARED FOR:

Tran Consulting Engineers
4444 El Cajon Boulevard, Suite 15
San Diego, California 92115

PREPARED BY:

Ninyo & Moore
Geotechnical and Environmental Sciences Consultants
5710 Ruffin Road
San Diego, California 92123

June 4, 2010
Project No. 106843001

June 4, 2010
Project No. 106843001

Mr. John Austin
Tran Consulting Engineers
4444 El Cajon Boulevard, Suite 15
San Diego, California 92115

Subject: Geotechnical Reconnaissance
Torrey Pines Road Realignment
San Diego, California


Dear Mr. Austin:


Transmitted herein are the results of Ninyo & Moore's geotechnical reconnaissance study for the City's proposed realignment of Torrey Pines Road. This study was conducted in accordance with your request and included review and analysis of available geologic and geotechnical background data, and a geologic reconnaissance of the project site area.


We appreciate the opportunity to be of service.


Respectfully submitted,
NINYO & MOORE


Francis O. Moreland, C.E.G. 2071
Senior Geologist




Randal L. Irwin, C.E.G. 1521
Chief Engineering Geologist


Gregory T. Farrand, C.E.G. 1087
Principal Geologist



FOM/RI/GTF/gg

Distribution: (5) Addressee

TABLE OF CONTENTS

	<u>Page</u>
1. INTRODUCTION	1
2. SCOPE OF SERVICES	1
3. PROJECT AND SITE DESCRIPTION	1
4. GEOLOGY	2
4.1. Regional Geologic Setting	2
4.2. Site Geology	3
4.2.1. Artificial Fill	3
4.2.2. Alluvium	3
4.2.3. Old Paralic Deposits (Bay Point Formation)	3
4.2.4. Cabrillo Formation	4
4.2.5. Point Loma Formation	4
4.2.6. Groundwater	4
4.3. Faulting and Seismicity	4
4.3.1. Strong Ground Motion	5
4.3.2. Ground Surface Rupture	5
4.3.3. Liquefaction and Seismically Induced Settlement	5
4.3.4. Tsunamis	6
4.4. Landsliding	6
4.5. Geologic Hazards Map	6
5. CONCLUSIONS	7
6. PRELIMINARY RECOMMENDATIONS	7
7. LIMITATIONS	8
8. REFERENCES	9

Figures

Figure 1 – Site Location Map

Figure 2 – Site Plan

Figure 3 – Fault Location Map

Figure 4 – Geologic Map

Figure 5 – Geologic Hazards Map

1. INTRODUCTION

In accordance with your request, Ninyo & Moore has performed a geotechnical reconnaissance study of the project site. This report presents our preliminary findings and conclusions pertaining to the City's proposed realignment of Torrey Pines Road. The purpose of this study was to evaluate geologic and geotechnical conditions using available geologic and geotechnical data and to provide a geotechnical reconnaissance report, which we understand will be utilized as part of a study for the subject project. Subsurface exploration and laboratory testing of materials were not included in the scope of this reconnaissance study.

2. SCOPE OF SERVICES

Ninyo & Moore's scope of services has included review of background materials and geologic reconnaissance of the site area. Specifically, we have performed the following tasks:

- Review of pertinent, available geotechnical literature including topographic maps, geologic maps, stereoscopic aerial photographs, and geotechnical and geologic reports. Documents reviewed for our site study are listed in the References section of this report.
- Geologic reconnaissance of the project study area by a California-certified engineering geologist from our firm.
- Compilation and analysis of the data obtained.
- Preparation of this report presenting our preliminary findings, conclusions, and recommendations.

3. PROJECT AND SITE DESCRIPTION

The site is located in the residential community of La Jolla in northwestern San Diego (Figure 1). The project extends along Torrey Pines Road from Prospect Place on the southwest to Calle Juela (near La Jolla Shores Drive) on the northeast. Elevations across the alignment range from a high of approximately 155 feet above mean sea level (MSL) at Prospect Place to a low of approximately 55 feet above MSL at the Calle Juela.

The purpose of the project is to provide continuous sidewalks on both sides of Torrey Pines Road. Retaining walls, soil nail walls, durawalls or other measures are planned along portions of the

alignment west of Amalfi Street, and between Hillside Drive and East Roseland Drive. Relatively minor vertical and lateral changes in the roadbed (less than 3 feet) will be made to Torrey Pines Road.

4. GEOLOGY

The following sections present our findings relative to regional geology, site geology, groundwater, faulting, and seismicity.

4.1. Regional Geologic Setting

The project study area is situated in the western portion of the Peninsular Ranges geomorphic province of southern California. This geomorphic province encompasses an area that extends roughly 125 miles from the Transverse Ranges and the Los Angeles Basin, south to the Mexican border, and beyond another 795 miles to the tip of Baja California (Norris and Webb, 1990; Harden, 1998). The geomorphic province varies in width from 30 to 100 miles, most of which is characterized by northwest trending mountain ranges separated by subparallel fault zones. In general, the Peninsular Ranges are underlain by Jurassic- and Cretaceous-age metavolcanic and metasedimentary rocks and by Cretaceous-age igneous rocks of the southern California batholith. The westernmost portion of the province in San Diego County generally consists of Upper Cretaceous-, Tertiary-, and Quaternary-age sedimentary rocks.

The Peninsular Ranges are traversed by several major active faults (Figure 3). The Whittier-Elsinore, San Jacinto, and the San Andreas faults are major active fault systems located northeast of the site and the Agua Blanca-Coronado Bank and San Clemente faults are active faults located to the west-southwest. The nearby Rose Canyon fault zone, which crosses the eastern portion of the site, has also been recognized as active by the State of California. Major tectonic activity associated with these and other faults within this regional tectonic framework is right-lateral strike-slip movement. These faults, as well as other faults in the region, have the potential for generating strong ground motions at the project site. Further discussion of faulting relative to the site is provided in the Faulting and Seismicity section of this report.

4.2. Site Geology

Based on our literature review of published geologic maps and available geologic reports and our site reconnaissance, the project vicinity is underlain by surficial soils consisting of artificial fill underlain by young alluvium, old paralic deposits (formerly designated Bay Point Formation), the Cabrillo Formation, and the Point Loma Formation. A geologic map is provided as Figure 4. A brief description of these units, as described in the cited literature or as observed on the site, is presented below.

4.2.1. Artificial Fill

Artificial fill soils are present beneath the roadway and within utility trenches. The fill soils may have been derived from nearby alluvial and formational materials or imported soils and are expected to range in composition from loose to medium dense, silty sand to sandy silt with scattered gravel and cobbles.

4.2.2. Alluvium

Alluvial soils are expected to underlie the eastern end of the project alignment. These soils are generally expected to be composed of soft to firm silt and clay to loose to medium dense silty sand and clayey sand, possibly with scattered gravel and cobbles.

4.2.3. Old Paralic Deposits (Bay Point Formation)

Pleistocene-age old paralic deposits are mapped on the west side of Torrey Pines Road. The old paralic deposits in the vicinity of the site generally consist of a brown to reddish brown, weakly cemented, silty fine to coarse grained sandstone.

4.2.4. Cabrillo Formation

The Cretaceous-age Cabrillo Formation is mapped at the western end of the project alignment. The Cabrillo Formation in the vicinity of the site generally consists of massive medium-grained sandstone and cobble conglomerate.

4.2.5. Point Loma Formation

The Cretaceous-age Point Loma Formation is mapped on the east side of Torrey Pines Road in the central portion of the alignment. The Point Loma Formation in the vicinity of the site generally consists of interbedded fine-grained dusky yellow sandstone and olive-gray clay shale. Relative weak clay-rich strata such as sheared bedding surfaces (bedding plane faults) and fractures are common in the Point Loma Formation in this region.

4.2.6. Groundwater

The depth to groundwater in the vicinity of the project is expected to be located roughly at or near sea level. Groundwater levels are expected to fluctuate due to seasonal variations, tidal changes, and other factors.

4.3. Faulting and Seismicity

The project site, like the rest of southern California, is considered to be located in a seismically active area. The western portion of the alignment is located within a State of California Earthquake Fault (Alquist-Priolo Special Studies) Zone. In addition, multiple known, inferred, and concealed inactive or potentially active faults are located in the site vicinity. The approximate locations are shown on Figure 5.

The Rose Canyon fault zone is a part of a more extensive fault zone that includes the Offshore Zone of Deformation and the Newport-Inglewood fault to the north, and several possible extensions southward, both onshore and offshore (Treiman, 1993). The Rose Canyon fault zone consists predominantly of right-lateral strike-slip faults that extend south-southeast through the San Diego metropolitan area. Various fault strands display strike-slip, normal, oblique, or reverse components of displacement (Treiman, 1993). South of downtown San Diego, the Rose Canyon fault breaks into several subparallel splays that underlie much of central and southern San Diego Bay. Portions of the Rose Canyon fault zone in the Mount Soledad, La Jolla, Rose Canyon, Mission Bay, and downtown areas of San Diego have been recognized by the State of California as Earthquake Fault Special Studies Zones

(California Geological Survey [CGS], 2001). The Coronado Bank fault zone, located approximately 13 miles southwest of the project and the Elsinore fault zone, located approximately 40 miles northeast of the site, are also considered to be active.

4.3.1. Strong Ground Motion

The 2007 California Building Code (CBC) recommends that the design of structures be based on the horizontal peak ground acceleration (PGA) having a 2 percent probability of exceedance in 50 years, which is defined as the Maximum Considered Earthquake (MCE). The statistical return period for PGA_{MCE} is approximately 2,475 years. Based on our review of subsurface data, the project site corresponds to a Site Class D. The site modified PGA_{MCE} was estimated to be 0.68g using the United States Geological Survey (USGS) (USGS, 2010) ground motion calculator (web-based). The site modified design PGA was estimated to be 0.45g. These estimates of ground motion do not include near-source factors that may be applicable to the design of structures on site.

4.3.2. Ground Surface Rupture

Based on our review of the referenced literature and our site reconnaissance, the active Rose Canyon fault is known to cross the project site. Therefore, the potential for ground rupture due to faulting at the site is high. Lurching or cracking of the ground surface as a result of nearby seismic events is also possible.

4.3.3. Liquefaction and Seismically Induced Settlement

Liquefaction of cohesionless soils can be caused by strong vibratory motion due to earthquakes. Research and historical data indicate that loose granular soils and non-plastic silts that are saturated by a relatively shallow groundwater table are susceptible to liquefaction. The eastern end of the alignment is mapped as being underlain by alluvium. If groundwater is present within the alluvium, this portion of the alignment may be subject to liquefaction and seismically induced settlement during a nearby seismic event. Based on the competent nature of the underlying formational materials and lack

of shallow groundwater beneath remaining portions of the alignment, it is our opinion that the potential for liquefaction and seismically induced settlement to occur is not a design consideration.

4.3.4. Tsunamis

Tsunamis are long seismic sea waves (long compared to ocean depth) generated by sudden movements of the sea floor caused by submarine earthquakes, landslides, or volcanic activity. Due to the orientation of California's coastline with regard to Pacific Ocean tsunami generating areas and our relatively wide continental shelf, wave heights from historic tsunamis in the San Diego Region have generally been within the normal tidal range. Based on these factors, there is little potential for catastrophic tsunamis in San Diego, however some coastal flooding and damage may occur. Based on its elevation, the potential for damage due to tsunamis at the site is not a design consideration.

4.4. Landsliding

Based on our review of published geologic maps and stereoscopic aerial photographs, as well as our site reconnaissance, no landslides or indications of deep-seated slope instability were observed underlying the project site. However, numerous large landslides have been mapped approximately 1,000 feet south of the alignment.

4.5. Geologic Hazards Map

We have included as Figure 5 a portion of Sheet 29 of the City of San Diego Seismic Safety Study that includes the site. The hazard map indicates the mapped location of known or suspected faults and landslides and areas of potentially unfavorable geologic structure relative to slope stability. The hazard map indicates that the Alquist-Priolo earthquake fault zone for the Active Rose Canyon fault crosses the eastern portion of the alignment. The active strand of the Rose Canyon fault crosses the alignment at approximately Roseland Drive. Multiple strands of the Rose Canyon fault which are classified as potentially active or inactive cross the western portion of the alignment.

5. CONCLUSIONS

The following sections discuss site-specific geologic and geotechnical issues.

- The active Rose Canyon fault crosses the eastern portion of the alignment. There is therefore, a high potential for ground rupture at the alignment in the event of a nearby seismic event.
- Based on our seismic hazard analysis, there is a potential for high ground accelerations at the site as a result of nearby earthquakes.
- Landslides or indications of deep-seated slope instability were not observed underlying the project site but are mapped in areas to the south of the project site.
- Potentially compressible fill soils may be encountered in some areas under the existing roadways. In addition, unknown thicknesses of potentially compressible alluvium may exist at the eastern end of the alignment. The presence of compressible soils could potentially impact the design of improvements or other related structures. The nature and extent of potentially compressible subsurface soils should be further evaluated by a subsurface geotechnical evaluation.
- Potentially liquefiable alluvial soils are present beneath the eastern end of the alignment.
- It is our understanding that a soil nail retaining wall with a dura-block facing is under consideration for the project. This retaining wall type would be feasible at the site.
- In general, the soils in the area should be excavatable with standard heavy-duty excavation equipment. The engineering properties of the subsurface soils should be further evaluated by a subsurface geotechnical evaluation.

6. PRELIMINARY RECOMMENDATIONS

We recommend that a comprehensive geotechnical evaluation, including subsurface exploration and laboratory testing, be conducted prior to design and construction. The purpose of the subsurface evaluation would be to further evaluate the subsurface conditions and to provide information pertaining to the engineering characteristics of earth materials at the project site. From these data, a geotechnical design report would be prepared presenting recommendations pertaining to geotechnical aspects of the design and construction of the project.

7. LIMITATIONS

The field evaluation and geotechnical analyses presented in this report have been conducted in accordance with current engineering practice and the standard of care exercised by reputable geotechnical consultants performing similar tasks in this area. No warranty, implied or expressed, is made regarding the conclusions, recommendations, and professional opinions expressed in this report. Variations may exist and conditions not observed or described in this report may be encountered. Our preliminary conclusions and recommendations are based on an analysis of the observed conditions and the referenced background information.

The purpose of this study was to evaluate geologic and geotechnical conditions within the project site and to provide a geotechnical reconnaissance report to assist in the preliminary design of the project. A comprehensive geotechnical evaluation, including subsurface exploration and laboratory testing, should be performed prior to design and construction of structural improvements.

8. REFERENCES

- Anderson, J.G., Rockwell, T.K., and Agnew, D.C., 1989, Past and Possible Future Earthquakes of Significance to the San Diego Region: Earthquake Spectra, Volume 5, No. 2.
- California Building Standards Commission, 2007, *California Building Code*, Title 24, Part 2, Volumes 1 and 2.
- California Geological Survey (CGS), 2001, State of California, Special Studies Zones, La Jolla Quadrangle: effective November 1, 2001, scale 1:24,000.
- California Geological Survey (CGS), 2003, Probabilistic Seismic Hazard Assessment Maps (PSHA), World Wide Web, <http://www.consrv.ca.gov/cgs/rghm/psha/index.htm>.
- City of San Diego, 1963, Topographic Survey, Sheet 246-1683, Scale 1" = 200'.
- City of San Diego, 1963, Topographic Survey, Sheet 246-1689, Scale 1" = 200'.
- City of San Diego, 1979, Topographic Survey (Orthotopographic), Sheet 246-1683, Scale 1" = 200'.
- City of San Diego, 1979, Topographic Survey (Orthotopographic), Sheet 246-1689, Scale 1" = 200'.
- City of San Diego, 1979, Topographic Survey, Sheet 250-1689, Scale 1" = 200'.
- City of San Diego, 1995, Seismic Safety Study, Sheet 29, scale 1" = 800'.
- Geotechnics, Inc., 2000, Report of Geotechnical Evaluation, Torrey Pines Road Slope Repair Between Little Street and Roseland Drive, La Jolla, California, Work Order No. 526740: dated April 20.
- Harden, D.R., 1998, *California Geology*: Prentice Hall, Inc.
- Jennings, C.W., 1994, Fault Activity Map of California and Adjacent Areas: California Geological Survey, California Geologic Data Map No. 6, scale 1:750,000.
- Kennedy, M.P., 1975, Geology of the La Jolla Quadrangle, San Diego County, California Geological Survey, Bulletin 200, Scale 1:24,000.
- Kennedy, M.P., and Tan, S. S., 2008, Geologic Map of the San Diego 30' X 60' Quadrangle, California Regional Geologic Map Series, 1:100,000 Scale, Map No. 3, Sheet 1 of 2.
- Norris, R.M., and Webb, R.W., 1990, *Geology of California*: John Wiley & Sons, Inc.
- Rockwell, T.K., Lindvall, S.C. Haraden, C.C., Hirabayashi, C.K., and Baker, E., 1991, Minimum Holocene Slip Rate for the Rose Canyon Fault in San Diego, California in Abbott, P.L. and Elliott, W.J., eds., Environment Perils, San Diego Region: San Diego Association of Geologists.

Tan, S.S., 1995, Landslide Hazards in the Southern Part of the San Diego Metropolitan Area, San Diego County, California, Plate A: Open File Report 95-03.

Treiman, J.A., 1993, Rose Canyon Fault Zone, Southern California: California Geological Survey.

United States Geological Survey, 2010 Ground Motion Parameter Calculator v. 5.0.9a, World Wide Web, <http://earthquake.usgs.gov/research/hazmaps/design/>.

AERIAL PHOTOGRAPHS				
Source	Date	Flight	Numbers	Scale
United States Department of Agriculture	5/2/53 & 4/11/53	AXN-7M/8M	189 & 190	1:20,000



REFERENCE: 2005 THOMAS GUIDE FOR SAN DIEGO COUNTY, STREET GUIDE AND DIRECTORY,



Map © Rand McNally, R.L.07-S-129

Ninyo & Moore

SITE LOCATION MAP

FIGURE

PROJECT NO.




DATE

TORREY PINES ROAD REALIGNMENT
SAN DIEGO, CALIFORNIA


1

106843001

6/10




SOURCE: TRAN CONSULTING ENGINEERS, 2010



LEGEND	
	PROPERTY ENCROACHMENT
	RETAINING WALL ENCROACHMENT
	RETAINING WALL
	POTENTIAL RETAINING WALL
	ABOVE-GROUND UTILITY SIDEWALK CONFLICT


		SITE PLAN TORREY PINES ROAD REALIGNMENT SAN DIEGO, CALIFORNIA	FIGURE
			2
PROJECT NO.	DATE		
106843001	6/10		

NOTE: ALL DIMENSIONS, DIRECTIONS AND LOCATIONS ARE APPROXIMATE.



LEGEND

Qya	YOUNG ALLUVIAL FLOODPLAIN DEPOSITS		FAULT - SOLID WHERE ACCURATELY LOCATED, DASHED WHERE APPROXIMATE, DOTTED WHERE CONCEALED. U = UPTHROWN BLOCK, D = DOWNTHROWN BLOCK. ARROW AND NUMBER INDICATE DIRECTION AND ANGLE OF DIP OF FAULT PLANE
Qop	OLD PARALIC DEPOSITS, UNDIVIDED		ANTICLINE - SOLID WHERE ACCURATELY LOCATED, DASHED WHERE APPROXIMATE, DOTTED WHERE CONCEALED. ARROW INDICATES DIRECTION OF AXIAL PLUNGE
Qop6	OLD PARALIC DEPOSITS, UNIT 6		SYNCLINE - SOLID WHERE ACCURATELY LOCATED, DOTTED WHERE CONCEALED. ARROW INDICATES DIRECTION OF AXIAL PLUNGE
Qvop10a	VERY OLD PARALIC DEPOSITS, UNIT 10a		LANDSLIDE - ARROWS INDICATE PRINCIPAL DIRECTION OF MOVEMENT, QUERIED WHERE EXISTENCE IS QUESTIONABLE
Qvop11	VERY OLD PARALIC DEPOSITS, UNIT 11		
Ta	ARDATH SHALE		
	STRIKE AND DIP OF INCLINED SEDIMENTARY BEDS		



















NOTE: ALL DIMENSIONS, DIRECTIONS AND LOCATIONS ARE APPROXIMATE. REFERENCE: KENNEDY, M.P., AND TAN, S.S., 2008, GEOLOGIC MAP OF THE SAN DIEGO 30' X 60' QUADRANGLE, CALIFORNIA.

fig4 106843001 geol.cdr

		GEOLOGIC MAP TORREY PINES ROAD REALIGNMENT SAN DIEGO, CALIFORNIA	FIGURE
			4
PROJECT NO.	DATE		
106843001	6/10		

LEGEND

- | | | | |
|---|--|---|--|
|  | ACTIVE FAULT ZONE, ALQUIST-PRIOLO EARTHQUAKE ZONE |  | OTHER LEVEL AREAS, GENTLY SLOPING TO STEEP TERRAIN, FAVORABLE GEOLOGIC STRUCTURE, LOW RISK |
|  | POTENTIALLY ACTIVE, INACTIVE, PRESUMED INACTIVE, OR ACTIVITY UNKNOWN, FAULT ZONE |  | LEVEL OR SLOPING TERRAIN, UNFAVORABLE GEOLOGIC STRUCTURE, LOW TO MODERATE RISK |
|  | CONFIRMED, KNOWN, OR HIGHLY SUSPECTED LANDSLIDES |  | WATER (BAYS AND LAKES) |
|  | POSSIBLE OR CONJECTURED LANDSLIDE |  | FAULT |
|  | OTAY, SWEETWATER, AND OTHER SLIDE-PRONE FORMATIONS |  | INFERRED FAULT |
|  | GENERALLY UNSTABLE COASTAL BLUFFS, UNFAVORABLE JOINTING, LOCAL HIGH EROSION |  | CONCEALED FAULT |
|  | GENERALLY UNSTABLE COASTAL BLUFFS, BROAD BEACH AREAS, DEVELOPED HARBOR |  | SHEAR ZONE |



NOTE: ALL DIMENSIONS, DIRECTIONS AND LOCATIONS ARE APPROXIMATE. REFERENCE: CITY OF SAN DIEGO SEISMIC SAFETY STUDY, 2008.

Ninyo & Moore

GEOLOGIC HAZARDS MAP

FIGURE

5

PROJECT NO.	DATE
106843001	6/10

TORREY PINES ROAD REALIGNMENT
SAN DIEGO, CALIFORNIA

fig4 106843001 geo haz.cdr