

- The Checklist is required only for projects subject to CEQA review.²
- ❖ If required, the Checklist must be included in the project submittal package. Application submittal procedures can be found in Chapter 11: Land Development Procedures of the City's Municipal Code.
- The requirements in the Checklist will be included in the project's conditions of approval.
- The applicant must provide an explanation of how the proposed project will implement the requirements described herein to the satisfaction of the Planning Department.

Application Information						
Contact Information						
Project No./Name:						
Property Address:						
Applicant Name/Co.:						
Contact Phone:						
Was a consultant retained to complete this checklist?	☐ Yes ☐ No If Yes, complete the following					
Consultant Name:	Contact Phone:					
Company Name:	Contact Email:					
Project Information						
1. What is the size of the project (acres)?						
2. Identify all applicable proposed land uses:						
\square Residential (indicate # of single-family units):						
\square Residential (indicate # of multi-family units):						
☐ Commercial (total square footage):						
☐ Industrial (total square footage):						
☐ Other (describe):						
3. Is the project or a portion of the project located in a Transit Priority Area?	□ Yes □ No					
4. Provide a brief description of the project proposed:						

² Certain projects seeking ministerial approval may be required to complete the Checklist. For example, projects in a Community Plan Implementation Overlay Zone may be required to use the Checklist to qualify for ministerial level review. See Supplemental Development Regulations in the project's community plan to determine applicability.



CAP CONSISTENCY CHECKLIST QUESTIONS

Step 1: Land Use Consistency

The first step in determining CAP consistency for discretionary development projects is to assess the project's consistency with the growth projections used in the development of the CAP. This section allows the City to determine a project's consistency with the land use assumptions used in the CAP.

Step 1: Land Use Consistency		
Checklist Item (Check the appropriate box and provide explanation and supporting documentation for your answer)	Yes	No
 A. Is the proposed project consistent with the existing General Plan and Community Plan land use and zoning designations?;³ OR, B. If the proposed project is not consistent with the existing land use plan and zoning designations, and includes a land use plan and/or zoning designation amendment, would the proposed amendment result in an increased density within a Transit Priority Area (TPA)⁴ and implement CAP Strategy 3 actions, as determined in Step 3 to the satisfaction of the Development Services Department?; OR, C. If the proposed project is not consistent with the existing land use plan and zoning designations, does the project include a land use plan and/or zoning designation amendment that would result in an equivalent or less GHG-intensive project when compared to the existing designations? 		
If " Yes ," proceed to Step 2 of the Checklist. For question B above, complete Step 3. For question C above, provide missions under both existing and proposed designation(s) for comparison. Compare the maximum buildout of and the maximum buildout of the proposed designation. If " No ," in accordance with the City's Significance Determination Thresholds, the project's GHG impact is significantly nonetheless incorporate each of the measures identified in Step 2 to mitigate cumulative GHG emissions impartmentally in the comparison of the measure is infeasible in accordance with CEQA Guidelines Section 15091. Proceed and comparison of the measure is infeasible in accordance with CEQA Guidelines Section 15091.	of the existing of the existin	designation at must decision

³ This question may also be answered in the affirmative if the project is consistent with SANDAG Series 12 growth projections, which were used to determine the CAP projections, as determined by the Planning Department.

⁴ This category applies to all projects that answered in the affirmative to question 3 on the previous page: Is the project or a portion of the project located in a transit priority area.

Step 2: CAP Strategies Consistency

The second step of the CAP consistency review is to review and evaluate a project's consistency with the applicable strategies and actions of the CAP. Step 2 only applies to development projects that involve permits that would require a certificate of occupancy from the Building Official or projects comprised of one and two family dwellings or townhouses as defined in the California Residential Code and their accessory structures. All other development projects that would not require a certificate of occupancy from the Building Official shall implement Best Management Practices for construction activities as set forth in the Greenbook (for public projects).

Step 2: CAP Strategies Consistency			
Checklist Item (Check the appropriate box and provide explanation for your answer)	Yes	No	N/A
Strategy 1: Energy & Water Efficient Buildings			
1. Cool/Green Roofs.			
 Would the project include roofing materials with a minimum 3-year aged solar reflection and thermal emittance or solar reflection index equal to or greater than the values specified in the voluntary measures under <u>California Green Building Standards Code</u> (Attachment A)?; <u>OR</u> Would the project roof construction have a thermal mass over the roof membrane, including areas of vegetated (green) roofs, weighing at least 25 pounds per square foot as specified in the voluntary measures under <u>California</u> 			
 Green Building Standards Code?; OR Would the project include a combination of the above two options? 			
Check "N/A" only if the project does not include a roof component.			

Actions that are not subject to Step 2 would include, for example: 1) discretionary map actions that do not propose specific development, 2) permits allowing wireless communication facilities, 3) special events permits, 4) use permits or other permits that do not result in the expansion or enlargement of a building (e.g., decks, garages, etc.), and 5) non-building infrastructure projects such as roads and pipelines. Because such actions would not result in new occupancy buildings from which GHG emissions reductions could be achieved, the items contained in Step 2 would not be applicable.

2.	Plumbing fixtures and fittings		_
	With respect to plumbing fixtures or fittings provided as part of the project, would those low-flow fixtures/appliances be consistent with each of the following:		
	Residential buildings:		
	Kitchen faucets: maximum flow rate not to exceed 1.5 gallons per minute at 60		
	psi; • Standard dishwashers: 4.25 gallons per cycle;		
	 Compact dishwashers: 3.5 gallons per cycle; and 		
	 Clothes washers: water factor of 6 gallons per cubic feet of drum capacity? 		
	Nonresidential buildings:		
	 Plumbing fixtures and fittings that do not exceed the maximum flow rate specified in <u>Table A5.303.2.3.1 (voluntary measures) of the California Green</u> <u>Building Standards Code</u> (See Attachment A); and 		
	Appliances and fixtures for commercial applications that meet the provisions of		
	Section A5.303.3 (voluntary measures) of the California Green Building Standards Code (See Attachment A)?		
	Check "N/A" only if the project does not include any plumbing fixtures or fittings.		

⁶ Non-portable bicycle corrals within 600 feet of project frontage can be counted towards the project's bicycle parking requirements.

If the project includes nonresidential development that would accommodate over 10 tenant occupants (employees), would the project include changing/shower facilities in accordance with the voluntary measures under the California Green Building Standards Code as shown in the table below? Number of Tenant Occupants (Employees) Shower/Changing Facilities Required Two-Tier (12" X 15" X 72") Personal Effects Lockers Required D-10	Shower fo	acilities					
Occupants (Employees) Occupants (Incomplete Required) Incomplete Required (Incomplete Required) Occupants (Incomplete Required) Incomplete Required (Incomplete Required) Inco	tenant occup accordance	pants (employees), with the voluntary n	would the project inclune as ures under the Ca	de changing/shower f	acilities in		
11-50		Occupants		72") Personal Effects			
51-100		0-10	0	0			
101-200		11-50	1 shower stall	2			
Over 200 1 shower stall plus 1 additional shower stall for each 200 additional tenant-occupants 1 two-tier locker plus 1 two-tier locker for each 50 additional tenant-occupants Check "N/A" only if the project is a residential project, or if it does not include nonresidential development that would accommodate over 10 tenant occupants		51-100	1 shower stall	3			
Over 200 additional shower stall for each 200 additional tenant-occupants Check "N/A" only if the project is a residential project, or if it does not include nonresidential development that would accommodate over 10 tenant occupants		101-200	1 shower stall	4			
nonresidential development that would accommodate over 10 tenant occupants		Over 200	additional shower stall for each 200 additional	two-tier locker for each 50 additional tenant-			
	nonresider	ntial development th					

	Number of Required Parking Spaces	Number of Designated Parking Spaces			
	0-9	0	-		
	10-25	2	7		
	26-50	4	7		
	51-75	6	7		
	76-100	9	7		
	101-150	11	7		
	151-200	18	7		
	201 and over	At least 10% of total			
Juition to			a alcoda		
	A" only if the project is a residential use in a TPA.	ential project, or if it does not ir	nciude		

Transportation Demand Management Program		
If the project would accommodate over 50 tenant-occupants (employees), would it include a transportation demand management program that would be applicable to existing tenants and future tenants that includes:		
At least one of the following components:		
Parking cash out program		
 Parking management plan that includes charging employees market-rate for single-occupancy vehicle parking and providing reserved, discounted, or free spaces for registered carpools or vanpools 		
 Unbundled parking whereby parking spaces would be leased or sold separately from the rental or purchase fees for the development for the life of the development 		
And at least three of the following components:		
 Commitment to maintaining an employer network in the SANDAG iCommute program and promoting its RideMatcher service to tenants/employees 		
On-site carsharing vehicle(s) or bikesharing		
Flexible or alternative work hours		
Telework program		
Transit, carpool, and vanpool subsidies		
 Pre-tax deduction for transit or vanpool fares and bicycle commute costs 		
 Access to services that reduce the need to drive, such as cafes, commercial stores, banks, post offices, restaurants, gyms, or childcare, either onsite or within 1,320 feet (1/4 mile) of the structure/use? 		
Check "N/A" only if the project is a residential project or if it would not accommodate over 50 tenant-occupants (employees).		

Step 3: Project CAP Conformance Evaluation (if applicable)

The third step of the CAP consistency review only applies if Step 1 is answered in the affirmative under option B. The purpose of this step is to determine whether a project that is located in a TPA but that includes a land use plan and/or zoning designation amendment is nevertheless consistent with the assumptions in the CAP because it would implement CAP Strategy 3 actions. In general, a project that would result in a reduction in density inside a TPA would not be consistent with Strategy 3. The following questions must each be answered in the affirmative and fully explained.

1. Would the proposed project implement the General Plan's City of Villages strategy in an identified Transit Priority Area (TPA) that will result in an increase in the capacity for transit-supportive residential and/or employment densities?

Considerations for this question:

- Does the proposed land use and zoning designation associated with the project provide capacity for transit-supportive residential densities within the TPA?
- Is the project site suitable to accommodate mixed-use village development, as defined in the General Plan, within the TPA?
- Does the land use and zoning associated with the project increase the capacity for transit-supportive employment intensities within the TPA?

2. Would the proposed project implement the General Plan's Mobility Element in Transit Priority Areas to increase the use of transit? Considerations for this guestion:

- Does the proposed project support/incorporate identified transit routes and stops/stations?
- Does the project include transit priority measures?

3. Would the proposed project implement pedestrian improvements in Transit Priority Areas to increase walking opportunities? Considerations for this guestion:

- Does the proposed project circulation system provide multiple and direct pedestrian connections and accessibility to local activity centers (such as transit stations, schools, shopping centers, and libraries)?
- Does the proposed project urban design include features for walkability to promote a transit supportive environment?

4. Would the proposed project implement the City of San Diego's Bicycle Master Plan to increase bicycling opportunities? Considerations for this guestion:

- Does the proposed project circulation system include bicycle improvements consistent with the Bicycle Master Plan?
- Does the overall project circulation system provide a balanced, multimodal, "complete streets" approach to accommodate mobility needs of all users?

5. Would the proposed project incorporate implementation mechanisms that support Transit Oriented Development? Considerations for this question:

- Does the proposed project include new or expanded urban public spaces such as plazas, pocket parks, or urban greens in the TPA?
- Does the land use and zoning associated with the proposed project increase the potential for jobs within the TPA?
- Do the zoning/implementing regulations associated with the proposed project support the efficient use of parking through mechanisms such as: shared parking, parking districts, unbundled parking, reduced parking, paid or time-limited parking, etc.?

6. Would the proposed project implement the Urban Forest Management Plan to increase urban tree canopy coverage?

Considerations for this question:

- Does the proposed project provide at least three different species for the primary, secondary and accent trees in order to accommodate varying parkway widths?
- Does the proposed project include policies or strategies for preserving existing trees?
- Does the proposed project incorporate tree planting that will contribute to the City's 20% urban canopy tree coverage goal?



This attachment provides performance standards for applicable Climate Action Pan (CAP) Consistency Checklist measures.

Table 1 Roof Design Values for Question 1: Cool/Green Roofs supporting Strategy 1: Energy & Water Efficient Buildings of the Climate Action Plan						
Land Use Type	Roof Slope	Minimum 3-Year Aged Solar Reflectance	Thermal Emittance	Solar Reflective Index		
Low-Rise Residential	≤2:12	0.55	0.75	64		
Low-Rise Residential	> 2:12	0.20	0.75	16		
High-Rise Residential Buildings,	≤2:12	0.55	0.75	64		
Hotels and Motels	> 2:12	0.20	0.75	16		
Non-Residential	≤2:12	0.55	0.75	64		
INUTFRESIDETIDAL	> 2:12	0.20	0.75	16		

Source: Adapted from the California Green Building Standards Code (CALGreen) Tier 1 residential and non-residential voluntary measures shown in Tables A4.106.5.1 and A5.106.11.2.2, respectively. Roof installation and verification shall occur in accordance with the CALGreen Code.

CALGreen does not include recommended values for low-rise residential buildings with roof slopes of ≤ 2:12 for San Diego's climate zones (7 and 10). Therefore, the values for climate zone 15 that covers Imperial County are adapted here.

Solar Reflectance Index (SRI) equal to or greater than the values specified in this table may be used as an alternative to compliance with the aged solar reflectance values and thermal emittance.

Table 2 Fixture Flow Rates for Non-Residential Buildings related to Question 2: Plumbing Fixtures a Fittings supporting Strategy 1: Energy & Water Efficient Buildings of the Climate Action Pla				
	Fixture Type	Maximum Flow Rate		
	Showerheads	1.8 gpm @ 80 psi		
	Lavatory Faucets	0.35 gpm @60 psi		
Kitchen Faucets Wash Fountains Metering Faucets Metering Faucets for Wash Fountains Gravity Tank-type Water Closets Flushometer Tank Water Closets Flushometer Valve Water Closets		1.6 gpm @ 60 psi		
		1.6 [rim space(in.)/20 gpm @ 60 psi]		
		0.18 gallons/cycle		
		0.18 [rim space(in.)/20 gpm @ 60 psi]		
		1.12 gallons/flush		
		1.12 gallons/flush		
		1.12 gallons/flush		
_	Electromechanical Hydraulic Water Closets	1.12 gallons/flush		
	Urinals	0.5 gallons/flush		

Source: Adapted from the California Green Building Standards Code (CALGreen) Tier 1 non-residential voluntary measures shown in Tables A5.303.2.3.1 and A5.106.11.2.2, respectively. See the California Plumbing Code for definitions of each fixture type.

Where complying faucets are unavailable, aerators rated at 0.35 gpm or other means may be used to achieve reduction.

Acronyms:

gpm = gallons per minute psi = pounds per square inch (unit of pressure)

in. = inch

Table 3 Standards for Appliances and Fixtures for Commercial Application related to Question 2: Plumbing Fixtures and Fittings supporting Strategy 1: Energy & Water Efficient Buildings of the Climate Action Plan					
Appliance/Fixture Type	Standard	Standard			
Clothes Washers	Maximum Water Factor (WF) that will reduce the use of water by 10 percent below the California Energy Commissions' WF standards for commercial clothes washers located in Title 20 of the California Code of Regulations.				
Conveyor-type Dishwashers	0.70 maximum gallons per rack (2.6 L) (High-Temperature)	0.62 maximum gallons per rack (4.4 L) (Chemical)			
Door-type Dishwashers	0.95 maximum gallons per rack (3.6 L) (High-Temperature) 1.16 maximum gallons per rack (2.6 L) (Chemical)				
Undercounter-type Dishwashers	0.90 maximum gallons per rack (3.4 L) (High-Temperature)	0.98 maximum gallons per rack (3.7 L) (Chemical)			
Combination Ovens	Consume no more than 10 gallons per hour (38 L/h) in the full operational mode. Function at equal to or less than 1.6 gallons per minute (0.10 L/s) at 60 psi (414 kPa) and • Be capable of cleaning 60 plates in an average time of not more than 30 seconds per plate. • Be equipped with an integral automatic shutoff. • Operate at static pressure of at least 30 psi (207 kPa) when designed for a flow rate of 1.3 gallons per minute (0.08 L/s) or less.				
Commercial Pre-rinse Spray Valves (manufactured on or after January 1, 2006)					

Source: Adapted from the California Green Building Standards Code (CALGreen) Tier 1 non-residential voluntary measures shown in Section A5.303.3. See the California Plumbing Code for definitions of each appliance/fixture type.

Acronyms: L = liter

L/h = liters per hour
L/s = liters per second
psi = pounds per square inch (unit of pressure)
kPa = kilopascal (unit of pressure)