PUBLIC UTILITIES DEPARTMENT CITY OF SAN DIEGO

# **APPROVED MATERIALS LIST**

# FOR WASTEWATER



MICHAEL ROSENBERG DEPUTY DIRECTOR WASTEWATER COLLECTIONS



SURRAYA RASHID

DEPUTY DIRECTOR

ENGINEERING & PROGRAM MANAGEMENT

JOHN STUFFLEBEAN

ASSISTANT DIRECTOR

Pure Water and Technical Services

May 2021

### PUBLIC UTILITIES DEPARTMENT

#### **CITY OF SAN DIEGO**

#### **APPROVED MATERIALS LIST**

## FOR MUNICIPAL SEWER

#### May 2021

SUBJECT		SPEC. REF	MANUFACTURER (Series/Model No.)	SELECTION	ADDITIONAL REQUIREMENTS
A. Sew	er Pipes				
1.		Titrified Clay 207-8	Pacific Clay Pipe		Plain End and Bell and Spigot Type Pipe
	Pipe and Fittings		Gladdin and McBean		~F-8
	-		Mission Clay		
2.	PVC Sewer Pipe and	207-17 ASTM D 3034	J-M		Green Bell
	Fittings— Gasket Joints 4	SDR-35	CertainTeed		
	thru 15 inches diameter		Vinyltech Corporation		Phoenix, Arizona Plant
			Northern Pipe Products		Fargo, North Dakota Plant
			Diamond Plastics Corporation		Casa Grande, Arizona (primary plant) GrandIsland, Nebraska (secondary plant)
			North American Pipe Corporation		Yucca, Arizona (primary plant) Wichita Falls, Texas (secondary plant)
					Lasimo

\*References are to the current edition of the Standard Specifications for Public Works Construction, the "GREENBOOK", and/or the "WHITEBOOK" or the latest version of the ASTM Specifications.

Any projects funded by the Clean Water State Revolving Fund (CWSRF) and/or Drinking Water State Revolving Fund (DWSRF) require iron and steel products must be produced in the United States to meet the "American Iron and Steel (AIS)" requirements, unless the Environmental Protection Agency (EPA) waives the AIS requirement.

SUBJECT	SPEC.	MANUFACTURER	SELECTION	ADDITIONAL
	REF	(Series/Model No.)		REQUIREMENTS
A. Sewer Pipes (cont.)				
3. PVC Sewer Pipe and	207-17 ASTM F 679	J-M		*Up to 30-inch pipe
Fittings— Gasket Joints		CertainTeed		*Up to 30-inch pipe
18 thru 36 inch diameter		Vinyltech Corporation		Phoenix, Arizona Plant *18-inch pipe only
		Northern Pipe Products		Fargo, North Dakota Plant *up to 24-inch pipe
		Diamond Plastics Corporation		Casa Grande, Arizona (primary plant) GrandIsland, Nebraska (secondary plant)
		North American Pipe Corporation		Yucca, Arizona (primary plant) Wichita Falls, Texas (secondary plant)
4. Fusible PVC Sewer Pipe— 4 thru 36 inch diameter	*209-8 AWWA C900 (4"-12") AWWA C905 (14"-36")	Underground Solutions		Yucca, AZ Plant
5. Fiberglass Reinforced Polymer Mortar (FRPM) Sewer Pipe	207-20, ASTM D3262 (gravity sewer)	US Composite Pipe South - Flowtite (FRPM) Pipe		Zachary , Louisiana Plant *Resin: Only vinyl ester resin is approved. Use of any other resin is strictly prohibited.
6. Centrifugally Cast Fiberglass Reinforced Polymer Mortar (CCFRPM) Sewer Pipe	207-20, ASTM D3262 (gravity sewer)	Hobas Pipe USA		Houston, Texas Plant *Direct bury installations
7. Polymer Concrete Sewer Pipe (4 thru 36 inch diameter)	ASTM D6783	Meyer Polycrete Pipe		Zachary, Louisiana Plant *Resin: Only Dion Impact 9133-055 Epoxy Vinyl Ester Resin is approved. Use of any other resin is strictly prohibited. *Microtunneling and pipe jacking applications

Any projects funded by the Clean Water State Revolving Fund (CWSRF) and/or Drinking Water State Revolving Fund (DWSRF) require iron and steel products must be produced in the United States to meet the "American Iron and Steel (AIS)" requirements, unless the Environmental Protection Agency (EPA) waives the AIS requirement.

Revised May 2021

٠

	SU	JBJECT	SPEC. REF	MANUFACTURER (Series/Model No.)	SELECTION	ADDITIONAL REQUIREMENTS
B	Sowe	er Laterals		(Series/Model No.)		<b>REQUIREMENTS</b>
р.	1.	Vitrified Clay	207-8 ASTM C-700	Gladdin and McBean		Plain End and Bell and Spigot Type Pipe
		Pipe	ASTM C-700	Mission Clay		Spigot Type Tipe
	2.	PVC Pipe	207-17 ASTM D 2751	J-M		
				CertainTeed		
				Vinyltech		
	3.	ABS (Acrylonitrile-	207-15 ASTM D 2751	Colby		
		butadiene- styrene) Solid Wall Pipe		Standard Plastics		
C.	Sewe	er Fittings				
	1.	Vitrified Clay Fittings	207-8 ASTM C-700	Gladdin and McBean		Plain End and Bell and Spigot Type Pipe
				Mission Clay		
	2.	PVC Fittings	207-17 ASTM D-	Vassallo		
			3034 or ASTM F 679	Multi-Fittings		
			depending upon size	G.P.K.		
				J-M		
				Plastic Trends Inc: Series G (SDR 35), Series H (SDR 26), Series C pressure sewer (DR-18 Class C-900 or C- 905)		Shelby Township, Michigan
	3.	ABS Fittings	207-15	U-Brand		

Any projects funded by the Clean Water State Revolving Fund (CWSRF) and/or Drinking Water State Revolving Fund (DWSRF) require iron and steel products must be produced in the United States to meet the "American Iron and Steel (AIS)" requirements, unless the Environmental Protection Agency (EPA) waives the AIS requirement.

	SUBJECT	SPEC.	MANUFACTURER	SELECTION	ADDITIONAL
		REF	(Series/Model No.)		REQUIREMENTS
D.	Sewer Manhole Components				
	1. Precast Manhole & Precast Base	ASTM C 478, 201-10	Mar-Con Products		San Marcos, California
			Oldcastle Precast, Inc		San Diego, CA Plant Riverside, CA Plants
			Olson Precast Company		Rialto, California
	2. Manhole Covers and Frames		Pamrex & Pamtight (Pacific Pipeline Supply (or Pam Saint Gobain)		Saint Gobain Canalizaco, Ituana, Brazil Plant (All components shall be ductile iron.)
			National Casting (NC2531)		Trident Export Corporation 58, N.S. Road Liluah, Howrah 711 204, India Plant
			South Bay Foundry Inc. (1310, 1325)		Maquiladora-KM. 10.5 CRT. A San Luis Mexicali, BC Mexico

Any projects funded by the Clean Water State Revolving Fund (CWSRF) and/or Drinking Water State Revolving Fund (DWSRF) require iron and steel products must be produced in the United States to meet the "American Iron and Steel (AIS)" requirements, unless the Environmental Protection Agency (EPA) waives the AIS requirement.

Revised May 2021

'n

	SUBJECT	SPEC. REF	MANUFACTURER (Series/Model No.)	SELECTION	ADDITIONAL REQUIREMENTS
E.	Sewer Rehabilitation Products				
	1. PE Solid Pipe	500-5.11	Chevron Plexco		Reno, Nevada Plant
			Chevron Phillips Driscopipe		Watsonville Plant
	2. Cured-in-Place	500-5.5	Inliner-Fabric Tube: Polyester felt Resin: Dow Derakane 411 Vinyl Ester		Houston, Texas Plant Memphis, Tennessee Plant
			Insituform-Fabric Tube: Polyester felt Resin #1: Shell Epon 9215 epoxy Resin #2: Interplastics VE8319 Vinyl Ester		
			National Liner		Martinsville, Virginia
			Applied Felts Polyester felt AOC Vipel L704-Net-11 Isophthalic polyester resin or AOC Vipel L010-PPA Vinyl Ester resin		Perris, California
			EasyLiner CleanOutLiner System: Bullseye Liner		Lateral rehabilitation only Gadmon Industries 57 Glengall Road, London, United Kingdom SE15 6NF
			CORVE 8190 Vinyl-Ester Resin		2015 Northeast Broadway Street, Minneapolis, Minnesota 55413-1775.
					Product shall be applied by an applicator approved and certified by Easy Liner LLC.
	3. Profiled PVC	500-5.6	Danby		Toronto, Canada Plant
	4. Deformed Solid Wall PE	500-5.7	Hydroconduit		Roaring Springs, Texas Plant
			Uliner—Navacor Resin		Houston, Texas Plant

Any projects funded by the Clean Water State Revolving Fund (CWSRF) and/or Drinking Water State Revolving Fund (DWSRF) require iron and steel products must be produced in the United States to meet the "American Iron and Steel (AIS)" requirements, unless the Environmental Protection Agency (EPA) waives the AIS requirement.

	SU	JBJECT	SPEC. REF	MANUFACTURER (Series/Model No.)	SELECTION	ADDITIONAL REQUIREMENTS
Е.		ver nabilitation ducts (cont.)		(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
	5.	FRPM	500-5.8.1	Hobas Pipe		Birmingham, New York Plant Waco, Texas Plant
	6.	Folded Solid Wall PVC	500-5.10	America Plastic		· · · · · · · · · · · · · · · · · · ·
				AMLiner		
				Insituform Nupipe		
	7.	Machine Spiral Wound PVC (November 2001)	500-5.13	RIB LOC		Gepps Gross, South Australia Plant
	8.	MultiPlexx Liner System, Type PVCP	502 Cured-In- Place Manhole Rehabilitation	Product: MultiPlexx Liner System by Terre Hill Composites MultiPlexx Liner System: Type/Model PVCP 20- 28≥88 mils consisting of: PVC Liner: 20 mils PVC Polyester Fleece Backing:10 oz/yd <sup>2</sup> Fiberglass Backing: 18 oz/yd <sup>2</sup> Resin: EPON 9215 at 0.0005 gallons per square foot of manhole area Epoxy: Application to substrate surface of manhole to be rehabilitated.		Manufacturing Plant Site: Terre Hill Composites, Division of Terre Hill Concrete Products, Terre Hill, Pennsylvania Resin: Manufactured by Resolution Performance Products Installers: Tejon Constructors, Inc.

Any projects funded by the Clean Water State Revolving Fund (CWSRF) and/or Drinking Water State Revolving Fund (DWSRF) require iron and steel products must be produced in the United States to meet the "American Iron and Steel (AIS)" requirements, unless the Environmental Protection Agency (EPA) waives the AIS requirement.

Revised May 2021

3.

	SUBJECT	SPEC. REF	MANUFACTURER (Series/Model No.)	SELECTION	ADDITIONAL REQUIREMENTS
Е.	Sewer Rehabilitation Products (cont.)	KET			
	9. Raven 405 Epoxy Lining System	502	Product: Raven 405 Epoxy Liner Systems by Raven Lining Systems, Inc. Raven 405 is a solvent-free 100% solids, extra high-build epoxy which can be applied over 200 mils in a single application. Light blue is the standard color when applied. Theoretical coverage averages 40 ft <sup>2</sup> per gallon at 40-mil thickness.		Raven 405 Epoxy is manufactured by Raven Lining Systems, Inc. Plant is located at 1024 North Lansing Avenue, Tulsa, Oklahoma 74106 Product shall be applied by an applicator approved and certified by Raven Lining Systems.
	10. Raven AquaFlex 505 Hybrid Polyurethane Coating with Raven 175 Primer	502	Product: Raven AquaFlex 505 Hybrid Polyurethane with Raven 175 Primer by Raven Lining Systems, Inc.		13105 E. 61st Street, Broken Arrow, OK 74012 Product shall be applied by an applicator approved and certified by Raven Lining Systems.
	<ol> <li>Zebron Epoxy 9000/Poly- urethane 386 Lining System</li> </ol>	502	Zebron Low Temperature Epoxy 9000 Primer, and Polyurethane 386. Epoxy 9000 is100 percent solids moisture tolerant		The Low Temperature Epoxy 9000 is manufactured by a third party. However, Polyurethane 386 is Zebron's proprietary product. Zebron Epoxy 9000 and Polyurethane 386 are processed at: 1141 N Cosby Way Units H, I & J Anaheim, CA 92806 (800) 824-4214
	12. Sherwin Williams Duraplate 6100 High Performance Epoxy Lining System/ Polycote 115 Elastomeric Urethane Lining System		Duraplate 6100 High Performance Epoxy Lining System Polycote 115 Elastomeric Urethane Lining System		1655 Harbor Ave., Memphis, TN, 38106 3813 Helios Way, Pflyger, TX, 78660

Any projects funded by the Clean Water State Revolving Fund (CWSRF) and/or Drinking Water State Revolving Fund (DWSRF) require iron and steel products must be produced in the United States to meet the "American Iron and Steel (AIS)" requirements, unless the Environmental Protection Agency (EPA) waives the AIS requirement.

	SUBJECT	SPEC.	MANUFACTURER	SELECTION	ADDITIONAL
Е.	Sewer Rehabilitation Products (cont.)	REF	(Series/Model No.)		REQUIREMENTS
	13. Utilithane Epoxy- Polyurethane	502	Prime Coatings Incorporated Utilithane 1600 Polyurethane and Utilithane 900 Low Temperature Epoxy are proprietary products of Prime Coatings Inc. This product is spray applied using airless spray equipment. Utilithane 1600 is dense polyurethane with no VOCs, and Utilithane 900 Epoxy is a two component product formulated as a "Fast-Set" or "Slow-Set".		Address of Prime Coatings Inc. is: P.O. Box 3056 Tustin, California PlantA 92781 Phone (714) 963-9583 Email: <u>utilithane@sbcglobal.net</u> Website: www.utilithane.com
	14. Sancon 100 Polyurethane	502	Sancon 100 Epoxy Primer and Sancon 100 Polyurethane spray applied liner manufactured by PTM&W Industries at 10640 South Painter Ave, Santa Fe Springs, CA 90670 This product is spray applied using airless spray equipment		Sancon Engineering Inc. 5841 Engineer Dr Huntington Beach, California Plant 92649 (714) 891-2323 (800) 726-2664
	<ol> <li>Saueresin SewerGard No.</li> <li>210X Epoxy Lining System</li> </ol>	502	Saueresin SewerGard No. 210X Epoxy Lining System		Pittsburg, PA Plant
	16. PVC Sheet Lining Systems	502	Ameron T-Lock and Arrow- Lock		Brea, CA Plant
	17. Sprayroq Spraywall Polyurethane Liner System	502	Sprayroq Spraywall Polyurethane Liner System		Creative Polymer Solutions Grantswood Road, Suite100 Irondale, AL 35210
	18. Tophat Lateral Connection Sealing System		Cosmic Tophat Lateral Connection Sealing System		Kasten, Austria Plant *Only ATLAC E-NOVA RE 3475 Vinyl Ester Resin with ECR fiberglass mat is approved.

Any projects funded by the Clean Water State Revolving Fund (CWSRF) and/or Drinking Water State Revolving Fund (DWSRF) require iron and steel products must be produced in the United States to meet the "American Iron and Steel (AIS)" requirements, unless the Environmental Protection Agency (EPA) waives the AIS requirement.

	SUBJECT	SPEC. REF	MANUFACTURER (Series/Model No.)	SELECTION	ADDITIONAL REQUIREMENTS
F.	Miscellaneous				REQUIREMENTS
-	1. Flexible Couplings		Smith-Blair 441 Rockwell APAC (331,323,335), (CDC-EC)		
	2. Transition Gaskets	ASTM D 1869	Newby Rubber, Inc.		
	3. High-Deflection Couplings 4 thru 12 inches diameter		CertainTeed		
	4. Flexible Saddles (Wyes)		DFW Plastics, Inc.		
	5. Transition Coupling with Shear Shield	ASTM C 1173	Mission Rubber Company, Flex-Seal ARC with 304SS shear band		Mission Rubber Company 1660 Leeson Lane Corona, CA 92878-2349 1-800-854-9991
	6. Repair Couplings		Fenco Inc Series 5000 RC (Repair Coupling) with 316 stainless steel nut and bolt clamps (with 300 stainless steel sheer ring) Series 1000 RC (Repair Coupling) with 301 stainless steel worm gear clamps (with 300 stainless steel sheer ring)		Davison, Michigan Plant
			Joints Coupling Inc Banded Calder Repair Couplings		El Monte, CA Plant
	7. Casing Spacers, End Seals, Pipe Penetration Seals	212-3	BWM Company (SS-8 for carrier pipe up to 24 inches, SS-12 for carrier pipe greater than 24 inches, ESW, ESPO, SSPS, CPS)		Forest City, NC Plant

Any projects funded by the Clean Water State Revolving Fund (CWSRF) and/or Drinking Water State Revolving Fund (DWSRF) require iron and steel products must be produced in the United States to meet the "American Iron and Steel (AIS)" requirements, unless the Environmental Protection Agency (EPA) waives the AIS requirement.