



SECTION

NOTES:

1. THE FOLLOWING SHALL BE AS REQUIRED:
  - A. LOW FLOW CHANNEL
  - B. FILTER BLANKET
  - C. CUTOFF WALL
  - D. FENCE
2. CHANNELING FENCING IS REQUIRED PER DRAWING SDM-112 OR SDM-114. UNLESS OTHERWISE SHOWN ON THE PLANS, A CHAIN LINK FENCE 6' HEIGHT, WITH A TOP RAIL SET AT 6" INSIDE EASEMENT BOUNDARY LINES SHALL BE CONSTRUCTED ON BOTH SIDES, INCLUDING BOX CULVERTS OR ANY OTHER STRUCTURE AT THE END OF THE CHANNEL. ACCESS POINTS SHALL BE PROVIDED ON BOTH SIDES AT 500' MAXIMUM INTERVALS. TWO 10' GATES OR ONE 20' GATE FOR VEHICULAR ACCESS ARE REQUIRED AT A MAXIMUM OF 1000' INTERVALS AND MAY BE PLACED ON EITHER SIDE. THE REMAINING ACCESS POINTS SHALL BE 4' GATES.

LEGEND ON PLANS



REVISION	BY	APPROVED	DATE	CITY OF SAN DIEGO - STANDARD DRAWING	RECOMMENDED BY THE CITY OF SAN DIEGO STANDARDS COMMITTEE
ORIGINAL*	KA	J. NAGELVOORT	01/12		<i>CA Brungca</i> 10/5/15
UPDATED	RB	J. NAGELVOORT	10/15	<b>GRADED EARTH CHANNEL</b>	COORDINATOR R.C.E. 56523 DATE
					DRAWING NUMBER
					<b>SDD-109</b>