



TYPE	W	*AREA
G	24"	1.34 SQ FT
H	30"	1.61 SQ FT

* WITH 6" CURB FACE

NOTES:

1. CONCRETE SHALL BE 520-C-2500.
2. SEE JOINT DETAIL DRAWING, G-10.
3. ON THE SIDE OF OF SUPER ELEVATED CURVES THE GUTTER SHALL BE SLOPED TO MATCH CROSS SECTION GRADE OF THE ROADWAY.
4. PLACE EXPANSION JOINTS AT CURB RETURNS ADJACENT TO STRUCTURES AND AT NO GREATER THAN 45' INTERVALS.
5. PLACE WEAKENED PLANE JOINTS AT DRIVEWAYS AND AT 15' INTERVALS FROM POINT OF CURB RETURN.
6. ALL HISTORICAL STAMPS / IMPRESSIONS SHALL BE PRESERVED.

LEGEND ON PLANS

REVISION	BY	APPROVED	DATE	CITY OF SAN DIEGO - STANDARD DRAWING	RECOMMENDED BY THE CITY OF SAN DIEGO STANDARDS COMMITTEE
ORIGINAL*	KA	J. NAGELVOORT	01/12		<i>CA Brungoa 10/5/15</i>
UPDATED	RB	J. NAGELVOORT	10/15	CURB AND GUTTER - COMBINED	COORDINATOR R.C.E. 56523 DATE
					DRAWING NUMBER
					SDG-151