



NOTES:

1. NO CONCRETE SHALL BE PLACED UNTIL FORMS AND SUBGRADE ARE INSPECTED.
2. CONCRETE SHALL BE 520-C-2500.
3. SEE STANDARD DRAWING SDG-164 FOR WIDTH AND LOCATION REQUIREMENTS.
4. DRIVEWAY RAMP TO EXTEND TO 10' FROM CURB FACE OR TO PROPERTY LINE WHICHEVER IS LESS. (FOR COMMERCIAL DRIVEWAYS ONLY)
5. SEE OTHER STANDARD DRAWINGS FOR CURB AND JOINT DETAILS.
6. METER BOXES SHALL NOT BE LOCATED WITHIN DRIVEWAY.
7. ALL HISTORICAL STAMPS / IMPRESSIONS (STREET NAME, CONTRACTOR NAME, AND DATE) SHALL BE PRESERVED.
8. FOR DESIGNATED URBANIZED COMMUNITIES, SIDEWALK DESIGN (SCORING PATTERN, COLOR, TEXTURE) SHALL BE IN CONFORMANCE WITH HISTORIC DESIGN ADJACENT PROPERTIES.

REVISION	BY	APPROVED	DATE
ORIGINAL*	KA	J. NAGELVOORT	01/12
UPDATED	RB	J. NAGELVOORT	10/15

CITY OF SAN DIEGO - STANDARD DRAWING

**RESIDENTIAL
CONCRETE DRIVEWAY
(PARKWAY LESS THAN 10' IN DEPTH)**

RECOMMENDED BY THE CITY OF SAN DIEGO
STANDARDS COMMITTEE

CA Bunting 10/5/15
COORDINATOR R.C.E. 56523 DATE

DRAWING NUMBER **SDG-161**