


NOTES:

1. CONCRETE SHALL NOT BE PLACED UNTIL FORMS AND SUBGRADE ARE INSPECTED AND APPROVED BY THE RESIDENT ENGINEER.
2. CONCRETE SHALL BE 560-C-3250.
3. SEE STANDARD DRAWING SDG-164 FOR WIDTH AND LOCATION REQUIREMENTS.
4. SEE OTHER STANDARD DRAWINGS FOR CURB AND JOINT DETAILS.
5. METER BOXES SHALL NOT BE LOCATED WITHIN DRIVEWAY. SEE WS-03.
6. DRIVEWAY IN EXCESS OF 150' IN LENGTH FROM CURB FACE SHALL BE A MINIMUM OF 7" PCC.
7. DRIVEWAY SHALL BE CONTINUOUS POUR FROM BACK OF CURB TO PROPERTY LINE.
8. ALL HISTORICAL STAMPS / IMPRESSIONS (STREET NAME, CONTRACTOR NAME, AND DATE) SHALL BE PRESERVED.
9. FOR DESIGNATED URBANIZED COMMUNITIES, SIDEWALK DESIGN (SCORING PATTERN, COLOR, TEXTURE) SHALL BE IN CONFORMANCE WITH HISTORIC DESIGN ON ADJACENT PROPERTIES.

LEGEND ON PLANS



REVISION	BY	APPROVED	DATE
ORIGINAL		M.V.R	592
NOTES	SM	A. OSKOU	12/03 & 806
UPDATE	FC	A. OSKOU	1206
REPLACED SDG-114	KA	J. NAGELVOORT	01/12
UPDATED	RB	J. NAGELVOORT	10/15

CITY OF SAN DIEGO - STANDARD DRAWING

COMMERCIAL CONCRETE DRIVEWAY

RECOMMENDED BY THE CITY OF SAN DIEGO STANDARDS COMMITTEE
CA Branga 10/5/15
 COORDINATOR R.C.E. 56523 DATE

DRAWING NUMBER **SDG-163**