


**NOTES**

1. Posts to be structural grade redwood or pressure treated (with wood preservative) Douglas Fir, surfaced four sides; cross pieces to be 2"x8" select grade Douglas Fir, surfaced four sides.
2. All exposed portions of barricades shall be painted with two coats of white exterior enamel over prime coat.
3. Connections shall be made with 3/8" x 6" galvanized lag screws with one (1) washer each.
4. Reflector sign fasteners to be 3/8" x 1 1/2" galvanized lag screws.
5. Reflector signs - California Type N. Size 18" x 18" - Yellow with nine (9) 3 1/4" reflectors (center mount).
  - a. Reflectors shall be red for use on dead end streets, in all other cases they shall be yellow. Reflector material shall be plastic or other approved reflectorized material.
  - b. Sign material shall be aluminum alloy 6061-T6 or 5052-H38, aluminum thickness 0.063".
6. 6' long hat section metal post per Caltrans Std. Plan A74-A optional for guard post.

**LEGEND ON PLANS**



Revision	By	Approved	Date
ORIGINAL		Kercheval	12/75
Add Metric		T. Stanton	03/03
Reviewed		T. Stanton	04/06
Delete Metric		D. Gerschoffer	05/12

**SAN DIEGO REGIONAL STANDARD DRAWING**

**GUARD POST AND BARRICADE**

RECOMMENDED BY THE SAN DIEGO REGIONAL STANDARDS COMMITTEE

*T. Stanton* 7/26/2012  
Chairperson R.C.E. 19246 Date

DRAWING NUMBER **M-9**