


- NO DIPS OR LOW SPOTS WILL BE ALLOWED IN INSTALLATION.
- LOCATE ENCLOSURE. 2.
- INSTALL /IDENTIFICATION TAPE. 3.
- AIR & VACUUM INSTALLED FOR THE USE OF RECYCLED WATER SHALL BE SHOWN ON THE PLANS.
- ON STEEL MAINS USE WELD ON COUPLINGS, ON DUCTILE IRON MAINS USE DUCTILE IRON SERVICE SADDLES (INSULATING BUSHINGS ARE REQUIRED).



ITEM NO	SIZE AND DESCRIPTION	ITEM NO	SIZE AND DESCRIPTION
1 2 3 4 5 6 7 8	2" PVC SCH 80 CLOSE NIPPLE & 2-SCH 80 STREET ELLS& INSECT SCREEN VALVE ENCLOSURE 2" MIPT X COMPRESSION ADAPTER 2" AUTOMATIC COMBINATION AIR RELEASE & AIR/VACUUM VALVE 12" X 3" STAINLESS STEEL DROP-IN ANCHORS (3 EA @120 APART) 8", 3/8" STEEL GATE CASING WELL WITH CAP COLD JOINT STRIP 3'-6" X 2'-6" X 6" THICK CONCRETE SLAB	9 10 11 12 13 14 15 16 17 18	2" X 1/2" BLACK FOAM SLEEVE COPPER TUBING 90" ELL (NO SWEAT, NO GLUED JOINTS ALLOWED) 2" BRONZE COMPRESSION COUPLING COPPER TO COPPER (IF REQUIRED) 2" COMP BALL BALVE W/TEE HEAD 2" 90" BRONZE FIPT X COMP ELL 2" BRONZE MIPT X MIPT CORPORATION STOP SIZE X 2" SERVICE SADDLE WATER MAIN VALVE STEM EXTNESION

REVISION ORIGINAL*		APPROVED J. NAGELVOORT	01/12	CITY OF SAN DIEGO - STANDARD DRAWING
UPDATED	KA	J. NAGELVOORT	09/13	2" AUTOMATIC COMBINATION AIR RELEASE & AIR/ VACUUM VALVE INSTALLATIONS

RECOMMENDED BY THE CITY OF SAN DIEGO STANDARDS COMMITTEE

Duga 9/16/13

R.C.E. 56523 DATE

DRAWING **SDW-159** NUMBER