


- NOTES:
- 1) FOR BLOW-OFF INSTALLATION AT END OF MAIN SEE OTHER STANDARD DRAWINGS
 - 2) BLOW-OFF ASSEMBLIES INSTALLED FOR THE USE OF RECYCLED WATER SHALL BE IDENTIFIED AS DESCRIBED IN SPECIFICATIONS
 - 3) ON STEEL MAINS USE WELD ON COUPLINGS, ON DUCTILE IRON MAINS USE DUCTILE IRON SERVICE SADDLES (INSULATING BUSHINGS ARE REQUIRED)
 - 4) 45° BEND SHALL BE USED FOR MAINS UP TO 30°. 90° BEND SHALL BE USED FOR MAINS IN EXCESS OF 30° AS DIRECTED BY THE ENGINEER



ITEM NO	SIZE AND DESCRIPTION	ITEM NO	SIZE AND DESCRIPTION
1	GATE WELL WITH CAP SEE SDW-153 OR SDW-154	8	DUCTILE IRON OR C-900 PVC
2	GALVANIZED IRON PLUG	9	4" OR 6" FLG x MJ / PO / FLG RWGV
3	GALVANIZED IRON COUPLING, THREADED	10	4" OR 6" FLG x MJ / PO ADAPTER (IF REQUIRED)
4	10" STEEL GATE WELL WITH CAP	11	4" OR 6" x 24" FLG DISPOOL
5	4" OR 6" FLG DI PIPE x REQUIRED LENGTH (MAXIMUM OF 2 SPOOLS)	12	WATER MAIN
6	CONCRETE THRUST BLOCK SEE SDW-151	13	SIZE x 4" OR 6 MJ / PO / FLG x FLG TEE
7	FLANGE x FLANGE x 90° BEND	14	4" OR 6" FLANGED 45° BEND, SEE NOTE 4

REVISION	BY	APPROVED	DATE	CITY OF SAN DIEGO - STANDARD DRAWING	RECOMMENDED BY THE CITY OF SAN DIEGO STANDARDS COMMITTEE
ORIGINAL*	KA	J. NAGELVOORT	01/12		
UPDATED	KA	J. NAGELVOORT	12/12	4" & 6" BLOW-OFF INSTALLATION IN STREET TYPE B	<i>J. Nagelvoort</i> COORDINATOR R.C.E. 65271
					12/17/2012 DATE
					DRAWING NUMBER SDW-145