A.B.D.

Preliminary

Surveys

1

FIELD BOOK

364 S

F.B.106

KEUFFEL & ESSER C
DRAWING MATERIALS
AND
SURVEYING INSTRUMENTS.
NEW YORK.
CHICAGO. ST. LOUIS. SAN FRANCISCO. MONTREAL.

MICROFILMED
DEC 1964

TABLES FOR EXCAVATIONS AND EMBANKMENTS.

DISTANCES FROM CENTER OF ROADWAY FOR CROSS-SECTIONING.
ROADWAY 18 FEET WIDE. SIDE SLOPES 1 TO 1.
FOR SINGLE TRACK EXCAVATION.

"Copyright, 1895, by Keuffel & Esser Co."

	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	
0	9.0	9.1	9.2	9.3	9.4	9.5	9.6	9.7	9.8	9.9	0
1	10.0	10.1	10.2	10.3	10.4	10.5	10.6	10.7	10.8	10.9	1
2	11.0	11.1	11.2	11.3	11.4	11.5	11.6	11.7	11.8	11.9	2
3	12.0	12.1	12.2	12.3	12.4	12.5	12.6	12.7	12.8	12.9	3
4	13.0	13.1	13.2	13.3	13.4	13.5	13.6	13.7	13.8	13.9	4
5	14.0	14.1	14.2	14.3	14.4	14.5	14.6	14.7	14.8	14.9	5
6	15.0	15.1	15.2	15.3	15.4	15.5	15.6	15.7	15.8	15.9	6
7	16.0	16.1	16.2	16.3	16.4	16.5	16.6	16.7	16.8	16.9	7
8	17.0	17.1	17.2	17.3	17.4	17.5	17.6	17.7	17.8	17.9	8
9	18.0	18.1	18.2	18.3	18.4	18.5	18.6	18.7	18.8	18.9	9
10	19.0	19.1	19.2	19.3	19.4	19.5	19.6	19.7	19.8	19.9	10
11	20.0	20.1	20.2	20.3	20.4	20.5	20.6	20.7	20.8	20.9	11
12	21.0	21.1	21.2	21.3	21.4	21.5	21.6	21.7	21.8	21.9	12
13	22.0	22.1	22.2	22.3	22.4	22.5	22.6	22.7	22.8	22.9	13
14	23.0	23.1	23.2	23.3	23.4	23.5	23.6	23.7	23.8	23.9	14
15	24.0	24.1	24.2	24.3	24.4	24.5	24.6	24.7	24.8	24.9	15
16	25.0	25.1	25.2	25.3	25.4	25.5	25.6	25.7	25.8	25.9	16
17	26.0	26.1	26.2	26.3	26.4	26.5	26.6	26.7	26.8	26.9	17
18	27.0	27.1	27.2	27.3	27.4	27.5	27.6	27.7	27.8	27.9	18
19	28.0	28.1	28.2	28.3	28.4	28.5	28.6	28.7	28.8	28.9	19
20	29.0	29.1	29.2	29.3	29.4	29.5	29.6	29.7	29.8	29.9	20
21	30.0	30.1	30.2	30.3	30.4	30.5	30.6	30.7	30.8	30.9	21
22	31.0	31.1	31.2	31.3	31.4	31.5	31.6	31.7	31.8	31.9	22
23	32.0	32.1	32.2	32.3	32.4	32.5	32.6	32.7	32.8	32.9	23
24	33.0	33.1	33.2	33.3	33.4	33.5	33.6	33.7	33.8	33.9	24
25	34.0	34.1	34.2	34.3	34.4	34.5	34.6	34.7	34.8	34.9	25
26	35.0	35.1	35.2	35.3	35.4	35.5	35.6	35.7	35.8	35.9	26
27	36.0	36.1	36.2	36.3	36.4	36.5	36.6	36.7	36.8	36.9	27
28	37.0	37.1	37.2	37.3	37.4	37.5	37.6	37.7	37.8	37.9	28
29	38.0	38.1	38.2	38.3	38.4	38.5	38.6	38.7	38.8	38.9	29
30	39.0	39.1	39.2	39.3	39.4	39.5	39.6	39.7	39.8	39.9	30
31	40.0	40.1	40.2	40.3	40.4	40.5	40.6	40.7	40.8	40.9	31
32	41.0	41.1	41.2	41.3	41.4	41.5	41.6	41.7	41.8	41.9	32
33	42.0	42.1	42.2	42.3	42.4	42.5	42.6	42.7	42.8	42.9	33
34	43.0	43.1	43.2	43.3	43.4	43.5	43.6	43.7	43.8	43.9	34
35	44.0	44.1	44.2	44.3	44.4	44.5	44.6	44.7	44.8	44.9	35
36	45.0	45.1	45.2	45.3	45.4	45.5	45.6	45.7	45.8	45.9	36

Calculated by Julien A. Hall, M. Am. Soc. C. E.

For Keith's Railroad Curve Tabels see end of book.

#1

Datum 00.0 Gauge
= U.S.G.S. 1446.123

Pin by road = 9+16.6
elev 180.210 = 1626.333

Base line = N41°39'W
Azim = ~~41°39'~~

Bottom grade outlet
57.8 = 1503.923

37

Index

	Page
Checking Inst.	1
Levels West side	2
Traverse Upstream face of O'Shaughnessy dam	5-8
Flagging out line dam	8
Profile + Traverse ℄ Plant	9-11
Tieing in Core drill holes #5+6	12
Levels between Two concrete walls Upper + Lower Sites	13
Staking Crusher Plant	14
Staking Plant - Rock + Sand Storage	15
Staking Plant Mixing plant + bins	16
Locate Core drill holes #7+8	17
Locate Core drill holes 6-7-8	18
Camp Location. Traverse along road	19-25
Staking Road Quarry floor to Barn	20-27
Staking Road from Barn to Barrett Camp Road	
Setting flags - 175' Contour	35-36
Tie to Core Drill ~~Hole~~ #6-10-41	38
Traverse along Lyons Valley Road	40-41
Tie To Transformer Station from A-1	42
Measurement of water Wilson Creek	42-
Road to Gueshouse	43
Proposed Location of East Cableway Tower	44
Topog East Edge Weir Old Harris Dam	45-49
Tie to Core Drill Hole #15-16	50
Staking Curtain Wall	51
Ry Track E side Canon to dumpe below Suspension bridge	52-54
Adjustment of Transit	56
Hand Level Elevations from Cottonwood Creek to Conduit	56
Elev of Stakes along Traverse of Upstream line of Dam	57-58
Grade for flume Thru Harris Dam	56
Road + landing to Storehouse	57
Continuation Quarry Road -	37
" " " "	38
" " " "	55

Inst

Checking adjustment

160			526	
				.073
155			453	
				73
			4145	
			73	
			4872	.01 in 320'

Read	Checking	Stadia	Interval
435	act. Dist		
Act.	read stadia		
425	435		
325	332		
225	229		
125	127		
25	24		

Stadia constant

= 1.025

Differential levels

	side to	top		B.M. West dam
Harris Base Line 97166				180.210
	0.30	180.51		
		985	11.17	169.34
	1.32	170.66 ✓		
		956	12.57	158.09
	3.01	161.10		
Hub on line		1325	2.70	158.40
			27c 1374	147.36
	.049	147.85		
Hub on line		1215	8.03	139.82
			1332	134.53
	1.17	135.70 ✓		
Hub on line		1163	9.21	126.49
			1335	122.35 ~~.30~~
	1.72	124.07 ~~123.42~~		
Iron Bi red flag				115.97 ~~115.32~~
			8.16	11453
			1254	111.04
		112.58		
	0.95	112.03		
				100.66
On rock			1152	100.21
		0296		
	2.30	102.51		
Hub W				89.70
			13.26	89.25
		9062		
	0.92	90.17		
				78.61
On rock			1201	78.16
		7913		
	0.52	78.68		
				6646
			1267	~~6661~~
	1240			
	1270 ✓		12645	

126.49		180.210
12.70 ✓		113.73
113.79		66.46

Same Cont.

				66.46
	0.97	67.43		66.01
	660	66.98		
on rock by path				54.14
			13.29	53.69
		54.87		
	0.73	54.42		
Anchor pin for walk. Blake				.72
			11.15	43.27
			11.97	42.90
			12.42	42.45
		43.47		
	0.57	43.02		
Iron pin				
			1045	33.82
		34.42		33.37
	1.40	33.97		
				21.29
			1313	21.86
	3 67			21.37
			1305	20.92
			48.76	
			3.67	
			4509	
			2792	
			6701	
		26.00		
	47	25.55		20.82
1st hole core Drill	45'	N 20° E	3.8	22.2
Base line		0' 54748 E		
		54740' E		

Marked 21.2

66.46
45.09
.37

Curve - Upstream face of Dam.

Seton 9+16.6 of Harris Base Line
Deflect 63° Left measure
49 ft = B.C. curve 400' R.
= U.S. face dam. (O'Shaughnessy)
projection
Deflection of 43' for 10
gives practically 400' R.

5'	=	21½'
10	=	43'
20	=	1° 26'
30	=	2 09'
40	=	2 52'
50	=	3 35'
60	=	4 18'
70	=	5 1'
80	=	5 44'
90	=	6 27'
100	=	7° 10'

		Slope Dist	312°20' Azim.	Traverse near	Vert ∠
BM 9446	Baseline		~~227°40'~~	947°40'E	
	A	97.73	253°45' ~~69°47'~~		20°20'
A					
	94166		73°45'		
	B	66.40	252°57'		18°58'
B					
	A		72°57'		
	C	68.10	256°46' ~~68°~~	N76°40E	28°0'
C					
	B				
	D	93.2	291°17'		30°51'
D					
	C		111°17'		
	E	81.15	291°17'	S68°15E	32°3'
E					
	D		111°17'	(N0°0'15"E)	
	Eside notch in dam	level 93.25	45°50'		
	Edge Wier gauge		18°52'		
A	13		252°57'		
	PT 94164	45.41	99°30'		12.4°10'
	B				

upstream face O'Shaughnessy dam 5

360°40'
47°40
312°20

91.6

140'
40°R — 220

34 62.8

60.2

80.0

68.8

41.4

Levels along Traverse

A-?						
E	296	14+24.25				2129.
(293) 306	31'	109° 0'		+124	to 1.0 +6° 30'	26.6
(40.9) 429	53'	"		+198	∠ - 0.0 25° 50'	44.0
(70.0) 717	94'	"		343 +~~1370~~	∠ - 4.0 29° 7'	58.6
(94.0) 964	124'	"		453	∠ - 5 28° 10'	69.6
(145.0) 1485	195'	111° 44'		783 +~~1371~~	∠ - 5 29° 14'	102.6
A-7						
B						
(59.2) 412	68'	136° 7'		34.1	∠ - 14.0 - 18° 30'	
(19.5) 20	20				135 ro'	1242
00 00	0.0				4.4 "	1323
(62.8) 644 A	68			138	∠ - 1.0 13° 18'	1505
(101.0) 1035	112	+275			∠ - 1.0 15° 46'	1642
(157.4) 1614 PM 4+44.4	176			+435	{ ∠ - 30 16° 45'	1802



Upstream face dam traverse

E	292	24.21			21.29	
5 side						
W to G	1782	18°52				
	12852	291°16'		+ 8°50'		
	index 65	"		3.6	20.6	
	85	"	+31	GV = 2.0	27.3	
	105	"	+103	+10°0'	34.5	
(1265)	(1282)			7.2		
F	133°	"	S68°30'E	8°51'	+197' 43.91	
Inst Hole	558	88°10 (6810)				
F						
E		111°10'	+8.28			
	00			rod 4.37		
	10 (56 stadia)			24 to 00 +2.33	1439	
(446) G	49.50	306°48	S53°E	25°48'	6983	546 H53
G						
F		126°48				
	10 55 std. g.		+303	rod 00 3.20		
(93.2) H	10 97.50	328°37	S31°15W	+17°16'		
Tunnel mouth				+		S47°E
PT.	67'	31½		+10°0'		
	43	328°37		to 1.8	78.4	419 407
H			10548	3585		
(93.2) G		148 37		-21°5'		
H	00			rod 3.75	101.93	
9+166		109°50'				
I 80 g	87.95	328°50	S31°15'E	+248 23°14'	140.48	

cont.

Corrected Reading Inclined	Corrected Reading Horiz. Dist.
634	634
829	825
1024	995
1297	(1247)
1027	937
419	407

Upstream face dam

I		144.00			
H		148°38'			
00				rod. 3,5	140.48
A		115°17'	N64°30W	0°43'	151.1

Point	U.S face	D.S. face	
A	10'	4'	⊥
B	6'	18'	⊥
C	5' down	44' down	Bisect ∠
D	22' up	57	same level
E	30' up	E+20 85'	⊥ distant
F	7' up	67' D	∠
G	00	G+45 50' D	⊥
H	2' up	35' D	⊥
I	10' down	28' D	⊥

32' further to end.

Flagging outlines of Dam from traverse

15' below wind diversion dam.

63' " " " "

35' " E center " "

50 x 90

Traverse (cont).

1505

Plant Layout

100' from 9+16.6
Then N 83½° W.

9+166 (86.5)		213.0			
	93.8	318°21		-22°48	
BM	105 ST		3+8	-11°39'	
	102.4	353°22	2.08	∠ -140	180.2
TP ①				2.1	212.9
				G.S.	
J	13.5'	138°21'		0.3	214.7
J					
	9+160	318°21			
	TP ①		219.1	rod	
				6.2	
				+9°42'	
~~K~~	~~47.9~~	~~83°30'~~	~~N83°30W~~	tr 00	
	46.5 H			+12x	
K	48.1	96°36'	N83°30W	14°39'	231.3
K					
					(Stake
V		276°30			
			234.7		(230.6)
	00			3.48	~~210~~ Stake 0.7 right
	34'			7.1	227.6
	60			26	238.1
	95.3			+13°31'	+22.9
L	98.3	96°30'	N83°30W	tr 00	257.6
L					
K		276°30			
			261.3		
	00			3.7	
	tape		+13.9		Stake 0.6 Rt
	411 113.4			18°43'	275.2
	865 tape		+28°	tr 00	
M	90.4			18°0'	289.3
	visible		+27.9	tr 2.0	
M	100'			18°53	289.2

Profile ℄

9

Rt.
98°

Profile & Traverse

M					
L		276°30'	292.7		
-	00			rod 3.7 +7°45'	289.3
Face rock	34'		+1.6	W 3.0	294.3
	254 (S)		80.2 ~~738~~	L - 4.0 -17°56'	212.5 ~~384~~
From J		run 276°30'	75'		
then		302°50'			
J					
Base line	P	318°21'			
	00	~~276°30~~	219.0	4.3 +24°30'	214.7
edge track	38.1 43'		17.4		201.6
N	82.05	276°30	N83°15W	-23°8'	186.5
N	B				
J		96°30'			
edge road	32	96°30		5.8	
	00		190.35	3.85 30°36'	184.5
S edge stk.	84.9 898.2	302°50			140.4
O					
N		122°50			
	00	(289°?)	144.0	3.6	
B	23	297°0		11.5	132.5
P	50.2	302°50			

Plan

Top stake 289.0
0.3 high edge road.

2475

465
953
861
2279

Top stake
0.6 high
for stake

0.8 Fill

(132.5)

Profile 4

P						
	O	46.45 47.9	122°50'		+14°33' -12.1 40.00	140.4
		00		128.3	38	
	Q	43 63.2	302°50'		-30°44' 32.3 +.00	96.0
Q						
		00		100.3	43	
	R	50.5 70.5	302°50'		-49.3 -44°15'	51.1
S						
	R	95° top 98.4	122°50'	-26.0	+15°21' 40.00	
		82	~~310°~~	25.4	13	23.8
	Water surf	63	310°50'		67	18.4
	B.M	60	98°50'		42	20.9
		00			4.6	20.5
		24.9 25.1/2			13° +5.7	30.8
		50.2 52.2			15°25' +3.8	38.9
	U	68.2 74'	302°50'		+22°50' +14.7	53.8

Traverse ℄ Plant 11

08hi.

Keelmark ~~—~~.
on rock.

Tieing in Core drill holes No 546. Johnson & Stebbins
June 10 - 1919.

Set up at Hole No 4
Plate set by magnetic bearing

H.I 250	Cor Wier	67'	100°10'	-3°37'	423	21.25	2543 / 2584	254	
	E	79'	180°5'	-3°08'	455	21.29			
	Point 1	80'	292°0'	+21°21'12"			Mag Bear S 68° E	29.1	74 9
Set up at Point 1									
H.I 573	Hole 4	00	3.25 above Point 1			540		3.25	
	Hole 5	44.	185°0'				Top casing	4.00	
	Point 2	47½	282°47	(4.00 +23°4			S 75° 45 E	18.6	437½
Point 2			H.I 759						
H.I 759	00	4.0							
	Hole 6	33'	315°10'	L-4.0 +15°0'	+45	804		85	31 9
	G	Nov 4 59	224°25	L-4.0 -2°1'		698	N 45° E		594

Note, This No 6 hole lost trig moved 5' down canon

Levels top Harris Dam to Stebbins Johnson's

June 10 - 1919

	Lower	dam site			
Top old dam	550	69.6	-4°36' 80 4.4	rod 48.4	21.2
Sand below Harris Dam T.P.	520		-0°54' 12 3.3	65.7	03.9
	505		-4°36' 81 4.3	44.7	24.9
TP.	153	02.0	+11°30 300 to 7.7	30.6 -22.9	
Stream bed Lower Site.				5.1	96.9
" below Wall				12.7	89.3
on Wall	150		60 20	+7.0	09.0
upstream face of wall	147	S12°15'W		4.7	97.3
	80'	N16°30'E		3.2	98.8
	100	S1°E	03.2	4.4	
	130	N9°W		2.6	00.6
	175	S30°45'W	05.8	5.2	
Below Harris dam.	270			2.5	03.3
	902	+30	97.2		

Corrected Elev

09.6 Top of Upper Concrete wall = Harris Dam - 21.2

97.9 River bed below Harris dam 03.9

99.4 River bed above lower wall 97.9

01.2 Top of wall

03.9 Lower Site = 09.6 (09.8) in old book

9.6

14461

14357

937

14461

Staking Crushers Plant.

A+M			
=0+34			1735.4
	34 1738.8		
0+50		8.8	1730.0
0+81.5		18.6	1720.2
			1703.7
	37 1707.4		
1+00		+3.8	1711.2

Quarry floor 1730'
0+50 - drops to 1717'
0+81.5 ℄ No 8C elev 1713.7
Level 5' more.
℄ of No 4 & 5 crushers
Sta 1+00 Base 1696.9
Crushers 12' c-c + 32' overall
Top of 4X4 stringer
14.3 on conveyor abt 1696.9 at 1+00
1+22.4 = 1701.65
2+35 = 1730.0

Quarry 1730'

Staking Plant
Rock + Sand Storage

Setup at J

K		96°30'		
	27.6 +12°			
2+35	26.9	96°30'		
End of S-R. Bulkhead	60'	145°0'	+22°40	
End S- Bulkhead	70'	171°30'	73' +	16°40'
Discharge from Sand Bin	41'	233°30'		
Cor. Sand Bulkhead	60'	244°30		
Cor. S+R Bulkhead	38'	267°30		
Rock Discharge	17'	302°		
Cor Rock Bin	38'	338°30	36'	15°10
Cor. Rock Bin	51'	34°		
End Rock Bulkhead	91'	78°36'		
			∠ 7010	
	104		+12°5.5"	
			∠ 7010	
	97'	78°20	12°40'	

Conveyor to Storage Discharge

Staking Plant Mixing Plant + Bins. Concrete Towers

N = 3+37.4

3+94.7 57.3' 66.4 3° 30'

G 0.5 12.2 1597.9 1585.7

+0.2 1598.1

5+73 959 +16° = 92' horiz.
92
6+65

Top Bins = Elev 16

Top Measuring Bin = El. 1620



℄ Concrete towers at 5+63 and 6+81

June 28. Locate holes No 7 & 8.

Inst @ A E S.38°45' E True Meridl bearing
H.I. = E+4'-0" Vert Angle to top of casing = 21°10' up

Ison Hole No 7 N. D. Top of casing + 3.6'
N 44°0' W to hole No 6
Vert Angle 74°21' down to top Casing hole 6
56°0' E to point 2
Up 22°17' 68.4' Slope measure to Top of Stake 1 + 2'
Vert Angle down 74°11' 87.8' slope measure to top of casing hole No 6

+13.95				112.60
	126.65	- 0.10		126.55
+12.8				
+13.25	139.35	-0.6	1	138.75
	152.0	-	-11.5	140.5
			+0.25	152.75

Top Casing hole No 7

Top of Stake I.
Top of Casing 9" above N.D.

See core drill log book page 11

June 28. Diatholes 6, 7, + 8. also well for temporary water supply

Dus at △ E.	N 57°00'E 95' to Casd well	
" at △ I	N 69°00'W to Hole #7	
" " "	H.I. = I + 3.75'	
	down 26°26' to Top casing Hole #7.	
" at △ I	up 11°17'	58.9' Slope Meas. to
	top of Casing hole # 6 + 3'	

Dus @ △ I N.30°30'W to well for Temp. Water supply
down 20°57' to top of well casing
Dus at Hole #7. H.I. = Top Casing + 3.92
down 24°20' to Top of Casing hole # 6
N. 44° 30' W. to Hole # 6
N. 57° 30' W. to Temporary well.



Johnson - Ahern. July 29-19 19

0 to 9+16.6 665

Camp Location

Traverse		along Road
A 1	74.1	chained
	165.9	Distances
2	99.4	between
3	137.9	traverse
4	127.3	points.
5	164.7	
6	132.4	
7	107.1	
8	166.1	
9	252.5	
10	228.0	
11	174.6	
12	101.4	
13	224.9	
14	177.7	
15	246.3	
16	89.5	
17	125.8	
18	132.8	
19	96.0	
20	.1	
	2951.0	

Johnson Ketchum

Stadia Survey along road toward Wilson Creek from Barrett dam site

Traverse of A Line

Setup		Dist (Hamilton)	Azim				
J		9416	318°21	S41°15'E			
	A1	118.5	235°30				
	A2	280'	225°33	N45°45'E			
	O		276°30'				
A2				HI 1648			
	J		45°33				
	A1	170 (1659)	38°45'	S39°15'W			
	A3	102 (994)	179°33	N0°0'W			
A3				HI 1651			
	A2						
1		29'	78°15'	∠-0.00 +40°50'		+24 1653	F Cor BH 16' Wide
2		72'	118°15'	∠-1 +3°0'		+28 1654	N " " " "
3		57'	66°30'	∠-00 +12°20'		+163 67	
4		27'	166°30		5.1		46 } Scr office
5		68'	157'		5.2		46 } 22 wide Wcr office
6		43'	210°30'	∠-14.0 -2°45'		160 352	Scr MH 30' wide N to other house.
7		~~153~~ 153	254°5.	∠-14 -14°40'		51 15 99.7	Scr BH-14' wide two of and 8' N of west
8		~~[illegible]~~	239°45'				intersect end house
9		122	271°45'	∠-14 -20°0'		525 787 53 98.1	105'
A4				HI 1650.6			
	A3	140 (1379)	328°15'		S31°30'E		
		53	10°30		5.1		45.5 Bend in road
		97'	12°30'		∠-to 0 49°25	+14.9 1665	Crown of culvert

		Dist	Azim	Mag Bear	∠ ° ' red	Elev DE	
				1650 G	∠-00		
	3	200'	26° 0'		16° 20'	54	1704
	4	135'	74°		∠-6 20° 38'	+44.3 27	171 178
	5	121	112°		∠-00 20° 52'	40.3	90
	6	44	340°		49		45
	7	39'	317°		∠-14.0 -3° 30'	16	34
	8	65'	262°		∠-14.0 14° 37'	29.9	20
	9	145'	268° 50		∠-14.0 -5° 46'	28.5	22.1
	A 5	130 127	165° 30	N14° 20' W	5.45		45 1
△5				Ht 1650			
	A 4		346° 6				
	a	150'	112°		∠-4 +4° 56'	8.8	59
	b	118	132° 30'		5.2		45
	c	118	145° 30'		∠-14.0 -2° 5'	18.2	32.0
	d	130	168° 10		∠-14.0 -8° 53'	33	16.4
	e	72	217° 15'		∠-14 -15° 28'	32	17.7
	f	177	257°		∠-14 -2° 50'	73°	1577
	A 6		121° 30'				
△4				Ht 1651			
	A 3	169 164	30° 20'				
		140'	19° 30		∠-10.0 +27° 30'	47	989
		400'	78° 40'		∠-10.0 +5° 10'	91°	1742
		625	93° 30'		∠-10.0 +14° 31'	+142°	1993
	A 7	137 132	98° 30'	N81° 30' W	53		

cont. From P 20

21

Top of ridge

Bottom draw

Top ridge

Con fence

Bottom draw

" " Top of ridge by buggy

Ht 4.95 above road Ht. 1650 ±

By tel. pole near bar.

Edge road

Con draw.

Fence corner.

On fence & top ridge

Bottom of draw

Levels along
stadia traverse
See P 22

BM.	8.8	1635.1		1626.3
A 1			+1.2	1636.3
	11.65	1647.95		
A 3			1.80	1646.15
	4.5	1650.65		
A 5			5.45	1645.2
	6.4	1651.6		
A 7			5.3	1646.3
	5.0	1651.3		
T.P A 10			-1.1	1652.4
	6.3	1658.7		
A 12			1.6	1657.1
	7.0	1664.7		
A 14			-.03	1664.7
	7.3	1671.7		
A 16			7.4	1664.3
	4.5	68.8		
△ 18			2.8	1664.0
	7.5	71.5		
△ 20			2.9	1668.9

at A 6

Road 935+85

1668.9 By Road Forks

A 9 — H.I 1651 3

A 7	276	330° 30'	S 29° 30' E			
	335	315°		16.9	34	
	310	301° 20		40.1	112	
	255			63	1588	
		63°	slope 21° from	100	33.5	161 7
		88° 15'				
A 8	170	338°		4.8		46 3
	75'	269°			30°	81 3
		203°	slope	34° 45'		
	155	138° 2W.		51		160 3
		160° 30				
	175	125°		35 4		157
TP 10	410	102° 30'	N 77° 30' W	−1.1		1652 4
△ 10	252½		H I 1654.3			
A 9	260	283° 35'	S 76° 15' E			
	135'	323°			295	83.8
		294 15'				
	115	45° 45'			36°	1690 3
	50'	206				242
T.P. 11	150'	99° 50'	N 88° 10' W	1.9		52 4
△ 11	228		H.I 1658 3			
A 10	235	278° 10'	S 80° 40' E			
	175'	354°			77°	1735 3
		188° 45'				
	165	67° 35'				171 54

cont. from p 20



Cr fence
Cr cut bank
bottom dry.

tel pole 1

Top ridge
~~Top ridge~~ ~~at 100~~ contours. 7 feet apart.

Top ridge across draw

Base of big rock 18' high. 5 feet
tel pole 822 x drain
ridge trends
guyed drain

Pt on ridge.

A 11							
		155°	Slope	24'	10'		
A 12	1744	180	106°20'	N73°45W			
A 12				H.I 1662			
A 11		180'	286°35'	S73°15E			
					∠-0.0	+	954
		90'	30°0'		+27°	364	
					∠-14.0		
		100	181°30		-21°30	482	13.9
A 13	1014	109'	92°0	N88°W			
A 13			H.I 1664'				
A 12		104	272°25	S87°35E			
					∠-4.0	+	
		210	20°		+25°30'	82°	1746
					∠-12.0	+	
		280	65°		+23°45	93°	1757
					∠-14.0		
		50	187°30'		-24°30'	329	312
					∠-14.0		
		110	186°20'		-19°38	487	1615
					∠-14.0		
		135	155°		-15°40'	49°	1615
A 14	2242	230	108°15'	N71°45W	-0.3		1664
A 14			H.I = 1669				
A 13		230	287°0'	S72°45E			
					∠-7.0		
		150'	32°		+32°35'		
					∠-10°	+	
		180	74°		+23°10'	55.0	1724
A 13	1772	182	115°20	N64°30W	2.5		
					∠-14.0		
		180	145°30		-12°22'	516	1615
					∠-14.0		
		247	146°		-8°16'	491	1620
					∠-10		
		430	122°50'		+8°10'	80°	1719
			219°15'				
					∠-10.0		
		370	117°45'		+7°28'	378	1707

Cont. from P20

P24

contours 11 ft apart

guessed dist

on rock face

4 4 4
4 9

straight up hill

152

172 draw

243 on rock ledge

425

pt on ridge N view

564 draw

A 14	300'	109°30		∠-10.0 +110°43'	+447	1714
△ 15						
A 14	177± 183'	296°0'	S64°E	7.3		
A 16	246± 255'	155°45'	N24°15W	7.4		
		213°				
		25-0				
A 16		H.I. = 1669±				
△ 15	253'	~~335°~~ 50	S24°E			
	148	72°		∠-5.0 +26°18'	+540	1723
		230°		-31°30'	-445	1625
	170	96°30'		∠-10.0 +15°0'	+325	1702
	250'	138°		∠-1.0 +22°10'	+860	1755 ~~1583~~
	300'	163°30'		∠-1.0 +19°34'	+850	1754 ~~1584~~
	310	180°15'		∠-5.0 +14°55'	+720	1741 ~~1571~~
△ 17						
△ 14	89± 92	303°35	S56°30E	45		
△ 14	125± 128	225°6'	N45°E	2.8		
△ 19	~~135~~		1671±			
18	132± 135	45°45'	S45°45W			
		290°		-35°0'		
A 20	94± 98	201°30'	N21°30'E	2.9	1668	6

Tie to Sect Cor		16 | 15 / 21 | 22	
A 10	N 37°30 W		
	213 / 218 ~~205~~	-16°	

290' top ridge

line of draw 12' W

draw abt 158' away

" " 130 "

119 near top ridge

bottom draw abt 85'

159 " " near water supply spring

214 ~~Top~~ boulder.

266

280

143' between 10' contours

angle of slope for 200'

Staking Road Quarry Floor to Barn

M. 00	36	S27°W	11.2	1746.3	1735.1
0+36	00			4.7	1741.6
1+72	136	N46°30E		7.0	1739.3
1+72	146 / 150	S51°30W	1722.8	-16.5	
3+18	00				
1+72	112 / 115	S37°15'W	1739	10.6	
2+84	00			4.6	35.3
4+70	186 / 190	N3°15'W		12.2	1727.7
4+70	61 / 62	S26°30E	-7.4	1720.1	
5+31	00			4.5	1715.6
5+72	41 / 42	N33°W	1c	18.2	1701.9
5+72	98 / 100	S64°E	-13.8	1688.1	
6+70	00			4.4	1683.7
7+40	70 / 72	N87°30W		11.1	1677.0
7+40	53 / 54	S9°30E	09	1677.9	
7+93	00			4.5	1673.4
8+53	60 / 62	N15°E	6d 12.8	16.5	1661.4
8+53	88 / 90	S0°30W	+20 4.5	-13.5	
9+41	00		1647.9	4.5	1643.4
A 9	147	N27°W		5.45	1642.4

Quarry floor 1730

grade.

1750 sr

1747.1

1736.2 8% grade.

1758 with uncrushed storage.



286

1703

@ 10%

470

1696.9

1692.8

grade

830

760

Staking Road from Quarry floor
To Barn

9+41	00				
A7				5.2	16427
Set up					
at 9+41 A7			5.2	1651.5	16463
A9	143 147	N27°W			
pt by tel post	312 ~~320~~	S87°40'E			1590.7
	546 ~~560~~	S18°45'E	-98'		
	00		1492.6		
a	68 70	S14½°W		+3.8	15030
b	110 113	S76°W		0.4	1499
c	205 210	N89½°W		3.3	1494
d	222 228	N60°W		13.9	1485
e	24 24'	S87°E			
f	169 173	N45°W		13.9	1485
g	69 71	S35°E		9.0	1490
h	177 181	N15°10'E		12.4	1487
i	190 193	N55°30'E		11.8	1487
j	212 217	S88°E		9.7	1490
k	263 270	S58°E		3.5	1496
l	103 106	S45°E		2.1	1497
Stable Road 0+00	133	N40°30'W		13.4	1479.2
0+00	224 230	S38°W	92	20.5	
2+24	00		1499.7	4.9	1494.8
4+04	180 183	N42¼°W	30 55	0.0	1499.7

end quarry road

467

Stadia survey near proposed barns

Tel line 4' west edge

east side flume

edge clear

rock bottom

cow barn 21' × 13' N88½°E

Rock bottom & ℄ flume

edge clear

Road from stable connect with Tax Barrett Campo road

~~Staking Road from Quarry floor to Barn~~ Barn floor to Barnett Canyon Road.

	193				
4+04	198			12.5	1499
5+97	00	S16°45E	1512.2		
edge culvert	8'	West		7.2	
	429				
10+26	~~440~~	N31°30W		6.7	1505.5
	317				
10+26	325	55°E		6.9	
13+43	00	00	1511.9		
	17	S48°W		4.6	1507.3
	310		44-77		
	318	N19°20W		20.4	1491.5
	Line from Wilson creek			9%	
	278		9d 7.1		
	285	N9½°W		32.1	1497.2
	00		1529.2		
	361		9d 3.7	+	
	~~370~~	S6°45'W		28.7	1537.9
	61		9d 3.4	+	
	63	N29°E		8.9	
	0.0		1546.8		
	180		9d 8.7	+	
	185	S48°W		7.5	1537.3
	264		9d 6.7		
	273	N53°W		30.6	
	66		1604.9		
	61		9d 3.8	+1.7	
	63	S16½W			1606.6

add 6.6 to elevations

200' of 6' wide to be built up

1513.9

~~X~~ concrete bridge marked 9.8 above bottom of grade on outlet

127 near oak at Wilson Xing

Road from Wilson Creek to top of ridge on 9% grade

278
9
2502

2.1 high

~~2.4~~ high

361
9
3749

1.5 high

19 low

18
9
1662
87
75

264
9
2394
67

0.2 low

1.0 hi old 822 + 23

OO = A 3740

~~Starting Point from Quarry to To Barns~~

Traverse of old road top of ridge to proposed barns.

125		1618.8			
~~128~~	N88°30E		12.2	1406.6	
50					
~~54~~	N44°E		5.1	1413.7	
156		16d - 5.7			
~~160~~	S49¼E		30.7	1548.1	
300		16d 0.2			
~~308~~	S35°E		48.2	1570.6	
51					
~~54~~	N77°W	10d 47	-0.4	1570.4	
00		1570.2			
108		10d 6.1			
~~111~~	N29°30E		14.9	1553.3	
136		18d 5.4			
~~140~~	S14°W		-19.1		
02		153 4.2			
131		8d 11.8			
~~134~~	N83°E		22.3	1571.9	
29					
~~30~~	N3°30W		5.0		
00		1566.9			
114					
~~117~~	S32°E		10.3	1506.6 ~~1446~~	

Road from Barns to connect with Barnett Campsite Road.

Old 822+25

Pt Triangulated to ~~a~~ corner on old road OO = Beginning.

E line from Top ridge to Barns.

57a

4+04 of first line from barns

concrete Bridge	414 ~~425~~	S 59°30'W	70.122 —	−16.8	1513.9
	00		1497.1		
center Wilson Crk Bridg	20	S 20° E		5.8	
2+73	273 ~~280~~	S 54° E		5.0	1492.1
2+73	247 ~~253~~	N 62° W		7.0	
5+20			1499.1		
7+93	273 ~~280~~	S 12°15' E		−0.1	1499.2
7+93	82 ~~84~~	N 28° W		7.3	
8+75			1506.5		
11+77	302 ~~310~~	S 1°45' E		3.6	1502.9
11+77	232 ~~238~~	N 13°50' W	10.23	0.0	
14+09			1502.9		
14+84	75 ~~77~~	S 5°15' W		7.6	1495.3
~~14+84~~ ~~16+72~~	137 ~~140~~	N 12°30' W		−0.1	
16+21	00		1495.2		
19+26	305 ~~313~~	S 39°15' E		8.0	1487.2
19+26	152 156	N 47°50' W		8.6	
20+78	10 258		1495.8 1.8V 8.5		
23+36	~~260~~	S 64° E		+37.9	15 337

414 − 375 = 39

290 − 122 = 168

Road from Wilson Creek Bridge across Cottonwood Creek and South to Damsite and Cableway Towers.

758 − 54 = 704

704 − 240 = 464

464 − 8 = 37.9

	445		12d 39		
23+36	460	N41°50'W		57.7	1533.7
27+84		N'	1591.4		
29+30	146 ~~150~~	58°E	14d 64	+16.0	1607.4
29+30	361 ~~370~~	N9°W	7d 5.6	30.9	
32+91	00		1638.3		
cor bend.	179 184	N4°W	7d 41	14.6	1621.7
"	110 113	N39°E		11.3	1627.0
"	112 115	S2°15'E	1d 00		1639.4
36+24	333 ~~342~~	S25°30'W	6d 21	+17.9	1656.2
36+24	148 ~~152~~	N13°E		10.1	
37+72	00		1666.3		
H Bas. Line 9+16.6		N188°30'W			
39+83	211 ~~214~~	S54°W	14d 54	+24.1	1690.4
~~47~~+88	405 ~~413~~	N31°E	8d 50	37.4	
43+88	00		1727.8		
H B.L. 9+16.0		N49°W			
		N53°25'W	-7°13'		
CH&OBM on Upper road	405 ~~413~~	N48°E	10d 73	+33.2	1761.0
45+93	205 210	S1°15'E		00.	1727.8
	191 ~~194~~	N0°W	1740.5	12.7	
47+84	00		~~77~~		
	124 127	S30°E	10d 79		1745



			17405		
	177				
X	~~182~~	S24°E	10v 14.2	+3.5	1744
	205				
	~~210~~	S5°E	4v 5.1	+3.1	1744
		N80°20'W			
	244		4v 8.1		
	~~250~~	S23°15'W		+17	1742
	180		2v 4.0		
	~~185~~	S23°W		6H	1740
	102				
	~~105~~	S14°W		2.0	17385
1 Telpole under cableway Pole No2		N85°W	-8°54'	1385	16020
		N64°30'W	-7°36'	1365	1604
3		N53°30'W	-6°43'	1280	1612
4		N41°W	-6°1'	1145	1626
			~~-7°36'~~		
	On upper road				
C4+05					
Tel Pole 4		N81°30'W			
		S89°W			
		S79°15'W			
1		S63°20'W			
C4+05	249				
	~~255~~	S72°W	7v 9.2	26.6	17610
C6+54	ov		17874		
	99				
C7+53	102	N49°30E	6v 3.5	+25	1790'
	421				
C7+57	~~432~~	S41°45'W	1v 2.2	-20	
11+74	ov		17881		
	270	S23°15'W		19.5	
C13+86	~~217~~	N42°E	6v 11.6	+11.1	17892

end of exc.
~~end~~ & sheave West cableway

end of exc.
& Cableway

13+86	317 ~~325~~	S 62°W	30 10.2	0.7	17892
			17899		
	113 ~~116~~	S 37°W		5.3	17846
17+03	00				
17+75	72 ~~74~~	N 69°45'E		70.1	1790.0
	234		6d 12.5		
17+75	~~240~~	N 87°45'W		26.5	
bend	78	S 37°30'W	~~18165~~	12.2	
20+09			18165		
21+84	175 ~~180~~	N 60°E		46	1811.9
	253		2d 12.8		
21+84	~~260~~	S 51°15'W	4d 12.5	17.9	
	170	S 29°30'W		19.1	18107
24+37	00		1829.8		
C 27+57	320		~~148~~		
23 = 04	~~328~~	N 73°E		14.9	1814.9
equation for					
Re-do in road					
C27+57 = C28+81					
C 24+37			1829.8		
- D 0+00			10d 8.4		
D 1+56	154 ~~162~~	S 57°30'W		24.0	1805.8
	126		10d 13.1		
	130	S 88°30'E		4.5	
D 2+82	00	S	1806.3		
	151		12d 4.9		
	~~155~~	N 62°30'W		23.0	1783.3
	299		12d 5.1		
	~~307~~	N 82°30'W		41.0	1745.3
D 7+79	497 ~~510~~	S 89°W	12d 5.8	65.4	1740.9

Garrett summit. n ~~road~~ road.

East of Saddle. on road.

234
146
88

5.9
12.8

491
17
474
97
497
496

596
58
654

7+79	5+27 ~~5+40~~	N75°E	180 11.2	-83.7	1740.9
13+06	00 122		1645.2		
14+28	~~1+15~~	S29½W		7.0	1650.2
14+28	166 ~~1+70~~	S44°30'E	20v 78 1624.8 4d 10.6	-25.4	
on road. C 29+30	60 180 ~~185~~	N2°W		18.2	1606.6

527
18
4216
527.

449
112

flagpole side draw -

332
78
254

166 old 1607.4

175 Contour

Setting Flags on.

BM:	6.48	186.69			180.210
40.2	285				
9+16.6	~~292~~	534° W		1345	173.24
	00				
	246				
	~~250~~	N12½° E		1107	175.62
	373				
	383	S42½° E		596	
			181.58		
	373				
	~~383~~	N54° W		640	175.18
	1043				
	~~1070~~	S30° 30' E	181.58	640	
	716				
	~~730~~	S14° 15' W		560	175.98
	756	S56° W		670	174.88
A:20	575		80 35		
	~~590~~			+425	2241
	22'	N57° E		666	175.0
	249		60 61		
	255	S88° E		210	160.6
	558	N2½° E		603	175.58

Aug 1 - 1919

Johnson - Kelchum

35

Red Flag.

Top Stake below cookhouse

below Barn 12' from fire

(west ∠ - 21° to bottom creek straight South)

on point on bank inside road

old 822+25 24.9 1406.7

Top of stake

B	17 ~~18~~	N16°15'W		0.2
P.I.	~~30~~ ~~34~~	N24°45E	✓	
	~~60~~ ~~62~~	N8°E		
	285	S79½°W		
	325	S73¼E		
G	374			
	365	S68°30E	✓	
	402	S61°30E	✓	
	439 ✓	58°30'	✓	
	476	54°	✓	
	512	50	✓	
	502	49°	✓	
	461	52°		
	392	55°30'		
	315	58°30'		
E	91 ~~95~~	N37°E		3.8
	34 ~~35~~	S29½E	✓	

At ⊡ #1

P-Line 2+71.75	Fill 0.4	5.72	25.47		19.75
			grade Out	5.32	20.15
0-0 2+71.75	31-5	88.9			N 35°-0 E
Point of Rock	57.2				S 12-45 W
⊡ #2	381.0		~~350'~~		S 8°-0 W
Hub on ⊡ #2		4.43	27.97	1.93	23.54
End of Level section = 0.0				7.82	20.15

At ⊡ #2

Beginning of 0/0 0-0	274.0 N				N-3°-0 E
	Grade				
0+25	7.57				N 2°-0 E
0+50	7.32				N 0-40 E
0+75	7.07				N 0-45 W
1+00	6.82				N 0-45 W
1+25	6.57 ✓				N 1°-30 W
1+50	6.32 ✓				N 2°-15' W
1+75	6.07 ✓				~~N 4°-10' W~~
2+10	5.72 ✓				N 18°-15 W
2+25	5.57 ✓				N 23°-30 W
2+50	5.32 ✓				N 16°-0 W
2+75	5.07				N 19°-0 W
⊡ #3	212.0				S 12-30 E
		4.52	29.52	2.97	25.00

14/9/19 Continuation Quarry Road (OR)

37

Grade

El Floor Quarry 1737.0

El = Road 1740.0

37' back from ⊡ #1

3+07 P Line 7.58 1742.52 1734.94

17400

Road 2.52

P Line

℄ 2+71.75 5.88 1725.63 - 1719.75

1740 = Road + 14.37

Fill	20.5	6.1
Fill	27.5	13.1
Fill	24.7	10.3
Fill	25.1	10.7
Fill	24.1	9.7
Fill	19.4	5.0
	10.88 1750.88	1740.00

0+00 =	10.88 ✓
0+25	10.63 ✓
0+50	10.38 ✓
0+75	10.13 ✓
1+00	9.88 ✓
1+25	9.63 ✓
1+50	9.38 ✓
1+75	9.13 ✓
2+00	8.88 ✓
2+25	8.63
2+44	8.44 1742.44

Hole No 6	82 ~~84~~	N51°E	Ad 1285	16.1	1526.5
10	11	S34°30'E	1548.6 ∠ -3.0	2.0	1540.6
11	~~87~~ 84	S28°45'E	+22°48	+30.7	1573
	~~34~~ ~~35~~	S29°E			

AT ⊡ #3 BI

2952

3+10	6.27				N 4°-0W
3+25	6.12				N 4°-45W
3+50	5.87				N 8°-20'W
3+75	5.62				N 8°-30'W
4+00	5.37				N 8°-30'W
4+25	5.12				N 8°-30
4+50	~~4.87~~				N 17°-15W
4+75	~~4.62~~				N 22°15 W
5+00	4.37				S 21°-0 E
5+25	4.17			1.0	S 22-15E
5+50	3.87				S 29-30 W
⊡#4	58.3				S-25-15W
		4.40	32.91	1.01	28.51
5+75	7.01				S 9°-0E
6+00	6.76				S 25-45E

Continued Page 55

804
1446.1

1526.5
1.0
1542.6

90 above GS

80.1 dust

12/19/19 Continuation Quarry Road -

1750.88 OK

9.36 · 48.83 11.41 1738.47

Rod

2+44	6.39			1742.44
2+90	5.93			1742.90
3+00	5.83			1743.00
3+25	5.58			43.25
3+50	6.38			43.50
3+75	5.08			43.75
	6.01	1751.15	3.69	45.14
#				
4+00	44.50		7.15	
	11.44	1752.05	10.54	1740.61
4+25	44.25	C-3.0	7.80	
4+50	44.50		7.55	
4+75	44.75		7.30	
5+00	45.00		7.05	
5+25	45.25		6.80	
5+50	45.50		6.50	
5+75	45.75		6.30	

Cont. Page 55

	150		L-14		
M	155	S24°W	-6°49'	32.0	1735.1
	00		1767.1		
on rock	127	N28¾E	40.20	+2.6	17697
	169				
	~~173~~	S56°30E		15.5	
	60		1785.2		
	52	S74°E		13.1	17721
	5'	N0°W		13.0	1772.7
	3'		20		
	~~93~~	S7½°W	98	+8.4	17936
	draw		N30°W		
	181		20	+	
	~~186~~	S34¾°W	106	25.6	8810.8
	195		100	+	
	~~200~~	S79°30W	142	5.3	1790.5
H	~~177~~		-18°10'		
168	~~182~~	N40°W	to 100	65.1	1720.1
	00		1774.3	4.6	17697
	45	N47°W		0.5	17738
14	~~48~~	S43°W	L-14 -7°30'	16.3	1758.0
	18'	S40°E	to	1.760	
	31	S86°E	104 137	16.8	17575
	31	N16°E		14.2	1660.1

46



mountain with three draw

36

13 thru draw

Top ridge

Along Dyon's Valley Road

A20	307 ~~345~~	S45°30W	11.8	1680.4	1668.6
	00				
Bend in road. Top Tel pole.	325	N12°W	20 43 +9°43		
		N29°30W			
TP	530 ~~544~~	N26°45E	20 1.9	+8.7	1689.1
	344 ~~353~~	S51°E	4.8	1693.9	
	00				
	917 ~~940~~	N68°15W		5.8	1688.1
	468 ~~480~~	S64°E	5.5	1693.6	
	00				
	1053 1080	N57°30W	20.33	+17.8	1711.4
	912 ~~935~~	S53°15E	3.0	1714.4	
	00				
	543 ~~557~~	N68°30W	20 31	+ 7.8	1722.2
	916 ~~940~~	S65°50E	12.6	1734.8	
	00				
	314 322	N56°30W		8.6	1726.2
	297	S67°45E	4.9	1731.1	
	00				
	188	N88°30W		5.2	1725.9

Johnson 40
Stebbins

E side road

10.4

21.3 +1. PK 70' E of gate.

9.3

10.9

41.7
41

217 223	S52°10'E	4.9	1730.8	1725.9
00 239 245	N66°15W	1.8		1729.6
410 421	S49°15E	4d 12.2	28.6	
00 190 195	N53°45W	1757.6 140 65	+20.1	1777.7
96 98	N28°45E	1d 13.9	14.9	
241 247	S62°30W	1792.6 20 00	+4.8	1797.4
456 468	N72°45E	4d 9.9	28.1	
00 247 253	N77°15W	1825.5 40 3.4	+ 6.5	1832.0
327 335	S45°E	2d 12.1	18.6	
00 748 788	N71°10W	18506	+3.5	1854.1
348 357	S59°45E	20 42	=2.8	
366 375	N53°15W	18513	00	1851.3
64 65	N39°E		1.2	
87 89	S39°45W	1852.5 12d 12.5	22.9	1829.6

Pile rocks opposite fireplace

Tie to Transformer Sta.

At	222		L-3.0
A1	~~228~~	N26°15W	+21°35
	206 horizontal		

Measurement of Water in Wilson Creek abt 600' below ~~x~~ of fireplace.

Creek filled canteen in seven seconds. Canteen holds $\frac{22}{16}$ gallons.

$\frac{22}{16} \times \frac{60}{7} \times \frac{60}{1} \times \frac{24}{1} = 17{,}000$

17,000 Gallons per day

Road to Guest House

AG 90+50			1651.6	5.0	1646.6
			6v = 2.5		
1+00	50	S49°E	10v 8.0	+0.5	
2+00	150	S47°E		+7.0	1658.6
	273		6d 5.5	21.9	
	~~280~~	N12°30'W	6d 5.5		
	180	N12°W	6d 5.5		
	80	N23°45'W			
	00			1680.5	
	20	S1°W			
	70	S20°45'W	6v 5.5		
	25	S22°E		13.3	
	54	S37°W		10.2	



Set up on P 7 J.

East Cableway Tower		S 27° E
Tel Post #1	-4° 8'	S 15° 13' W
2		S 27° 30' W
4		S 22° W
Center Cableway Tower		S 29° 30' W
ground under cable	+4° 56'	S 28° 45' W
aft ~~west~~ end dam		S 6 1/2° W
east under cableway		S 10° 45' W

Electric Power Line

Bearing of N 34° 15' W

Set up on A 1

16363

1/5/10 47

Occupy 18-488 Sight

C R for - Zero Chained ~~to~~ 17 25

toward Center = 18-470.75

Nail in Rock —

16608 Chained ~~to~~ 14 17 North

+765 Nail in Rock = 18-502 17

37

-42 0

Topog — Johnson & Stebbins

241 / 247	N27°10E	8d 11.4 / 1934	30.7	1467.3
00 / 105 / 108	S10°30W	1498.0	5.2	1492.8
91 / 93	N11°10W		10.0	
31 / 37	S56°E	15028	2.8	1500.
52 / 63	S41°E		4.2	1498.
95 / 97	S12°30E		4.0	1498.8
171 / 175	N35°15E		12.4	
125 / 128	N41°30E	1511.2	11.1	1500.
108 / 110	N50°30E		10.9	1500.3
103 / 106	N67°45E		12.1	1499.
65 / 67	N60°E		14.0	97.2
49 / 50	N71°30E		10.1	01.1
Sta 9+16.6 Tel Pole	N3°15W			
	S78°W			
12	N1°W		13.7	99
17 / 47	S5°W		13.7	97.5
48 / 72	S6°30E		11.6	99.4
74 / 89	S30°30W		11.8	99.2
91 / 92	S34°45W		11.1	00.0
T.P. 94	S37°W		15.9	1495.3

East Edge Weir in Old Harris Dam

45

241 / 1928

21.2 / 1446 X / 1467.3

Bottom Drain

6" up = 4 ft 2 in

BM-303

78/80	S29°45W		485	1495.3	
		1500.1			
		4414.0			
74/78	S50°15W		17.0	1483.1	
85/87	S35°15W		11.8		
		1494.9			
102	S37°W		14.6	80.3	edge drift
45	S24°W		14.6	80.3	
37	S9°30W		14.8	80.1	bottom drag
19	N20°W		16.2	78.7	at 19 in Cr canyon
86	N59°45E		13.6	81.3	Bottom drag
102	N44°E		15.0	79.9	
142	N39°E		14.7	80.2	
187	N29°30'E		16.3	78.6	
181/186	N17½°E		14.1	1480.8	
59	N32°30W		2.7		
		1483.5			
50	N67°30W		13.1	1470.4	
22	S90°W		13.5	70.0	bottom drag
65	S64°30W		13.7	69.8	
90	S54°W		1.39	69.6	
100	S37°W		1.37	69.8	bottom drag
Tel pole	S62°15W				
	N24°45W				

7.6/30.4

30.4
1444
9.6.5

			14835		
	115	S44°W		12.8	70.5
	~~130~~ 127	S44°15W		11.9	1471.6
	~~95~~ 93	N32°15E	2052	3.3	
			14749		
	53	N31°15E		4.7	70.2
	34	N 54 E		5.6	69.3
T.P.	27	S53°W		14.6	1460.3
	116	N37°30E		0.5	
			14608		
	78	N48°E		1.1	59.7
	53	N62°E		0.8	60.0
	40	S82°E		0.9	59.9
	39	S69°30E		4.6	56.2
	23	"		17.0	1443.8
T.P.	49	N75°30W		4.8	1456.0
	56	N43°30E		12.0	45.8
	106	N25°E		15.2	45.6
	~~173~~ 169	N22°15E		15.0	1445.8
	93	56°W		4.8	56.0
			14506		
	11	S83°E		1.4	49.2

1846 1.9

on pt
of flat dam

Set up on old dam 13' wide

Center dam E edge
" " bottom break
Temp. steel dam

		14506			
			20v 22	+	
37	S83°E			5.7	14558
			20v 1.1	+	
67	S85°E			12.3	14625
20	N83½°W			1.9	48.7
			10v 28		
35 36	"			10.7	57.3
07			10v 15	+	
69	"			5.2	14558
106	N1°W			3.9	14467
118	S16°45'E			10.7	39.9
		14374			
		+4665			
75	S36°E			8.4	49.0
66	N86°30'E			8.0	49.4
33	N41°E			6.7	50.7
			10v 160		14510
96	N36°30'E			+64	14601
34	S25°W			7.2	50.2
40	S10°E			6.5	50.9
58	S4½°E			6.5	50.9
					14493
82	S28°E			8.1	14584
123			4d 142		
126	N50°30'E		49	19.1	
73			14684		
			14775		
73	N31°30'E			16.0	14524
23	N50°E			12.2	5.62
20	S12°30'E			4.6	14638
					14329

46

bottom slope 20° E

~~about 10 east. Uphill slope~~

against hillside

	61 63	N11°30E	1478.1 1487.2	14.3	1463.8 ~~1472.9~~
	37	S14°E		10.1	1468.0 1477.1
	90	N6°45E	4.53 1469.7 ~~1478.8~~	17	
	45	N25°E		9.2	605
	11	S49°E		8.8	609
	56	S5½W		10.9	548
Old T.P.	99	S10°W		13.8	1435.9 ~~1445.7~~

foot of calipers

09.8 elev given in old book.

1446.1
1435.9

Tie Hole 14



Set up at					
X-1	D7				
B		10.4	1588.8		1578.4
14			+109'		1589.8
			-0.2	+1.0	

Top Casing





Top		Hor	+15° 37'		
Stake B		Dist 28.9	-8.1	1570.3	1578.4
Hole					
15			9.8		1560.5

Staking Curtain No

E.	3.9	1471.3	Dist		1467.4
0			9.8	13	70.1
20				45	66.8
40				47	66.6
60				36	67.7
80				00	71.3
100				16.6	67.9

		C 3.0			C 3.0
00	Rock 1467	5.3	C 3.0 8.6		16.3
0+20	43	C 24.0 3.80			24.0 50.2
0+40	"	C 24.0 380			C 24.0 502
0+60	145.2	C 15 24	C 16		C 15.0 36.0
0+80	1465	C 6.0 1.0	C 4		C 6.0 22.0
1+00	1472	C 5.9 0.5	C 5.9		C 9. 11.3



110	7° 52.7'	10	43'
120	8° 35.6	20	1° 26'
130	9° 18.6	30	2° 09'
140	10° 1.6	40	2° 52'
150	10° 44.6	50	3° 35'
160	11° 27.5	60	4° 18'
		70	5° 01'
		80	5° 44'
		90	6° 27'
		100	7° 10'

6) 430
42
10

Ry Track E side

canan to dump below suspension bridge

T.P. Wall	13.0	1480.3			1467
T.P.				6.9	1473
125' dist.	11.4	1484.8			

Setting Grades

	Grade Rod		
1+00			1.8
1+44			2.7
2+25			4.3
3+08.3			5.7
T.P			2.8 1482.0

66'	12.2	1494.2			1474.7
2+88	Dist				
2+72	56			17.0	1477.2
2+56	40'			22.5	1471.7
2+40	24	S 33° 10' W		19.2	1475.0
2+24	8			3.0	1491.2
2+08	8'	N 33° 10' E		4.7	1489.5
1+92	24'			6'	1488.1
1+76	42			11.8	1482.4
1+60	58'			14.7	1479.5
1+44	74		-1°23' to 20°	21.8	1472.4
1+28	90			12.0	1482.2
1+12	106		Cd 115	17.9	1476.3
0+96	122			12.0	1482.2
0+80	136			11.0	1483.2

212

1446.1

1462.3

Grade

1467

1.8

1485

Grade 00 = 1485

1483		
1482.1		
1480.5		

CUT

Grade		
79.24	2+25	2+81 C 0.5
79.56		F 2.4
79.88		F 8.2
80.20		F 5.2
80.52		C 10.7
80.84		C 8.7
81.16		C 6.9
81.48		C 0.9
81.80		F 2.3
82.12	1°57'	F 9.7
82.44		F 0.2
82.76		F 6.5
83.08		F 1.9
83.40		F 6.2

	Dist	4.65	HT		Top Wall
~~0+80~~	~~85~~		14720		14673
0+80	85			2.1	14699
0+64	69			2.1	14699
0+48	53			2.7	14693
0+32	37			4.1	14679
0+16	21			3.9	14681
0+00	5			4.8	14672

1485.40
83.72
84.04
84.36
84.68
1485.0

F138
F14.7 or 2% grade
F16.5
F16.6
F17.8
Grade at 0+00 = 1485

Bent No	Left			Rt. = West of ℄
①	0+00	+5.5 / 115	F17.8 00	-0.3 / 10
②	0+16	+5.5 / 130	F16.6 00	-1.5 / 10
③	0+32	+5.5 / 117	F16.5 00	-1.4 / 10
④	0+48	+5.5 / 97	F14.7 00	-2.6 / 10
⑤	0+64	~~+5.5~~ / 97	F13.8 00	-2.5 / 10
⑥	0+80	+20 / 100	+20 / 3 F02 00	-80 / 8 -14.0 / 10
⑦	0+96	+3.7 / 10	+5.7 / 5.0 F04.9 00	-8.0 / 5 -8.0 / 1.0
⑧	1+12	00 / 50	F05.00 00 / 5	-1.5 / 7
⑨	1+28	On Boulder. good for	FOR	

4 feet off
foundation by shooting top of boulder

10	1+44	+10.2 / 9.0	+0.9 / 4.0	F9.7 / 0	-6.5 / 100	
11	1+60	edge of boulder / bedrock / rff / 0.0 / 3.0		F2.3 / 0.0	-1.2 / 5.0	
12	1+76	+2.2 / 7.0	C0.9 / 0.0	-2.3 / 5.0	-4.8 / 8.0	
13	1+92	dirt / +0.8 / 10.0	C0.9	-5.1 / 5	-7.2 / 10.0	
14	2+08	0.0 / 1.0	C8.7 / 0.0	-5.8 / 10.0		
15	2+24	+4.8 / 12.0	C10.7 / 0.0	-4.6 / 10.0		
16	2+40	~~+5.0~~ / 5.0	F5.2 / 0.0	-10.0 / 8.	-11.3 / 10.0	
17	2+56	+5.4 / 5.0	+5.5 ✓ / 2.0	+0.8 ✓ / 2.0	F8.2	-2.8 / 8 -6.1 / 10.0
18	2+72	+5.5 / 11.0	F2.4	-1.7 / 4.0	-7.2 / 7	-7.2 / 10
19	2+88	+4.5 / 7.0	C0.5	-2.5 / 5.0		

Boulder 8' diam broken will make another 16' [illegible]

5 2 1 / 7 2 2

Dirt & Coarse Rock

abt 25% loose rock

Grade for flume thru Halus Dam

	Rod	Dist
Sandmpace at coffer dam	2.9	170
Top West edge weir	2.7	48



6+25	6.51	S-18°-30E
6+50	6.26	S 19°-15E
6+75	6.01	S 20°-0E

Bottom flume ± 18
G. Rod.

6.9

8.0 + 1.33 to bottom stringers
= 9.33 G.R.
2.7
6.63

1752.05

12.05 52.66 11.44 1740.61

6+50	46.00	6.64
+25	46.25	6.41
+50	46.50	6.16
+75	46.75	5.91
7+00	47.00	5.66
7+25	47.25	5.41

Adjustment of Transit

Lag Scient Base		5.365	
~~Pt. of~~ Tel Pole			
75' S of office			
		5.410	045
		6.115	
		6.160	0.45

Hard lined Cot. Oak to Sandstone

Pin 4 Cott

W.S.	68		
		4.1	2.7
	13.0	15.7	
		1.1	14.6
	8.1	22.7	
		2.0	20.7

6.03
.45
5.985

5.969
.45
5.915

12/15/13 Road & Landing To Storehouse

Sub-Fisher	Grade	+	=	−	Elc
Floor of Store House	3000 ft. S. to 2 parts/65 X	2.25	1653.60 ~~1702.25~~		1651.35 ~~1700.00~~
Floor of Landing				5.75	1647.85
20'				6.75	46.85
40'				7.75	45.85
60'				8.75	44.85
Butt in Tele. pole 75'S. of office		1.58	1646.88 ~~1695.53~~	8.30	1645.30 ~~1693.95~~
T.P.		2.15	1638.65 ~~1687.30~~	10.38	1636.50 ~~1685.15~~
00-429				8.09	1630.56 ~~1679.21~~
					30.56

Elev of stakes along travers of upstream line of dam

57

Sta	Stake Marked	Top Stake Elev	Ground Surface elev
0+00	A	150 5	1596.6
0+62 8	B	132 3	1578.4
0+82 3		124 2	1570.3
1+23 0	C	102 6	1548 7
1+74		69 6	1515 7
2+03 0	D	58 6	1504 7
2+32.1		44 0	1490 1
2+43.2		26 6	1472 7
2+71.8	E	21 3	1467 4
3+36.8		20 6	1466 7
3+56.8		27 3	1473 4
3+76 8		34 5	1480 6
3+98 3	F	43 9	1490 0
4+08 3		45 9	1492.0
4+42 9	G	69 8	1515.9
4+86		78 4	1524.5
5+35 9	H	101 9	1548.0
6+16 8	I	140 5	1586.6

	Sta	℄ Plant Elev G.S	℄ Plant Elev Top Stake	Sea level Elevation Datum Elev GS	Sea level Elevation Datum Top Stake
	0+00	294.3		1740.4	
M	0+34.0	289.0	289.3	1735.1	
	0+79	275.2		1722.3	
L	1+20.1	257.0	257.6	1703.1	
	1+55.4	238.1		1684.2	
	1+81.4	227.6		1673.7	
K	2+15.4	230.6	231.3	1676.7	
J	2+61.9	214.7	GS.	1660.8	
	3+00	201.6		1647.7	
	3+05.4	185.1		1631.2	
N	3+37.4	185.9	186.5	1632.0	
O	4+21.8	139.6	(Knocked off) 140.4	1585.7	
P	4+68.2	123.7	124.5	1569.8	
Q	5+22.5	96.0	Reel mark. rock	1542.1	
R	5+73.0	49.5	Top ingrain 51.1 by trail	1495.6	
	5+86	23.8		1469.9	
	6+05	18.4		1464.5	
S	6+68	20.5	K	1466.6	
	6+92.9	30.8		1476.9	
	7+18.2	38.9		1485.0	
U	7+36.2	~~53.6~~	53.8	~~1499.9~~	1499.9

Page 4 x

8% = 1°

1°30'

488

1725.4°

47°75'

20

$\frac{1}{3} \cdot h \cdot r$

455

1 x 17

50

Base = $\pi r^2 \cdot \frac{2}{9} r$

$h = \frac{2}{3} \cdot r$ $\frac{2}{9} \pi r^3$

$\frac{22}{7} \cdot \frac{2}{9} = \frac{44}{63} r^3$

$\frac{2}{3} r^3$

$r = 10$

$\frac{2}{3} r^3 = 5000$ 1000

$r^3 = 7500$ 20 20 400 20 8000

20

4-455

18-303
4-330
0-330

0-28

0-429.

El Rhany
Floor

1/140

Page 37

DISTANCES FROM CENTER OF ROADWAY FOR CROSS-SECTIONING.

ROADWAY 14 FEET WIDE. SIDE SLOPES 1½ TO 1.

FOR SINGLE TRACK EMBANKMENT.

	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	
0	7.0	7.2	7.3	7.5	7.6	7.8	7.9	8.1	8.2	8.4	0
1	8.5	8.7	8.8	9.0	9.1	9.3	9.4	9.6	9.7	9.9	1
2	10.0	10.2	10.3	10.5	10.6	10.8	10.9	11.1	11.2	11.4	2
3	11.5	11.7	11.8	12.0	12.1	12.3	12.4	12.6	12.7	12.9	3
4	13.0	13.2	13.3	13.5	13.6	13.8	13.9	14.1	14.2	14.4	4
5	14.5	14.7	14.8	15.0	15.1	15.3	15.4	15.6	15.7	15.9	5
6	16.0	16.2	16.3	16.5	16.6	16.8	16.9	17.1	17.2	17.4	6
7	17.5	17.7	17.8	18.0	18.1	18.3	18.4	18.6	18.7	18.9	7
8	19.0	19.2	19.3	19.5	19.6	19.8	19.9	20.1	20.2	20.4	8
9	20.5	20.7	20.8	21.0	21.1	21.3	21.4	21.6	21.7	21.9	9
10	22.0	22.2	22.3	22.5	22.6	22.8	22.9	23.1	23.2	23.4	10
11	23.5	23.7	23.8	24.0	24.1	24.3	24.4	24.6	24.7	24.9	11
12	25.0	25.2	25.3	25.5	25.6	25.8	25.9	26.1	26.2	26.4	12
13	26.5	26.7	26.8	27.0	27.1	27.3	27.4	27.6	27.7	27.9	13
14	28.0	28.2	28.3	28.5	28.6	28.8	28.9	29.1	29.2	29.4	14
15	29.5	29.7	29.8	30.0	30.1	30.3	30.4	30.6	30.7	30.9	15
16	31.0	31.2	31.3	31.5	31.6	31.8	31.9	32.1	32.2	32.4	16
17	32.5	32.7	32.8	33.0	33.1	33.3	33.4	33.6	33.7	33.9	17
18	34.0	34.2	34.3	34.5	34.6	34.8	34.9	35.1	35.2	35.4	18
19	35.5	35.7	35.8	36.0	36.1	36.3	36.4	36.6	36.7	36.9	19
20	37.0	37.2	37.3	37.5	37.6	37.8	37.9	38.1	38.2	38.4	20
21	38.5	38.7	38.8	39.0	39.1	39.3	39.4	39.6	39.7	39.9	21
22	40.0	40.2	40.3	40.5	40.6	40.8	40.9	41.1	41.2	41.4	22
23	41.5	41.7	41.8	42.0	42.1	42.3	42.4	42.6	42.7	42.9	23
24	43.0	43.2	43.3	43.5	43.6	43.8	43.9	44.1	44 2	44.4	24
25	44.5	44.7	44.8	45.0	45.1	45.3	45.4	45.6	45.7	45.9	25
26	46.0	46.2	46.3	46.5	46.6	46.8	46.9	47.1	47.2	47.4	26
27	47.5	47.7	47.8	48.0	48.1	48.3	48.4	48.6	48.7	48.9	27
28	49.0	49.2	49.3	49.5	49.6	49.8	49.9	50.1	50.2	50.4	28
29	50.5	50.7	50.8	51.0	51.1	51.3	51.4	51.6	51.7	51.9	29
30	52.0	52.2	52.3	52.5	52.6	52.8	52.9	53.1	53.2	53.4	30
31	53.5	53.7	53.8	54.0	54.1	54.3	54.4	54.6	54.7	54.9	31
32	55.0	55.2	55.3	55.5	55.6	55.8	55.9	56.1	56.2	56.4	32
33	56.5	56.7	56.8	57.0	57.1	57.3	57.4	57.6	57.7	57.9	33
34	58.0	58.2	58.3	58.5	58.6	58.8	58.9	59.1	59.2	59.4	34
35	59.5	59.7	59.8	60.0	60.1	60.3	60.4	60.6	60.7	60.9	35
36	61.0	61.2	61.3	61.5	61.6	61.8	61.9	62.1	62.2	62.4	36

Calculated by Julien A. Hall, M. Am. Soc. C. E.

MADE IN GERMANY.