Misc. Surveys.

9

TRANSIT

F.B. 13

13

Return to City Engineers Office
City Hall, San Diego, Cal.

Table showing the difference of latitude and departure in running 80 chains at any course from 1 to 60 minutes.

Minutes.	Lks.	Minutes.	Lks.	Minutes.	Lks.
1	2⅓	21	49	41	95⅔
2	4⅔	22	51⅓	42	98
3	7	23	53⅔	43	100⅓
4	9⅓	24	56	44	102⅔
5	11⅔	25	58⅓	45	105
6	14	26	60⅔	46	107⅓
7	16⅓	27	63	47	109⅔
8	18⅔	28	65⅓	48	112
9	21	29	67⅔	49	114⅓
10	23⅓	30	70	50	116⅔
11	25⅔	31	72⅓	51	119
12	28	32	74⅔	52	121⅓
13	30⅓	33	77	53	123⅔
14	32⅔	34	79⅓	54	126
15	35	35	81⅔	55	128⅓
16	37⅓	36	84	56	130⅓
17	39⅔	37	86⅓	57	133
18	42	38	88⅔	58	135⅓
19	44⅓	39	91	59	137⅔
20	46⅔	40	93⅓	60	140

PUBLISHED BY
EDWARD DENNY & CO.
DRAWING PAPER & MATERIAL, MATHEMATICAL INSTRUMENTS
STATIONERS AND PRINTERS
SAN FRANCISCO, CAL.

Table for Running on Slopes.

In the following table the first column shows the angle, the second, the n links to be added to a chain on the slopes, to make one chain, horizontal measurem

Angle.	Cor. in links	Angle.	Cor. in links.	Angle.	Cor. in links.	Angle.	Cor.
°		°		°		°	
4	0·24	11	1·88	18	5·14	25	1
5	0 38	12	2·24	19	5·76	26	1
6	0·55	13	2·63	20	6·42	27	1
7	0·76	14	3·06	21	7·11	28	1
8	0·98	15	3·53	22	7·85	29	1
9	1·24	16	4·02	23	8·64	30	1
10	1·55	17	4·56	24	9·47	35	2

MICROFILMED
DEC 21964

13

Return to City Engineers Office
City Hall, San Diego, Cal.

Thomas W. Shaw

San Diego

Keating Blk survey for 1
Payne front lot 5 & 6 Blk 2
Jetty add 2
Masonic Hall Sidewalk 3
S.F. Cable Co. survey of Blk 10 and of W mi Ave 4
Court house survey & grades for — — — — — 5
Ties joints of NE cor of 1123 and NW cor 1124 — — — 6
B St flume grades 7
Keating Estate check of survey cor 6th & T St 12
4th St track to coal yard 10
Pueblo line on Coronado Beach 11
Boring Bs survey of lot C and 10' of lot D Blk 230 HA 13
Show T. Av. x sec of lot K Blk HA 14

Barboye wharf soundings at foot of 9th St 15
Cable road drain from turn table at foot of 6th St 24
House on K & H and L & J cor Holds 19-23
6th St x sect L to K 18
Court house grades 25
Keating Estate grades 26
Cable road drain from conduit 28
Chapin & Lee Geo Survey of E ½ Blk 136 Mt T 29
Court House grades 33
Board of Education 8th ward School House Survey of lot 35
Sixth Street drain at lower end 37
Philips Survey 38
Board of Education 8th ward 39
Playa grades 41
Court House Sewer 42
8th St x sec with Set Stakes 43

April 18th 1890

Survey of Lot G. and South 1/5 Lot H. Block 62 Hortons Add, for the Keating Estate per order of Read Bros. Arch.

Hudson. Transit
Orton chain
Hensley "

POSTED

Note. Line of 5-th St. chained to slope
F St. chained level
Points set one ft off true corner

Checked May 1st by Hamlin and party



Front line of lots 5 and 6 Blk 43 Wtts Add to N.E. cor of 20th and C St. for Payne

completed Wed May 28

Hamlin { Arturo Williams Hemsley



Sketch of sidewalk at NW cor of 6th and H St



June 6 1890

Sur
1/5
Add
per

Cable Co Survey of Blk N. of Univ Ave.



Note.
slope
P
Pa
com

Check
and

June 10 1890

Sta	+	HI	Gull	Grd
Survey of Court house block bein[g] Blk 2 in Horton Add. and Blk D in Middle Town, for Co. of San Diego.				
B M	3.97	36.11		32.14
			30.25	3.86
			31.00	5.11
			31.75	4.36
#	2.81	34.56		4.36 31.7
			30.50	4.06
			29.25	5.31
B.M.	Winn and Est.			5.13 29.43
#	2.60	31.85		5.31 29.25
			28.50	3.35
			27.75	4.10
B.M.				4.86 27.02

Hamlin and Party



June 6 1892

Sur
1/5 2
Add
per

Tie points to cor's of 1123 and 1124 N.E. cor 1123 and NW 1124



Note.
slop
P
Pa
com

Check
and

Grades bottom of side walls of flume across 4th on B. St.

E property line	40.417	
W " "	40.250	
Height of Culvert over all		8' 11"
Thickness of pavement		6"

June 27 1890 Hamlin { Sketch showing location of RR track
Items { Items relating from P.C.S.S. wharf to end
Curb on 4th St. left K and I St

See next page

20.9 ft

+38.9	Sta at which Track crosses West line	
0	3.8	West of center
+72.4	Track crosses center of St.	
+4+	4.0	East center
1	13.5	East of center
2+50	13.5	East of center
2	13.5	East of center
1+50	20.1	East of center



Sketch Showing location of RR track at East of 4th St

June 28 1890

Hamlin { Acton Williams Hemsley.

1+29.65			Left	West line of 4th
1+15	25°	08'	"	
+90	20°	30'	"	
+82.13	13°	07'	"	North line of K St
+65	10°	55'	"	
+40	7°	47'	Left	
0	5°	02		

Beginning at south line of K St. B.S. on a line 11.55 from center and parallel to center line of 4th



67°44'
33°52' -

1.980003
9.836805
1.806808

closed with a 60° curve



Location of line bet. SW Corner of San Diego & Old Light house across Coronado Sand Spit

July 11 1890

Shaw
Jenkins
Hamlin
Flow
Williams

Set up on line in the Center of the Coronado Belt track

#1 & 3 are Cop. tacks in Stakes 2x2x36
#2 " " 2x2x12



Resurvey of Lot G and S10' of Lot H Blk 62 H.A. for the Keating Estate

July 12 1890

12

Sta	+	H.I.	Grade	Bmk : El	
	10,583 below proving grade for cor of 5th = grade of bottom of cellar. Points on 5th St 3' from line with 5th St point on back of lot on true corners.				
B.M.	5.63	36.68			4th 31.0
~~B.M.~~	~~5th and F St~~			~~4.00~~	~~37.~~
B.M.	5th and F St			3.25	33
#	2.21	27.15		11.74	24.
	Bottom of cellar		23.767	3.383	
#	11.98	35.747			23.
B.M.	4th and F St			4.71	31.
			34.35	1.40	
			23.77	10.58	
				1.98	

POSTED



July 21 1890

13

Survey of Lot C 10' of Lot
Block 230 Hartine Add.
For Dr Soring.

Set points for front of lot 2'
east of front

POSTED



Cross sections of Sub K Aug 2 1890 Hamlin level
Hastings Add for F.M.S.R. Williams rod
Hemsley chain

Sta	Rod	Elev	Sta	Rod	Elev
		(157.7)			
a 0	0.7	157.0	b 0	1.8	155
a +20	1.6	156.1	b +20	2.8	155
a +40	3.1	154.6	b +40	3.9	153
a +60	5.0	152.7	b +60	5.6	152
a +80	6.7	151.0	b +80	7.2	150
a 1	8.4	149.3	b 1	9.2	148
c 0	4.0	153.7	d 0	6.2	151
c +20	4.5	153.2	d +20	6.4	151
c +40	5.3	152.4	d +40	7.0	150
c +60	6.7	151.0	d +60	7.8	149
c +80	8.3	149.4	d +80	9.1	148
c 1	10.0	147.7	d 1	11.1	146

+	H.I.	−	Elev
0.72	166.34	11.16	165.62
2.54	157.72		155.18
			150.21
Trunt & Hawthorn.		7.53	150.19
Ref & Bupe		12.19	



Soundings for garbage wharf at foot of 9th

1913
Hamlin
Cutin
Wilhim
Bensley

Beginning at Mon at Sta 148+49 on shore line B.S. to Sta 130+46.9 on shore line measured 20' farther on this line and set flag.

From this point turned an angle of 99° 33' Left and set a flag on line on last bent of old wharf also in line with tel. pole near 10th & N Sts.

B.S. on Sta 130+46.9 angle 30° 24' Right to NE 7' point of 9th & N Sts. dist 166.40

From this point 4° 43' Left on East 7' line of 9th St

Set up at Sta 130+46.9 on shore line and took the following angle. the boatman lining in with flag and tel.

F.S. on Sta 148+49



Soundings for garbage wharf at foot of 9th St

Surv 13 1890

Sta	+	HD	−	Elev
B.M.	2.18	10.68		8.50
B.M.			4.59	6.09
#	2.13	5.84	6.97	3.71
B.M.			6.66	−0.82
"			10.70	−4.86
			10.57	−4.73

Sta	Angle	Sound	Height of tide	Corrected sounding
1	7° 34′	−2.6 0	−4.86	−7.46
2	10° 24′	−3.4 0	−4.85	−8.25
3	12° 40′	−3.7 0	−4.85	−8.55
4	14° 50′	−4.1 0	−4.85	−8.95
5	16° 58′	−4.5 0	−4.84	−9.34
6	20° 08′	−4.9 0	−4.84	−9.74
7	22° 29′	−5.4 0	−4.84	−10.24
8	25° 25′	−5.7 0	−4.83	−10.53
9	27° 51′	−6.0 0	−4.83	−10.83
10	29° 55′	−6.7 0	−4.83	−11.53
11	31° 52′	−7.0 0	−4.82	−11.82
12	33° 53′	−7.5 0	−4.82	−12.32
13	36° 11′	−8.0 0	−4.82	−12.82

th St
& 9th St s/s cor fence S.W.

of B.M. on Mon at Sta 148+49
Height of water at 8h 45m AM
" " " " 9h 05m " "

Taken at 8h 45 min AM

Soundings for garbage pier 13 1890
wharf at foot of 9th St

Sta	Angle	Sounding	Height of tide	corrected Sounding	
14	38° 55'	-8.80	-4.81	-13.61	
15	40° 36'	-9.00	-4.81	-13.81	
16	42° 28'	-9.30	-4.81	-14.11	
17	44° 31'	-9.20	-4.81	-14.01	
18	46° 09'	-9.70	-4.80	-14.50	
19	48° 12'	-10.80	-4.80	-15.60	
20	49° 36'	-12.00	-4.80	-16.80	aken at 8h 55m AM
Sta	+	HO	—	Elev	
		5.84			
#	5.63	7.26	4.21	1.63	
BM #	4.80	11.39	0.67	6.59	th & Ind St
B.M.			2.27	9.12	th & D St

Aug 22 1890

Sewer on line for drain[ing] ... to take water from foot ... 6th St (along cut line produced)

Rod East	Elev. East		Rod West	Elev West	Sta	+	H I	−	Elev.
					6th St				
					B M	0.77	9.09		8.32
		(5.7)			6th St B M	1.50	5.41	5.18	3.91
2.7	2.7		3.1	2.3	0	North line of 2d St			
2.5	2.9		3.2	2.2	+				
3.1	2.3		3.8	1.6	+	South line of 2d St.			
3.9	1.5		4.1	1.3	1+				
4.8	0.6		4.7	0.7	+				
4.4	1.0		4.9	0.5	2+				
4.9	0.5		4.5	0.9	+				
5.4	0.0		4.0	1.4	3+				
			4.0	1.4	+3	center RR track			
			4.4	1.0	+4	Edge of Bank			
4.7	1.4		10.4	-5.0	+6				
4.0	1.4		10.2	-5.0	+7	Center of track			
4.0	1.4				+8				
4.5	0.9				+8	Edge of Bank			
10.4	-5.0				4+6				
					#	6.16	7.73	3.84	1.57 / 6.61
		8th St Br.			B M			1.11	6.62

Profile 8 Box. U

Number of Houses on Le
Ave from South 20th St to 26th

South	20th	to South	21
"	21st	"	22nd
"	22nd	"	23rd
"	23rd	"	24th
"	24th	"	25th
"	25th	"	26th
"	26th	"	26th St

No of Houses on Streets in Land & Town K & K Sect having water laid

	East	West
Milton Ave		
South 20th to South 21st	3	1 - 2 Stats
" 21st to " 22nd	6	3
" 22nd to " 23rd	5	4
" 23rd to " 24th	0	4
" 24th to " 25th	2	2
" 25th to " 26	8	3
" 26th to " 27th	3	8
End of Street	27	25
		27
		52 on Milton
Dogan Ave		
South 20th to South 21st	10	5
" 21st to " 22nd	10	5
" 22nd to " 23rd	9	3
" 23rd " " 24th	5	0
" 24th " " 25th	7	5
" 25th " " 26th	7	3
" 26 to 26th St	1	2
End of Street	49	23
		49
		72 on Dogan

No. of Houses connected with water pipe on L & T and R &

	East	West
Kearney Ave		
South 24th to South 25th	5	10
" 25th to " 26th	2	4
	7	14 / 21 Kearney
Julian Ave		
South 25th to South 26th	1	1/2 on Julian
Inter Ocean Ave		
South 26th St to South 27th	5	4 9 on Inter Ocean
Harrison Ave		
South 24th St to South 25th.	2	0
" 25th " " " 26th	0	4 6 on Harrison
Grant Ave		
South 24th St to South 25th	3	4 7 on Grant

Houses in R & H and Wh
Add connected with sew
pipes

			North	South
Alive Ave				
26th	to	27th	5	5
27th	to	28th	4	1
28th	to	29th	1	2
29th	to	30th	5	4
30th	to	31st	2	3
31st	to	32nd	5	2
			22	17
National Ave				
26th	to	27th	4	6
27th	to	28th	3	8
28th	"	29th	9	11
29th	"	30th	12	5
30th	"	31st	4	9
31st	"	32nd	0	3
			32	42
Grand Ave				
26th	to	27th	2	7
27th	to	28th	2	2
28th	"	29th	6	4
29th	"	30th	2	1
				26

Houses connected with sewa
pipes in R & H and Whitneys

Grand Ave			North	South
30 St	to	31 rd	1	2
31 St	to	32 nd	2	3
Bastin Ave				4
28 th	to	29 th	0	4
29 th	to	30 th	2	4
30 th	to	31 St	1	2
31 St	to	32 nd	2	0
			6	15 6 23
Topeka Ave				
27 th	to	28 th	2	0
Colter Ave				
28 th	to	29 th	2	0
			4	

Drain from turn table p Aug 27. 1890

at foot of 6th St at S. this line is 6' East of West curb

Sta	+	H I	−	Elev	Grade		
						'	"
B M	2.20	6.11		3.91			
0			3.99	2.12	−4.2	6'	1 1/2" N. of S. St
+20			3.72	2.39	−4.4	6'	5 1/4"
+40			3.80	2.31	−4.1	6'	3 7/8" Centre of S St
+60			4.18	1.93	−4.8	6'	1"
+80			4.51	1.60	−4.0	5'	9 5/8" S. of S. St
1+05			4.76	1.35	−4.1	5'	7 3/8"
+30			4.81	1.30	−4.3	5'	7 5/8"
+55			5.13	0.98	−4.7	5'	4 1/2"
+80			5.36	0.75	−4.0	5'	2 3/8"
2+05			5.63	0.48	−4.9	4	11 7/8"
+30			5.59	0.52	−4.0	5'	1 1/4"
+55			5.37	0.74	−4.8	5'	4 5/8"
+80			5.15	0.96	−4.6	5'	7 7/8"
3+05			5.30	0.81	−4.7	5'	6 7/8"
+30			4.73	1.38	−4.1	6	2 5/8"
+50			5.05	1.06	−4.4	5'	11 1/4"
+80							North line S. St
			9.91	−3.80		Centre of Pit of turn-table	
#	6.95	9.58	3.48	2.63			
B.M.			1.27	8.31		6th & K St	

Aug. 28.

Hamlin { Aston, Williams, Hemsley }

Grades for Steps of circular block

B.M.	+	H.I.	Grade	Rod
			Set the N.E. & N.W. cor of Court-house Block.	
27.01	6.21	33.22		
N or ✠ of 16			27.75	5.47
Step 84' N of 16			28.22	5.00
South of bldg			29.25	3.97
1 + 85 Step			28.78	4.44
			29.25	3.97
✠	2.47	31.25		4.44
B.M. State & C St				6.25
Trans. C				
28.78	7.24	36.02		
			31.75	4.27
			30.25	5.77

Sur
1/5
Add
per

Note.
slop

con

Check
and



Aug 2 1894

10.58 / 10.62

23.72

+	HI	Grade	Rod	Elev
		Grade in cellar for		
		E & S 10' of lot G Block 6		
		Hosteine Add for the		
		Keating Estate,		
		By order of J Simpson		
				Bm. 4 ✠ E
4.57	35.62			31.05
BM			2.19	33.43 ✠
2.183	28.23		10.22	25.40
		23.72 →	4.51	grade for

Bottom of iron pillar = 10' 7½" below cur ✠ E

9.54	35.95		1.82	26.41
			2.52	33.43

Hamlin
Arthur
Williams
Hemsley



Sept 17 1890

Hambin { Cator Williams Hemsley

+	HS	Grade Rod	-	B
		Lines & grades for wall		
		lots E & F Blk 278 H.A.		
		King		
7.63	219.79			21
		216.58	3.21	
		214.92	4.87	
		213.25	6.54	
		-	Elev Grade	cu
		4.18	215.61	214.50
6.82	223.07	3.54	216.25	215.75
BM	2nd & Kalmia		1.62	22

(checked) Sept 29
Hambin
Cator
Williams



Grades for drain from old conduit at foot of [illegible]

Sta	Elev	Grade	Cut		
+64	3.24	-1.05	4.29	4	
+50	2.78	-1.12	3.90	3	1
+25	2.21	-1.26	3.47	3	
0	2.48	-1.40	3.88	3	1 Catch Basin
+20	2.12	-1.61	3.73	3	8
+40	2.25	-1.81	4.06	4	Center of L St
+60	1.91	-2.02	3.93	3	1
+80	2.14	-2.22	4.36	4	4 South of L St
1+05	1.95	-2.32	4.27	4	3
+30	1.34	-2.41	3.75	3	9
+55	0.90	-2.51	3.41	3	4
+80	0.76	-2.60	3.36	3	4
2+05	0.67	-2.70	3.37	3	4
+30	0.82	-2.79	3.11	3	1
+55	0.80	-2.89	3.49	3	5
+80	0.87	-2.98	3.85	3	10
3+05	0.62	-3.08	3.70	3	8 Junc old flume

Sept 11 1890

Survey of East 1/2 of Blk 136 Middle Town.
for Mrs Geo Chairsiof

2f plug N.E. & N.W. of lot 12 and S.E. & S.W. of lot 7 all intermediate points are only line; measurement approximate

POSTED



Measurements from cent
must be face of guy po
on 5th & F Sts. for
S.B. Gas & Electric Co.

Measurements in parenthes
are to turn buckle.
Set plug 2' beyond meas
ments not in parenthes
making face of post dist
shown from plugs



Ditch is 17' North of centre of New Track -

1) Distance from 16th St Car Track to where Bullock pointed out a place where he fell = 83' from E

2) Dist from 16th St Car Track to a pt 20' E of where Bullard fell = 103'

3) 7' when Bullard fell Saths to N. rail of new Track

4) 44' to N. side 36' to South

5 201 to Edge of old trim cut on

6 243' to Edge of old trim cut

7) 136' to Edge of cut 149' to centre of New Track

8) 16th St Car Track centre of 16th

16 End to ends Each 80' wide

Su
1/5
Ad
per

Note.
slo

co

Che
and

N



Maple St

Sept 17 1890
Court House

Hamlin
Atty
Williams
Kensley

Sta	+	H.I.	Grade	Dist	Elev
			Datum of coping is N½" above property grade at 16 St and ½" below property grade at C St. Grades in circles are grades for wall. The other grades are property grades.		
B.M.	4.36	36.50			32.14
Wmin & C St				7.70	28.80
			31.75 (21)	4.75	
			31.54 (30)	4.96	
			31.24 (15)	5.26	
			31.39 (.67)	5.11	
			30.72	5.78	
			31.21	5.29	
			30.25	6.25 (.96)	
B.M. nozzle of hydt				2.90	33.65

Note. Slope

Che and



Elevs on top of Manh sewer at curb line of L St.

7.31 / 2.5 / 4.86

Sta	+	HI	−	Elev	
B.M.	3.45	7.36			3.96 at E L St
0			5.05	2.31	gutter on E of 6th St N of L St
			.60	.60	
			5.65	1.71	top of pipe where curb line crosses it on 6th St

Board of Education

Lots 1 2 3 4 5 6 7 & 38 to 48

Sept 19 1890

Survey of lots 1 to 7, 38 to 48 Blk 192
S. & T. Add. for Board of Educ

POSTED



Survey of Lot 45 Blk 15 D & H for T. M. Shaw.

Set a temporary plug 600' N of center of 29th St



Grades for drain from [illegible] gutter at foot of 6th St

Sta	+	HI	−	Elev	Grade			
BM	3.69	7.60		3.91				6th & L St
0			5.25	2.35	0.02	2'	0 1/4"	Catch Basin
+25			4.95	2.65	−1.62	4	7 1/2"	Sewer pipe
+50			5.26	2.34	−2.40	4	4 3/4"	
+75			5.62	1.98	−2.13	4'	1 5/8"	
+93			5.45	2.15	−2.37	4'	4 1/2"	0 of L St
BM	3.96	7.87		3.91				
0				2.25	0.33	.02		
+16			5.39	2.48	−1.97	4.45	4'	5 1/4"
+25			5.23	2.64	−2.00	4.64	4	7 3/4"
+50				2.34	−2.09	4.43	4	5"
+75				1.98	−2.18	4.16	4	2"
+93				2.15	−2.22	4.37	4	4 5/8"

Sept 25 1890

Survey of Sub 2 Blk 225 H.F.
for R F Philips

Hamilton
Clinton
Williams
Kofoknun

POSTED



Section of 8th Ward School

Feb 6th 1891 Hamlin Asmuth
Peter Williams } Chain
Hamsley & Lacy

Begining at a point 60' N
of where the center line of 27
St intersects the North line
Union Ave to the Point
beginning, thence North
3.92', thence West 39.83', then
N. 36.67', thence West 18.83', then
N. 37.33', thence East 117.33' th
S. 37.33' thence West 15.33' then
South 33.17' thence West 43.3
thence South 7.42' to Point of
beginning.

(⊡ Plug) set as shown in Sketch



Elevations for foundation wall for the 8th Ward School House

Feb 9 1891 Hamlin level and rod William Stone

Sta	+	H I	-	Elev.
B.M.,	7.09	72.86		65.47
#	5.90	76.26	2.50	70.36
B.M.			1.27	74.99
			7.61	68.65

Wmain & 29th St

Julian & 27th St.

6" below the top of floor.

Feb 20 1891

Hamlin Book
Hemsley Rod
Williamson level
Aitken Stake

Cut stakes around Plot
beginning at N.W. cor to SW cor to
SE cor to NE cor

Sta	+	H.I.	Grade	Rod	Elev
B.M.	4.26	44.26	.		40. Set & B.S.
			41.00	3.26	0.06 N.W. cor
0			39.00	5.26	SW cor
				1.26	
1			40.26	4.00	100' E of SW cor.
				1.26	
2			41.53	2.73	SE cor
0			43.70	0.56	NE cor
#	3.95	47.67		0.54	43.
B.M.				1.17	46.5

F 0.9' ab. NW cor. Rotten
F 0.9' ab. SE cor. Rotten

Grades for court house Sew

Feb 20 1891 Hamlin Book
Williams level
Hemsley rod
Acton Stake

Sta	+	HI	−	Elev	Ground
B.M.	2.93	36.53		33.60	Front & C St.
B.M			7.77	28.76	W min & B St.
			8.93	27.60	Elev of upper end of pipe
				23.70	Elev of y
B.M	5.47	34.23		28.76	W min & C St.
0			23.70	10.53 ✓	elev of y
+50			24.65	9.58 ✓	
1			25.60	8.63 ✓	
+50			26.55	7.68 ✓	
2			27.50	6.73	
+05		✓	27.60		point where pipe goes under closet
B.M			0.63	33.60	Front & C St.

9.93 − .3 = 9.63

10.30

1.902 − 1.175 = .727

Levels Section of Walk bet ~~State~~ and Union on Elm (~~North~~ West Walk) Curb.

Chas 2 1891 Hamblin actg Williams pencilled

Sta	Rod	Elev.	Rod	Elev		+	HI	−	Elev
B M		(78.4)			State	elev 4.31	78.34		70.03
0	4.3	74.1	5.0	73.4		East line of State St			
+25	4.5	73.9	4.5	73.9					
+50	3.7	74.7	4.3	74.1					
+75	3.4	75.0	4.5	73.9					
1	2.1	76.3	4.7	73.7					
+25	2.9	75.5	3.9	74.5					
+50	2.4	76.0	3.2	75.2					
+75	2.2	76.2	2.6	75.8					
+96	2.1	76.3	2.6	75.8		West line of Union			
					B.M. on State			0.90	77.46

Degrees

Degrees

(7.28) 11 1/2 " (4.36) , 1/2 below

31.75
30.25
1.50

Motor 1' P.M.
from centre of mast to face of guy post

84
12
96

30.25
96
31.21

92
4
96

31.75
4
31.71

83
1
95



91
83
12
84
270

31.21
1.355
31.365

31.71
31.21
.500
270
2300
2160
1400
1350

.270

.00185
96
1110
1665
.17760

.00185
84
740
1480
.15546

.00185
91
185
1665
1.6835

.00185
83
555
1480
.15355

81.9
193.04

31.21
.1776
31.3876
.1535
31.5411
.1683
31.70994

93
16
67

25
10
9

222
197
.25

53
39
14

67).250 (3.73
201
490
469
210
201

.003735
9
.033637 × 25

.003735
25
18675
7470
.09338 × 25

.003735
14
29940
3735
.052290 × 73

1.9733 × 25
2.0093 × 25
2.0093 × 73
2.1685
2.25
2.

Degrees

30.75
4.62
30.7162
52 73
31.2435
50 5
31.7985

3.1416) 2640.0000 (840.3
25 13 28
12 67 20
12 56 64
10 56 00

Wire	0	0	
1 fur	1	1/8	.10
2 "	2	2/8	.10
3 "	3	3/8	.10
4 "	4	4/8	.10
5 "	5	5/8	.10
6 "	6	6/8	.10
7 "	7	7/8	.10
Check	8	3	.10

270) 1.500 (.005555
1350
1500
1350
150
.00555 5
84
2220
4440
.46620
.00555 5
55
27775
49995
.5 2.7225

36.53
8.54
28.00 25
27.77

8.40
6.93

36.53
8.54
27.60

.00555
91
55525
49995
.3 0 5 6 5

99.87
37.50
137.37

99.87
37.50
137.37
137.37
274.74

4/5 X .083

275) .0300 (.1090
75
250
250

3.332 (.666
30
32
30
20

10.38
.67
10.75

10.58
.07
10.65

34.35
10.65
23.70

140) .0300
140 X .00
120

274.74
37.50
237.24
230
07.24

274.74
87.5
137.24
130
7.24

Degrees

9.91

20.0

Rod Upper Co #1 3.22
#2 3.17
Lower Cor #2 3.47
#1 4.48
Water 8.00
lower end of tank 1' above water

1½' at lower end 4' wide
to 1' at upper end 3' wide
wall batter from 2' to 1' at lower end
Same batter all through
floor 1' below lower #1

	15.52	5.27	20.79	16.78	4.01 -
#3	5.47	15.32	15.32	0.0	
#1	3.47	17.32	19.32	+ 2.0	
#2	4.47	16.32	19.32	+ 3.0	
#4	4.47	16.32	15.32	- 1.0	

.84

7.78

174 91 83

16.78
16.83
16.33
15.52
12.00

72.86
6.85
66.01

Bottom Tank



2.071

24.19
23.95
.24



Return to City Engineers Office
City Hall, San Diego, Cal.

TRAVERSE TABLE FOR TRANSIT BOOK.

From 1° to 90° for a distance of 100.

Return to City Engineers Office
City Hall, San Diego, Cal.

DEGREES.		¼ DEGREE.		½ DEGREE.		¾ DEGREE.		Degrees
Lat.	Dep.	Lat.	Dep.	Lat.	Dep.	Lat.	Dep.	
		100.00	0.44	100.00	0.87	99.99	1.31	89
99.98	1.75	99.98	2.18	99.97	2.62	99.95	3.05	88
99.94	3.49	99.92	3.93	99.91	4.36	99.88	4.80	87
99.86	5.23	99.84	5.67	99.81	6.10	99.79	6.54	86
99.76	6.98	99.73	7.41	99.69	7.85	99.66	8.28	85
99.62	8.72	99.58	9.15	99.54	9.58	99.50	10.02	84
99.45	10.45	99.41	10.89	99.36	11.32	99.31	11.75	83
99.25	12 19	99.20	12.62	99.14	13.05	99.09	13.49	82
99.03	13.92	98.97	14.35	98.90	14.78	98.84	15.21	81
98.77	15.64	98.70	16.07	98.63	16.50	98.56	16.93	80
98.48	17.36	98.40	17.79	98.33	18.22	98.25	18.65	79
98.16	19.08	98.08	19.51	97.99	19.94	97.90	20.36	78
97.81	20.79	97.72	21.22	97.63	21.64	97.53	22.07	77
97.44	22.50	97.34	22.92	97.24	23.34	97.13	23.77	76
97.03	24.19	96.92	24.62	96.81	25.04	96.70	25.46	75
96.59	25.88	96.48	26.30	96.36	26.72	96.25	27.14	74
96.13	27.56	96.00	27.98	95.88	28.40	95.76	28.82	73
95.63	29.24	95.50	29.65	95.37	30.07	95.24	30.49	72
95.11	30.90	94.97	31.32	94.83	31.73	94.69	32.14	71
94.55	32.56	94.41	32.97	94.26	33.38	94.12	33.79	70
93.97	34.20	93.82	34.61	93.67	35.02	93.51	35.43	69
93.36	35.84	93.20	36.24	93.04	36.65	92.88	37.06	68
92.72	37.46	92.55	37.86	92.39	38.27	92.22	38.67	67
92.05	39.07	91.88	39.47	91.71	39.87	91.53	40.27	66
91.35	40.67	91 18	41.07	91.00	41.47	90.81	41.87	65
90.63	42.26	90.45	42.66	90 26	43.05	90.07	43 44	64
89.88	43.84	89.69	44.23	89.49	44.62	89.30	45.01	63
89.10	45.40	88.90	45.79	88.70	46.17	88.50	46.56	62
88.29	46.95	88.09	47.33	87.88	47.72	87.67	48.10	61
87.46	48.48	87.25	48.86	87.04	49 24	86.82	49.62	60
86.60	50.00	86.38	50.38	86.16	50.75	85.94	51.13	59
85.72	51.50	85.49	51.88	85.26	52.25	85.04	52.62	58
84.80	52.99	84.57	53.36	84.34	53.73	84.10	54.10	57
83.87	54.46	83.63	54.83	83.39	55.19	83.15	55.56	56
82.90	55.92	82 66	56.28	82.41	56.64	82.16	57.00	55
81.92	57.36	81.66	57.71	81.41	58.07	81.16	58.42	54
80.90	58.78	80.64	59.13	80.39	59.48	80.13	59.83	53
79.86	60.18	79.60	60.53	79.34	60.88	79.07	61.22	52
78.80	61.57	78.53	61.91	78 26	62.25	77.99	62.59	51
77.71	62.93	77.44	63.27	77.16	63.61	76.88	63.94	50
76.60	64.28	76.32	64.61	76.04	64.94	75.76	65.28	49
75.47	65.61	75.18	65.93	74.90	66.26	74.61	66.59	48
74.31	66.91	74.02	67.24	73.73	67.56	73.43	67 88	47
73.14	68.20	72.84	68.52	72.54	68.84	72.24	69.15	46
71.93	69.47	71.63	69.78	71.33	70.09	71.02	70.40	45
70.71	70.71							
Dep.	Lat.	Dep.	Lat.	Dep.	Lat.	Dep.	Lat.	Degrees
DEGREES.		¼ DEGREE.		½ DEGREE.		¾ DEGREE.		

Published by Edward Denny & Co., Stationers, Drawing Materials, Mathematical Instruments, Etc., San Francisco.