1624

DIXIGEN

ENGINEER'S

LABEL BOOK

No. 410E

# EUGENE DIETZGEN CO.

DRAWING MATERIALS, MATHEMATICAL and
SURVEYING INSTRUMENTS

Chicago New York San Francisco New Orleans Pittsburg Toronto

Distances from Center of Roadway for Cross-Sectioning
Roadway 16 feet wide. Side Slopes 1 on 1.
For Single Track Embankment.

| H | 0 | .1 | .2 | .3 | .4 | .5 | .6 | .7 | .8 | .9 | H |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 0 | 8.0 | 8.1 | 8.2 | 8.3 | 8.4 | 8.5 | 8.6 | 8.7 | 8.8 | 8.9 | 0 |
| 1 | 9.0 | 9.1 | 9.2 | 9.3 | 9.4 | 9.5 | 9.6 | 9.7 | 9.8 | 9.9 | 1 |
| 2 | 10.0 | 10.1 | 10.2 | 10.3 | 10.4 | 10.5 | 10.6 | 10.7 | 10.8 | 10.9 | 2 |
| 3 | 11.0 | 11.1 | 11.2 | 11.3 | 11.4 | 11.5 | 11.6 | 11.7 | 11.8 | 11.9 | 3 |
| 4 | 12.0 | 12.1 | 12.2 | 12.3 | 12.4 | 12.5 | 12.6 | 12.7 | 12.8 | 12.9 | 4 |
| 5 | 13.0 | 13.1 | 13.2 | 13.3 | 13.4 | 13.5 | 13.6 | 13.7 | 13.8 | 13.9 | 5 |
| 6 | 14.0 | 14.1 | 14.2 | 14.3 | 14.4 | 14.5 | 14.6 | 14.7 | 14.8 | 14.9 | 6 |
| 7 | 15.0 | 15.1 | 15.2 | 15.3 | 15.4 | 15.5 | 15.6 | 15.7 | 15.8 | 15.9 | 7 |
| 8 | 16.0 | 16.1 | 16.2 | 16.3 | 16.4 | 16.5 | 16.6 | 16.7 | 16.8 | 16.9 | 8 |
| 9 | 17.0 | 17.1 | 17.2 | 17.3 | 17.4 | 17.5 | 17.6 | 17.7 | 17.8 | 17.9 | 9 |
| 10 | 18.0 | 18.1 | 18.2 | 18.3 | 18.4 | 18.5 | 18.6 | 18.7 | 18.8 | 18.9 | 10 |
| 11 | 19.0 | 19.1 | 19.2 | 19.3 | 19.4 | 19.5 | 19.6 | 19.7 | 19.8 | 19.9 | 11 |
| 12 | 20.0 | 20.1 | 20.2 | 20.3 | 20.4 | 20.5 | 20.6 | 20.7 | 20.8 | 20.9 | 12 |
| 13 | 21.0 | 21.1 | 21.2 | 21.3 | 21.4 | 21.5 | 21.6 | 21.7 | 21.8 | 21.9 | 13 |
| 14 | 22.0 | 22.1 | 22.2 | 22.3 | 22.4 | 22.5 | 22.6 | 22.7 | 22.8 | 22.9 | 14 |
| 15 | 23.0 | 23.1 | 23.2 | 23.3 | 23.4 | 23.5 | 23.6 | 23.7 | 23.8 | 23.9 | 15 |
| 16 | 24.0 | 24.1 | 24.2 | 24.3 | 24.4 | 24.5 | 24.6 | 24.7 | 24.8 | 24.9 | 16 |
| 17 | 25.0 | 25.1 | 25.2 | 25.3 | 25.4 | 25.5 | 25.6 | 25.7 | 25.8 | 25.9 | 17 |
| 18 | 26.0 | 26.1 | 26.2 | 26.3 | 26.4 | 26.5 | 26.6 | 26.7 | 26.8 | 26.9 | 18 |
| 19 | 27.0 | 27.1 | 27.2 | 27.3 | 27.4 | 27.5 | 27.6 | 27.7 | 27.8 | 27.9 | 19 |
| 20 | 28.0 | 28.1 | 28.2 | 28.3 | 28.4 | 28.5 | 28.6 | 28.7 | 28.8 | 28.9 | 20 |
| 21 | 29.0 | 29.1 | 29.2 | 29.3 | 29.4 | 29.5 | 29.6 | 29.7 | 29.8 | 29.9 | 21 |
| 22 | 30.0 | 30.1 | 30.2 | 30.3 | 30.4 | 30.5 | 30.6 | 30.7 | 30.8 | 30.9 | 22 |
| 23 | 31.0 | 31.1 | 31.2 | 31.3 | 31.4 | 31.5 | 31.6 | 31.7 | 31.8 | 31.9 | 23 |
| 24 | 32.0 | 32.1 | 32.2 | 32.3 | 32.4 | 32.5 | 32.6 | 32.7 | 32.8 | 32.9 | 24 |
| 25 | 33.0 | 33.1 | 33.2 | 33.3 | 33.4 | 33.5 | 33.6 | 33.7 | 33.8 | 33.9 | 25 |
| 26 | 34.0 | 34.1 | 34.2 | 34.3 | 34.4 | 34.5 | 34.6 | 34.7 | 34.8 | 34.9 | 26 |
| 27 | 35.0 | 35.1 | 35.2 | 35.3 | 35.4 | 35.5 | 35.6 | 35.7 | 35.8 | 35.9 | 27 |
| 28 | 36.0 | 36.1 | 36.2 | 36.3 | 36.4 | 36.5 | 36.6 | 36.7 | 36.8 | 36.9 | 28 |
| 29 | 37.0 | 37.1 | 37.2 | 37.3 | 37.4 | 37.5 | 37.6 | 37.7 | 37.8 | 37.9 | 29 |
| 30 | 38.0 | 38.1 | 38.2 | 38.3 | 38.4 | 38.5 | 38.6 | 38.7 | 38.8 | 38.9 | 30 |
| 31 | 39.0 | 39.1 | 39.2 | 39.3 | 39.4 | 39.5 | 39.6 | 39.7 | 39.8 | 39.9 | 31 |
| 32 | 40.0 | 40.1 | 40.2 | 40.3 | 40.4 | 40.5 | 40.6 | 40.7 | 40.8 | 40.9 | 32 |
| 33 | 41.0 | 41.1 | 41.2 | 41.3 | 41.4 | 41.5 | 41.6 | 41.7 | 41.8 | 41.9 | 33 |
| 34 | 42.0 | 42.1 | 42.2 | 42.3 | 42.4 | 42.5 | 42.6 | 42.7 | 42.8 | 42.9 | 34 |
| 35 | 43.0 | 43.1 | 43.2 | 43.3 | 43.4 | 43.5 | 43.6 | 43.7 | 43.8 | 43.9 | 35 |
| 36 | 44.0 | 44.1 | 44.2 | 44.3 | 44.4 | 44.5 | 44.6 | 44.7 | 44.8 | 44.9 | 36 |
| 37 | 45.0 | 45.1 | 45.2 | 45.3 | 45.4 | 45.5 | 45.6 | 45.7 | 45.8 | 45.9 | 37 |
| 38 | 46.0 | 46.1 | 46.2 | 46.3 | 46.4 | 46.5 | 46.6 | 46.7 | 46.8 | 46.9 | 38 |
| 39 | 47.0 | 47.1 | 47.2 | 47.3 | 47.4 | 47.5 | 47.6 | 47.7 | 47.8 | 47.9 | 39 |
| 40 | 48.0 | 48.1 | 48.2 | 48.3 | 48.4 | 48.5 | 48.6 | 48.7 | 48.8 | 48.9 | 40 |

**Example**—If point is 22.6 ft. above grade, how far should it be from center line to be a slope stake point? Ans. from Table 30.6. For same slopes but other widths of roadbed, correct above figures by one-half difference in width of roadbed; thus in example above, for 20 ft. roadbed distance will be 30.6+(20—16)÷2 or 2 ft. added to 30.6 =32.6. For slopes of 1 on 1½ see inside of back cover.

Copyright, 1914, by Eugene Dietzgen Co.

MICROFILMED
JAN 1, 1985

Boyd

1624

ENGINEERING DEPARTMENT,
CITY OF SAN DIEGO,
CALIFORNIA.

The paper stock of this book is made of a **high grade 50% rag** paper having a **water resisting surface.** This book is sewed with Bing **Special Enamel Waterproof Thread.**

Made in U. S. A.

| | | |
|---|---|---|
| 29th St. | O.V.B. to Imp. | 1 - 18 |
| Alley Blk 6 | Plumosa Park | 19 - 22 |
| " | N.T.S. " " | 23 - 24 |
| " | E & W " " | 25 - 28 |
| A - Street | Kettner to Pacific Blvd | 29 - 30 |
| Survey Lots 21 & 22 | Blk 160 U.H. | 31 - 32 |
| 20' Alley | Blk 160 U.H. | 33 - 38 |
| Glenfield | Fairmount to Manzanita | 39 - 43 |
| Manzanita Dr | Heather & Place | 44 - 50 |
| C - St | Columbia to Union | 51 - 53 |
| Art St. | El Cajon to Catalina | 54 - 58 |
| Fire Sta. Lots 21 & 24 | Blk. 160 U.V. Hts | 59 - |
| Cabin | Texas St. Grade | 60 - 62 |
| " | east of 39th @ Edna Pl. | 63 - 65 |
| Kurtz St. | East of Noell | 66 - 68 |

Moore
Rand
France
1-6-47.

Indexed
C.S.K.



X sec of 29th St.

60' wide
10' curbs
10' 1/2's

Ocean View Blvd. to Imperial Ave.






Sec. 401-60
878.36



X sec of 29th

Ocean View Blvd nly.

| | | | | |
|---|---|---|---|---|
| NEBP | 3.70 | 101.15 | 97.45 | 29th and Ocean View |
| | 0-1x | | | |
| E cb | | 3.68 | 97.47 | |
| E gut | | 4.40 | 96.75 | |
| cb pav. | | 4.25 | 96.90 | |
| 1/4 " | | 4.11 | 97.04 | |
| c " | | 3.97 | 97.18 | |
| 1/4 " | | 3.89 | 97.26 | |
| cb " | | 3.83 | 97.32 | |
| W gut | | 3.81 | 97.34 | |
| W cb | | 3.14 | 98.01 | |
| | 0+00 | N/L Ocean View | | |
| W | | 2.84 | 98.31 | |
| cb | | 3.11 | 98.04 | |
| gut pav | | 3.79 | 97.36 | |
| 1/4 " | | 3.65 | 97.50 | |
| c " | | 3.57 | 97.58 | |
| 1/4 " | | 3.71 | 97.44 | |

Reduced & Plotted Jan 13-1942 CBHough



| | | | |
|---|---|---|---|
| | 101.15 | | |
| E out pav | 4.1 | 96.99 | |
| E c6 | 3.5 | 97.50 | |
| E | 3.4 | 97.73 | |
| 0+50 | | | |
| E | 3.5 | 97.7 | |
| c6 | 3.9 | 97.3 | |
| +1 | 4.6 | 96.6 | |
| 1/4 | 4.3 | 96.9 | |
| c | 4.1 | 97.1 | |
| 1/4 | 4.0 | 97.2 | |
| +9 | 4.2 | 97.0 | |
| c6 | 3.8 | 97.4 | |
| +7 | 3.5 | 97.7 | |
| w | 2.9 | 98.3 | |
| 1+00 | | | |
| w | 2.2 | 99.0 | |
| +2 | 3.7 | 97.5 | |
| c6 | 4.2 | 97.0 | |
| +1 | 4.7 | 96.5 | |
| 1/4 | 4.5 | 96.7 | |
| c | 4.5 | 96.7 | |

| | | | |
|---|---|---|---|
| | 101.15 | | |
| 1/4 | | 4.7 | 96.5 |
| +9 | | 5.1 | 96.1 |
| c6 | | 4.4 | 96.8 |
| E | | 3.6 | 97.6 |
| 1+38 | | | |
| E | | 4.3 | 96.9 |
| c6 | | 5.3 | 95.9 |
| +2 | | 5.6 | 95.6 |
| w 1/4 +9 | | 5.0 | 96.2 |
| w c6 | | 4.0 | 97.2 |
| w | | 3.5 | 97.7 |
| 1+40.2 | | | |
| w | | 3.8 | 97.4 |
| c6 | | 5.1 | 96.1 |
| 1/4 | | 5.2 | 96.0 |
| c | | 5.2 | 96.0 |
| 1/4 | | 5.4 | 95.8 |
| c6 | | 5.5 | 95.7 |
| E | | 4.6 | 96.6 |
| 1+60 | | | |
| E | | 4.8 | 96.4 |

| | | | | |
|---|---|---|---|---|
| | | 101.15 | | |
| E +9 | | 5.4 | 95.8 | |
| c6 | | 6.4 | 94.8 | |
| 1/4 | | 5.1 | 95.1 | |
| c | | 5.8 | 95.4 | |
| 1/4 | | 5.8 | 95.4 | |
| +9 | | 6.0 | 95.2 | |
| c6 | | 5.0 | 96.2 | |
| W | | 3.8 | 97.4 | |
| | 1+Co.rd | | | |
| E | alley Ret. | 4.8rd | 96.33 | |
| c6 | | 5.36 | 95.79 | |
| 9UT | | 6.4 | 94.8 | |
| | 2+00 | | | |
| E | | 6.77 | 94.38 | |
| c6 | | 7.13 | 94.02 | |
| 9UT | | 8.4 | 92.8 | |
| 1/4 | | 7.9 | 93.3 | |
| c | | 7.7 | 93.5 | |
| 1/4 | | 7.7 | 93.5 | |
| +9 | | 8.1 | 93.1 | |
| c6 | | 6.3 | 94.9 | |

| | | | | |
|---|---|---|---|---|
| | | 101.15 | | |
| W | | 6.0 | 95.2 | |
| | 2+50 | | | |
| W | | 8.3 | 92.9 | |
| c6 | | 8.9 | 92.3 | |
| +1 | | 10.5 | 90.7 | |
| 1/4 | | 10.3 | 90.9 | |
| c | | 10.5 | 90.7 | |
| 1/4 | | 10.8 | 90.4 | |
| 9UT | | 11.1 | 90.1 | |
| c6 | | 9.83 | 91.32 | |
| E | | 9.5C | 91.59 | |
| | 3+00.40 | SL Franklin | | |
| E | | 12.16 | 88.99 | |
| c6 | | 12.45 | 88.70 | |
| 9UT | Pav | 13.01 | 88.14 | |
| 1/4 | | 12.57 | 88.63 | |
| c | | 12.20 | 88.95 | |
| 1/4 | | 12.11 | 89.04 | |
| 9UT | | 12.16 | 88.99 | |
| c6 | | 11.26 | 89.79 | |
| W | | 11.2 | 90.0 | |

| | | | | | |
|---|---|---|---|---|---|
| | | 10,15 | | | |
| TP | 205 | 91.29 | 11.91 | 89.24 | |
| 5h.+00 = S c6 Franklin | | | | | |
| -10 | c6 | | 1.99 | 89.30 | |
| -10 | gut | | 2.84 | 88.45 | |
| W | pav | | 2.96 | 88.33 | |
| c6 | " | | 2.90 | 88.39 | |
| 1/4 | " | | 2.93 | 88.36 | |
| C | " | | 3.03 | 88.26 | |
| 1/4 | " | | 3.37 | 87.92 | |
| c6 | " | | 3.86 | 87.43 | |
| E | " | | 4.33 | 86.96 | |
| +10 | gut | | 4.48 | 86.81 | |
| +10 | c6 | | 3.64 | 87.67 | |
| 0+00 = N c6 Franklin | | | | | |
| -10 | c6 | | 4.94 | 86.35 | |
| -10 | gut | | 5.49 | 85.80 | |
| E | pav | | 5.44 | 85.87 | |
| c6 | " | | 5.11 | 86.18 | |
| 1/4 | " | | 4.65 | 86.64 | |
| C | " | | 4.40 | 86.89 | |

91.29

| | | | | |
|---|---|---|---|---|
| 1/4 | pav | | 4.20 | 87.09 |
| c6 | " | | 4.10 | 87.19 |
| W | " | | 4.04 | 87.25 |
| +10 | gut | | 3.81 | 87.48 |
| +10 | c6 | | 3.45 | 88.04 |
| | 0+00 | N | Franklin | |
| W | | | 4.1 | 87.2 |
| c6 | | | 4.09 | 87.20 |
| gut | pav | | 4.94 | 86.35 |
| 1/4 | " | | 4.80 | 86.49 |
| C | " | | 4.85 | 86.44 |
| 1/4 | " | | 5.41 | 86.08 |
| gut | " | | 5.74 | 85.57 |
| c6 | | | 5.49 | 86.00 |
| E | | | 5.1 | 86.2 |
| | 0+50 | | | |
| E | | | 5.3 | 85.0 |
| c6 | | | 7.3 | 84.0 |
| +N | | | 8.0 | 83.3 |
| 1/4 | | | 7.7 | 83.6 |
| C | | | 7.5 | 83.8 |

91.~9

| | | | | |
|---|---|---|---|---|
| 1/4 | | | 7.3 | 84.0 |
| +7 | | | 7.5 | 83.8 |
| c6 | | | 6.0 | 85.3 |
| W/ | | | 5.8 | 85.5 |
| | 1+00 | | | |
| W | | | 7.3 | 84.0 |
| c6 | | | 7.~ | 84.1 |
| +3 | | | 8.9 | 82.4 |
| 1/4 | | | 8.8 | 82.5 |
| C | | | 8.9 | 82.4 |
| 1/4 | | | 9.1 | 82.2 |
| +3 | | | 9.~ | 82.1 |
| c6 | | | 8.7 | 82.6 |
| E | | | 8.0 | 83.3 |
| | 1+05 | | | |
| E+0.5 E 8" | | Conc. drive | 8.30 | 82.99 ✓ |
| | 1+37 | | | |
| W | | | 8.3 | 83.0 |
| c6 | | | 8.4 | 82.9 |
| +4 | | | 9.7 | 81.6 |
| | 1+40.30 | | | |
| E | | | 9.4 | 81.9 |

91.~9

7

| | | | |
|---|---|---|---|
| c6 | | 9.4 | 81.9 |
| +3 | | 9.8 | 81.5 |
| 1/4 | | 9.9 | 81.4 |
| C | | 10.3 | 81.0 |
| 1/4 | | 10.~ | 81.1 |
| c6 | | 9.4 | 81.9 |
| W | | 8.8 | 82.5 |
| | 1+50 | | |
| W | RIM M.H. | 8.6~ | 82.65 ~ |
| | 1+C0.30 | | |
| W | Alley Ret | 8.73 | 82.56 |
| W/ | OUT dirt | 9.1 | 82.2 |
| c6 | Top | 9.00 | 82.29 |
| OUT | | 10.~ | 81.1 |
| 1/4 | | 10.7 | 80.6 |
| C | | 10.7 | 80.6 |
| 1/4 | | 10.3 | 81.0 |
| OUT | | 9.8 | 81.5 |
| c6 | Top | 9.56 | 81.73 |
| E | Top Ret | 9.30 | 81.99 |
| E | dirt | 9.4 | 81.9 |

| | | | | |
|---|---|---|---|---|
| | | 91.29 | | |
| | 2+00 | | | |
| E | | | 10.6 | 80.7 |
| cb | | | 10.57 | 80.72 |
| gut | | | 11.9 | 79.4 |
| 1/4 | | | 11.9 | 79.4 |
| c | | | 11.6 | 79.7 |
| 1/4 | | | 11.2 | 80.1 |
| gut | | | 11.0 | 80.3 |
| cb | | | 10.22 | 81.07 |
| W | | | 10.05 | 81.24 |
| T.P. | 2.56 | 81.84 | 12.01 | 79.28 |
| | 2+50 | | | |
| W | | | 2.06 | 79.78 |
| cb | | | 2.29 | 79.55 |
| gut | | | 3.2 | 78.6 |
| 1/4 | | | 3.2 | 78.6 |
| c | | | 3.3 | 78.5 |
| 1/4 | | | 3.4 | 78.4 |
| gut | | | 3.5 | 78.3 |
| cb | | | 2.43 | 79.41 |
| E | | | 2.3 | 79.5 |

| | | | |
|---|---|---|---|
| | | 81.84 | |
| | 2+51 4" drain through cb | | |
| E cb | | 2.46 | 79.38 |
| F.L. outlet | | 3.36 | 78.48 |
| | 3+00.6 SL clay | | |
| E | | 3.5 | 78.3 |
| cb | | 3.78 | 78.06 |
| gut Pav | | 4.36 | 77.48 |
| 1/4 " | | 4.01 | 77.83 |
| c " | | 3.88 | 77.96 |
| 1/4 " | | 3.97 | 77.87 |
| gut " | | 4.27 | 77.57 |
| cb | | 3.83 | 78.01 |
| W | | 3.53 | 78.31 |
| | SL+12 5cb clay | | |
| W cb | | 3.84 | 78.00 |
| W gut pav | | 4.45 | 77.39 |
| cb " | | 4.28 | 77.56 |
| 1/4 " | | 4.13 | 77.71 |
| c " | | 4.07 | 77.77 |
| 1/4 " | | 4.14 | 77.70 |
| cb " | | 4.27 | 77.57 |
| E gut " | | 4.44 | 77.40 |
| E cb | | 3.81 | 78.03 |

81.84

| | | | | | |
|---|---|---|---|---|---|
| Found check to SEBP w 9th + Clay | | 3.81 | 78.03 | | |
| | 0-14 N c6 Clay | | | | |
| E c6 | | 4.78 | 77.06 | | |
| E gut Pav | | 5.36 | 76.48 | | |
| c6 | " | 5.08 | 76.76 | | |
| 1/4 | " | 4.96 | 76.92 | | |
| c | " | 4.82 | 77.02 | | |
| 1/4 | " | 4.96 | 76.92 | | |
| c6 | " | 5.14 | 76.60 | | |
| W gut | " | 5.38 | 76.46 | | |
| W c6 | | 4.85 | 76.99 | | |
| | 0+00 NL Clay | | | | |
| W | | 4.52 | 77.32 | | |
| c6 | | 4.83 | 77.01 | | |
| gut Pav | | 5.45 | 76.39 | | |
| 1/4 | " | 5.14 | 76.70 | | |
| c | " | 4.98 | 76.86 | | |
| 1/4 | " | 5.12 | 76.72 | | |
| gut | " | 5.38 | 76.46 | | |
| c6 | | 4.85 | 76.99 | | |
| E | | 4.54 | 77.30 | | |

81.84

| | | | | | |
|---|---|---|---|---|---|
| | 0+40.5 | | | | 75.4 EL. 4" Conc. Pipe drain |
| W c6 | | | 6.40 | | |
| | 0+50 | | | | |
| E | | | 5.6 | 76.2 | |
| c6 | | | 5.97 | 75.87 | |
| gut | | | 7.2 | 74.6 | |
| 1/4 | | | 6.9 | 74.9 | |
| c | | | 6.7 | 75.1 | |
| 1/4 | | | 6.7 | 75.1 | |
| gut + Curb | | | 6.4 | 75.4 | |
| W | | | 6.0 | 75.8 | |
| T.P. | IW | 76.09 | 7.16 | 74.68 | |
| | 0+85 | | | | |
| W E of r' Conc walk | | | 0.94 | 75.15 | |
| | 1+00 | | | | |
| W | | | 1.3 | 74.8 | |
| c6 | | | 1.6 | 74.5 | |
| 1/4 | | | 2.2 | 73.9 | |
| c | | | 2.3 | 73.8 | |
| 1/4 | | | 2.3 | 73.8 | |
| E gut | | | 2.7 | 73.4 | |

| | | | |
|---|---|---|---|
| E c6 | | 1.44 | 74.65 |
| E | | 1.2 | 74.9 |
| | 1+13 | | |
| w E 2' cent walk | | 1.30 | 74.79 |
| | 1+40N | | |
| EL c6 alley RET | | 2.00 | 74.09 |
| EL gut | | 2.6 | 73.5 |
| E c6 | | 2.30 | 73.79 |
| gut | | 3.0 | 73.1 |
| 1/4 | | 3.5 | 72.6 |
| c | | 3.5 | 72.6 |
| 1/4 | | 3.1 | 73.0 |
| c6 | | 2.5 | 73.6 |
| W | | 2.2 | 73.9 |
| | 1+50 | | |
| w/ RIM M.H. | | 2.05 | 74.04 ✓ |
| | 4Co.N | | |
| w/ | | 2.7 | 73.4 |
| c6 | | 3.3 | 72.8 |
| 1/4 | | 3.7 | 72.4 |
| c | | 3.9 | 72.2 |





| | | | |
|---|---|---|---|
| 1/4 | | 4.1 | 72.0 |
| c6 | | 3.6 | 72.5 |
| E | | 2.7 | 73.4 |
| | 2+00 | | |
| E | | 3.5 | 72.6 |
| c6 | | 4.2 | 71.9 |
| +2 | | 4.7 | 71.4 |
| 1/4 | | 4.8 | 71.3 |
| c | | 4.7 | 71.4 |
| 1/4 | | 4.7 | 71.4 |
| c6 | | 4.4 | 71.7 |
| W | | 3.5 | 72.6 |
| | 2+11 | | |
| W & 4.2 Cent. walk | | 3.47 | 72.62 ✓ |
| | 2+50 | | |
| w edge of 5.2 wide cent walk | | 4.02 | 72.07 |
| +1 | | 4.9 | 71.2 |
| c6 | | 5.5 | 70.6 |
| 1/4 | | 5.6 | 70.5 |
| c | | 5.4 | 70.7 |
| 1/4 | | 5.5 | 70.6 |

76.09

| | | | |
|---|---|---|---|
| 1/4 + 5 | 5.4 | 70.5 | |
| c6 | 5.1 | 71.0 | |
| E | 4.4 | 71.7 | |
| 3+00.5R 5L Webster Ave | | | |
| E | 5.76 | 70.33 | |
| c6 | 5.94 | 70.15 | |
| gut Pav | 6.54 | 69.55 | |
| 1/4 " | 6.56 | 69.53 | |
| C " | 6.46 | 69.63 | |
| 1/4 " | 6.60 | 69.47 | |
| gut " | 6.91 | 69.18 | |
| c6 | 6.34 | 69.77 | |
| WL | 6.16 | 69.93 | |
| T.P. Id. C.T. Mon. 10' RR 5.86 | 75.0R | 6.93 | 69.16 |
| 5.2. +14 S c6 Webster | | | |
| WL c6 | 5.33 | 69.69 | |
| WL gut | 5.90 | 69.06 | |
| c6 Pav | 5.90 | 69.12 | |
| 1/4 " | 5.85 | 69.17 | |

75.0R

| | | |
|---|---|---|
| C Pav | 5.81 | 69.21 |
| 1/4 " | 5.78 | 69.24 |
| c6 " | 5.67 | 69.35 |
| EL gut | 5.54 | 69.48 |
| EL c6 | 4.86 | 70.18 |
| 0+14 R c6 Webster | | |
| EL c6 | 5.47 | 69.55 |
| " gut | 6.01 | 69.01 |
| c6 Pav | 6.16 | 68.86 |
| 1/4 " | 6.30 | 68.72 |
| C " | 6.36 | 68.66 |
| 1/4 " | 6.42 | 68.60 |
| c6 " | 6.46 | 68.56 |
| WL gut | 6.58 | 68.44 |
| " c6 | 5.96 | 69.06 |
| 0+00 WL Webster | | |
| W | 5.64 | 69.38 |
| c6 | 5.85 | 69.17 |
| gut Pav | 6.03 | 68.59 |
| 1/4 " | 6.18 | 68.84 |
| C " | 5.97 | 69.05 |

| | | | | |
|---|---|---|---|---|
| | | 750N | | |
| 1/4 | Pav. | | 5.98 | 69.04 |
| qut | " | | 6.07 | 68.95 |
| cb | | | 5.43 | 69.59 |
| E | | | 5.33 | 69.69 |
| | 0+50 | | | |
| E | | | 4.6 | 70.4 |
| +9 | | | 5.2 | 69.8 |
| cb | | | 5.7 | 69.3 |
| 1/4 | | | 5.9 | 69.1 |
| c | | | 6.0 | 69.0 |
| 1/4 | | | 5.9 | 69.1 |
| cb | | | 5.7 | 69.3 |
| W | | | 5.0 | 70.0 |
| | 1+00 | | | |
| W | | | 4.6 | 70.4 |
| cb | | | 5.4 | 69.6 |
| 1/4 | | | 5.5 | 69.5 |
| c | | | 5.2 | 69.8 |
| 1/4 | | | 5.0 | 70.0 |
| cb | | | 4.9 | 70.1 |
| +1 | | | 4.4 | 70.6 |

| | | | | |
|---|---|---|---|---|
| | | 750N | | |
| E | | | 4.2 | 70.8 |
| | 1+40.1 | SL | Valley | Pl. = Δ 36°52' Lt. |
| E | | | 4.0 | 71.0 |
| cb | | | 4.4 | 70.6 |
| 1/4 | | | 4.6 | 70.4 |
| c | | | 4.7 | 70.3 |
| 1/4 | | | 5.0 | 70.0 |
| cb | | | 5.1 | 69.9 |
| +2 | | | 4.4 | 70.6 |
| W | | | 4.3 | 70.7 |
| | E. Valley Pl. ∥ Parallel | | | |
| 1/4 | | | 5.0 | 70.0 |
| cb | | | 5.1 | 69.9 |
| 1/4 | | | 5.3 | 69.7 |
| c | | | 4.9 | 70.1 |
| 1/4 | | | 4.6 | 70.4 |
| c | | | 4.4 | 70.6 |
| E | | | 4.5 | 70.5 |
| | 1+90.1 | NL | Valley & W ∥ | Parallel |
| E | | | 4.1 | 70.9 |
| cb | | | 4.3 | 70.7 |

| | | | | |
|---|---|---|---|---|
| | | 75.0+ | | |
| 1/4 | | | 4.7 | 70.3 |
| c | | | 4.8 | 70.2 |
| 1/4 | | | 5.+ | 69.8 |
| cb | | | 5.2 | 69.9 |
| w/ | | | 4.7 | 70.3 |
| | 1+90.1 | at 90° w. to sq to | | |
| w' | | | 4.7 | 70.3 |
| +9 | | | 4.7 | 70.3 |
| cb | | | 5.3 | 69.7 |
| 1/4 | | | 5.+ | 69.8 |
| c | | | 5.3 | 69.7 |
| 1/4 | | | 5.0 | 70.0 |
| cb | | | 4.7 | 70.3 |
| E | | | 4.0 | 71.0 |
| | 2+50 | at 90° | | |
| E | | | 4.7 | 70.3 |
| cb | | | 5.0 | 70.0 |
| 1/4 | | | 5.3 | 69.7 |
| c | | | 5.6 | 69.4 |
| 1/4 | | | 5.5 | 69.5 |
| cb | | | 5.5 | 69.5 |

| | | | | |
|---|---|---|---|---|
| | | 75.0+ | | .9 |
| +9 | | | 5.1 | 69.X |
| w | | | 4.8 | 70.2 |
| | 3+14.77 = Δ | | 36° 58' 30" Rt. | Section on split of Δ |
| w | | | 4.8 | 70.2 |
| cb | | | 5.1 | 69.9 |
| 1/4 | | | 6.3 | 68.7 |
| c | | | 5.9 | 69.1 |
| 1/4 | | | 6.6 | 68.4 |
| +9 | | | 6.7 | 68.3 |
| cb | | | 6.+ | 68.8 |
| E | | | 6.0 | 69.0 = Δ Pt. |
| | Sec. A | p+ | | |
| E | | | 6.0 | 69.0 |
| +9 | | | 6.0 | 69.0 |
| cb | | | 6.5 | 68.5 |
| +9 | | | 7.0 | 68.0 |
| 1/4 | | | 6.7 | 68.3 |
| c | | | 6.+ | 68.8 |
| 1/4 | | | 6.5 | 68.5 |
| +5 | | | 6.6 | 68.4 |
| cb | | | 4.8 | 70.2 |
| w | | | 5.+ | 69.8 |

75.0 ↓

8 + 34.87
~~3 + 38.87~~ S.L Comm'l = 80' wide 14 cbs

| | | | | |
|---|---|---|---|---|
| W | | | 6.3 | 68.7 |
| cb | | | 6.5 | 68.5 |
| 1/4 | | | 6.5 | 68.5 |
| c | | | 6.2 | 68.8 |
| 1/4 | | | 6.8 | 68.2 |
| +8 | | | 6.9 | 68.1 |
| cb | | | 6.2 | 68.8 |
| E | | | 6.0 | 69.0 |

| | | | | | |
|---|---|---|---|---|---|
| T.P. Ld. C.T. 12.5 S. of NW Cor. | 5.13 | 74.2 ↓ | 5.91 | 69.11 | 29th ↓ Comm'l. |

S cb Comm'l.

| | | | |
|---|---|---|---|
| E | | 6.3 | 67.9 |
| cb | | 6.3 | 67.9 |
| 1/4 | | 6.1 | 68.1 |
| c | | 5.7 | 68.5 |
| 1/4 | | 5.6 | 68.6 |
| cb | | 6.5 | 67.7 |
| W | | 6.3 | 67.9 |

74.2 ↓

S cb + 2

| | | | |
|---|---|---|---|
| W | | 6.1 | 67.6 |
| cb | | 6.3 | 67.9 |
| 1/4 | | 5.6 | 68.6 |
| c | | 5.7 | 68.5 |
| 1/4 | | 6.0 | 68.2 ✓ |
| cb | | 6.4 | 67.8 |
| E | | 6.3 | 67.9 |

E. Comm'l.

| | | | |
|---|---|---|---|
| E | S 29.1 | 5.38 | 68.86 |
| E | N " | 5.34 | 68.90 |
| C | S " | 5.52 | 68.72 |
| C | N " | 5.52 | 68.72 |
| W | S " | 5.61 | 68.63 |
| W | N " | 5.63 | 68.61 |

E. + 30

| | | | |
|---|---|---|---|
| W | | 6.0 | 68.2 |
| cb | | 6.0 | 68.2 |
| 1/4 | | 5.5 | 68.7 |
| c | | 5.5 | 68.7 |
| 1/4 | | 5.6 | 68.6 |

74.24

| | | | |
|---|---|---|---|
| cb | | 5.9 | 68.3 |
| E | | 5.9 | 68.3 |
| N cb Comm'l | | | |
| E | | 5.7 | 69.0 |
| cb | | 5.9 | 68.3 |
| 1/4 | | 5.5 | 68.7 |
| c | | 5.4 | 68.8 |
| 1/4 | | 5.5 | 68.7 |
| cb | | 6.0 | 68.2 |
| NW | | 5.7 | 69.0 |
| N L Comm'l = 0+00 | | | |
| W | | 4.5 | 69.7 |
| cb | | 4.7 | 69.5 |
| +W | | 5.8 | 68.4 |
| 1/4 | | 5.3 | 68.9 |
| c | | 5.7 | 69.0 |
| 1/4 | | 5.4 | 68.8 |
| +9 | | 5.7 | 68.5 |
| cb | | 4.7 | 69.5 |
| E | | 4.4 | 69.8 |

74.24

| | | |
|---|---|---|
| cb inlet NE Cor Comm'l & 49th | | |
| E Top | 5.07 | 69.22 curb Level |
| " grate | 6.00 | 68.24 |
| cb. inlet NW Cor | | |
| E Top | 5.17 | 69.07 |
| both ends cb | 5.11 | 69.13 |
| grate | 6.14 | 68.10 |
| cb. inlet SW Cor | | |
| W Top cb | 5.75 | 68.49 |
| S " " | 5.78 | 68.46 |
| E " " | 5.81 | 68.43 |
| grate | 6.77 | 67.47 |
| cb inlet SE Cor | | |
| E Top cb | 5.50 | 68.74 |
| both ends " | 5.47 | 68.77 |
| grate | 6.46 | 67.78 |
| 0+04 | | |
| E | 4.1 | 70.1 |
| cb | 4.3 | 69.9 |
| +1 | 5.6 | 68.6 |
| 1/4 | 5.3 | 68.9 |

74.24

| | | | |
|---|---|---|---|
| c | | 5.1 | 69.1 |
| 1/4 | | 5.3 | 68.9 |
| +7 | | 5.7 | 68.5 |
| cb | | 5.0 | 69.2 |
| +7 | | 4.5 | 69.7 |
| W | | 4.3 | 69.9 |
| | 0+26.7 | | |
| E - 1.8 | Brick walk | 3.43 | 70.81 |
| | 0+50 | | |
| E | | 3.6 | 70.6 |
| +8 | | 4.1 | 70.1 |
| cb | | 4.7 | 69.5 |
| 1/4 | | 4.6 | 69.6 |
| c | | 4.6 | 69.6 |
| 1/4 | | 4.8 | 69.4 |
| +9 | | 5.0 | 69.2 |
| cb | | 4.4 | 69.8 |
| W | | 3.8 | 70.4 |
| | 0+66.4 | | |
| E - 0.8 | Cent Walk | 2.77 | 71.47 |

74.24

| | | | |
|---|---|---|---|
| | 0+93 | | |
| E - 0.8 | Cent Walk | 2.20 | 71.94 |
| | 1+00 | | |
| W | | 3.5 | 70.7 |
| cb | | 4.2 | 70.0 |
| +7 | | 4.7 | 69.5 |
| 1/4 | | 4.5 | 69.7 |
| c | | 4.4 | 69.8 |
| 1/4 | | 4.5 | 69.7 |
| cb | | 4.6 | 69.6 |
| +8 | | 3.7 | 70.5 |
| E | | 3.3 | 70.9 |
| | 1+50 | | |
| E | | 3.5 | 70.7 |
| +8 | | 3.7 | 70.5 |
| cb | | 4.4 | 69.8 |
| 1/4 | | 3.9 | 70.3 |
| c | | 3.7 | 70.5 |
| 1/4 | | 4.0 | 70.2 |
| +7 | | 4.3 | 69.9 |
| cb | | 3.5 | 70.7 |
| W | | 3.4 | 70.8 |

74.24

| | | | |
|---|---|---|---|
| | 2+00 | | |
| w | | 3.1 | 71.1 |
| cb | | 3.3 | 70.9 |
| +r | | 3.8 | 70.4 |
| 1/4 | | 3.6 | 70.6 |
| c | | 3.5 | 70.7 |
| 1/4 | | 3.6 | 70.6 |
| +9 | | 4.1 | 70.1 |
| cb | | 3.4 | 70.8 |
| E | | 3.0 | 71.2 |
| | 2+50 | | |
| E | | 2.8 | 71.4 |
| +9 | | 3.2 | 71.0 |
| cb | | 3.8 | 70.4 |
| 1/4 | | 3.5 | 70.7 |
| c | | 3.4 | 70.8 |
| 1/4 | | 3.5 | 70.7 |
| cb | | 3.2 | 71.0 |
| w | | 2.8 | 71.4 |

+ or SL = Stony Frame Stone

74.24

| | | | | |
|---|---|---|---|---|
| T.P | 5.10 | 76.32 | 3.02 | 71.22 |
| | 2+97 | | | |
| w | | | 4.2 | 72.1 |
| cb | | | 4.6 | 71.7 |
| +1 | | | 5.2 | 71.1 |
| 1/4 | | | 4.8 | 71.5 |
| c | | | 4.6 | 71.7 |
| 1/4 | | | 4.8 | 71.5 |
| +8 | | | 4.9 | 71.4 |
| +8.5 | | | 6.0 | 70.3 |
| +9.5 | | | 6.0 | 70.3 |
| cb | | | 5.2 | 71.1 |
| E | | | 4.7 | 71.6 |
| | 3+00 SL Imp. grc | | | |
| E | | | 4.46 | 71.86 |
| cb - gut + Pav. | | | 4.76 | 71.56 |
| +0.75 F.L. of drain | | | 6.22 | 70.10 outlet |
| 1/4 | Pav | | 4.67 | 71.65 |
| c | " | | 4.63 | 71.69 |
| 1/4 | " | | 4.60 | 71.72 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | | 76.37 | | | Fd. BM. BP in Curb | | 76.37 | | | 79th & |
| gut | | | 4.88 | 71.44 | SW Cor IP | 7.84 | 79.64 | 4.37 | 72.10 | Imperial |
| w/ c6 | | | 4.37 | 22.09 | | | | | | |
| w | | | 3.87 | 22.50 | SE BP check to 79th & L | 57. | 7.97 | 76.97 | 76.97 | |
| | 5. c6. of Imp. | | | | | | | | | 0.05 |
| w/ c6 | | | 4.37 | 22.04 | | | | | | |
| " | gut | | 4.71 | 71.61 | | | | | | |
| c6 | pav | | 4.53 | 71.79 | | | | | | |
| 1/4 | " | | 4.37 | 72.09 | | | | | | |
| c | " | | 4.37 | 72.04 | | | | | | |
| 1/4 | " | | 4.40 | 71.92 | | | | | | |
| c6 | " | | 4.67 | 71.70 | | | | | | |
| E.L. | Top pav | | 4.77 | 71.60 | | | | | | |
| " | " c6 | | 4.77 | 21.60 | | | | | | |
| " | Fd. inlet drain | | 5.99 | 70.33 | | | | | | |
| +5 | " conc apron | | 5.70 | 70.62 | | | | | | |
| " | Top c6 | | 4.75 | 71.57 | | | | | | |

Indexed
C.S.K.

Alley X sec of Blk L, Plumosa Park

all alleys = 20' wide

E. Sta.

Moore
Rand
Mayne

19

2-19-42.




Δ = 21°20'51"
R = 470
ch = 174.08

Xsec of South, E & W alley

Blk 2 Plumosa Park

| | | | | | |
|---|---|---|---|---|---|
| Sw BP | 1.97 | 159.11 | | 157.14 | Elliott's Nail & Shiner |
| T.P. | 9.99 | 167.29 | 1.11 | 158.00 | |
| | 0-13 E gut. on Jonquil | | | | |
| S | Pav. | | 4.33 | 162.96 | |
| C | " | | 4.00 | 163.07 | |
| N | " | | 3.96 | 163.33 | |
| | 0+00 Ely Jonquil | | | | |
| N-1 | Beg. Eng. hedge | | | | |
| N 06 | | | 3.19 | 164.10 | |
| N' | Pav. | | 3.57 | 163.72 | |
| C | " | | 4.07 | 163.22 | |
| S | " | | 3.89 | 163.40 | |
| S .06 | | | 3.62 | 163.67 | |
| | 0+20 | | | | |
| S +0.07 | Beg. Stuccowall | | 3.0 | 163.7 | 0.07 in alley |
| C | | | 3.9 | 163.4 | |
| N | | | 3.7 | 163.6 | |

Red & Plotted 2/24/42. (KD)

167.29

| | | | | |
|---|---|---|---|---|
| | 0+47.4 End hedge | | | |
| N' +0.17 | Beg. Con. Blk wall | 4.5 | 162.8 | 0.17 in alley |
| C | | 4.9 | 162.4 | |
| S | | 4.7 | 162.6 | |
| | 0+59 | | | |
| S +0.5 | 1.7 P.P. | | | |
| | 0+60 End Stuccowall | | | |
| S -0.15 | Wk Con. apron | 5.39 | 161.90 | 0.15 back |
| | 0+70 | | | |
| S -.4 | & do. gar. cem. | 5.43 | 162.06 | |
| S -0.15 | cem. apron | 5.48 | 161.81 | |
| C | | 5.6 | 161.7 | |
| N | | 5.6 | 161.7 | |
| | 0+75 | | | |
| N +0.17 | end Con. Blk wall | | | in alley |
| | 0+76.5 | | | |
| N' +0.17 | 3.3 Cem walk | 5.15 | 162.14 | in alley |
| " | ground | 5.6 | 161.7 | |
| C | | 5.9 | 161.4 | |
| S | | 5.6 | 161.7 | |
| S +0.15 | on Cem. apron | 5.53 | 161.76 | |

167.29

| | | | | |
|---|---|---|---|---|
| | 0+80 End apron | | | |
| S −0.15 | Beg. Stucco wall | 5.60 | 161.69 | |
| | 0+84.5 | | | |
| N +0.10 | E 12.3 wide Brick R-66-3th Stand | 5.31 | 161.98 | in alley |
| | 0+90.6 | | | |
| S | | 6.0 | 161.3 | |
| C | | 6.4 | 160.9 | |
| +9.8 | Beg. Picket fence | 5.9 | 161.4 | |
| N +3 | | 5.9 | 161.4 | |
| | 1+00 | | | |
| N −5 | | 9.6 | 157.7 | |
| N | | 6.7 | 160.6 | |
| C | | 6.9 | 160.4 | |
| S | | 6.4 | 160.9 | |
| | 1+04.5 | | | |
| S −0.7 | end Stucco wall | | | Back fence |
| | 1+27.93 W.L. of N+S alley | | | |
| S | | 8.3 | 159.0 | |
| C | | 8.9 | 158.4 | |
| C +9.93 | end picket fence Corner | 9.4 | 157.9 | |

167.29

21

| | | | | |
|---|---|---|---|---|
| | 1+37.93 E alley to N. | | | |
| N | | 9.9 | 157.4 | |
| C | | 9.3 | 158.0 | |
| S | | 8.8 | 158.5 | |
| T.P. | 3.80 | 161.80 | 9.99 | 158.00 |
| | 1+47.93 E.L. alley to N | | | |
| S | | 4.0 | 157.8 | |
| +0.3 | in" P.P. | | | |
| C | | 4.6 | 157.2 | |
| N" | | 5.0 | 156.8 | |
| | 1+50.7 | | | |
| N +0.05 | W.L. Cem apron | 5.48 | 156.32 | 0.05 in alley |
| N −5 | " de gar. Cem | 5.97 | 156.53 | |
| | 1+66 | | | |
| N −5 | E.L. de. gar | 5.97 | 156.53 | |
| N +0.06 | " apron | 5.57 | 156.23 | 0.06 in alley |
| | 1+84 | | | |
| N | | 6.1 | 156.7 | |
| C | | 6.1 | 156.7 | |

161.80

| | | | |
|---|---|---|---|
| S | 5.9 | 155.9 | |
| +46.N & do. gar. Cent | 3.78 | 158.02 | |
| 1+96 | | | |
| N +1.0 & 3' cent walk | 1.63 | 156.17 | 1' in alley |
| 1+98 | | | |
| N' +1' beg. of Evg. hedge | | | |
| 1+93 (Please back up) | | | |
| S on line beg. wire fence | | | |
| 2+27.8 | | | |
| S on line end " fence | 6.9 | 154.9 | |
| S +3 | 7.4 | 154.4 | |
| C | 7.7 | 154.1 | |
| N' | 7.5 | 154.3 | |
| 2+50 | | | |
| N | 8.8 | 153.0 | |
| C | 9.1 | 152.7 | |
| +8 | 8.8 | 153.0 | |
| S | 8.3 | 153.5 | |
| = +74.44 W/ 2 Narcissus | | | |
| S c6 | 9.34 | 152.46 | |
| S gut pav. | 9.93 | 151.87 | |

161.80

| | | |
|---|---|---|
| C pav | 10.49 | 151.31 |
| N " | 10.47 | 151.33 |
| N' c6 | 10.17 | 151.63 |
| N' +1.4 end hedge | | |
| W gut Narcissus DC. | | |
| N' pav | 11.10 | 150.70 |
| S pav. | 10.35 | 151.45 |

Xsec N & S alley Blk L Plumosa Park

161.80

0+0 = N.L. of South E & W alley.

| | | | |
|---|---|---|---|
| W | | 3.8 | 158.0 |
| +0.7 beg. picket fence | Corner | | |
| C | | 4.4 | 157.4 |
| E | | 5.0 | 156.8 |
| 0+05 | | | |
| E -0.4 Sw. Cor garage | | 5.1 | 156.7 |
| C | | 4.7 | 157.1 |
| W | | 4.6 | 157.2 |
| 0+37 | | | |
| W | | 5.2 | 156.6 |
| C | | 5.4 | 156.4 |
| E | | 5.6 | 156.2 |

South entrance

+0.35 N. wall Cor garage & beg. rail fence

0+48.5

W -0.6 end picket fence

161.80

0+54.7

E end rail fence on line

0+55

E +0.10 1 in" P.P.

0+55.4

| | | | |
|---|---|---|---|
| E | | 6.5 | 156.3 |
| C | | 6.4 | 156.4 |
| +9.3 SL Conc. apron | | 5.93 | 155.87 |
| W +4.8 " do. gar. Conc. | | 5.0 | 156.8 |
| 0+7 N | | | |
| W -4.8 N.L. do. gar. | | 4.93 | 156.87 |
| W -0.7 Beg. Tile wall | | | |
| W +0.7 N.L. Conc. apron | | 5.93 | 155.87 |
| C | | 6.9 | 154.9 |
| E | | 6.9 | 154.9 |
| 1+10 | | | |
| - S | | 7.3 | 154.5 |
| E | | 7.4 | 154.6 |
| C | | 7.0 | 154.8 |
| W | | 6.5 | 156.3 |

0.7 in alley

" "

+0.7 end Tile wall

beg. hedge 0.5 in alley on West

| | | | | | |
|---|---|---|---|---|---|
| | | 161.80 | | | |
| | 1+25 | | | | |
| W | | | 6.5 | 156.3 | |
| C | | | 6.8 | 155.0 | |
| E | | | 7.0 | 154.8 | |
| +10 | | | 8.0 | 153.8 | |
| | 1+65 | | | | |
| -10 | | | 8.6 | 153.2 | |
| E | | | 7.9 | 153.9 | |
| +0.3 | 12" P.P. | | | | |
| C | | | 7.8 | 154.0 | |
| W/ end of hedge | | | 7.7 | 154.1 | |
| | | | | | |
| T.P. | 4.37 | 157.94 | 8.43 | 153.57 | |
| | | | | | |
| | 2+03 | | | | |
| W | | | 3.4 | 154.5 | |
| C | | | 4.1 | 153.8 | |
| E | | | 4.3 | 153.6 | |
| +9.7 | 3' conc walk | | 5.07 | 152.87 | |

157.94

| | | | |
|---|---|---|---|
| 2+57.3 | | | |
| E - 6.8 Sh. do. gar. Conc. | 5.00 | 152.94 | |
| E - 1.0 " conc apron | 5.19 | 152.75 | 1' Back |
| E | 5.0 | 152.9 | |
| C | 4.7 | 153.2 | |
| W | 3.8 | 154.1 | |
| 2+59 | | | |
| W - 33.6 ft do. garage | 2.19 | 155.75 | Golden Comment |
| 2+72.7 | | | |
| E - 6.8 Nl do. gar. Conc. | 5.02 | 152.92 | |
| E - 1.0 " conc. apron | 5.17 | 152.77 | 1' Back |
| 2+75 | | | |
| W + 0.1 beg. Stucco wall | 4.0 | 153.9 | 0.1 in alley |
| C | 5.0 | 152.9 | |
| E | 5.3 | 152.6 | |
| +14 beg picket fence | | | |
| 3+06 | | | |
| E - 1.2 end picket fence & SW Car gar. | | | E of W1 with door to alley |
| E | 5.0 | 152.9 | |
| C | 5.1 | 152.8 | |
| +7 | 4.8 | 153.1 | |
| W | 4.2 | 153.7 | |

157.94

3+76

E – 1,4 NW Cor garage

3+79.95 = SL of N, E & W alley

| | | | | | |
|---|---|---|---|---|---|
| W – 0.03 | Con Stucco wall | | 4.3 | 153.6 | |
| C | | | 5.0 | 152.9 | |
| E | | | 5.5 | 152.4 | |
| T.P. | 8.94 | 16+67 | 4.21 | 153.73 | Nail in pole |

X Sec of N. E & W alley

Blk L Pluviosa Park

16+67

E Cor Jonquil Dr

| | | | |
|---|---|---|---|
| S. Pav | | 1.91 | 160.76 |
| N " | | 2.24 | 160.43 |
| 0+00 Ea Jonquil Dr. | | | |
| N cb | | 1.61 | 161.07 |
| N Pav. | | 1.80 | 160.87 |
| C " | | 2.05 | 160.62 |
| S " | | 1.50 | 161.17 |
| S cb | Beg. of hedge 1.0 in alley | 1.26 | 161.41 |
| 0+16.2 | | | |
| S | | 1.3 | 161.4 |
| +4 | | 2.4 | 160.3 |
| C | | 2.6 | 160.1 |
| N | | 2.6 | 160.1 |
| +0.3 | SW Cor gar. | | |
| +1.4 | S edge | Conc apron 2.06 | 160.61 |
| 0+34.6 | | | |
| N – 0.3 | SE Cor garage | 3.8 | 158.9 |

W. entrance to Jonquil

167.67

| | | | | |
|---|---|---|---|---|
| N | | 3.8 | 158.9 | |
| +1.N | 12" I.P. | | | |
| +4 | | 4.6 | 158.1 | |
| C | | 4.3 | 158.4 | |
| +5 | | 4.0 | 158.7 | |
| S end hedge | | 2.5 | 160.2 | |
| S +0.1 | W.L. Cem walk | 1.98 | 160.69 | |
| | 0+38.4 | | | |
| S -0.1 | E.L. Cem walk | 2.08 | 160.59 | |
| | 0+38.45 | | | |
| S -0.5 | Beg. N' Cem. walk parallel | 2.7N | 159.95 | With alley |
| | 0+39 | | | |
| S | beg. hedge L' in alley | 3.3 | 159.4 | |
| +5 | | 4.5 | 158.2 | |
| C | | 4.7 | 158.0 | |
| N | | 5.2 | 157.5 | |
| +5.5 | W.L. Cem. apron | 5.74 | 156.93 | |
| +8.3 | " 3 car gar. | 5.70 | 156.97 | |
| | 0+47.7 | | | |
| N -5.4 | Cem apron | 5.74 | 156.93 | Break in grade of this 3 car garage |
| N -8.6 | gar. Fl. | 5.65 | 157.02 | |

167.67

| | | | | |
|---|---|---|---|---|
| | 0+48.7 | | | |
| N -5.4 | Cem apron | 5.99 | 156.68 | |
| N -8.6 | gar cem | 5.95 | 156.72 | |
| | 0+64.6 | | | |
| N -8.8 | E.L. above 3 Car gar. | 5.95 | 156.72 | |
| N -5.9 | " cem apron | 6.21 | 156.46 | |
| N | | 6.8 | 155.9 | |
| C | | 6.9 | 155.8 | |
| +9 | end hedge | | | |
| +9.4 | W.L. cem. apron | 6.89 | 155.78 | 0.6 in alley |
| S +0.4 | Hedge 2' walk | 6.84 | 156.83 | & end walk |
| S +7 | W.L. S. in cem. gar. | 6.87 | 156.80 | |
| T.P | 2.31 | 154.04 | 8.94 | 153.73 |
| | 0+66.7 | | | |
| N -2.8 | Beg. Lattice fence | | | |
| | 0+74 | | | |
| S +0.55 | E. edge Cem apron | 0.44 | 155.60 | 0.55 in alley |
| | 0+76 | | | |
| S +0.08 | Beg. Stucco wall | | | 0.08 " |

## 156.0W

| | | | | |
|---|---|---|---|---|
| | 0+85.3 | | | |
| N-3 | end lat. fence | | | |
| | 1+00 | | | |
| S | | 2.1 | 153.9 | |
| C | | 2.5 | 153.5 | |
| N | | 2.3 | 153.7 | |
| | 1+10.09 | WL of N+5 alley | | |
| N | | 2.6 | 153.4 | |
| C | | 3.0 | 153.0 | |
| C+9.9 | Cor. end Stucco wall | 2.4 | 153.6 | |
| | 1+20.09 | ℄ alley to So. | | |
| S | | 3.2 | 152.8 | |
| C | | 3.4 | 152.6 | |
| N | | 3.2 | 152.8 | |
| | 1+30.09 | EL alley to So. | | |
| N | | 3.0 | 153.0 | |
| +3 | | 3.8 | 152.2 | |
| C | | 3.8 | 152.2 | |
| S | | 3.6 | 152.4 | |
| | 1+32.5 | | | |
| S-0.5 | WL Conc apron | 3.70 | 152.34 | |

## 156.0X

| | | | | | |
|---|---|---|---|---|---|
| S-4 | w. edge door | do. gar. conc. | 3.43 | 152.61 | |
| | 1+34.3 | | | | |
| N+0.6 | 14" P.P. | | | | |
| N'-0.10 | Beg. Lat. fence | | | | |
| | 1+48 | | | | |
| S-0.30 | E edge | conc. apron | 3.84 | 152.20 | Beg. Picket fence |
| S-4.0 | " | do. gar. | 3.45 | 152.59 | |
| | 1+67 | | | | |
| S | | | 5.0 | 151.0 | |
| C | | | 5.2 | 150.8 | |
| +7 | | | 5.2 | 150.8 | |
| N | | | 4.3 | 151.7 | |
| +0.10 | end lat. fence | | | | |
| | 1+74.5 | | | | |
| N+1.0C | WL | conc apron | 5.25 | 150.79 | 1.0C in alley |
| N-2.2 | " | " gar. | 4.21 | 151.83 | |
| | 1+82.5 | | | | |
| N+1.0C | on | apron | 5.25 | 150.79 | |
| N-2.2 | EL | gar. conc | 4.14 | 151.90 | |
| | 1+84 | | | | |
| N+1.0C | Ely Cor. of above | apron | 5.24 | 150.80 | 1.0C in alley |

156.0K

| | | | | |
|---|---|---|---|---|
| | 1+90.5 | | | |
| S +0.3 | & 3' conc. walk | 5.70 | 150.34 | 0.3 in alley |
| | 2+00 | | | |
| N | | 5.7 | 150.3 | |
| +N | | 6.N | 149.8 | |
| C | | 6.1 | 149.9 | |
| +9.9 | end Pick. fence | 6.0 | 150.0 | |
| | 2+17.8 | | | |
| S +0.3 | Beg. Pick. fence | | | 0.3 in alley |
| | 2+34 | | | |
| N +0.3 | 14" P.P | | | |
| | 2+50 | | | |
| S +0.3 | end pick fence | 7.3 | 148.7 | 0.3 " |
| C | | 7.8 | 148.N | |
| +7 | | 7.7 | 148.3 | |
| N | | 7.4 | 148.6 | |
| | 2+58.65 w/y Narcissus Dr | | | |
| N c6 | | 8.13 | 147.91 | |
| N pav. | | 8.40 | 147.64 | |
| C " | | 8.57 | 147.47 | |
| S " | | 8.7N | 147.82 | |

156.0K

| | | | | |
|---|---|---|---|---|
| S c6 | | | 7.89 | 148.15 |
| | w/y gutter | Narcissus | | |
| S pav | | | 8.86 | 147.18 |
| N " | | | 9.07 | 146.97 |
| T.P. | 12.7N | 159.9N | 8.84 | 147.20 |
| check to Orig. B.M. | | | 2.76 | 157.16 | 157.1K 0.0N |

Red. & Plotted 2/24/42 (MM)

Lewis & A St Kelhoer to Pacific Hwy
Pacific Hwy. 28' West of E.L. A St to 2 Beech

| | | | | | |
|---|---|---|---|---|---|
| BM | 2.29 | (17.29) | | (15.00) | WE BP A St & 4K |
| 0+0 | = 20' W of E.L. Kelhoer | | 3.47 | 13.82 | |
| +11 | = ℄ SO Electrack Top Rail | | 3.50 | 13.79 | |
| +55 | = W.L. Kelhoer : Wly Paving | | 4.04 | 13.25 | |
| 1+0 | | | 5.0 | 12.3 | |
| +50 | | | 6.1 | 11.2 | |
| +88 | = Ely Santa Fe Spur Top Rail | | 6.56 | 10.73 | |
| 2+0 | | | 7.1 | 10.2 | |
| +05 | = Ely Rail Spur Top Rail | | 6.83 | 10.46 | |
| +32 | = Ely " " | | 7.63 | 9.76 | |
| +40 | = Ely Main Line TR | | 7.60 | 9.69 | |
| +54 | = Ely " " TR | | 7.67 | 9.62 | |
| +55 | = E.L. Calif | | 8.1 | 9.2 | |
| +77 | = Ely Main Line TR | | 7.91 | 9.38 | |
| +91 | = Ely Spur Top Rail | | 8.17 | 9.12 | |
| +97 | = Ely " | | 8.20 | 9.09 | |
| 3+0 | | | 8.7 | 8.6 | |
| +20 | = Ely Spur | | 8.78 | 8.51 | |
| +24 | = Ely Spur | | 8.83 | 8.46 | |
| +50 | | | 9.5 | 7.8 | |

March 7.42 Sissons Northern W Moore
(17.29)

29

| | | | | | |
|---|---|---|---|---|---|
| TP | 1.81 | (9.42) | 9.68 | (7.61) | |
| 4+0 | | | 5.1 | 6.3 | |
| +50 | | | 4.7 | 4.7 | |
| 5+0 | | | 6.1 | 3.3 | |
| +30 | = E.L. Pacific Hwy. | | 6.5 | 2.9 | |
| +33 | = Existing Culvert See plan & Culvert | | 6.5 | 2.9 | |
| +33 | 61.6 South of ℄ Flow Line | = Curb Inlet | 10.47 | - 1.05 | |
| +33 | 31.0 W of ℄ Flow Line | = Curb Inlet | 10.83 | - 1.41 | |
| 5+58 | = 4.18' W of E.L. Pacific = 6' E of E Edge of Pav | | 6.5 | 2.9 | |
| 5+58 | 6' W = Ely Paving | | 6.44 | 2.98 | |
| 6+0 | | | 6.7 | 2.7 | |
| 6+0 | 6' W = Ely Paving. | | 6.53 | 2.89 | |
| +50 | | | 6.6 | 2.8 | |
| 7+0 | | | 6.4 | 3.0 | |
| 7+0 | 6' W = Ely Paving | | 6.01 | 3.41 | |
| TP | 6.01 | (9.05) | 6.38 | (3.04) | |
| +48 | = 54' Full Width Pav | | 5.63 | 3.42 | |
| 8+0 | on Pav | | 5.29 | 3.76 | |
| +50 | | | 5.10 | 3.95 | |
| 8+98 | = E.L. A St | | 5.09 | 3.96 | |

| | | | | | |
|---|---|---|---|---|---|
| | | (9.05) | | | |
| 9+38 | ⅞ Ash | on Paving | 5.03 | 4.02 | |
| +78 | ⅛L Ash | " " | 4.99 | 4.06 | |
| 10+0 | | " " | 4.90 | 4.15 | |
| +50 | | " " | 4.88 | 4.37 | |
| 11+0 | | " " | 4.66 | 4.39 | |
| +50 | | " " | 4.41 | 4.64 | |
| 12+0 | | " " | 4.26 | 4.79 | |
| +50 | | " " | 4.13 | 4.92 | |
| +78 | ⅝L Beech | " " | 4.10 | 4.95 | |
| 13+18 | ⅞ Beech | " " | 4.07 | 4.98 | |
| TP | 10.71 | (5.38) | 4.38 | (4.67) | |
| TP | 8.53 | (22.31) | 1.60 | (13.78) | |
| BM | | | 2.34 | (19.97) | N.W.B.P. Beech × Kathar. 19.99 |

Survey, Levels on Lots 21-24 / 160 U.H.

and xsec of 20' alley

Moore
Hazard
Hoops
6-1-04

Indexed
C.S.K.





Levels on lots 21-24/100 U.H.

Baseline
N. Curb
Lincoln

Left

Right →
gutter

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| 1 + 20 | 347.49<br>1.3<br>11x | 347.29<br>1.5<br>Cx | 346.29<br>2.5<br>1C | 344.89<br>3.9<br>1x | 343.79<br>5.0<br>10 | 343.56<br>5.23 | 342.91<br>5.88 |
| 0 + 80 | 347.79<br>1.0<br>11x | 346.89<br>1.9<br>Cx | 345.89<br>2.9<br>1C | 345.19<br>3.6<br>1x | 343.89<br>4.9<br>10 | 343.66<br>5.13 | 343.07<br>5.72 |
| 0 + 40 | | 347.39<br>1.4<br>11x | 345.89<br>2.9<br>Cx | 344.89<br>3.9<br>1C | 342.19<br>6.6<br>1x | 343.88<br>4.91 | 343.27<br>5.52 |
| 0 + 14 = E.L. 32nd | | | 346.19<br>2.6<br>11x | 345.49<br>3.3<br>Cx | 344.35<br>4.44<br>1x | 344.01<br>4.78 | 343.40<br>5.39 |
| 0 + 00 = E Curb 32nd | | | 345.46<br>3.33<br>11x | 344.69<br>4.10<br>Cx | 344.04<br>4.75<br>1x | | |

| | | | | | |
|---|---|---|---|---|---|
| T.P. N.E. | | | | | 32nd |
| 7' C.T. | 4.61 | 348.79 | 9.00 | 344.18 | Lincoln |
| SEBP | 0.1x | 353.18 | | 353.04 | 32nd Polk. |

348.74

X Sec no' alley Blk 160 U.K.

H.I. Fwd
3v8.79

00-14 : N C6. Line Lincoln

| | | | |
|---|---|---|---|
| W | pav. gut | 5.81 | 342.98 |
| E | " " | 5.88 | 342.91 |
| | 0+00 N/ Q6e. | | |
| E | c6 | 5.08 | 343.71 |
| E | Pav | 5.31 | 343.48 |
| C | " | 5.59 | 343.20 |
| W | " | 5.29 | 343.50 |
| W | c6 | 5.06 | 343.73 |
| | 0+01 | | |
| W | -3 | 3.7 | 345.1 |
| W | | 4.5 | 344.3 |
| C | | 5.2 | 343.6 |
| E | | 4.2 | 344.6 |
| | 0+08 | | |
| E | | 2.1 | 346.7 |
| | +6 | 4.0 | 344.8 |
| C | | 4.1 | 344.7 |

Reduced & Plotted on #1890
6-4-1962

3v8.79

| | | | | |
|---|---|---|---|---|
| C | +6 | | 3.8 | 345.0 |
| C | +8 | | 2.6 | 346.2 |
| W | | | 2.3 | 346.5 |
| | +0.3 SE Cor. shed ✓ | | | |
| TP | 7.76 | 35v.95 | 3.60 | 345.19 |
| | 0+23 | | | |
| W | +1.7 = 24" P.P ✓ | | | |
| | 0+26 | | | |
| W | | | 6.0 | 347.0 |
| C | | | 6.0 | 347.0 |
| C | +8.5 10" Tel. P. ✓ | | | |
| E | | | 6.1 | 346.9 |
| | 0+38 | | | |
| W | +0.1 NE Cor. shed ✓ also beg. old wire fence | | | |
| | 0+50 | | | |
| E | -0.6 Low Bd. fence ✓ | | | |
| E | | | 5.3 | 347.7 |
| C | | | 5.9 | 347.1 |
| W | | | 5.7 | 347.3 |

| | | | |
|---|---|---|---|
| | 0+77 | | |
| E −0.6 | end Low Bd fence ✓ | | |
| | 0+87 | | |
| W −0.1 | end wire fence ✓ | | |
| | 0+88 | | |
| W | ℄ Sew. gar. ✓ | 5.7 | 347.8 dirt |
| C | | 5.3 | 347.7 |
| E | 12 wide Sew. gar. | 5.0 | 348.0 dirt |
| | 0+97 | | |
| W +0.8 | SE Cor wooden Shed ✓ | | |
| | 1+00 | | |
| E | | 4.9 | 348.1 |
| C | | 5.2 | 347.8 |
| W | | 5.1 | 347.9 |
| | 1+25 | | |
| E −3 | ℄ Sew. gar. ✓ | 5.0 | 348.0 on 1 ft. |
| | 1+34 | | |
| W +0.9 | NE Cor Wooden Shed ✓ | | |
| | 1+50 | | |
| −10 | | 4.4 | 348.6 |
| W | | 4.5 | 348.5 |





| | | | |
|---|---|---|---|
| W +1.6 | 16" RP ✓ | | |
| C | | 4.8 | 348.2 |
| C +8.2 | 10" Tel P. ✓ | | |
| E | | 4.9 | 348.1 |
| +10 | | 5.2 | 347.8 |
| | 1+Co. C | | |
| E +0.2 | E 5 in wide add. to dwelling ✓ | | |
| W −2.3 | ℄ Cent apron | 4.40 | 348.55 ✓ |
| W −5.1 | E Sew gar | 4.01 | 348.94 Cem. ✓ |
| | 1+71 | | |
| E +0.2 | SW Cor ✓ add. to above dwelling | | |
| | 1+85 | | |
| E +0.1 | NW Cor ✓ | | |
| | 2+00 | | |
| −10 | | 5.3 | 347.7 |
| E | | 5.2 | 347.8 |
| C | | 4.8 | 348.2 |
| W | | 4.7 | 348.3 |
| +0.5 | end E & W fence Line | | |
| +10 | | 4.5 | 348.5 |

35+95

| | | | |
|---|---|---|---|
| | 2+09 | | |
| E−4.5 | ℄ Sim. gar. | 5.3 | 347.7 oil ft. Sly entrance |
| E+0.3 | SW Cor above gar. | | |
| T.P. | V.00 | 35+32 | 4.63 | 348.32 |
| | 1+26 | | |
| −6 | SL Sim. gar | 4.0 | 348.3 dirt |
| W | | 4.N | 348.1 |
| C | | 4.3 | 348.0 |
| +9.9 | NW Cor gar. | 4.4 | 347.9 Sly entrance |
| E+10 | | 5.0 | 347.3 |
| | 2+28 | | |
| E | beg. Earth fence | | |
| | 2+41 | | |
| W−0.3 | ℄ 13' wide Cor apron | 4.00 | 348.32 |
| W−6.0 | ℄ Sim gar. | 2.91 | 349.41 Conc ft. |
| | 2+50 | | |
| W−0.8 | beg. picket fence | | |
| | 2+56 | | |
| E+0.2 | end fence and SW Cor Bd & Bat. add. to dwelling | 5.0 | 347.3 |

35+32

| | | | |
|---|---|---|---|
| C | | 4.4 | 347.9 |
| W | | 3.8 | 348.5 |
| | 2+66 | | |
| E+0.1 | NW Cor above add. also beg. Earth fence | | |
| | 2+75 | | |
| −10 | | 6.0 | 346.3 |
| −1 | | 5.3 | 347.0 |
| E | end Earth fence | 4.6 | 347.7 |
| +2.0 | beg. wire fence also 10" Tel. P. | | |
| C | | 4.6 | 347.7 |
| +7 | | 4.3 | 348.0 |
| W | | 3.4 | 348.9 |
| +5 | | 3.4 | 348.9 |
| | 2+78 | | |
| W+0.8 | 16" P.P. | | |
| | 3+00 | | |
| −0.2 | end picket fence end | | beg. High Bd. fence |
| W | | 4.1 | 348.2 |
| +3 | | 4.5 | 347.8 |
| C | | 4.6 | 347.7 |

| | | | |
|---|---|---|---|
| C +7.7 | Wire fence ✓ | 4.8 | 347.5 |
| +8 | | 5.7 | 346.6 |
| E | | 5.8 | 346.5 |
| +10 | Lawn | 6.0 | 346.3 |
| | 3+25 | | |
| E +3.8 | end wire fence ✓ | | |
| | 6eg tot. " " | | |
| | 3+26 | | |
| W -0.6 | end high Bd. fence ✓ | | |
| | 3+33 | | |
| -2.5 | against frame Porch | 6.0 | 346.3 |
| E | | 5.9 | 346.4 |
| +3.8 | Fence | 4.9 | 347.4 |
| C | | 4.5 | 347.8 |
| W | | 3.7 | 348.6 |
| +0.6 | SL Con apron | 3.73 | 348.59 |
| +3.8 | " " " | 3.04 | 349.28 |
| +8.8 | " do. gar. | | Con. Fl. |
| | 3+50 | | |
| W -8.8 | Fl. above gar. | 3.15 | 349.17 |
| W -3.8 | " apron | 3.21 | 349.11 |
| W -0.6 | " " | 3.92 | 348.30 |





| | | | |
|---|---|---|---|
| | 3+60 | | |
| W -6.6 | E Sill gar. | 3.26 | 349.06 Con. Fl. |
| W -0.7 | E Finish Con apron | 3.96 | 348.36 |
| W | | 4.0 | 348.3 |
| C | | 4.8 | 347.5 |
| +8.7 | fence | 4.7 | 347.6 |
| +9 | | 6.4 | 345.9 |
| E | | 4.6 | 347.7 |
| +.4 | | 6.7 | 345.6 |
| | 3+70 | | |
| W -0.1 | 6eg. Bd. fence ✓ | | |
| | 3+77 | | |
| E +1.5 | end laz fence ✓ | | |
| E +0.4 | 6eg. " " ✓ | | |
| | 3+86 | | |
| E +1.8 | "L" Tel. Pole ✓ | | |
| | 3+93 | | |
| E +1.8 | angle in Laz. fence ✓ | | |
| | 4+00 | | |
| -.4 | | 6.0 | 346.3 |

| | | | |
|---|---|---|---|
| F | | 5.9 | 346.4 |
| + ~ | | 5.x | 346.9 |
| c | | 5.~ | 347.1 |
| + 9.7 | end of Rd fence beg Conc. Ret. wall | x.3 | 348.0 end fence |
| | 4 + 03 | | |
| W + 1.3 | P.P. ✓ | | |
| | 4 + ~ | | |
| W + 0.9 | end Conc. Ret Wall | 5.0 | ✓ 347.3 ground at Base wall |
| | 4 + ~9 | | |
| W + 0.9 | SE Cor Stucco Bldg ✓ | | |
| | 4 + 31 | | |
| W + 3.3 | SE Cor add to above Stucco | | |
| | 4 + 37 | | |
| - 10 | | 7.~ | 345.1 |
| E | | 6.8 | 345.5 |
| + 0.9 | end Lat. Fence | 6.~ | 346.1 ✓ |
| + 5 | | 5.7 | 346.6 |
| c | | 5.6 | 346.7 |
| + 6.7 | | 5.1 | 347.2 |





| | | | |
|---|---|---|---|
| | 4 + 38 | | |
| W + 3.3 | NE Cor add to above Stucco ✓ | | |
| | 4 + 49 | | |
| W + 1.3 | NE Cor Stucco Bldg ✓ | | |
| | beg. wire fence which is falling into alley ✓ | | |
| | 5 + 00 | | |
| W + ~.0 | 12" P.P. | | |
| T.P. | 3.11 | 349.63 | 5.80 3 x C.5~ |
| | 5 + 0.3 | | |
| E - 5 | | 3.8 | 345.8 |
| E | | 3.7 | 345.9 |
| C | | 3.~ | 346.2 |
| C + 5.9 | SE Cor. apron | 3.00 | 346.63 |
| C + 8.3 | SE Cor. do. gar. | ~.5~ | 347.09 Conc Fl. |
| | 5 + ~3 | | |
| W + 1.7 | NE Cor. do. gar. | ~.51 | 347.12 " " |
| W + 4.1 | NL Conc. apron | ~.95 | 346.68 |
| | 5 + ~3.~ | | |
| W + 1.7 | Beg. picket fence | | |

3 x 9.03

| | | | | |
|---|---|---|---|---|
| | 5+50 | | | |
| W+2.0 | end picket fence | | ✓ | |
| | 5+54 | | | |
| W+0.7 | ℄ Sidewalk | 2.36 | 347.27 | Con. rt. |
| W+6.0 | ℄ 8' Con. apron | 2.88 | 346.75 | |
| C | | 3.4 | 346.2 | |
| E | | 3.8 | 345.8 | |
| | 5+58.37 /wz. ℄ alley & wL Boundary | | | |
| | Sec. on wL Boundary | | See Sketch | |
| | | | 346.52 | Top alley Rct. |
| 5L30 S of ℄ alley | | 3.11 | | |
| " " on ground | | 3.8 | 345.8 | |
| ℄ on rxn H46 | | 3.58 | 346.05 | |
| 1L+3 N of ℄ alley | | 2.67 | 346.96 | Top alley Rct |
| " " ground | | 3.1 | 346.5 | |
| TP | 4x8 | 355.72 | 2.32 | 347.24 |
| check to orig. B.M. | | | 2.48 | 353.04 353.04 |

7-12-42

Sommermeyer Bagg Fox — X-Sec. Glenfield Fairmount to Manzanita Dr. — Sketch on page 43

| | | | | | |
|---|---|---|---|---|---|
| B.M. S.E. Thorn on Fairmount | 1.33 | 319.35 | | 318.02 | F.B. 1556 P.22. |
| T.R | 0.35 | 311.09 | 8.61 | 310.74 | |
| 0+00 = Psop to south ↑ 309.76 | | | {Glenfield + Poplar | | |
| 0+00 on S. to 0+48.02 on N. (Along W. Line Fairmount) | | | | | |
| 34.66 Lt | | | 5.9 | 305.2 | |
| 13.86 Lt Ground | | | 6.7 | 304.2 | |
| ← Top Curb | | | 7.13 | 303.96 | |
| ← Gutter | | | 7.40 | 303.69 | |
| 10.40 Lt 1/4 | | | 7.09 | 304.09 | |
| ℄ | | | 6.57 | 304.52 | |
| 10.40 Rt 1/4 | | | 6.29 | 304.80 | |
| 20.86 Rt. cb. | | | 5.92 | 305.17 | |
| 34.66 Rt. Prop. P.I. | | | 5.77 | 305.32 | |
| 37.6 Rt Gutter | | | 5.77 | 305.32 | |
| ← Curb top broken | | | 5.76 | 305.33 | |
| 44' Rt | | | 5.0 | 306.1 | |
| 53.43 Rt Prop. Curve Pint on Fairmount | | | 4.9 | 306.2 | |
| 5' W. west line Fairmount 0+05 on South to 0+53.02 on N. | | | | | |
| 53.4 Rt. | | | 4.9 | 3062 | |
| 44' Rt. | | | 4.1 | 307.0 | |

Indexed C.S.R.

π 311.02

Reduced & Plotted 1-15-42 C.B.H.

| | | | |
|---|---|---|---|
| 20.8 Rt | | 5.8 | 3053 |
| ℄ | | 6.7 | 3044 |
| 10' Lt | | 7.0 | 3041 |
| 21 Lt | | 5.6 | 3055 |
| 34.66 Lt Prop | | 5.6 | 3055 |
| 0+66.79 | | | |
| 35' Lt. | | 4.9 | 3062 |
| 25' Lt | | 4.9 | 3062 |
| 15 Lt cb | | 5.0 | 3061 |
| 13 Lt | | 6.6 | 3045 |
| 7.5 Lt 1/4 | | 6.4 | 3047 |
| ℄ | | 6.1 | 3050 |
| 7.5 Rt 1/4 | | 5.9 | 3052 |
| 13 Rt | | 5.7 | 3054 |
| 15 Rt cb | | 5.4 | 3057 |
| 25 Rt. Prop | | 4.9 | 3062 |
| 1+00 25' Rt. Prop | | 4.2 | 3069 |
| 15 Rt | | 4.8 | 3063 |
| 7½ Rt | | 5.2 | 3059 |
| ℄ | | 5.3 | 3058 |

X - Soc Glen Field

| | | | |
|---|---|---|---|
| 1+00 | | | |
| 7.5' Lt | 311.99 | 5.7 | 305.4 |
| 15' Lt | | 5.9 | 305.2 |
| 15 Lt | | 4.9 | 306.2 |
| 25 Lt | | 5.0 | 306.1 |
| 35 Lt | | 5.2 | 305.9 |
| 1+22.5 | | | |
| 16.8 Lt | 1" P. Pole ✓ # P3124 | | |
| 1+23.3 | 16' Rt. 1' Diam Guy post | | |
| 1+24.99 | East Line alley to South | | |
| 25' Lt | | 4.8 | 306.3 |
| 15 Lt | | 4.7 | 306.4 |
| 11' Lt | | 5.2 | 305.9 |
| 7.5 Lt | | 5.1 | 306.0 |
| ℄ | | 4.8 | 306.3 |
| 7.5 Rt | | 4.8 | 306.3 |
| 15 Rt | | 4.3 | 306.8 |
| 25 Rt | | 3.9 | 307.2 |
| 1+40 | W. Line alley to South | | |
| 25 Rt | | 3.9 | 307.2 |
| 23.8 Rt | Corner of Bound Batt. garage 1/2 IN Street | | |
| 15' Rt | | 4.1 | 307.0 |



| | | | | |
|---|---|---|---|---|
| 1+40 | | 311.99 | | |
| 7.5 Rt | | | 4.7 | 306.4 |
| ℄ | | | 4.6 | 306.5 |
| 7.5 Lt | | | 4.8 | 306.3 |
| 15 Lt | | | 4.6 | 306.5 |
| 25 Lt | | | 4.8 | 306.3 |
| 50 Lt | | | 5.0 | 306.1 |
| 75 Lt | | | 5.7 | 305.4 |
| T.P. | 5.14 | 311.97 | 4.26 | 306.83 |
| 1+69 | 25' Rt. Edge of drive | | 3.98 | 307.99 |
| 1+74 | 21' Rt Corner of drive | | 4.05 | 307.92 |
| ~~1+77.5~~ | ~~24.5 Rt.~~ | ~~Edge of walk~~ | ~~4.05~~ | |
| 1+75 | | | | |
| 25 Lt | | | 5.5 | 306.5 |
| 15 Lt | | | 4.9 | 307.1 |
| 11 Lt | | | 5.5 | 306.5 |
| 7.5 Lt | | | 5.2 | 306.8 |
| ℄ | | | 4.8 | 307.2 |
| 7.5 Rt | | | 4.9 | 307.1 |
| 12 Rt | | | 4.9 | 307.1 |
| 15 Rt | | | 4.6 | 307.4 |

X-Sec - Glenfield

π 31197

| | | | |
|---|---|---|---|
| 1+75 - 22 E Rt | Edge of drive | 4.01 | 307.96 |
| +77 5 | 24 E Rt. Junction walk & drive | 4.05 | 307.92 |
| 1+80 3 - 23 4 Rt. | P. Pole 1 Guy pole | | |
| +86 5 - 21 5 Rt | Lin walk edge " | 3.86 | 308.11 |
| +87 6 - 23 11 Rt | corner conc. porch. | 3.65 | 308.32 |
| +94 - 21 5 Rt. | Lin walk edge " | 3.84 | 308.13 |
| +97 2 25' Rt. | Edge walk | 3.78 | 308.19 |
| 2+00 - 25' RT | | 4.0 | 308.0 |
| 15 RT | | 4.2 | 307.8 |
| 7 E RT | | 4.6 | 307.4 |
| ℄ | Rim M.H. ✓ | 4.5 | 307.5 |
| 7 E Lt | | 5.0 | 307.0 |
| 12' Lt | | 5.3 | 306.7 |
| 15' Lt | | 5.0 | 307.0 |
| 25' Lt | | 5.4 | 306.6 |
| 2+14 = E. Line Alley to N. | | | |
| ℄ | | 4 6 | 307.4 |
| 7 5 Rt | | 4 5 | 307.5 |
| 15 Rt | | 4 1 | 307.9 |
| 25 Rt | | 3 8 | 308.2 |

π 31197

| | | | |
|---|---|---|---|
| 2+34 80 = W. Line alley to North | | | |
| 5 Rt | | 3.3 | 308.7 |
| 25' Rt | | 3.7 | 308.3 |
| 15 Rt | | 4.2 | 307.8 |
| 7 5 Rt | | 4.5 | 307.5 |
| ℄ | | 4.5 | 307.5 |
| 7 5 Lt | | 4 E | 307.2 |
| 15 Lt | | 5 E | 307.0 |
| 25 Lt | | 5 1 | 306.9 |
| 2+60 - 24' Lt. End cedar Hedge to South ✓ | | | |
| 2+70 27 6 Lt. 8" acacia ✓ | | | |
| 2+78 5 25' Rt | Edge of 3' conc. walk | 4 20 | 307.07 |
| +86 4 - 27 2 Lt 8" acacia tree ✓ | | | |
| 2+93 - 25' Lt | E Edge Ribbon drive | 5.03 | 306.94 |
| +99 2 - 25' Lt | W. " " " | 4.99 | 306.98 |
| 3+00 25' Lt | | 4.9 | 307.1 |
| 15 Lt | | 4.8 | 307.2 |
| 7 5 Lt | | 4 7 | 307.3 |
| ℄ | | 4 4 | 307.6 |
| 7 E Rt | | 4 3 | 307.7 |

X-Sec. Glenfield

3/11/97

| | | | |
|---|---|---|---|
| 3+00 - 11' Rt | | 4.3 | 307.7 |
| 15' Rt | | 3.8 | 308.2 |
| 25' Rt | | 3.3 | 308.7 |
| 50' Rt | | 3.2 | 308.8 |
| +45.8 25' Lt | ℄ 84' cone. drive | 4.82 | 306.15 |
| 3+50 25' Rt | | 3.8 | 308.2 |
| 15 Rt | | 4.1 | 307.9 |
| 13 Rt | | 4.5 | 307.5 |
| 7.5 Rt | | 4.4 | 307.6 |
| ℄ | | 4.3 | 307.7 |
| 7.5 Lt | | 4.6 | 307.4 |
| 15 Lt | | 4.8 | 307.2 |
| 25 Lt | | 4.8 | 307.2 |
| 3+54 18 Lt | ✓ 1' acacia tree | | |
| 3+59.5 25.5 Lt | ON 3' cone. walk | 4.55 | 307.42 |
| 17 Lt. | End. 3' piece of walk to Prop. | 4.65 | 307.32 |
| +71.4 26.4 Lt | ✓ 10" acacia | | |
| +80.1 25 Lt | | 5.2 | 307.0 |
| 24.2 Lt | ✓ start Fence. E. End picket fence | | |
| 15 Lt. | | 4.8 | 307.2 |

3/11/97

| | | | |
|---|---|---|---|
| 3+80.1 | 7.5 Lt | 4.8 | 307.2 |
| | ℄ | 4.6 | 307.4 |
| | 7.5 Rt | 4.4 | 307.4 |
| | 15 Rt | 4.2 | 307.8 |
| | 25' Rt | 3.6 | 308.4 |
| | 35 Rt | 3.4 | 308.6 |
| 4+11.64 = P.C. on North. | | | |
| 25 Rt | | 3.8 | 308.2 |
| 15 Rt | | 4.3 | 307.7 |
| 7.5 Rt | | 4.6 | 307.4 |
| ℄ | | 4.7 | 307.3 |
| 7.5 Lt | | 5.0 | 307.0 |
| 15 Lt | | 5.0 | 307.0 |
| 24.2 Lt | Picket Fence | 5.2 | 306.8 |
| 25' Lt | | 5.2 | 306.8 |
| 4+25.43 = P.C. on South | | | |
| 25' Lt | | 5.5 | 306.5 |
| 24.2 Lt | Edge fence on BC. | | |
| 15 Lt | | 5.1 | 306.9 |
| 11 Lt | | 5.3 | 306.7 |

| | | | | |
|---|---|---|---|---|
| | | 311.97 | X-500 - Glenfield | |
| 75 Lt | | | 5 1 | 3069 |
| ℄ | | | 4 6 | 3074 |
| 75 Rt | | | 4 5 | 3075 |
| 15 Rt | | | 4 3 | 3077 |
| 25 Rt | | | 3 8 | 3082 |
| L. From E.C. on North to E.C. on South along E. Line Manzanita Dr. | | | | |
| 02 N. of E.C. N. edge walk | | | 2.50 | 309.47 |
| E.C. on walk | | | 2.50 | 309.47 |
| 56 26 Rt S. Edge walk | | | 2.55 | 309.42 |
| 25 24 Rt = P.I | | | 4 1 | 3079 |
| 24 Rt | | | 4 2 | 3078 |
| ℄ | | | 4 5 | 3075 |
| 15' Lt | | | 5 5 | 3064 |
| 17 Lt | | | 5 1 | 3069 |
| 25 34 P.I. | | | 5 5 | 3065 |
| 37 13 At E.C. | | | 5 9 | 3061 |
| T.P. A177 | | 312.30 | 4.44 | 307.53 |
| Set B.M. S.E. cor. P.I. Hub | | | 5.92 | 306.38 |
| Set B.M. N.E. 7' Hub Manzanita Dr. + Manzanita Dr. | 9.75 | 316.13 | 1.15 | 314.98 |
| Check Original B.M. Thorn & Fairmount | 4.75 | 319.73 | 1.72 | 318.01 |
| | | | so 318.02 - .01 error | |



Sommermeyer Bagg Fay — X-Sec. Manzanita Drive. Manzanita Place to Heather — 7-13-42

| | | | | |
|---|---|---|---|---|
| B.M. Glenfield + Manz. Dr. | S.E. P.I. Hub (See P.A3) | | | 306.38 |
| | 10.07 | 316.45 | | |
| SW. Prop to SE prop. | 25.02 Rt | | 3.3 | 313.2 |
| | 15' Rt | | 3 1 | 313.4 |
| | 7.5 Rt | | 2 9 | 313.6 |
| | ℄ | | 2 8 | 313.7 |
| | 7.5 Lt | | 3 0 | 313.5 |
| | 15 Lt | | 3 3 | 313.2 |
| | 17' Lt | | 2 7 | 313.8 |
| | 25 Lt | | 2 6 | 313.9 |
| 0+00 = | Rt. Ls. to prop. on East. | | 2 6 | 313.9 |
| | 17 Lt | | 2 8 | 313.7 |
| | 15 Lt | | 3 3 | 313.2 |
| | 7.5 Lt | | 3 1 | 313.4 |
| | ℄ | | 2 8 | 313.7 |
| | 7.5 Rt | | 3 0 | 313.5 |
| | 15 Rt | | 3 3 | 313.2 |
| | 25 Rt | | 3 5 | 313.0 |
| | 50 Rt | | 5 2 | 311.3 |
| 0+46.5 | 15.2 Rt. | 8" Pepper Tree | | |

Reduced & Plotted on Profile # 2457 - 7-16-42

Indexed E-3.1K.

44

Deflections
~~to 4+93.55 18°-20'~~
- 4+75 - 13°-0'
4+50 9°-51'-30"
4+25 - 6°-42'-45"
4+00 - 3°-34'



X-Sec. Manzanita Dr.

| | | | | |
|---|---|---|---|---|
| | | 316.45 | | |
| 0+50 | 35 Rt | | 5.6 | 310.9 |
| | 25 Rt | | 5.4 | 311.1 |
| | 15 Rt | | 5.1 | 311.4 |
| | 7.5 Rt | | 5.0 | 311.5 |
| | ℄ | | 4.2 | 311.8 |
| | 7.5 Lt | | 4.2 | 311.6 |
| | 15 Lt | | 4.8 | 311.7 |
| | 25 Lt | | 4.5 | 312.0 |
| 0+64.8 | 17.4 Rt. | 1" pepper tree | | |
| 0+72 - | 27.3 Rt = ℄ Conc. walk | 2.5 | 5.75 | 310.70 |
| 0+78 - | 86 Rt ℄ Double garage Conc. floor | | 10.64 | 305.81 |
| 0+78.4 - | 24 Rt N. Edge Ribbon drive | | 5.97 | 310.48 |
| 0+86.8 - | 24.1 Rt. S. " " " | | 6.09 | 310.36 |
| 0+91.6 - | 17.5 Rt. = 6" Acacia tree | | | |
| 1+00 - | 25 Lt. | | 5.9 | 310.6 |
| | 15 Lt | | 6.0 | 310.5 |
| | 10 Lt | | 6.2 | 309.8 |
| | 7.5 Lt | | 6.4 | 310.1 |
| | ℄ | | 6.2 | 310.3 |
| | 7.5 Rt | | 6.5 | 310.0 |

| | | | |
|---|---|---|---|
| | 316.45 | | |
| 1+00 - | 12 Rt | 7.0 | 309.5 |
| | 15 Rt | 6.5 | 310.0 |
| | 25 Rt | 6.5 | 310.0 |
| | 35 Rt | 6.6 | 309.9 |
| 1+01 - | 17.5 Rt 2" Hybiscus bush | | |
| 1+17 | 25 Lt Picket Fence crosses prop. | 6.5 | 310.0 |
| 1+17.5 | 25 Lt = N. edge 9' conc. drive | 6.39 | 310.06 |
| 1+21 - | 18.2 Lt End picket fence | | |
| 1+22 - | 17.3 Lt. = ctr. 1.5' P. Pole | | |
| | 15.1 Lt = End of Flare (2.5' Rad.) Conc. drive | 6.66 | 309.79 |
| 1+23 - | 35 Rt | 7.5 | 309.0 |
| | 25 Rt | 7.1 | 309.4 |
| | 16.6 Rt = ctr. 1.5' Acacia tree | 6.7 | 309.8 |
| | 15 Rt | 7.2 | 309.3 |
| | 11 Rt | 7.6 | 308.9 |
| | 7.5 Rt | 7.3 | 309.2 |
| | ℄ | 7.0 | 309.5 |
| | 7.5 Lt | 7.2 | 309.3 |
| | 11 Lt. | 7.3 | 309.2 |
| | 14.8 Lt Edge. conc. drive | 6.67 | 309.78 |

# X-Sec. Manzanita Dr. (316.45)

| | | |
|---|---|---|
| 1+23 - 15 Lt | 6.67 | 309.78 |
| 25' Lt on drive | 6.50 | 309.95 |
| 1+27 - 25' Lt. = S. edge drive | 6.59 | 309.86 |
| 1+27.5 - 25' Lt. Picket fence crosses prop | | |
| 1+31 - 18.6 Rt. L.in picket fence | | |
| 1+33 - 17 Lt S. Edge flare at end of drive | 6.84 | 309.61 |
| 1+35 - 15.6 Lt. L.in picket fence | | |
| 1+39.6 - 25' Lt. Edge 3' 2.5" conc. walk. | 6.97 | 309.48 |
| 1+40.25 = 25 Lt = Prop. B.C. on walk. on east | 6.98 | 309.47 |
| 24 Lt = Edge walk | 6.99 | 309.46 |
| 18 Lt. Picket fence | | |
| 18 Lt. | 7.0 | 309.5 |
| 15' Lt. | 7.6 | 309.9 |
| 11' Lt | 7.2 | 308.6 |
| 7.5 Lt | 7.1 | 308.8 |
| ℄ | 7.5 | 309.0 |
| 7.5 Rt | 7.2 | 308.6 |
| 11 Rt | 8.4 | 308.4 |
| 15 Rt | 7.9 | 308.6 |
| 25 Rt | 7.8 | 308.7 |
| 35 Rt. | 7.9 | 308.6 |

316.45

| | | |
|---|---|---|
| 1+42.4 - 20 Lt = N. corner walk | 7.10 | 309.35 |
| +43.2 - 25 Lt. S. side walk | 7.03 | 309.42 |
| +45.3 - 21.3 Lt. S. corner conc. walk | 7.14 | 309.31 |
| T.P. 2.99 311.29 | 8.15 | 308.30 ✓ |
| 1+51.5 - 14.4 Rt. ℄ - 7' conc. drive To west | 2.72 | 308.57 |
| 25' Rt. = ℄ Drive on prop. | 3.10 | 308.19 |
| 46' Rt. 7' Drive changes to 2 - 2' Ribbons | 3.65 | 307.64 |
| 87' Rt. { ctr. 8' garage door | 6.95 | 304.54 |
| 1+54 - 25 Lt Picket fence crosses Property | | |
| 1+58 16 Rt. - 8" Acacia | | |
| 1+74.17 = {R+L to PI} 50' Rt. | 4.2 | 306.4 |
| 25 Rt | 4.1 | 307.2 |
| 15' Rt | 3.7 | 307.6 |
| 10 Rt | 4.1 | 307.2 |
| 7.5 Rt | 3.2 | 307.4 |
| ℄ | 3.4 | 307.9 |
| 7.5 Lt | 3.3 | 308.0 |
| 15' Lt | 3.3 | 308.0 |
| 25 Lt | 3.4 | 307.9 |
| 30' Lt | 3.0 | 308.3 |

X-Sec. Manzanita Dr.

311.29

| | | |
|---|---|---|
| 1+79 - 15' Rt. 6" Acacia ✓ | | |
| 1+98.3 24.8 Rt. - End picket fence to west | | |
| 1+99.51 = ℄ Glenfield | | |
| 25' Lt. | 3.9 | 307.4 |
| 15' Lt. | 3.9 | 307.4 |
| 7.5 Lt. | 4.2 | 307.3 |
| ℄ | 4.3 | 307.0 |
| 7.5 Rt. | 4.0 | 306.4 |
| 10 Rt. | 5.1 | 306.2 |
| 11 Rt. | 4.6 | 306.7 |
| 15 Rt. | 4.3 | 307.0 |
| 25' Rt. | 4.6 | 306.7 |
| 35' Rt. | 4.2 | 306.4 |
| 2+24.85 35' Rt. | 6.0 | 305.3 |
| 25' Rt. | 5.2 | 305.6 |
| 15' Rt. | 5.5 | 305.8 |
| 12 Rt. | 5.5 | 305.8 |
| 10 Rt. | 5.2 | 305.4 |
| 7.5 Rt. | 5.6 | 305.7 |
| ℄ | 5.2 | 306.3 |

311.29

| | | |
|---|---|---|
| 2+24.85 7.5 Lt. | 5.1 | 306.2 |
| 11 Lt. | 5.5 | 305.8 |
| 15 Lt. | 5.1 | 306.2 |
| P.I. on east 25 Lt. | 4.8 | 306.5 |
| 2+36.64 E.C. on 25' Lt. East | 5.2 | 306.1 |
| 15' Lt. | 5.3 | 306.0 |
| 12 Lt. | 5.3 | 306.0 |
| 7.5 Lt. | 5.9 | 305.4 |
| ℄ | 5.4 | 305.9 |
| 7.5 Rt. | 5.9 | 305.4 |
| 11 Rt. | 6.3 | 305.0 |
| 13 Rt. | 5.6 | 305.7 |
| 15 Rt. | 5.6 | 305.7 |
| 25 Rt. | 5.9 | 305.4 |
| 35 Rt. | 6.4 | 304.9 |
| 2+38 - 16.5 Lt. 1½" P. Pole ✓ | | |
| 2+50 - 35' Rt. | 6.8 | 304.5 |
| 25' Rt. | 6.2 | 305.1 |
| 15 Rt. | 6.0 | 305.3 |
| 11' Rt. | 7.0 | 304.3 |

# X-Sec. Manzanita Drive

311.29

| | | |
|---|---|---|
| 2+50 - 7.5 Rt. | 6.4 | 304.9 |
| ℄ | 6.0 | 305.3 |
| 7.5 Lt. | 6.5 | 304.8 |
| 8.5 Lt. | 6.6 | 304.7 |
| 11 Lt. | 6.0 | 305.3 |
| 15 Lt. | 5.9 | 305.4 |
| 25 Lt. | 5.6 | 305.7 |
| 2+80 - 25' Lt. picket fence comes onto prop. Line | | |
| 3+00 25 Lt. | 7.3 | 304.0 |
| 15 Lt. | 7.5 | 303.8 |
| 9' Lt. | 8.0 | 303.3 |
| 7.5 Lt. | 7.9 | 303.4 |
| ℄ | 7.6 | 303.7 |
| 7.5 Rt. | 8.0 | 303.3 |
| 12 Rt. | 8.4 | 302.9 |
| 13 Rt. | 8.0 | 303.3 |
| 15 Rt. | 7.9 | 303.4 |
| 25 Rt. | 8.2 | 303.1 |
| 50 Rt. | 9.8 | 301.5 |
| 3+47 - 28' Rt. Guy & dead man For P. Pole. | | |

311.29

| | | |
|---|---|---|
| 3+48 - 16.3 Rt. = 1.2 {Guy pole & P. pole} | | |
| 3+54 - 16 Lt. - 1.4 = P. Pole | | |
| 3+56.4 = North Line of Alley to East | | |
| 50' Rt. | 10.3 | 301.0 |
| 25' Rt. | 9.6 | 301.7 |
| 15 Rt. | 9.4 | 301.9 |
| 12 Rt. | 9.3 | 302.0 |
| 11 Rt. | 9.5 | 301.5 |
| 7.5 Rt. | 9.5 | 301.8 |
| ℄ | 9.2 | 302.1 |
| 7.5 Lt. | 9.4 | 301.9 |
| 9 Lt. | 9.5 | 301.8 |
| 15 Lt. | 8.2 | 302.4 |
| 24.7 Lt. = Corner Fence | 8.8 | 302.5 |
| 25' Lt. | 8.8 | 302.5 |
| 3+71.64 = P.C. also = S. Line Alley to East | | |
| 25' Lt. | 9.3 | 302.0 |
| 15 Lt. | 9.5 | 301.8 |
| 10 Lt. | 10.1 | 301.2 |
| 7.5 Lt. | 9.8 | 301.5 |

X-Sec. Manzanita Dr.

| | | ☆ 311.29 | | |
|---|---|---|---|---|
| | ℄ | | 9 5 | 301 8 |
| | 7 5 Rt | | 10 0 | 301 3 |
| | 10 Rt | | 10 2 | 301 1 |
| | 11 Rt | | 9 7 | 301 6 |
| | 15 Rt | | 9 7 | 301 6 |
| | 25 Rt | | 10 1 | 301 2 |
| | 50 Rt = P.C. | | 10 7 | 300 6 |
| T.P. | 0.68 | 307.07 | 4.90 | 306.39 |
| Curve stationing on ℄ Manzanita. | | | | |
| 4+00 | 50 Rt | | 6 2 | 300 2 |
| | 25 Rt | | 6 3 | 300 8 |
| | 15 Rt | | 6 2 | 300 9 |
| | 7 5 Rt | | 6 6 | 300 5 |
| | ℄ | | 6 0 | 301 1 |
| | 7 5 Lt | | 6 2 | 300 9 |
| | 12 Lt | | 6 6 | 300 5 |
| | 14 Lt | | 6 8 | 300 3 |
| | 15 Lt | | 6 8 | 300 3 |
| | 25 Lt | | 6 6 | 300 5 |
| 4+25 | 25 Lt | | 6 2 | 300 9 |
| | 17 Lt | | 6 3 | 300 8 |

| | | ☆ 309.07 | | |
|---|---|---|---|---|
| 4+25 | 15 Lt | | 7 1 | 300 0 |
| | 7 5 Lt | | 6 2 | 300 4 |
| | ℄ | | 6 6 | 300 5 |
| | 7 5 Rt | | 7 2 | 299 9 |
| | 15 Rt | | 6 7 | 300 4 |
| | 25 Rt | | 7 1 | 300 0 |
| | 35 Rt | | 7 3 | 299 4 |
| 4+49 | 24' Lt. = ℄ { 8' Conc. Drive | | 6.65 | 300 42 |
| | 44' Lt ℄ 8' Garage door | | 5.79 | 301 28 |
| 4+50 | 35 Rt | | 8 8 | 298 3 |
| | 25 Rt | | 8 5 | 298 6 |
| | 15 Rt | | 8 1 | 299 0 |
| | 7 5 Rt | | 7 8 | 299 3 |
| | ℄ | | 7 2 | 299 9 |
| | 7 5 Lt | | 7 3 | 299 8 |
| | 13 Lt | | 7 6 | 299 5 |
| | 15 Lt | | 7 1 | 300 0 |
| | 20 Lt Ground | | 6 2 | 300 2 |
| | 24 Lt Edge Drive | | 6.65 | 300.42 |
| | 25' Lt | | 6.62 | 300.45 |

X-Sec. Manzanita Drive

π 307.07

| | | | |
|---|---|---|---|
| 4+69 ℄ -23'Rt = ℄ 22 Conc. walk | 8.47 | 298.60 | |
| 4+75 35'Rt | 7 1 | 3000 | |
| 25' Rt | 7 3 | 2998 | |
| 15' Rt | 7 5 | 2996 | |
| 7 5/Rt | 7 8 | 2993 | |
| ℄ | 7 8 | 299.3 | |
| 7' Lt Rt | 8 3 | 298.8 | |
| 15' Lt Rt | 8 4 | 298.7 | |
| 23' Lt Rt | 8 7 | 298.4 | |
| 25' Lt Rt | 8 7 | 298.4 | |
| 35' Lt Rt | 8 7 | 298.4 | |
| 4+93 55 25' Rt. ℄ -8' Ribbon Drive | 8.82 North<br>8.80 South | 298.25<br>298.27 | |
| 25' Rt = P.R.C. | 8 8 | 298.3 | |
| 15' Rt | 8 6 | 298.5 | |
| 7 5 Rt | 8 6 | 2985 | |
| ℄ | 8 3 | 298.8 | |
| 7 5 Lt | 8 2 | 2989 | |
| 15' Lt | 7 6 | 299.5 | |
| 25' Lt. = P.C.C. | 7 7 | 299.4 | |
| 35' Lt. | 7 4 | 299.7 | |



π 307.07

| | | | |
|---|---|---|---|
| Check Original BM. Glenfield & Manzanita Dr. | | 0.68 | 306.39<br>306.38<br>.01 |

C St. Horiz Curb & Gutter Levels
Columbia to Union

| | | | | |
|---|---|---|---|---|
| BM | 7.58 | 27.98 | 20.40 | N.W. B.P. C St & Columbia |
| | 0+00 = E.L. Columbia St | | | |
| Top Cb | | 6.42 | 21.56 | |
| Gutter | | 7.62 | 20.36 | |
| | 0+09 | | | |
| Top Cb | | 6.39 | 21.59 | |
| Gutter | | 6.70 | 21.28 | |
| | 0+35 | | | |
| Top Cb | | 6.02 | 21.96 | |
| Gutter | | 6.30 | 21.68 | |
| | 0+50 | | | |
| Top Cb | | 5.71 | 22.27 | |
| Gutter | | 6.15 | 21.83 | |
| | 0+85 | | | |
| Top Cb | | 5.29 | 22.69 | |
| Gutter | | 5.69 | 22.29 | |
| | 1+00 | | | |
| Top Cb | | 5.15 | 22.83 | |
| Gutter | | 5.55 | 22.43 | |

Reduced & Plotted large scale 8-3-42 C.B.K.

Indexed
C.S.K.

51



| | | | | |
|---|---|---|---|---|
| | | 27.98 | | |
| | | 1+35 | | |
| Top Cb | | 4.79 | 23 | 19 |
| Gutter | | 5.19 | 22 | 79 |
| | | 1+50 | | |
| Top Cb | | 4.51 | 23 | 47 |
| Gutter | | 4.86 | 23 | 12 |
| | | 1+75 | | |
| Top Cb | | 4.27 | 23 | 71 |
| Gutter | | 4.70 | 23 | 28 |
| | | 1+90 | | |
| Top Cb | | 4.09 | 23 | 89 |
| Gutter | | 4.76 | 23 | 22 |
| | | 1+95 | | |
| Top Cb | | 4.00 | 23 | 98 |
| Gutter | | 4.92 | 23 | 06 |
| | | 2+0 = W.L. State | | |
| Top Cb | | 3.85 | 24 | 13 |
| Gutter | | 4.88 | 23 | 10 |
| TP | 7.29 | 31.52 | 3.75 | 24.23 |

| | | | | |
|---|---|---|---|---|
| | | 31.52 | | |
| | | W Cb State W.L. C St. | | |
| Top Cb | | 7.31 | 24 | 21 |
| Gutter | | 8.16 | 23 | 06 |
| | | 5' W of W.L. C St. | | |
| Top Cb | | 7.29 | 24 | 23 |
| Gutter | | 7.85 | 23 | 67 |
| | | E Cb State W.L. C St. | | |
| Top Cb | | 6.80 | 24 | 72 |
| Gutter | | 7.96 | 23 | 56 |
| | | 5' E of W.L. C St. | | |
| Top Cb | | 6.74 | 24 | 78 |
| Gutter | | 7.33 | 24 | 19 |
| | | 0+0 = E.L. State | | |
| Top Cb | | 6.83 | 24 | 69 |
| Gutter | | 8.00 | 23 | 52 |
| | | 0+06 | | |
| Top Cb | | 6.72 | 24 | 80 |
| Gutter | | 7.39 | 24 | 13 |
| | | 0+35 | | |
| Top Cb | | 6.38 | 25 | 14 |
| Gutter | | 6.91 | 24 | 61 |

| | | | |
|---|---|---|---|
| | 31.52 | | |
| | 0+50 | | |
| Top Cb | 6.04 | 25.48 | |
| Gutter | 6.55 | 24.97 | |
| | 0+75 | | |
| Top Cb | 5.68 | 25.84 | |
| Gutter | 6.11 | 25.41 | |
| | 1+0 | | |
| Top Cb | 5.09 | 26.43 | |
| Gutter | 5.59 | 25.93 | |
| | 1+25 | | |
| Top Cb | 4.78 | 26.74 | |
| Gutter | 5.08 | 26.44 | |
| | 1+50 | | |
| Top Cb | 4.33 | 27.19 | |
| Gutter | 4.70 | 26.82 | |
| | 1+75 | | |
| Top Cb | 4.04 | 27.48 | |
| Gutter | 4.49 | 27.03 | |

| | | | | |
|---|---|---|---|---|
| | 31.52 | | | |
| | 1+95 | | | |
| Top Cb | | 3.69 | 27.83 | |
| Gutter | | 4.39 | 27.13 | |
| | 2+0 = N.L. Union | | | |
| Top Cb | | 3.49 | 28.03 | |
| Gutter | | 4.49 | 27.03 | |
| BM | | 3.47 | 28.05 | N.W. BP. Cut in Union 28.00 |

Cross Section Art St.
El Cajon Blvd to Cafoctin Drive

Indexed
c.s.k.




Sta: 0+00 - 2+00

See Pg's 55-56

Sept 18-42
Sisson
Hazard
Bowlin





Cross Section Art 57

| | | | | |
|---|---|---|---|---|
| 1+00 | | | | |
| 0+50 | | | | |
| 0+00 = N.L. El Cajon Blvd on Diagonal | | | | |
| 0-12 = N Cb Line of El Cajon Blvd | | | | |
| TP | 3.14 | 466.36 | 5.04 | 463.22 |
| TP | 4.31 | 468.26 | 5.29 | 463.95 |
| B.M. | 3.58 | 469.24 | | 465.66 |

Reduced N.E. Trems
Plotted by B. Hough
9-21-42

N.M. RP El Cajon x Boston

55

Lt: M — Rt: E

61.77 @ 13.5

| 462.28 | 461.6 | 461.8 | 462.0 | 461.8 | 461.2 | 461.1 | 461.0 |
|---|---|---|---|---|---|---|---|
| 4.08 | 4.8 | 4.6 | 4.4 | 4.6 | 4.7 | 5.3 | 5.4 |
| 15-Cb | 15-Gutter | 7.5 | | 7.5 | 15 | 25 | 35 |

61.95 @ 13.5

| 462.67 | 461.9 | 462.1 | 462.2 | 462.1 | 461.9 | 462.2 | 461.5 | 461.3 |
|---|---|---|---|---|---|---|---|---|
| 3.69 | 4.5 | 4.3 | 4.2 | 4.3 | 4.5 | 4.2 | 4.9 | 5.1 |
| 15-Cb Top | 15-Gutter | 7.5 | | 7.5 | 14 | 15 | 25 | 35 |

62.53 @ 13.5

| 463.07 | 462.41 | 462.60 | 462.57 | 462.28 | 462.03 | 462.63 | 462.3 |
|---|---|---|---|---|---|---|---|
| 3.29 | 3.95 | 3.76 | 3.79 | 4.08 | 4.33 | 3.73 | 3.9 |
| 15-Cb Top | 15-Gutter | 7.5 | | 7.5 | 15-Gutter | 15-Top of Curb | 25 |

| 463.14 | 462.79 | 462.40 | 462.37 | 462.31 | 462.22 | 462.07 | 461.80 | 462.49 |
|---|---|---|---|---|---|---|---|---|
| 3.22 | 3.87 | 3.96 | 3.99 | 4.05 | 4.14 | 4.29 | 4.46 | 3.87 |
| 24.7-Top of Curb | 24.7-Curb Gutter | 15 | 7.5 | | 7.5 | 15 | 25-Gutter | 25-Cb & Top |

466.36

3+50

3+0

2+50

2+0 = 5½ Cb + Walk on East

1+50

466.36

Lt. | ℄ | Rt. | 56

| Lt. | | | ℄ | | Rt. | |
|---|---|---|---|---|---|---|
| 461.68 / 4.68 / 15:Cb | 461.5 / 4.9 / 15-Gut. | 461.4 / 5.0 / 7.5 | 461.4 / 5.0 | 461.3 / 5.1 / 7.5 | 461.3 / 5.1 / 15-Gut | 461.65 / 4.71 / 15:Cb |
| 461.68 / 4.68 / 15:Cb | 461.4 / 5.0 / 15-Gutter | 461.4 / 5.0 / 7.5 | 461.5 / 4.9 | 461.3 / 5.1 / 7.5 | 461.4 / 5.0 / 15-Gut. | 461.76 / 4.60 / 15:Cb |
| 461.80 / 4.56 / 15:Cb | 461.4 / 461.7 / 5.0 / 15-Gutter | 461.4 / 5.0 / 7.5 | 461.4 / 5.0 | 461.3 / 5.1 / 7.5 | 461.4 / 5.0 / 15-Gutter | 461.78 / 4.58 / 15:Cb |
| 461.86 / 4.46 / 15:Cb | 461.5 / 4.9 / 15-Gutter | 461.5 / 4.9 / 7.5 | 461.7 / 4.7 | 461.5 / 4.9 / 7.5 | 461.4 / 5.0 / 15-Gutter | 461.86 / 4.50 / 15:SYCB |

61.46 @ 13.5

461.7 / 4.7 / 7.5

61.56 @ 13.5

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| 461.99 / 4.27 / 15:Cb | 461.4 / 4.8 / 15:Gutter | 461.6 / 4.8 / 7.5 | 461.8 / 4.6 | 461.7 / 4.7 / 7.5 | 461.9 / 4.9 / 14 | 462.4 / 4.7 / 13 | 461.6 / 4.8 / 18 | 461.0 / 5.4 / 25 | 460.8 / 5.6 / 8.5 |

466.36

| | | | | |
|---|---|---|---|---|
| 5+75.0 = CL BC of Lt | | | | |
| 5+50 | | | | |
| 5+0 | | | | |
| 4+50 | | | | |
| TP | 4.17 | 465.66 | 4.87 | 461.49 |
| 4+0 | | | | |
| | | 466.36 | | |

| Lt | | | Rt | | | |
|---|---|---|---|---|---|---|
| 461.40 | 460.8 | 460.9 | 461.0 | 460.7 | 460.6 | 461.33 |
| 4.36 | 4.9 | 4.8 | 4.7 | 5.0 | 5.1 | 4.23 |
| 15=CL BC | 15=Gut | 7.5 | | 7.5 | 15 | 15 |
| 461.38 | 460.8 | 461.1 | 461.2 | 461.0 | 460.8 | 461.28 |
| 4.38 | 4.9 | 4.6 | 4.5 | 4.7 | 4.9 | 4.38 |
| 15 | 15 | 7.5 | | 7.5 | 15=Gut | 15 |
| 461.37 | 461.0 | 461.3 | 461.4 | 461.2 | 461.1 | 461.41 |
| 4.39 | 4.7 | 4.4 | 4.3 | 4.5 | 4.6 | 4.25 |
| 15=CL | 15 | 7.5 | | 7.5 | 15 | 15=CL |
| 461.34 | 461.1 | 461.3 | 461.4 | 461.3 | 461.0 | 461.49 |
| 4.14 | 4.6 | 4.4 | 4.3 | 4.4 | 4.7 | 4.17 |
| 15=CL | 15=Gut | 7.5 | | 7.5 | 15=Gut | 15=CL |
| | | | 465.66 | | | |
| 461.57 | 461.3 | 461.5 | 461.5 | 461.4 | 461.3 | 461.60 |
| 4.79 | 5.1 | 4.9 | 4.9 | 5.0 | 5.1 | 4.26 |
| 15=CL | 15=Gut | 7.5 | | 7.5 | 15=Gut Ber | 15=CL |
| | | | 466.36 | | | |

| | | | | | |
|---|---|---|---|---|---|
| BM | | | 2.84 | 466.66 | NW BP Elm 0.3' Dia 466.66 |
| TP | 4.90 | 468.50 | 2.06 | 468.60 | |
| BM | | | 4.21 | | SW 24" Elm 43' Lt of Rt S.L. Catoctin |

5+85 = S Curb Line Catoctin

5+80 = S.L. Catoctin

Lt. Ø Rt

461.1

| 461.54 | 461.36 | | 460.9 | 461.1 | 461.1 | 460.9 | 460.8 | 460.8 | 461.15 | 461.04 |
|---|---|---|---|---|---|---|---|---|---|---|
| 4.12 | 4.30 | 4.6 | 4.8 | 4.6 | 4.6 | 4.8 | 4.9 | 4.9 | 4.41 | 4.63 |
| 50 | 25-CL | 4.5-Gutter | 15 | 7.5 | | 7.5 | 15 | 25-Gut | 23-CL | 50-CL |

| 461.39 | 461.6 | 460.9 | 461.1 | 460.8 | 460.7 | 461.37 |
|---|---|---|---|---|---|---|
| 4.27 | 4.7 | 4.8 | 4.6 | 4.9 | 5.0 | 4.39 |
| 15.9-CL | 15.9-Gutter | 7.5 | | 7.5 | 15.2-Gutter | 15.2-CL |

Indexed
C.S.K.

1958
30 50
5008

59

# Fire Station Bldg. Layout. Lots 21-24

Block 160 U.Hts.

| | + | ↑ | − | Elev' | N.E 7°-7X |
|---|---|---|---|---|---|
| B.M. | 5.61 | 349.79 | | 349.18 | Lincoln 32nd see page 32 This Book |
| Ground SW Cor Bldg. | | | 4.21 | 345.58 | |
| " N.W " " | | | 3.05 | 346.74 | |
| " N.E " " | | | 1.80 | 348.00 | |
| " S.E " " | | | 2.76 | 347.03 | |
| Arbitrary Elev floor 0.92 Above SW Cor. | | | 3.29 | 346.50 | |
| Set Stake approx ctr Bldg Elev Foundation Wall | | | 2.79 | 347.00 | |
| SW Cor Training Tower Ground | | | 4.24 | 345.53 | |
| SE " " " " | | | 3.81 | 345.98 | |
| 11/7/42 Reset Tower Stakes | | | | | |
| | 4.95 | 349.13 | | 344.18 | |
| | | | 3.59 | 345.54 | 346.50 |

Bliss Notes
Sommermyer T
Begg Rod
Nov 6, 1942

Note: 1x1' stakes at Bldg Corners



Proposed Car Bin
Adams Ave - Mission Ave & Texas St. Grade
Levels Next Page

Indexed
C.S.K.

Nov. 17-42
Swan Hazard H.R. Hiser Plan Sommermeyer Begg








Levels For Proposed Cast Bin
Adams - Mission Ave & Texas St Grade

Lt. 5 — 8 — Pg. # 61

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 0+63 | | 314.1 | 318.3 | 328.4 | 330.7 | 337.9 | 341.3 | 343.0 | 344.1 |
| | | 32.7 | 31.0 | 26.8 | 16.7 | 14.4 | 7.2 | 6.8 | 2.1 | 1.0 |
| | | 50 | 50 | 44 | 34 | 25 | 15 | 30 | 40 |
| | | 59 = W1/4 Bv. | | | | | | | |
| 0+50 | | 309.1 | | 307.6 | 327.9 | 334.5 | 337.8 | 340.5 | 341.3 | 343.2 |
| | | 36.0 | | 37.5 | 17.2 | 10.6 | 7.3 | 4.6 | 3.8 | 1.9 |
| | | 52 = W1/4 Bv. | | 45 | 28 | 10 | | 12 | 30 | 40 |
| 0+35 | | 307.0 | 306.1 | 317.6 | 321.9 | 329.7 | 334.4 | 338.7 | 341.3 | |
| | | 38.1 | 39.0 | 28.5 | 23.2 | 15.4 | 10.7 | 6.4 | 3.8 | |
| | | 44 = W1/4 Bv. | 37 | 30 | 25 | 12 | | 20 | 40 | |
| 0+15 | | | 303.5 | 303.9 | | 316.1 | 323.8 | 329.7 | 335.2 | 339.4 |
| | | | 41.6 | 41.2 | | 29.0 | 21.3 | 15.4 | 9.9 | 5.7 |
| | | | 32 = W1/4 Bv. | 24 | | 10 | | 5 | 30 | 40 |
| 0+0 | = SL Adams Tan @ Line of Adams | | | 301.8 | | 308.4 | 314.1 | 320.8 | 330 | 336.5 |
| | | | | 43.3 | | 36.7 | 31.0 | 24.3 | 15.1 | 8.6 |
| | | | | 23 = W1/4 Bv. in | | 10 | | 10 | 30 | 40 |
| TP | 5.96 | 345.12 | 12.82 | 339.16 | | | | | | |
| BM | 0.91 | 351.98 | | 351.07 | SW Mon Adams & Louisiana | | | | | |
| | | | | | | 345.12 | | | | |

Lt = E  Δ  Rt = W  62

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | |
| BM | | 2.62 | 342.49 | 0.19 / 13.27 ✓ Nail / Pow Pole | | | | | | | |
| | | | | | | | | | | | |
| | | | | 327.7 | 327.0 | 330.7 | 330.7 | 342.0 | 343.5 | 343.0 | 343.5 |
| 1+95.8 = Opp NH Lmp Walk Cb x Paving | | | | 17.4 / 115 = NH/Pav | 18.1 / 106 | 14.4 / 101 | 14.4 / 78 | 8.1 / 59 | 16 / 60 | 2.1 / 48.5 = Lt NH Str/Pav | 16 / 37 on Pav |
| | | | | | | | | | | | |
| 1+50 | | | | | | | 327.0 | 320.8 | 328.3 | 330.8 | 335.4 |
| | | | | | | | 22.1 / 103 = NH/Pav | 24.3 / 95 | 16.8 / 88 | 14.3 / 68 | 9.7 / 54 |
| | | | | | | | | | | | |
| 1+25 | | | | | | | 318.3 | 316.9 | 330.1 | 335.8 | 339.4 |
| | | | | | | | 26.8 / 89 = NH/Pav | 28.2 / 83 | 15.0 / 70 | 9.3 / 57 | 5.7 / 45 |
| | | | | | | | | | | | |
| 1+0 | | | | | | | 315.1 | | 313.6 | 329.0 | 338.5 |
| | | | | | | | 30.0 / 78 = NH/Pav | | 31.5 / 71 | 16.1 / 58 | 6.6 / 37 |
| | | | | | | | | | | | |
| 0+94 | 13' Lt of Base Line = Power x Tel Pole | | | | | | 311.9 | 325.3 | 328.5 | 333.0 | 336.9 |
| 0+85 | | | | 312.9 / 32.7 / 70 = NH/Pav | | | 23.2 / 62 | 19.8 / 55 | 16.6 / 48 | 12.1 / 38 | 8.2 / 29 |
| | | | | | | | | | | | |
| | | 345.12 | | | | | | | 345.12 | | |

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| | | | | | | | | |
| | | | | | | | | |
| 345.6 | | | | | | | | |
| +0.5 | | | | | | | | |
| 1.8 / 23.5 = NH Curb | | | | | | | | |
| | | | | | | | | |
| 344.3 | 345.7 | | | | | | | |
| 0.8 | +0.6 / 20 | | | | | | | |
| | | | | | | | | |
| 344.5 | 345.1 | | | | | | | |
| 0.6 | 0.0 / 20 | | | | | | | |
| | | | | | | | | |
| 343.4 | 344.3 | | | | | | | |
| 1.7 | 0.8 / 20 | | | | | | | |
| | | | | | | | | |
| 342.7 | 343.6 | | | | | | | |
| 2.4 | 1.5 / 20 | | | | | | | |
| | | | | | | | | |
| | 345.12 | | | | | | | |

Proposed Con Bin East of 39th St
At Edna Place.

Levels Next Page

Nov 17-42

Swigert Hazard Hiser

Bliss Sommermyer Bragg

Indexed
C.S.K.

63



Levels For Proposed Cap Rd
East of 39th St At Edna Place

Lt = E  Rt = W  64

0+83

0+53 = N.L. Edna Place from West

0+47.1

0+28

0+17

0+0 = 24' South of S.L. Adams

BM 418 375.05 370.87 SFRP Adams + 39th St

327.7 327.8 334.3 336.9 368.3 369.0 370.07
474 473 38.8 38.2 6.8 6.1 4.98 0 Conc.
120 90 45 28 19 2

332.9
17.2
80

333.7 336.0 336.1 337.0 341.1 369.1 370.37
41.4 39.1 39.0 38.1 34.0 6.0 4.73 0 Conc.
86 86 40 33 26 20

370.16 370.08
4.90 4.97
2 = 21.4 Conc. 12 = C6

335.5 337.7 344.1 370.0 370.5
39.6 37.4 31.0 5.1 4.6
80 53 33 12

356.4 356.4 368.3 370.7 370.15
18.7 18.7 6.8 -4.4 4.90
40 30 30 12 = C6

367.1 368.6 370.4
8.0 6.5 4.7
76 29

375.05

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| BM | | 43.94 | 331.11 | NE Cor South Abut to Bottom | | | | | | | |
| 1+70 | | | | | 328.1 | 329.1 | 335.1 | 337.1 | 343.1 | 365.3 | 370.0 | 370.7 |
| | | | | | 47.0 | 46.0 | 39.4 | 37.4 | 32.0 | 9.8 | 5.1 | 4.4 |
| | | | | | 90 | 45 | 30 | 13 | 3 | 3 | | 25 |
| 1+50 | | | | 326.5 | 327.8 | 329.6 | 335.4 | 336.4 | 343.1 | 364.9 | 370.9 | 371.0 |
| | | | | 48.6 | 47.3 | 45.5 | 39.7 | 38.7 | 32.0 | 10.3 | 4.2 | 4.1 |
| | | | | 100 | 57 | 47 | 35 | 23 | 8 | 4 | | 30 |
| 1+35 | | | | | 325.7 | 328.4 | 334.0 | 337.1 | 344.1 | 363.3 | 370.8 | 371.1 |
| | | | | | 49.4 | 46.7 | 41.1 | 38.0 | 31.0 | 11.8 | 4.3 | 4.0 |
| | | | | | 117 | 60 | 42 | 23 | 10 | | 4 | 30 |
| 1+22 | | | | 324.9 | 327.6 | 329.6 | 334.0 | 335.8 | 338.5 | 368.4 | 370.3 | 370.8 |
| | | | | 50.2 | 47.5 | 45.5 | 43.1 | 39.3 | 36.6 | 6.7 | 4.8 | 4.3 |
| | | | | 120 | 75 | 57 | 51 | 38 | 20 | 15 | | 30 |
| 1+13 = SL Edna Place From West | | | | | 326.6 | 327.8 | 331.1 | 335.1 | 338.8 | 369.6 | 370.6 | 370.2 |
| | | | | | 48.5 | 47.3 | 44.0 | 39.2 | 36.3 | 5.6 | 4.5 | 4.9 |
| | | | | | 125 | 75 | 52 | 40 | 23 | 12 | | 30 |
| 0+92.5 | | | | | | | | | | 370.05 | | 369.97 |
| | | | | | | | | | | 5.06 | | 5.11 |
| | | | | | | | | | | 2.5 Ely Conc | | 12=6 |
| | 375.05 | | | | | | | | | | | |

Bliss
Sommermyer
Begg
12/16/42

Cross Section of Kurtz St East of Noell 200'

| | | | | |
|---|---|---|---|---|
| BM. | 4.44 | 20.27 | 15.83 | Spike in pole SW Kurtz & Noell Set on Serv. Constr. |

Note: Constructed C6 used as a base line for X Sections

0+00 – 31. Ex Rock & oil Paving on Noell

| | | |
|---|---|---|
| 27.6 Rt Ex Con Paving | 9.50 | 10.77 |
| 15 " | 4.88 | 15.39 |
| Base | 4.18 | 16.09 |
| 6.15 Lt S.F. R.R. Rail | 3.67 | 16.60 |

0+00 – 14. W.C. & G. Noell

| | | |
|---|---|---|
| 2.8 Lt Top & End cb | 4.48 | 15.79 |
| Base | 4.7 | 15.6 |
| 15 Rt | 5.1 | 15.2 |
| 27.6 " edge ex Con Paving | 5.77 | 14.50 |
| 29.5 C to P.L. | | |
| 35' Rt in Gutter | 6.52 | 13.75 |

0+00 – 10.5

| | | |
|---|---|---|
| 27.6 Rt end Con Paving on S.F. Return | 5.80 | 14.47 |
| " " Top cb | 5.13 | 15.14 |
| " cb | | |

0+00

| | | |
|---|---|---|
| 28.65 to P.L. | | |
| 27.4 Rt edge ex Walk | 5.20 | 15.07 |
| 15 " | 5.1 | 15.2 |
| 0+00 on Front | 4.8 | 15.5 |
| " " Top cb | 4.40 | 15.87 |

Indexed
C.S.K.

66

angle in Bldg. 0+51.

Door opening 0+74 / 0+59



| | | |
|---|---|---|
| | 0+03 Gr Lt Pole 16.5 Rt of Centerline | |
| | 0+08 | |
| 28.13 to PL | | |
| 27.2 Rt edge Ex. Walk | 5.28 | 14.99 |
| 15 " | 5.1 | 15.2 |
| 0+00 Ground | 4.9 | 15.4 |
| " " Top cb | 9.38 | 15.89 |
| | 0+25 | |
| Top cb | 9.28 | 15.99 |
| Ground | 5.1 | 15.2 |
| 15' Rt | 5.3 | 15.0 |
| 27.02 to PL | | |
| 28.7 Edge Bldg on Ground | 5.2 | 15.1 |
| | 0+32.75 | |
| 26.52 to PL | | |
| 27.1 Rt Concrete Lip of Bldg Entrance | 5.36 | 14.91 |
| | 0+92.45 | |
| 27.2 Rt E Side of Bldg on Concrete entrance Lip | 5.31 | 14.96 |
| 25.89 to PL | | |
| 15' Rt | 5.9 | 14.9 |
| 0+00 Ground | 4.9 | 15.4 |
| 0+00 Top cb | 4.20 | 16.07 |
| | 0+49.5 W Side of Loading Entrance of Bakery | |
| 0+00 Top cb | 9.16 | 16.11 |
| " " Ground | 5.1 | 15.2 |
| 10' Rt | 5.3 | 15.0 |

| | | |
|---|---|---|
| | 0+49.5 | |
| 16.75 Rt W Side of Loading entrance on concrete | 5.34 | 14.93 |
| " Top Curb | 5.29 | 14.98 |
| 25.43 to PL | | |
| 28' Rt Bldg on Ground | 5.3 | 15.0 |
| | 0+62.5 | |
| 28' Rt | | |
| Floor of Bldg in Loading entrance | 6.20 | 14.07 |
| 24.89 to PL | | |
| | 0+79.5 E Side of Loading entrance of Gas Up | |
| 23.81 to PL | | |
| 16.25 Rt on concrete | 5.30 | 14.97 |
| 4 " Top ex CG | 5.24 | 15.03 |
| 26.5 Rt Bldg Ground | 5.2 | 15.1 |
| 10' Rt | 5.1 | 15.2 |
| 0+00 Ground | 4.8 | 15.5 |
| " " Top cb | 4.05 | 16.22 |
| | 1+00 | |
| Base Top Curb | 3.96 | 16.31 |
| " on Ground | 4.4 | 15.9 |
| 10' Rt | 4.8 | 15.5 |
| 14 " | 5.5 | 14.8 |
| 22.15 to PL | | |
| 27.7 Rt Bldg | 5.1 | 15.2 |
| | 1+16.2 | |
| 27.2 Rt " | 5.1 | 15.2 |
| 21.10 to PL | | |
| 11 Rt | 5.3 | 15.0 |
| 10 " | 4.6 | 15.7 |

| | | |
|---|---|---|
| 0+00 Ground | 5.2 | 151 |
| " " Top cb | 3.86 | 1641 |
| | 1+50 | |
| 0+00 Top cb | 3.72 | 1655 |
| " Ground | 3.7 | 166 |
| 7.8 Rt Golden Rock Grd | 9.4 | 159 |
| 18.90 to PL | | |
| | 1+79.5 Endwall | |
| Base Top wall | 3.59 | 1668 |
| " Ground | 3.8 | 165 |
| 6.2 Rt | 4.6 | 157 |
| 16.98 to PL | | |
| 25 " | 5.0 | 153 |
| | 2+00 | |
| Base 00 Ground | 2.5 | 178 |
| 5' Rt | 2.8 | 175 |
| 8 ' | 4.6 | 157 |
| 18.65 to PL | | |
| 25 " | 5.1 | 152 |

C. Moore
Jos. Meinmeyer
H. Moore
3-18-43.

Cross Sec. alley 20' wide
Blk 285 Seaman & Choates 223

| | | | | | |
|---|---|---|---|---|---|
| NWBP | 0.51 | 51.58 | | 51.07 | 3rd & Logan |
| TP | 2.74 | 41.33 | 12.99 | 38.59 | |
| | 0 to 10 | | | | |
| S | Top curb | | 4.4C | 36.87 | |
| S | gutt oil pav. | | 5.2 | 36.1 | |
| C | " " | | 6.1 | 35.2 | |
| N | " " | | 7.1 | 34.2 | |
| | 0+00 E.L. 3rd to South | | | | |
| N | | | 6.C | 34.7 | |
| | +5 | | 6.2 | 35.1 | |
| C | | | 4.C | 36.9 | |
| S | ground | | 2.8 | 38.5 | |
| S | Top curb | oil-y Retain | 4.35 | 36.98 | |
| | 0 to 2.5 | | | | |
| S | | | + 1.5 | 42.8 | |
| C | | | 2.7 | 38.6 | |
| N | | | 6.C | 34.7 | |

Revised by A.E.B.
Plotted by C.B.H. 5-24-1943

Indexed
C.S.I.R.

69




276 Wetmore & Sanborns Add

New Cross Sections in FB 1023-53 C.B.W. 10-19-51

7.85

Logan Park 1498

T.P. #170

41.33

| | | | | | |
|---|---|---|---|---|---|
| N + 5 | W edge | Con walk | 6.94 | 34.39 | ✓ |
| | 0 + 07.8 | | | | |
| N − 5 | E edge | Con. walk | 7.02 | 34.31 | ✓ |
| N | | | 3.5 | 37.8 | |
| C | | | + 1.1 | 42.4 | |
| S | | | + 1.8 | 43.1 | |
| T.P. | 7.55 | 46.14 | 2.74 | 38.59 | |
| | 0 + 14 | | | | |
| S | | | 3.1 | 43.0 | |
| C | | | 3.9 | 42.2 | |
| N | Top Bank | | 5.3 | 40.8 | |
| | 0 + 48.5 | | | | |
| N − 30 | | | 11.4 | 34.7 | ✓ |
| N | | | 5.1 | 41.0 | |
| + 5.8 | ground | | 5.0 | 41.1 | |
| + 5.8 | N.W. Con | 14 × 20 BH | 4.1 | 42.0 | ✓ Con. Top Fd |
| C | ground | | 4.6 | 41.5 | |
| S | " | | 3.6 | 42.5 | |
| T.P. | 4.54 | 44.04 | 6.06 | 40.08 | |
| | 0 + 04.5 | | | | |
| N − 30 | | | 9.8 | 34.8 | ✓ |

44.04

| | | | | | |
|---|---|---|---|---|---|
| N | | | 4.1 | 40.5 | |
| + 5.8 | ground | | 3.6 | 41.0 | |
| + 5.8 | N.E. Con | 14 × 20 Bldg | 2.65 | 41.97 | ✓ Con Top Fd. |
| C | | | 3.2 | 41.4 | |
| S | | | 2.1 | 42.5 | |
| | 0 + 99 | | | | |
| S | | | 0.9 | 43.2 | |
| + 1 | | | 2.7 | 41.9 | |
| C | | | 3.2 | 41.4 | |
| N | | | 3.8 | 40.8 | |
| + 1 | | | 5.6 | 39.0 | ✓ |
| + 30 | | | 9.6 | 35.0 | ✓ |
| | 1 + 00 | | | | |
| − 30 | | | 9.6 | 35.0 | |
| N | | | 5.2 | 39.4 | |
| C | | | 4.0 | 40.6 | |
| S | P.P. on Line | | 2.7 | 41.9 | |
| | 1 + 35 | | | | |
| S | | | 3.1 | 41.5 | |
| C | | | 4.5 | 40.1 | |
| N | | | 5.6 | 39.0 | |

44.62

| | | | | | |
|---|---|---|---|---|---|
| | 1+35 | | | | |
| N + 30 | | | 12.3 | 32.3 | ✓ |
| | 1+70 | | | | |
| N - 30 | | | 14.4 | 30.4 | |
| N | | | 6.3 | 38.3 | |
| C | | | 4.6 | 40.0 | |
| S | | | 3.1 | 41.5 | |
| | 1+98 | | | | |
| S + 1.2 P.P. | | | | | |
| | 2+00 | | | | |
| S | | | 2.9 | 41.7 | |
| C | | | 3.8 | 40.8 | |
| N | | | 6.3 | 38.3 | |
| ± 19 | Top old RR Cut | | 12.7 | 34.9 | ✓ |
| | 2+15 | | | | |
| N - 17 | Top old RR Cut | | 12.6 | 32.0 | |
| N | | | 8.0 | 36.6 | |
| C | | | 5.7 | 38.9 | |
| S | | | 5.2 | 39.4 | |
| T.P. | 1.09 | 33.31 | 12.40 | 32.22 | |
| | 2+37 E. end 20' alley | | | | |
| S | | | 0.7 | 32.6 | |

33.31

| | | | | | |
|---|---|---|---|---|---|
| C | | | 1.8 | 31.5 | |
| N | | | 4.0 | 29.3 | |
| +15 | Top Cut | | 5.2 | 27.7 | ✓ |
| | N+47 = 30' E of E end alley | | | | |
| N - 17 | Bot Cut | | 20.1 | 13.2 | |
| N - 7 | Top " | | 12.8 | 20.5 | |
| N | | | 11.5 | 21.8 | |
| C | | | 11.0 | 22.3 | |
| S | | | 9.9 | 23.4 | |
| T.P. | 12.27 | 45.09 | 1.09 | 32.22 | |
| T.P. | 7.74 | 51.93 | 0.90 | 44.19 | |
| check back to orig. BM | | | 0.85 | 51.08 | 51.07 |

Indexed
C.S.K.

Moore Location of 2" water line on
4-20-43 Linwood bet. Wisherby & Bandini Sts.

See T.P.B.K. #1 - P 50



Indexed
C.S.K.

73

Location of 12" Water Main on
Wisteria St. Above 4-26-43.



C. Moore Sewer Location in
8-9-43. Blk 34. Middletown Add.



Proposed Sewer Block 44 Middletown Add
And Block 439 Sub. PL. 1122 Map #381

| | | | | | |
|---|---|---|---|---|---|
| BM | 12.32 | (88.66) | | 76.84 | HEBP Glenwood & 12 4/14/44 2" + Rest |
| | 13.06 | (101.40) | 0.32 | (88.34) | |
| | 11.07 | (111.79) | 0.68 | (100.72) | |
| | 12.11 | (123.62) | 0.28 | (111.51) | |
| | 13.11 | (136.29) | 0.44 | (123.18) | |
| BM Set | 12.52 | (148.66) | 0.15 | (136.14) | IPSH BP Walnut & Union |
| 0+0 | = Existing Manhole | | 4.70 | 143.96 | on Rim Ex. |
| " | | | 11.40 | 137.26 | Flow Line |
| +09.19 | Δ | | 4.1 | 144.6 | |
| +50 | | | 0.4 | 148.3 | |
| " | 9.7' Lt = Fence | | 0.4 | 148.3 | |
| TP | 12.59 | (161.02) | 0.23 | (148.43) | |
| 1+0 | | | 8.8 | 152.2 | |
| " | 16' Lt = Fence Line | | 7.7 | 153.3 | |
| +24 | = ℄ Garage Dirt Floor | | 6.0 | 155.0 | |
| +39.5 | 23' Lt = ℄ 16" Euc. Tree | | | | |
| 1+45.0 | Δ 21°26' Lt | | 6.56 | 157.46 | on Stob |
| +59 | 1.8' Lt = ℄ 18" Euc Tree | | | | |
| +61 | 19.3' Lt = Car House | | 3.4 | 152.6 | |
| +71 | 1.0' Rt = ℄ 14" Euc Tree | | | | |



| | | | | | |
|---|---|---|---|---|---|
| | | (161.03) | | | |
| TP | 7.95 | (168.19) | 0.78 | (160.24) | |
| 1+87 | 3.2' Rt = 2.18' Euc Trav | | | | |
| 798 | 19.0' Lt. to Hdy Ho. 1½ Story Frame | | 7.12 | 161.07 | on Ground Floor |
| 2+00 | | | 5.5 | 162.7 | |
| +18.84 | | | 8.84 | 164.35 | on Stub |

Walker Hazard Hardin 5-8-45

# 30TH And FERN ST.

Indexed C.S.K.

## Preliminary Levels for Rebuilding Storm Drain

| | | | | |
|---|---|---|---|---|
| | 2.97 | 291.47 | | S.E. B.P. |
| | ~~2.53~~ | ~~291.53~~ | | 289.00 |
| | | 288.07 | | 284.97 |
| T.P. | 3.10 | 288.13 | 6.50 | ~~285.03~~ |
| 0+00 | on curb | | 5.17 | |
| " | Grating - Gutter | | 5.56 | |
| 0+01 | = Flow from North | | 6.41 | |
| 0+01 | = Flow to South | | 7.17 | |
| 0+02 | = " from West | | 6.74 | |
| 0+02 | on Grating - Paving | | 5.23 | |
| 0+07 | on Paving | | 4.69 | |
| +12.5 | E Rail of East Track on Car Track | | 4.09 | |
| +16.7 | " " " W Rail | | 4.08 | |
| +23.65 4.7' | on E. Rail of W Track | | 4.07 | |
| 0+28.36 | " W " " " | | 4.07 | |
| +32.9 | on Paving | | 3.73 | |
| " | " Flow Existing Drain | | 5.7 | |
| 0+38 | on Flow to East | | 5.20 | |
| 0+39 | " Flow from North | | 4.41 | |
| 0+38 | | | 3.40 | |
| 0+39 | on Hd Wall - Paving to North | | 3.18 | |



Form & Juniper Drain - Laterals

| | 288.07 / 288.43 |
|---|---|
| 0+40 = on W cb 38th | 3.20 |
| Cleanout N° 1 | |
| on Flow | 6.42 |
| " Top | 5.18 |
| 11' East on Flow in lot N°1 | 6.26 |
| " " " cb | 5.02 |
| 16' " " Gutter | 5.60 |
| Cleanout N° 2 | |
| on Top | 4.23 |
| " Flow | 3.01 |
| 11' W on Hd Wall | 3.13 |
| 11' W " Flow Line | 4.26 |
| 16' West = Toe of Grating | 3.50 |
| Cleanout N° 3 | |
| on Flow | 4.22 |
| " Top | 3.13 |
| 11' West on Hd Wall | 2.99 |
| " " " Flow | 4.10 |
| 16' " Toe Grating | 3.55 |

| | 288.73 / 288.07 | | |
|---|---|---|---|
| # 15' N of St. cleanout N°3 | | | |
| on Hd Wall in Lot | | 3.10 | |
| on Flow | | 4.10 | |
| 20' N on Toe Grating | | 3.86 | |
| Cleanout N° 4 | | | |
| on Top | | 6.14 | |
| " Flow | | 5.08 | |
| 15' North on Hd Wall | | 5.05 | |
| " " " Flow | | 6.09 | |
| 20' " Toe Grating | | 5.46 | |
| 11' East on Hd Wall | | 5.02 | |
| " " " Flow | | 6.12 | |
| 16' " " Toe Grating | | 5.53 | |
| East Gutter Form | | | |
| St. Juniper = 0+00 on Hd Wall | | 5.08 | |
| 0+02 Toe Grating | | 5.57 | |
| +50 on Gut | | 5.63 | |
| " " cb | | 5.31 | |
| 1+50 " " | | 5.41 | |
| " " Gut | | 5.87 | |
| T.P. | 7.75 | 293.97 / 294.03 | 1.85 | 286.22 / ~~286.28~~ |
| Chk Starting B.M. | | | 4.98 | ~~289.05~~ 288.99 / 289.00 |

Proposed Sewer Block 251 Bergin's Add
Between Main St + Dalbergio St. Siva St + Rigol St

| | | | | | |
|---|---|---|---|---|---|
| BM | 6.55 | 11.96 ✓ | | 5.21 | N.W. Lot N'ly of Main N.E. Siva |
| 0=8.05 = Existing MH | | | 3.51 | 8.25 | on R.O. |
| " " | | | 19.30 | -7.54 | Flow Line |
| 0+0 | | | 5.00 | 6.8 | 6.76 on Stub |
| +50 | | | 4.6 | 7.2 | |
| 1+0 | | | 4.8 | 7.0 | |
| +50 | | | 4.4 | 7.4 | |
| 2+0 | | | 4.9 | 6.9 | |
| +50 | | | 4.7 | 7.1 | |
| 3+0 | | | 5.2 | 6.6 | |
| +65 | | | 4.86 | 6.90 | on Stub |

Indexed
C.S.K.

Nov. 1. 45
S. Simon
Bliss
Osborn

79



# DIETZGEN'S RAILROAD CURVE AND REDUCTION TABLES

Copyright, 1914, by Eugene Dietzgen Co., New York City




## CURVE FORMULAS

Radius=R=$\frac{50}{\text{sin. D/2}}$ (1) Degree of Curve=D and sin. $\frac{D}{2}=\frac{50}{R}$ (2)

Tangent=T=Rtan$\frac{\Delta}{2}$ (3) Length of Curve=L=100$\frac{\Delta}{D}$ (4)

Middle ordinate=M= R(1—cos. $\frac{\Delta}{2}$) (5) =Rvers $\frac{\Delta}{2}$ (6)

External=E=Ttan$\frac{\Delta}{4}$ (7) =R÷cos.$\frac{\Delta}{2}$—R (8)=Rexsec$\frac{\Delta}{2}$ (9)

Long Chord=C=2 R sin.$\frac{\Delta}{2}$ (10) Δ=Central Angle

## EXPLANATION AND USE OF TABLES

**Stations.**—Given P. I.=Sta. 161+60.35 to find Sta. of P. C. and P. T. Δ=62° 10′ D=8° 20′. From Table IV for 1° curve T=3454.1 and÷8⅓=414.49 ft. From Table V correction=.36 or T=414.85 ft. P. C.=Sta. P.I.—T=157+45.50. Also from (4) L=746.00 and P. T.=Sta. P. C.+L=164+91.50.

**Offsets.**—Tangent offsets vary (approximately) directly with D and with square of the distance. Thus tangent offset for Sta. 158 on above curve is 2.16 ft. found as follows. From Table III tangent offset for 100 ft.=7.27 ft. Distance=158—Sta. P. C.=54.50, hence offset=7.27 $(54.50\div100)^2$=2.16 ft. Also square of any distance divided by twice the radius equals (approximately) the distance from tangent to curve. Thus $(54.50)^2\div(2\times688.26)$=2.16 ft.

**Deflections.**—Deflection angle=½ D for 100 ft., ¼ D for 50 ft., etc. For c ft.=(in minutes) .3 x C x D° or=defl. for 1 ft. from Table III x C. For Sta. 158 of above curve=.3 x 54.5 x 8⅓=136.2′ or 2° 16.2′, or=2.50 x 54.5=136.2′ from Table III. For Sta. 159 deflection angle=2° 16.2′+8° 20′÷2=6° 26.2′, etc.

**Externals.**—May be found in similar manner to tangents. Thus E for curve above is 91.37. For from Table IV for 1° curve E=960.6 for 8° 20′=960.6÷8⅓=91.27 and from Table V correction=.10 or E=91.37 ft. Or suppose Δ=32° and E is measured and found to be 42 ft. What is D? From Table IV E=230.9 and÷42=5.5 or D=5° 30′.

## DISTANCES FROM CENTER OF ROADWAY FOR CROSS-SECTIONING.

Roadway 16 feet wide. Side Slopes 1 on 1½

For Single Track Embankment.

| H | 0 | .1 | .2 | .3 | .4 | .5 | .6 | .7 | .8 | .9 | H |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 0 | 8.0 | 8.2 | 8.3 | 8.5 | 8.6 | 8.8 | 8.9 | 9.1 | 9.2 | 9.4 | 0 |
| 1 | 9.5 | 9.7 | 9.8 | 10.0 | 10.1 | 10.3 | 10.4 | 10.6 | 10.7 | 10.9 | 1 |
| 2 | 11.0 | 11.2 | 11.3 | 11.5 | 11.6 | 11.8 | 11.9 | 12.1 | 12.2 | 12.4 | 2 |
| 3 | 12.5 | 12.7 | 12.8 | 13.0 | 13.1 | 13.3 | 13.4 | 13.6 | 13.7 | 13.9 | 3 |
| 4 | 14.0 | 14.2 | 14.3 | 14.5 | 14.6 | 14.8 | 14.9 | 15.1 | 15.2 | 15.4 | 4 |
| 5 | 15.5 | 15.7 | 15.8 | 16.0 | 16.1 | 16.3 | 16.4 | 16.6 | 16.7 | 16.9 | 5 |
| 6 | 17.0 | 17.2 | 17.3 | 17.5 | 17.6 | 17.8 | 17.9 | 18.1 | 18.2 | 18.4 | 6 |
| 7 | 18.5 | 18.7 | 18.8 | 19.0 | 19.1 | 19.3 | 19.4 | 19.6 | 19.7 | 19.9 | 7 |
| 8 | 20.0 | 20.2 | 20.3 | 20.5 | 20.6 | 20.8 | 20.9 | 21.1 | 21.2 | 21.4 | 8 |
| 9 | 21.5 | 21.7 | 21.8 | 22.0 | 22.1 | 22.3 | 22.4 | 22.6 | 22.7 | 22.9 | 9 |
| 10 | 23.0 | 23.2 | 23.3 | 23.5 | 23.6 | 23.8 | 23.9 | 24.1 | 24.2 | 24.4 | 10 |
| 11 | 24.5 | 24.7 | 24.8 | 25.0 | 25.1 | 25.3 | 25.4 | 25.6 | 25.7 | 25.9 | 11 |
| 12 | 26.0 | 26.2 | 26.3 | 26.5 | 26.6 | 26.8 | 26.9 | 27.1 | 27.2 | 27.4 | 12 |
| 13 | 27.5 | 27.7 | 27.8 | 28.0 | 28.1 | 28.3 | 28.4 | 28.6 | 28.7 | 28.9 | 13 |
| 14 | 29.0 | 29.2 | 29.3 | 29.5 | 29.6 | 29.8 | 29.9 | 30.1 | 30.2 | 30.4 | 14 |
| 15 | 30.5 | 30.7 | 30.8 | 31.0 | 31.1 | 31.3 | 31.4 | 31.6 | 31.7 | 31.9 | 15 |
| 16 | 32.0 | 32.2 | 32.3 | 32.5 | 32.6 | 32.8 | 32.9 | 33.1 | 33.2 | 33.4 | 16 |
| 17 | 33.5 | 33.7 | 33.8 | 34.0 | 34.1 | 34.3 | 34.4 | 34.6 | 34.7 | 34.9 | 17 |
| 18 | 35.0 | 35.2 | 35.3 | 35.5 | 35.6 | 35.8 | 35.9 | 36.1 | 36.2 | 36.4 | 18 |
| 19 | 36.5 | 36.7 | 36.8 | 37.0 | 37.1 | 37.3 | 37.4 | 37.6 | 37.7 | 37.9 | 19 |
| 20 | 38.0 | 38.2 | 38.3 | 38.5 | 38.6 | 38.8 | 38.9 | 39.1 | 39.2 | 39.4 | 20 |
| 21 | 39.5 | 39.7 | 39.8 | 40.0 | 40.1 | 40.3 | 40.4 | 40.6 | 40.7 | 40.9 | 21 |
| 22 | 41.0 | 41.2 | 41.3 | 41.5 | 41.6 | 41.8 | 41.9 | 42.1 | 42.2 | 42.4 | 22 |
| 23 | 42.5 | 42.7 | 42.8 | 43.0 | 43.1 | 43.3 | 43.4 | 43.6 | 43.7 | 43.9 | 23 |
| 24 | 44.0 | 44.2 | 44.3 | 44.5 | 44.6 | 44.8 | 44.9 | 45.1 | 45.2 | 45.4 | 24 |
| 25 | 45.5 | 45.7 | 45.8 | 46.0 | 46.1 | 46.3 | 46.4 | 46.6 | 46.7 | 46.9 | 25 |
| 26 | 47.0 | 47.2 | 47.3 | 47.5 | 47.6 | 47.8 | 47.9 | 48.1 | 48.2 | 48.4 | 26 |
| 27 | 48.5 | 48.7 | 48.8 | 49.0 | 49.1 | 49.3 | 49.4 | 49.6 | 49.7 | 49.9 | 27 |
| 28 | 50.0 | 50.2 | 50.3 | 50.5 | 50.6 | 50.8 | 50.9 | 51.1 | 51.2 | 51.4 | 28 |
| 29 | 51.5 | 51.7 | 51.8 | 52.0 | 52.1 | 52.3 | 52.4 | 52.6 | 52.7 | 52.9 | 29 |
| 30 | 53.0 | 53.2 | 53.3 | 53.5 | 53.6 | 53.8 | 53.9 | 54.1 | 54.2 | 54.4 | 30 |
| 31 | 54.5 | 54.7 | 54.8 | 55.0 | 55.1 | 55.3 | 55.4 | 55.6 | 55.7 | 55.9 | 31 |
| 32 | 56.0 | 56.2 | 56.3 | 56.5 | 56.6 | 56.8 | 56.9 | 57.1 | 57.2 | 57.4 | 32 |
| 33 | 57.5 | 57.7 | 57.8 | 58.0 | 58.1 | 58.3 | 58.4 | 58.6 | 58.7 | 58.9 | 33 |
| 34 | 59.0 | 59.2 | 59.3 | 59.5 | 59.6 | 59.8 | 59.9 | 60.1 | 60.2 | 60.4 | 34 |
| 35 | 60.5 | 60.7 | 60.8 | 61.0 | 61.1 | 61.3 | 61.4 | 61.6 | 61.7 | 61.9 | 35 |
| 36 | 62.0 | 62.2 | 62.3 | 62.5 | 62.6 | 62.8 | 62.9 | 63.1 | 63.2 | 63.4 | 36 |
| 37 | 63.5 | 63.7 | 63.8 | 64.0 | 64.1 | 64.3 | 64.4 | 64.6 | 64.7 | 64.9 | 37 |
| 38 | 65.0 | 65.2 | 65.3 | 65.5 | 65.6 | 65.8 | 65.9 | 66.1 | 66.2 | 66.4 | 38 |
| 39 | 66.5 | 66.7 | 66.8 | 67.0 | 67.1 | 67.3 | 67.4 | 67.6 | 67.7 | 67.9 | 39 |
| 40 | 68.0 | 68.2 | 68.3 | 68.5 | 68.6 | 68.8 | 68.9 | 69.1 | 69.2 | 69.4 | 40 |

**Example**—If point is 22.6 ft. above grade, how far should it be from center line to be a slope stake point? Ans. from Table 41.9. For same slopes but other widths of roadbed correct above figures by one-half difference in width of roadbed; thus in example above for 20 ft. roadbed distance will be 41.9 + (20—16) ÷ 2 or 2 ft. added to 41.9 = 43.9. For slopes of 1 on 1 see inside of front cover.

MADE IN U.S.A.