CONDUIT.

380

FIELD

F.B.415

## TRAVERSE TABLE FOR TRANSIT BOOK.

From 1° to 90° for a distance of 100.

| Degrees. | DEGREES. | | ¼ DEGREE. | | ½ DEGREE. | | ¾ DEGREE. | | Degrees. |
|---|---|---|---|---|---|---|---|---|---|
| | Lat. | Dep. | Lat. | Dep. | Lat. | Dep. | Lat. | Dep. | |
| 0 | | | 100.00 | 0.44 | 100.00 | 0.87 | 99.99 | 1.31 | 89 |
| 1 | 99.98 | 1.75 | 99.98 | 2.18 | 99.97 | 2.62 | 99.95 | 3.05 | 88 |
| 2 | 99.94 | 3.49 | 99.92 | 3.93 | 99.91 | 4.36 | 99.88 | 4.80 | 87 |
| 3 | 99.86 | 5.23 | 99.84 | 5.67 | 99.81 | 6.10 | 99.79 | 6.54 | 86 |
| 4 | 99.76 | 6.98 | 99.73 | 7.41 | 99.69 | 7.85 | 99.66 | 8.28 | 85 |
| 5 | 99.62 | 8.72 | 99.58 | 9.15 | 99.54 | 9.58 | 99.50 | 10.02 | 84 |
| 6 | 99.45 | 10.45 | 99.41 | 10.89 | 99.36 | 11.32 | 99.31 | 11.75 | 83 |
| 7 | 99.25 | 12.19 | 99.20 | 12.62 | 99.14 | 13.05 | 99.09 | 13.49 | 82 |
| 8 | 99.03 | 13.92 | 98.97 | 14.35 | 98.90 | 14.78 | 98.84 | 15.21 | 81 |
| 9 | 98.77 | 15.64 | 98.70 | 16.07 | 98.63 | 16.50 | 98.56 | 16.93 | 80 |
| 10 | 98.48 | 17.36 | 98.40 | 17.79 | 98.33 | 18.22 | 98.25 | 18.65 | 79 |
| 11 | 98.16 | 19.08 | 98.08 | 19.51 | 97.99 | 19.94 | 97.90 | 20.36 | 78 |
| 12 | 97.81 | 20.79 | 97.72 | 21.22 | 97.63 | 21.64 | 97.53 | 22.07 | 77 |
| 13 | 97.44 | 22.50 | 97.34 | 22.92 | 97.24 | 23.34 | 97.13 | 23.77 | 76 |
| 14 | 97.03 | 24.19 | 96.92 | 24.62 | 96.81 | 25.04 | 96.70 | 25.46 | 75 |
| 15 | 96.59 | 25.88 | 96.48 | 26.30 | 96.36 | 26.72 | 96.25 | 27.14 | 74 |
| 16 | 96.13 | 27.56 | 96.00 | 27.98 | 95.88 | 28.40 | 95.76 | 28.82 | 73 |
| 17 | 95.63 | 29.24 | 95.50 | 29.65 | 95.37 | 30.07 | 95.24 | 30.49 | 72 |
| 18 | 95.11 | 30.90 | 94.97 | 31.32 | 94.83 | 31.73 | 94.69 | 32.14 | 71 |
| 19 | 94.55 | 32.56 | 94.41 | 32.97 | 94.26 | 33.38 | 94.12 | 33.79 | 70 |
| 20 | 93.97 | 34.20 | 93.82 | 34.61 | 93.67 | 35.02 | 93.51 | 35.43 | 69 |
| 21 | 93.36 | 35.84 | 93.20 | 36.24 | 93.04 | 36.65 | 92.88 | 37.06 | 68 |
| 22 | 92.72 | 37.46 | 92.55 | 37.86 | 92.39 | 38.27 | 92.22 | 38.67 | 67 |
| 23 | 92.05 | 39.07 | 91.88 | 39.47 | 91.71 | 39.87 | 91.53 | 40.27 | 66 |
| 24 | 91.35 | 40.67 | 91.18 | 41.07 | 91.00 | 41.47 | 90.81 | 41.87 | 65 |
| 25 | 90.63 | 42.26 | 90.45 | 42.66 | 90.26 | 43.05 | 90.07 | 43.44 | 64 |
| 26 | 89.88 | 43.84 | 89.69 | 44.23 | 89.49 | 44.62 | 89.30 | 45.01 | 63 |
| 27 | 89.10 | 45.40 | 88.90 | 45.79 | 88.70 | 46.17 | 88.50 | 46.56 | 62 |
| 28 | 88.29 | 46.95 | 88.09 | 47.33 | 87.88 | 47.72 | 87.67 | 48.10 | 61 |
| 29 | 87.46 | 48.48 | 87.25 | 48.86 | 87.04 | 49.24 | 86.82 | 49.62 | 60 |
| 30 | 86.60 | 50.00 | 86.38 | 50.38 | 86.16 | 50.75 | 85.94 | 51.13 | 59 |
| 31 | 85.72 | 51.50 | 85.49 | 51.88 | 85.26 | 52.25 | 85.04 | 52.62 | 58 |
| 32 | 84.80 | 52.99 | 84.57 | 53.36 | 84.34 | 53.73 | 84.10 | 54.10 | 57 |
| 33 | 83.87 | 54.46 | 83.63 | 54.83 | 83.39 | 55.19 | 83.15 | 55.56 | 56 |
| 34 | 82.90 | 55.92 | 82.66 | 56.28 | 82.41 | 56.64 | 82.16 | 57.00 | 55 |
| 35 | 81.92 | 57.36 | 81.66 | 57.71 | 81.41 | 58.07 | 81.16 | 58.42 | 54 |
| 36 | 80.90 | 58.78 | 80.64 | 59.13 | 80.39 | 59.48 | 80.13 | 59.83 | 53 |
| 37 | 79.86 | 60.18 | 79.60 | 60.53 | 79.34 | 60.88 | 79.07 | 61.22 | 52 |
| 38 | 78.80 | 61.57 | 78.53 | 61.91 | 78.26 | 62.25 | 77.99 | 62.59 | 51 |
| 39 | 77.71 | 62.93 | 77.44 | 63.27 | 77.16 | 63.61 | 76.88 | 63.94 | 50 |
| 40 | 76.60 | 64.28 | 76.32 | 64.61 | 76.04 | 64.94 | 75.76 | 65.28 | 49 |
| 41 | 75.47 | 65.61 | 75.18 | 65.93 | 74.90 | 66.26 | 74.61 | 66.59 | 48 |
| 42 | 74.31 | 66.91 | 74.02 | 67.24 | 73.73 | 67.56 | 73.43 | 67.88 | 47 |
| 43 | 73.14 | 68.20 | 72.84 | 68.52 | 72.54 | 68.84 | 72.24 | 69.15 | 46 |
| 44 | 71.93 | 69.47 | 71.63 | 69.78 | 71.33 | 70.09 | 71.02 | 70.40 | 45 |
| 45 | 70.71 | 70.71 | | | | | | | |
| Degrees. | Dep. | Lat. | Dep. | Lat. | Dep. | Lat. | Dep. | Lat. | Degrees |
| | DEGREES | | ¾ DEGREE. | | ½ DEGREE. | | ¼ DEGREE. | | |

Published by H. S. Crocker Company, Stationers, Drawing Materials, Mathematical Instruments, etc., San Francisco.

MICROFILMED
FEB 1964

Return to City Engineers Office
City Hall, San Diego, Cal.

Crocker Quality

# FIELD BOOK

COMMUNI CONSENSU TRADE MARK PRIMO

No._____

MANUFACTURED BY

H. S. CROCKER CO.

SAN FRANCISCO AND SACRAMENTO
CALIFORNIA

Crocker Quality

FIELD BOOK

No

H. S. CROCKER CO.

MANUFACTURERS OF

SAN FRANCISCO AND SACRAMENTO

CALIFORNIA

7.40
61.67
12.33
1.7
8.63
1.233
20.961
.191

23.65

Grades for West Wing of Switzer Dam.

| | | | | |
|---|---|---|---|---|
| 74.17 | 2.45 | 2.25 | 2.07 | 5.90 |
| 2.74 | 74.46 | 74.06 | 74.84 | 71.01 |
| 76.91 M1 | -1.54 | -1.34 | 1.16 | 64.00 |
| | | | | +7.01 |

4/30/08 Smith, Davis, Dannon, Coltrath

Traverse Line for Drainage Area 16th St. Conduit

16+00 Δ R 5°0'

0+00 Δ R 48°0'



40+40 ΔR 22°0'

36+00 Δ∠ 32°30'

33+60 Δ∠ 17°30'

23+55 Δ∠ 33°0'

22°0'

32°

17°30'

33°0'

POSTED

81+55.1

54+93.2

51+50 Δ L 83°46'



5/1/08 { Davis, Donnan, Colbath

Levels over Traverse Line for drainage area - 16th St Conduit

| | 2.48 | H.I. 295.89 | | | 293.41 - B.M. Split in fence on Laurel St. 15' W of 30th | | |
|---|---|---|---|---|---|---|---|
| 0+00 - S.L. Juniper Ctr 30th | | | 6.9 | 289.0 | 22 | 11.7 | 290.7 |
| 1 | | | 8.1 | 287.8 | 23 | 10.1 | 392.3 |
| 2 | | | 9.5 | 286.4 | +55 △ | 10.0 | 392.4 |
| 3 | | | 7.4 | 288.5 | 24 | 10.2 | 392.2 |
| 4 | | | 6.5 | 289.4 | T.P. | 11.72 304.00 | 10.11 292.28 |
| 5 | | | 6.1 | 289.8 | 25 | 10.6 | 293.4 |
| 6 | | | 6.7 | 289.2 | 26 | 8.2 | 295.8 |
| 7 | | | 5.2 | 290.7 | 27 | 4.1 | 299.9 |
| 8 | | | 4.4 | 291.5 | 28 | 0.4 | 303.6 |
| 9 | | | 3.1 | 292.8 | T.P. | 6.90 310.49 | 0.41 303.59 |
| T.P. | 10.91 | 303.88 | 2.92 | 292.97 | 29 | 5.3 | |
| 10 | | | 9.8 | 294.1 | 30 | 5.6 | |
| 11 | | | 8.9 | 295.0 | 31 | 4.8 | |
| 12 | | | 7.1 | 296.8 | 32 | 3.5 | |
| 13 | | | 5.7 | 298.2 | 33 | 2.6 | |
| 14 | | | 4.1 | 299.8 | +60 △ | 1.6 | |
| 15 △ | | | 3.6 | 300.3 | T.P. | 4.96 315.78 | 1.67 308.82 |
| 16 | | | 4.9 | 299.0 | 34 | 6.5 | |
| 17 | | | 4.6 | 299.3 | 35 | 6.5 | |
| 18 | | | 5.6 | 298.3 | 36 | 6.0 | |
| T.P. | 4.03 | 302.39 | 5.52 | 298.36 | 37 | 5.4 | |
| 19 | | | 6.9 | 295.5 | 38 △ | 4.5 | |
| 20 | | | 10.0 | 292.4 | 39 | 4.7 | |
| 21 | | | 13.2 | 289.2 | 40 | 4.0 | |
| | | | | | +40 △ | 2.5 | |

| | | | | |
|---|---|---|---|---|
| | | #1 316.78 | | |
| TP | 6.76 | 318.09 | 3.45 | 312.33 |
| 41 | | | 4.9 | |
| 42 | | | 4.4 | |
| 43 | | | 6.0 | |
| 44 | | | 5.5 | |
| 45 | | | 4.9 | |
| TP | 8.70 | 322.96 | 8.81 | 314.28 |
| 46 | | | 8.0 | |
| 47 | | | 14.0 | |
| 48 | | | 12.8 | |
| 49 | | | 4.4 | |
| 50 | | | 2.3 | |
| 51 | | | 0.5 | |
| TP | 10.86 | 333.45 | 0.39 | 322.59 |
| 450△ | | | 9.9 | |
| 52 | | | 9.1 | |
| 53 | | | 8.4 | |
| 54 | | | 7.3 | |
| 1932△ - Ctr. Nash St. | | | 7.7 | |
| 56 | | | 6.2 | |
| 57 | | | 4.7 | |
| 58 | | | 3.8 | |
| 59 | | | 1.7 | |
| TP | 9.11 | 340.40 | 1.82 | 331.63 |
| 60 | | | 7.3 | |
| 61 | | | 6.6 | |
| 62 | | | 6.0 | |
| 63 | | | 5.1 | |
| 64 | | | 4.6 | |
| 65 | | | 3.4 | |
| 66 | | | 2.5 | |
| TP | 5.97 | 343.87 | 2.50 | 327.90 |
| 67 | | | 5.8 | |
| 68 | | | 5.6 | |
| 69 | | | 5.4 | |
| 70 | | | 6.1 | |
| 71 | | | 5.8 | |
| 72 | | | 5.4 | |
| 73 | | | 3.6 | |
| 74 | | | 2.5 | |
| TP | 9.17 | 350.19 | 2.85 | 341.02 |
| 75 | | | 8.0 | |
| 76 | | | 6.8 | |
| 77 | | | 5.1 | |
| 78 | | | 3.6 | |
| 79 | | | 2.4 | |
| 80 | | | 1.1 | |
| TP | 7.40 | 356.62 | 0.97 | 349.22 |
| 81 | | | 6.2 | |
| 755.1: S.L. Univ. Ctr. Nash | | | 5.4 | |
| Chk. B.M. N.E. Univ. of Missouri. | | | 3.16 | 353.46 / 353.50 |

"A" line

5/1/08 Smith, Davis, Denman, Colbath

# Location of 15th St. Conduit

12+82.29 So. end bridge
12+63.95 Int with "A" line
Sta. 11 ommited • all stations from here on are 10.0 ft too long.

9+98 Et. No. end bridge

9+72.85 E.C.

7+94.25 P.C.

6+31.47

3+01.05 P.T.

2+58.29 P.C.

0+0.0



"A" line

23+36.11 E.C

20+57.36
20+18.86 P.C

19+26.86
19+00

18+54.17

16+84.37 E.C.
16+64.75

16+11.38
16+03.62 P.C.

16+01.25 E.C.

15+60.86 Int with sewer in curve

15+07 P.C.

Continued P12

E.C.

D=20°0'
R=287.94'
T=177.14'
L=317.65'
Δ=63°12'

P.C.

Line of Storm Sewer from 16+11.8

E.C.

R 175.00'
T 41.48'
E 4.85'
L 81.45'
Δ 26°40'

P.C.

E.C.

R 200.0'
T 48.00'
E 5.68'
L 92.28'
Δ 27°0'

P.C.

5 & 6 of Smith Davis Penman Cultrath

Storm Sewer for draining district of 15th and A

6+78.27

2+21.2+ ∠30°12' R Man Hole

1+82.90
1+56.22

1+29.2+ ∠5°56' R - E. end old culvert

0+00 = W. end old culvert = 24" vit pipe.



Storm Sewer dist. at 15th and A

14+22.22
18+96



Levels over Line of Storm drain for dist of 15th and H

Davis Dunnan Colhatt.

| | + | 15th | − | elev. |
|---|---|---|---|---|
| | 1.89 | 95.22 | | 93.33 B.M. Spk pole SE 15th & |
| 0+00 = bottom pipe inlet old culvert. | | | 7.14 | |
| +07 = WL 15th | | | 1.2 | |
| 1+00 | | | 6.9 | |
| +24 = E.L. 15th | | | 7.2 | |
| +29.2 = bottom pipe outlet old culvert | | | 11.93 | |
| +46 | | | 11.2 | |
| +56.2 = top 2" Gas pipe | | | 10.46 | |
| +68 | | | 9.8 | |
| +81 | | | 7.9 | |
| +87.8 = Top 4" C.I. Water pipe | | | 9.30 | |
| 2 | | | 9.9 | |
| T.P | 2.26 | .87.27 | 10.21 | 85.01 |
| +21.25 = M.H. | | | 4.1 | |
| Stake 6' E. of M.H. | | | 0.89 | |
| +32 | | | 4.2 | |
| +52 | | | 2.7 | |
| +70 | | | 3.4 | |
| +80 | | | 6.1 | |
| 3 +00 | | | 6.7 | |
| +20 | | | 7.7 | |
| +21 | | | 9.4 | |
| +70 | | | 10.5 | |
| A +00 | | | 11.6 | |
| | 3.95 | 78.39 | 12.83 | 74.44 |

| | + | H.I. | − | E 16 |
|---|---|---|---|---|
| +27 | | | 4.6 | |
| +56 | | | 5.1 | |
| +60 | | | 4.4 | |
| 5 +00 | | | 3.9 | |
| +10 | | | 4.7 | |
| +62.96 △ | | | 5.0 | |
| 6+00 | | | 7.1 | |
| +16 | | | 8.1 | |
| +75 | | | 6.8 | |
| +78.27 △ | | | 7.7 | |
| 7+00 | | | 8.7 | |
| E | | | 11.7 | |
| T.P | 0.41 | 66.80 | 12.20 | 64.19 |
| 9 | | | 2.6 | |
| 10 | | | 6.3 | |
| 11 | | | 7.9 | |
| 12 | | | 9.3 | |
| 13 | | | 10.3 | |
| 7.96 W.L. edge bridge top | | | 16.8 | |
| " " bottom | | | 24.9 | |
| 14+24.2 | | | 10.9 | |

15th St Conduit Location "A" line

32+37.25
32+29.88

32+07.20

31+56.78

28+55.05

27+82.92
27+75.48

27+00.28

26+57.92 = 26+57.20 "B" line

Continued from P. 8



"A" line

99+00

38+48.25

37+51.86 PT.

36+98.77 PC.

36+88.73 ℄

36+82.07

35+86.47

34+80.77 PT.

33+92.47 P.C.

33+45.21 EC

32+37.92 PC.



"A" line

45+12

44+72.9

44+33.53 P.T.
44+32

42+68.89 P.C.

42+22.03 P.T.

41+17.21 P.C.

40+79.24

40+01.92

39+91.53

41+45.32



"A" line

56+83.74
56+74.87

56+37.91

55+81.19

55+68.66 E.C.

55+00.59 P.C.

52+40.72 Ctr. Track
52+32.29

793.45

48+85.95

48+12.55



"A" line

+89.00 – 5° rad
+84.83 – N. rad
+78.20 – S. rad
+69.71 – N. rad

60+46.63

59+79.77

59+11.70



72+11 Bk

67+08

64+39 Ck

64+06 St. P.I. = 67+43 ST. Bline

63+70 Ahd

62+61 Ahd



Location of 15th St. Conduit "B" line.

5/13/08 { Davis Donnow Gleath.

36+36.97
35+99.82

35+84.82

32+27.98

+12.99 - 3 rail } So Park X E. Side Ry.
28+17.63 - 4 rail }
27+81.67

26+57.90 = 26+57.90 "A" line




POSTED

B Line

47+10 2°

43+30 45°

40+16 22



"B" Line

58+93.20

58+73.68
21+52 Lt

58+07.47

55+01.11

54+70.68



64+06.66 P.T.

63+49.74 ℄ 14th St.

63+17.20 P.C.

62+70.46

61+29.0 Δ L 0°15'



Bilma

75+56.87 50 rail gague line
75+50.29 N. " "
75+48.25 opposite bridge "

70+45.44

66+86.34 S rail
66+60.22 rail

66+26.30



8+92

5+00

4+00

3+00

2+00

0+91

0+00



17+56.89

14+76.62

13+53.62



25+20.37
25+12.66

23+22.53

20+89.19

19+38.40
18+55.65



32+52.65

31+00

30+26.43

29+52.37



43+87.3

42+75.4

42+04.50

40+75.83

39+75.83

39+04.34

37+38

36+93.68

36+43.07

35+78.78



48+55.62

46+71.22

44+38.64
44+35.42

44+15.95

43+88.74



53+11 ±6
53+04 ±0

52+24.75

50+48.25

50+16.25



58+42.45

57+73.33

56+26.92

54+91.98

54+20.48 So. end culvert

53+90.45

53+36.13 - St. Car
53+34.02 - No end culvert

53+11.22



64+83.57

64+87.00

64+88.22

63+55.24 E.C.

62+76.30 - P.C

62+01.89 E.C

61+86.44
61+82.85 P.C.

61+54.34

59+88.32

59+38.52






66+08.25

65+27.82

10838
67.42
40.5-6

"5" Line leaves main line at Sta 61+92 ℄ and connects at Sta 64+67 on main line = 2+10 2± on "5" line

2+10 2± = PI of Curve = 64+67 main line

1+97 ES

1+96 ±

1+58

1+35 ES
1+33

1+00

0+46 ES

0+00 = 61+92 ℄ on main line = PI of 22° R. curve



| | + | H.I. | − | |
|---|---|---|---|---|
| | 2.01 | 62.55 | | 60.54-B.M. N.W. 16th & C |
| | 7.37 | 61.47 | 8.45 | 54.10 |
| | 3.79 | 61.92 | 3.34 | 58.13 ✓ |
| | 5.97 | 62.41 | 5.48 | 56.44 |
| 0+00 | taken along Park Line. | | | |
| 0+00 | taken at right angles to line of Conduit. | | | |
| 0+42 | | | | |
| 1+00 | | | | |
| +50 | | | | |
| 2 | | | | |
| +58.29 | PC | | | |
| +79 61 | CC | | | |
| 3+01 26 | PT | | | |
| TP | 5.06 | 61.50 | 5.97 | 56.44 |
| 3+36 | | | | |
| 4+00 | | | | |

1/7/08 { Davis, Donnan, Colvath



# Cross Sections for 16th St Conduit - "A" Line

Left: W. or No. C Right: E. or So.

77.6/52 62.6/51 58.8/37 60.4/15 60.3/0 59.8/21 61.3/80 ✓

84.4/45 78.0/35 66.5/20 61.0/14 60.3/0 60.3/19 61.7/43 60.3/50 59.9/73 61.0/80 62.8/82 ✓

75.8/40 70.0/30 62.9/24 61.5/18 60.9/6 59.9/0 ✓

78.8/36 69.9/26 59.7/15 58.2/7 58.6/0 59.0/7 60.2/17 60.3/56 ✓

77.9/36 75.4/32 69/24 59.0/17 57.4/7 57.6/3 58.4/0 58.6/6 60.6/13 62.4/24 63.0/64 ✓

73.9/37 62.8/24 58.2/16 56.6/11 56.6/4 57.2/0 59.4/21 61.9/22 62.0/45 ✓

71.1/26 60.5/18 59.4/14 56.8/9 56.0/5 56.5/0 58.1/32 58.6/40 60.5/46 61.0/65 ✓

70.7/25 67.6/18 59.2/12 58.4/9 56.4/6 55.6/3 56.2/0 57.7/37 59.0/45 60.5/47 61.9/65 ✓

70.2/29 61.9/18 56.6/8 56.4/0 56.7/20 57.4/27 56.1/42 57.6/51 60.0/53 60.5/70 ✓

→ 71.6/82 64.7/47 60.5/21 58.4/19 56.9/12 56.2/0 56.3/6 56.8/11 56.0/27 56.0/51 57.5/73 58.6/77 61.1/79 61.5/100 ✓

61.0/100 60.8/47 59.4/26 56.5/16 56.2/0 56.1/14 55.3/29 56.0/56 58.9/81 60.4/91 ✓

H.I.

61.50

4+78

4+75

5+00

6+00

7+00

7+94.25 BC

| | | | | |
|---|---|---|---|---|
| TP | 7.06 | 62.95 | 6.61 | 55.89 |

8+83.55 CC

9+72.05 EC

+90

9+98 ± No end bridge - Top

10+10

| | | | | |
|---|---|---|---|---|
| | 0.21 | 61.65 | 1.51 | 61.44 |

11+89 = Inside bottom of Sewer in "C" St

12

"A" line

Left = W or N. C Right = E or S.

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| 60.5 / 100 | 60.4 / 67 | 60.1 / 25 | 55.3 / 11 | 54.2 / 0 | 54.8 / 10 | 56.9 / 18 | 55.1 / 22 | 54.1 / 32 | 55.5 / 41 | 57.0 / 70 |

| | | | | |
|---|---|---|---|---|
| 54.2 / 0 | 55.2 / 9 | 57.9 / 20 | 58.1 / 34 | 58.8 / 70 |

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| 60.6 / 70 | 60.1 / 22 | 55.5 / 8 | 54.1 / 1 | 54.4 / 7 | 56.2 / 21 | 57.9 / 56 | 59.3 / 80 |

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| 59.0 / 100 | 57.8 / 32 | 57.2 / 7 | 54.4 / 1 | 52.4 / 0 | 52.7 / 6 | 55.7 / 12 | 57.0 / 25 | 56.6 / 34 | 59.4 / 100 |

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| 57.3 / 70 | 56.5 / 70 | 53.8 / 10 | 53.4 / 0 | 53.9 / 3 | 56.6 / 9 | 56.7 / 40 | 58.2 / 100 |

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| 55.5 / 100 | 55.6 / 40 | 53.8 / 37 | 53.0 / 16 | 53.2 / 11 | 53.9 / 5 | 56.9 / 0 | 57.3 / 42 | 57.7 / 90 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 55 / 51 | 55.1 / 50 | 54.7 / 14 | 53.8 / 9 | 51.3 / 6 | 52.8 / 5 | 52.2 / 2 | 53.2 / 0 | 54.9 / 2 | 55.9 / 22 | 58.1 / 70 |

| | | | | | | |
|---|---|---|---|---|---|---|
| 54.1 / 42 | 53.5 / 17 | 52.1 / 10 | 51.4 / 0 | 51.8 / 18 | 52.0 / 50 | |

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| 53.7 / 23 | 54.4 / 16 | 52.1 / 10 | 53.1 / 6 | 51.5 / 6 | 52.1 / 0 | 51.7 / 4 | 60.9 / 5 |

60.3

52.8 Top

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| 54.8 / 50 | 54.2 / 5 | 59.8 / 45 | 51.2 / 4.5 | 51.4 / 2 | 51.9 / 12 | 59.8 / 13 | 60 / 50 |

60.00
51.2 = Top bridge

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| 56.5 / 50 | 57.1 / 9 | 51.0 / 7 | 50.7 / 0 | 50.5 / 10.2 | 57.2 / 91.0 | 58.0 / 39 | 57.8 / 54 | 51.2 / 87 |

"A" line

Left - W or No  C  Right - E or So

56.6 - Top bridge

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 56.5 / 53 | 56.6 / 8 | 49.7 / 7 | 49.7 / 0 | 49.7 / 10 | 56.7 / 11 | 57.5 / 30 | 50.8 / 45 | 51.1 / 77 | 54.0 / 87 |
| " " | | 47.2 / 7 | 47.5 / 8 | 47.2 / 10 | " | " | " | " | |
| 55.3 - Top | | | | | | | | | |
| 55.9 / 58 | 56.7 / 9 | 48.0 / 8 | 48.1 / 0 | 48.2 / 9 | 56.3 / 10 | 51.7 / 25 | 50.1 / 68 | 50.5 / 73 | |
| 54.4 - Top | | | | | | | | | |
| | | | 47.8 / 0 | 49.0 / 10 | 53.0 / 16 | 51.7 / 25 | 49.7 / 47 | 50.0 / 61 | 54.7 / 72 |
| 55.8 | | | | | | | | | |
| 55.5 / 50 | 56.0 / 17 | 47.1 / 7 | 47.6 / 0 | 47.8 / 2 | 46.8 / 7 | 50.3 / 11 | 50.2 / 24 | 50.6 / 44 | 53.6 / 64 |
| 55.4 / 70 | 55.4 / 45 | 52.1 / 31 | 49.2 / 16 | 47.8 / 14 | 46.9 / 10 | 46.9 / 0 | 49.3 / 8 | 50.2 / 20 | 54.6 / 30 | 59.8 / 45 |
| 55.3 / 100 | 55.3 / 52 | 49.5 / 37 | 49.4 / 18 | 47.8 / 14 | 46.4 / 13 | 47.0 / 0 | 48.8 / 6 | 52.6 / 40 | 60.7 / 52 | |
| 55.0 / 61 | 51.6 / 51 | 51.6 / 35 | 49.3 / 29 | 48.9 / 21 | 46.6 / 15 | 46.1 / 8 | 47.0 / 0 | 49.3 / 31 | 49.9 / 22 | 51.8 / 51 |
| 54.4 / 70 | 51.3 / 46 | 50.5 / 29 | 48.6 / 24 | 48.1 / 20 | 46.1 / 12 | 46.0 / 0 | 47.4 / 12 | 48.6 / 34 | 50.4 / 66 | |
| | 50.2 / 66 | 48.7 / 47 | 47.5 / 15 | 45.4 / 9 | 46.7 / 0 | 46.1 / 17 | 50.3 / 56 | | |
| | | | | | 44.83 | | | | |
| 53.6 / 50 | 53.6 / 29 | 50.6 / 16 | 45.2 / 15 | 45.8 / 0 | 44.4 / 10 | 44.8 / 14 | 47.8 / 20 | 49.2 / 41 | 48.7 / 47 |

POSTED

12+19

+20

+54

+63

12+82.2 - End bridge Top

13+05

T.P  2.52  52.60  11.57  50.08

T.P  4.02  54.10  2.52  50.08

13+60

+82

14

16+07 - P.C

+54.13 - C.C

+60.98 - Top 6" sewer pipe in 17th St

6.75  52.59  8.24  45.84

16+01.25 P.T.

16+3.52 P.C. same as 16+01.25

H.I.
61.65

H.I

52.59

16+44 22 = CC

+64 75 Top 4" C.I Sewer pipe

16+84 97 = PT

17+80

18

+20

+42

+54 13 end bridge

+58

+89 27 = bottom 4" C.I water pipe

19

+10 42 = bottom 2" W.I pipe

| | | | | |
|---|---|---|---|---|
| | 2.71 | 45 54 | 9.76 | 42.83 |

+43 17 = 4" Salamica pipe bottom

| | | | | |
|---|---|---|---|---|
| T.P | 10.08 | 52 91 | 2.71 | 42 83 |
| TP | 9.83 | 60 76 | 1.98 | 50.93 |
| Cor HI = | 60.78 | 4.89 | 55.87 ✓ | 55.89 BM |

"A" line

Left = W. or N. Right E or So.

53.0/100 51.8/60 48.2/52 47.8/40 46.0/23 44.9/0 44.2/13 47.0/16 48.9/28 49.0/80 ✓

46.14

51.5/9 75 47.9/70 47.8/52 46.8/31 46.42 pipe/12 44.9/0 43.9/24 47.8/30 48.4/61 50.9/75 ✓

47.2/50 45.5/16 44.6/0 43.8/3 43.0/18 48.7/29 52.6/40 59.6/52 ✓

43.7/0 43.0/5 43.4/24 48.2/34 57.7/34 58.7/40 ✓

58/70 56.7/58 48.7/57 44.2/18 45.2/11 42.7/0 ✓

56/30 55.6/20 45.6/20 43.3/13 42.8/0 43.0/8 46.0/14 55.5/14 57.0/30 ✓

55.73 ✓

42.3/0 43.6/4.5 55.4/5 55.4/20 ✓

52.72 ✓

55.7 Top

56.1/50 55.7/72 41.9/21 43.2/0 43.2/3.7 55.9/5 56.7/50 ✓

POSTED

52.67 ✓

51.68 ✓

19 + 58.51 No rail } St. Ry. Dist.
+70.11 = 50 " }

1.79 57.68 55.89 B.M.S.W.I.C.

183.7 - 6" Kalomein pipe - bottom

20

+18.46 + P.C.

+45

+46

+50

+57.36 - end of bridge Top

+83

21

+50

22

+50

"A" line

Left W. or No. Right E. or So.

55.27 ✓

55.28 ✓

51.50 ✓
55.7 Top ✓

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 57.3 / 54 | 56.0 / 23 | 43.5 / 22 | 55.9 / 19 (41.0 / 16 New rail, Sorel rail) | 55.9 / 14 | 40.2 / 0 | 40.7 / 3 | 55.8 / 4 | 55.9 / 23 | 48.0 / 36 | 45.6 / 50 | 44.7 / 75 |

56.1 Top

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 57.3 / 73 New rail | 56.0 / 28 | 55.9 / 24 | 55.9 / 23 (50 rail) | 43.0 / 23 | 40.8 / 17 | 40.3 / 0 | 40.6 / 3 | 56.2 / 4 | 55.9 / 14 | 48.6 / 27 | 45.5 / 40 | 44.1 / 61 |

55.97 Top

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | 39.6 / 0 | 39.8 / 3 | 55.9 B.M. / 39.5 | 53.5 / 4 | 47.4 / 11 | 44.7 / 33 | 44.4 / 68 | | |

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | 39.6 / 0 | 39.7 / 3 | 42.7 / 4 | 47 / 15 | 44.5 / 35 | | | | |

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 56.7 / 50 | | 56.1 / 25 | 42.2 / 24 | 39.5 / 1 | 40.3 / 3 | 42.8 / 5 | 45.5 / 19 | 44.2 / 56 | | | |

55.7 ✓

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 57 / 69 | 56.4 / 33 | 55.9 / 31 | 43.1 / 30 | 42.8 / 9 | 39.7 / 8 | 38.9 / 0 | | | | | |

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 56.0 / 70 | 56.1 / 47 | 50.5 / 33 | 44.1 / 27 | 41.6 / 21 | 40.7 / 7 | 39.2 / 6 | 39.1 / 0 | 39.3 / 3 | 40.5 / 4 | 42.3 / 27 | |

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 56.5 / 75 | 55.9 / 55 | 44.8 / 32 | 39.9 / 17 | 38.5 / 2 | 38.9 / 0 | 40.1 / 17 | 41.5 / 31 | 42.9 / 36 | 42.1 / 70 | | |

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 56.1 / 75 | 55.6 / 49 | 44.3 / 33 | 38.4 / 17 | 40.6 / 0 | 38.8 / 7 | 39.3 / 27 | 42.8 / 30 | 42.6 / 71 | | | |

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 54.6 / 65 | 52.7 / 41 | 43.3 / 23 | 38.2 / 13 | 39.8 / 2 | 39.9 / 0 | 39.8 / 7 | 38.6 / 9 | 38.3 / 21 | 42.2 / 30 | 42.0 / 70 | |

"A" line

57.68

2.3

+36.11 = P.T.

| | | | | |
|---|---|---|---|---|
| TP | 1.36 | 47.23 | 11.81 | 45.87 |
| TR | 4.22 | 45.12 | 6.33 | 40.90 |
| TP | 6.20 | 47.10 | 4.22 | 40.90 |
| 24 | 1.37 | 47.55 | 0.92 | 46.18 |

+32

+42

25

+68. Top 4"C.I Sewer lateral 12' E. of ℄ Conduit Top. 33.52 – 17' E. 33.89

26

+57.90 = P.C

+78.99 = C.C.,

27+00.08

+16

+43

Left = W or N. Right = S. or E

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| 49.2 / 50 | 48.9 / 34 | 41.3 / 22 | 38.6 / 15 | 38.5 / 6 | 39.1 / 0 | 37.8 / 3 | 38.0 / 14 | 40.3 / 25 | 41.2 / 70 | ✓ |
| 45.7 / 50 | 46.7 / 30 | 40.0 / 18 | 37.9 / 7 | 38.3 / 0 | 37.9 / 15 | 39.4 / 28 | 39.5 / 53 | 40.6 / 61 | 41.1 / 70 | ✓ |
| 41.5 / 60 | 42.1 / 45 | 41.5 / 29 | 37.5 / 5 | 36.8 / 0 | 37.3 / 7 | 37.0 / 22 | 38.5 / 31 | 38.8 / 48 | 41.3 / 63 | 41.1 / 50 | ✓ |
| 39.8 / 60 | 39.3 / 40 | 38.5 / 20 | 36.4 / 0 | 36.3 / 20 | 38.3 / 37 | 40.7 / 65 | | | | ✓ |
| 47.0 / 60 | 46.8 / 40 | 45.9 / 26 | 38.4 / 8 | 37.1 / 0 | | | | | | ✓ |
| 46.3 / 45 | 46.0 / 19 | 36.4 / 0 | 35.0 / 4 | 34.8 / 11 | 36.3 / 16 | 37.4 / 26 | | | | ✓ |
| 43.7 / 52 | 43.6 / 18 | 37.9 / 6 | 36.5 / 0 | 35.3 / 4 | 34.8 / 10 | 33.7 / 13 | 34.2 / 25 | | | ✓ |
| 42.9 / 51 | 41.9 / 20 | 35.4 / 8 | 35.1 / 0 | 34.3 / 11 | 33.2 / 14 | 33.2 / 24 | 34.7 / 29 | | | ✓ |
| 42.9 / 56 | 42.0 / 35 | 34.4 / 13 | 34.4 / 0 | 33.9 / 10 | 33.0 / 14 | 32.6 / 23 | 34.0 / 25 | 34.7 / 28 | | ✓ |
| 43.2 / 53 | 42.0 / 35 | 34.4 / 20 | 34.2 / 0 | 33.8 / 4 | 33.0 / 8 | 33.1 / 21 | 34.6 / 26 | | | ✓ |
| 43.3 / 52 | 41.4 / 33 | 36.6 / 325 | 38.5 / 22 | 33.4 / 0 | 32.7 / 2 | 33.1 / 17 | 35.8 / 26 | 38.5 / 29 | | ✓ |
| 37.8 / 0 | 33.5 / 15 | 38.2 / 23 | 40.2 / 31 | | | | | | | ✓ |

| | | | | |
|---|---|---|---|---|
| TP | 1.47 | 38.75 | 10.27 | 37.28 |
| 27+75 | | | | |
| 28 | | | | |
| +05 | 3" W.I. pipe. | | | |
| 1 18.01 | No rail 50. Park Ry | | | 42.175 |
| 22.83 | 50 | | | 42.173 |
| +25.3 | 2" W.I. pipe | | | |
| TP | 6.54 | 43.82 | 1.47 | 37.28 |
| | CH HT. | 43.80 | 0.95 | 42.87 ✓ 42.85 |
| +50 | | | | |
| +55.25 | 3. end bridge | | | |
| +60 | | | | |
| +74 | | | | |
| TP | 3.64 | 39.50 | 7.94 | 35.86 |
| +83 | | | | |
| 29 | | | | |
| +40 | | | | |
| 30 | | | | |
| TP | 5.68 | 38.99 | 6.19 | 33.31 |

"J" line

Left - W or No. Right - E or So.

42.8 Top bridge.

43.4/47 42.8/24 31.8/23 31.1/21 31.6/10 33.2/0 34.9/6 42.9/7 43.1/32 ✓

42.6 Top bridge.

42.7/45 42.7/22 30.8/21.5 33.3/7 33.3/6 33.6/0 34.4/9 42.7/9 43.0/30 ✓

41.83 ✓

38.84 ✓

42.7 Top bridge.

31.6/1 32.3/0 34.9/13 42.7/14 42.9/43 ✓

42.9 Top bridge.

43.0/27 42.9/17 30.9/16 32.2/0 42.0/27 42.1/43 ✓

43.0/27 30.8/16 30.8/9 31.4/1 32.8/0 ✓

42.5/54 39.2/43 36.1/26 31.0/15 30.6/4 31.6/0 37.1/11 39.0/25 41.1/33 41.0/44 ✓

POSTED

41.2/53 35.2/38 32.8/22 30.9/15 30.8/4 32.0/0 ✓

38.4/46 33.9/36 31.2/20 30.7/4 31.8/0 38.4/10 38.0/28 38.8/29 39.6/42 ✓

34.1/34 37.1/20 30.5/16 30.7/2 31.5/0 36.4/14 37.0/24 39.0/34 39.3/48 ✓

31.1/27 29.7/9 29.8/0 30.8/7 33.6/12 34.0/18 38.1/29 39.4/52 ✓

N1.
38.99

31+29

+48

31

+38

+55

+56.75 N. end bridge top.

+58

32

+07.4' = 4" CI. water pipe - bottom.

+35

+37 25. S. end bridge top.

+37.92 - P.C.

T.P. 0.64 31.59 8.04 30.95



"A" line

Left Wor No. Right Eor S.

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| 307 / 24 | 31.1 / 19 | 29.4 / 12 | 29.4 / 0 | 29.4 / 7 | 31.1 / 9 | 32.4 / 22 | 35.0 / 34 | 38.7 / 53 |
| 31.1 / 23 | 30.4 / 13 | 29.4 / 9 | 28.8 / 0 | 31.2 / 11 | 32.3 / 19 | 37.7 / 29 | 38.5 / 54 | |
| | 30.3 / 18 | 28.9 / 0 | 29.3 / 10 | 31.6 / 21 | 36.6 / 31 | 37.4 / 61 | | |
| 30.6 / 14 | 30.7 / 31.7 / 4 | 28.7 / 0 | 30.1 / 2 | 31.4 / 24 | 34 / 29 | 36.4 / 29 | 36.0 / 65 | |
| 30.4 / 13 | 29.2 / 9 | 29.3 / 3 | 28.1 / 0 | 28.9 / 4 | 38.1 / 19 | 35.3 / 19 | 35.8 / 66 | |

? = 3 / 25.27

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| 35.0 / 25 | 35.4 / 12 | 29.7 / 12 | 28.0 / 0 | | | | |
| | | | 34.3 Top bridge | | | | |
| 35.0 / 31 | 24.5 / 8 | 28.4 / 7.6 | 25.0 / 0 | 28.6 / 21 | 34.3 / 21 | 34.9 / 70 | |
| | | | 31.6 | | | | |
| 34.8 / 20 | 34.2 / 5 | 28.2 / 5 | 27.7 / 0 | 27.0 / 12 | 29.5 / 25.5 | 34.2 bridge / 25.5 | 32.5 / 25.5 | 32.2 / 44 |
| | | | 34.1 | | | | |
| 34.5 / 20 | 34.2 / 5 | 28.5 / 5 | 27.7 / 0 | 27.0 / 14 | 29.5 / 24 | 31.7 / 24 | 32.1 / 35 | 34.1 / 48 |

H1
3.1.59

31+56

+91.59 - C.C.

33+45.26 P.T.

33+93.11 - P.C.

TP 3.53 28.70 6.42 25.17

34+36 Lt - C.C.

+56

+59

+80.77 - P.T.

+85

+87

35

+15

+52

## "A" line

Left W or N. Right E or S.

34.5/46 31.2/33 29.4/13 27.4/0 26.8/6 27.6/17 30.0/22 30.5/50 ✓

28.8/40 28.3/10 27.1/0 27.0/16 27.8/22 29.8/26 28.9/50 ✓

28.8/40 28.6/19 27.5/14 26.1/0 25.6/17 26.8/20 28.6/20 29.1/40 ✓

28.7/50 29.2/22 27.3/14 25.4/0 25.6/14 27.1/18 27.8/40 ✓

28.8/35 28.2/26 28.8/16 24.9/0 27.5/19 29.5/19 30.5/40 ✓

27.8/40 27.2/28 25.2/11 23.4/11 25.2/0 26.6/14 29.5/15 29.5/50 ✓

28.5/40 28.9/26 28.8/11 23.5/11 23.8/6 25.2/0 ✓

29.2/35 29.2/20 27.6/20 27.8/9 24.5/8 24.0/4 24.1/6 25.0/9 26.5/10 27.2/14 29.7/14 29.7/40 ✓

29.5/35 29.2/20 27.5/9 24.7/8 24.2/0 ✓

29.3/35 29.1/19 26.1/19 24.2/0 ✓

29.2/35 29.2/18 25.2/18 25.1/10 24.3/6 24.2/0 23.5/8 26.9/16 27.4/17 27.7/17 28.4/30 ✓

29.1/35 28.7/19 25/17 24.6/6 23.8/0 23.6/11 27.1/20 28.2/20 28.1/30 ✓

29.2/30 29.2/15 24.7/15 24.6/11 23.2/8 23.1/0 23.4/5 27.4/5 26.4/30 ✓

N.1.
28.70

+78

+86.47 = No end concrete arch - X section taken along face of wall

+86.47

36

T.P 7.33 28.47 7.56 21.14

+88.73 = S. end Arch X section taken along face of arch

+98.27 P.C.

37+25.32

+61.86

38

+20

+28

+39

+42

"A" line

Left: W or N. Right: E or S.

30.4/20 29.6/13 24.0/13 23.1/9 23.0/0 23.0/6 23.3/10 27.1/10 27.1/23 ✓

31.49 = Top arch inside

31.1/17 29.4/12 23.1/9 23.0/0 22.9/9 27.1/9 27.1/30 ✓

" " 22.0/9 22.0/0 22.0/9 " " ✓

22.5/9 22.4/0 22.7/9 ✓

31.76 = Top arch inside

31.7/47 30.5/35 27.3/31 26.5/21 21.5/9 21.6/0 21.9/9 26.8/15 32.3/24 31.3/40 ✓

27.3/29 25.5/21 22.7/16 21.1/5 21.7/0 21.8/5 23.3/9 25.8/24 25.7/46 ✓

27.1/39 25.0/33 23.2/12 20.9/8 20.4/0 21.1/4 23.4/8 23.8/14 24.9/20 26.0/40 ✓

24.2/31 23.0/20 22.8/4 21.2/3 20.5/0 20.5/9 23.5/14 25.0/27 24.5/50 ✓

26.2/24 22.4/12 21.1/0 19.5/4 19.8/15 23.7/21 24.6/50

27.1/22 25.9/14 24.3/6 21.4/6 21.1/0 19.0/7 19.3/16 23.4/28 23.8/50 ✓

28.1/32 27.8/21 24.3/4 22.3/0 20.2/8 18.9/9 18.2/16 21.3/20 24.1/35 24.9/50 ✓

28.3/34 24.3/0 23.7/6 20.1/6 18.5/18 23.3/18 24.7/26 26.0/50 ✓

27.8/33 24.5/4 23.5/4 22.6/0 18.7/10 18.5/18 23.1/18 25.1/26 26.7/50 ✓

POSTED

H.I.
28.47

+55

| | | | | |
|---|---|---|---|---|
| T.P. | 9.60 | 31.12 | 6.95 | 21.52 |

+91

39

+76

+91

+94.6 = N. end bridge X sect. taken along End of Bridge

40

+22

+75 X sect. taken parallel with line of I.St. ∠ 72°0'

+79.24 S. end bridge X sect. taken along end of bridge




| | | | | |
|---|---|---|---|---|
| | Cor H.I. | 31.14 | 5.66 | |
| T.P. | 1.18 | 30.47 | 11.86 | 19.29 |
| T.P. | 3.59 | 22.88 | 1.18 | 19.29 |

41

+17.31 = P.C

+69.67 C.C

424.203 = P.T

"A" line

Left Wes N. Right E or So.

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| 27.8 / 33 | 24.2 / 6 | 21.0 / 6 | 20.4 / 0 | 18.5 / 10 | 17.3 / 17 | 24.3 / 17 | 26.1 / 50 | ✓ |
| 26.8 / 35 | 29.5 / 12 | 22.1 / 17 | 20.3 / 0 | 19.9 / 1 | 18.5 / 2 | 17.6 / 7 | 18.2 / 16 | ✓ |
| 26.8 / 36 | 28.2 / 25 | 23.3 / 24 | 21.3 / 6 | 20.1 / 0 | 19.4 / 2 | 18.0 / 3 | 17.6 / 8 | 19.1 / 18 | ✓ |
| 28.6 / 41 | 27.2 / 30 | 23.1 / 15 | 20.1 / 6 | 18.4 / 0 | 16.8 / 2 | 16.8 / 11 | 19.4 / 18 | 21.2 / 30 | 27.3 / 47 | ✓ |
| 29 / 39 | 28.0 / 14 | 24.8 / 12 | 21.6 / 2 | 17.5 / 0 | | | | | | ✓ |
| 29.3 / 35 | 28.5 / 10 | 26.5 / 6 | 24.3 / 5 | 23.5 / 0 | 21.8 / 2 | 16.5 / 3 | 16.0 / 15 | 20.3 / 32 | 26.7 / 31 | for bridge 26.7 / 45 | ✓ |
| | 29.0 / 36 | | 28.2 / 0 | 27.9 / 1 | 16.7 / 3 | 16.8 / 14 | 19.2 / 15 | 24.5 / 27 | 27.0 / 30 | 26.1 / 50 | ✓ |
| | 29.0 / 28 | | 27.9 / 0 | 17.7 / 1 | 16.5 / 14 | 18.7 / 15 | 19.3 / 27 | 27.5 / 28 | 26.8 / 50 | ✓ |
| 30.8 / 50 | 29.9 / 25 | 28.9 / 4 | 18.5 / 3 | 17.3 / 0 | | | | | | ✓ |
| 28.3 / 50 | 27.5 / 25 | 25.1 / 4 | 18.7 / 3 | 18.0 / 0 | 16.3 / 2 | 16.0 / 11 | 19.1 / 27 | 27.4 / 28 | 26.7 / 50 | ✓ |
| 31.9 / 66 | 21.6 / 24 | 20.2 / 11 | 17.5 / 0 | 15.6 / 6 | 15.8 / 13 | 17.0 / 17 | 18.5 / 20 | 23.6 / 32 | 24.2 / 52 | ✓ |
| 23.8 / 68 | 21.3 / 52 | 17.0 / 42 | 16.4 / 14 | 18.4 / 10 | 18.1 / 7 | 16.3 / 0 | 16.0 / 14 | 18.6 / 17 | 22.6 / 27 | 24.6 / 36 | 24.8 / 60 | ✓ |
| 22.4 / 72 | 17.7 / 61 | 16.5 / 36 | 17.3 / 26 | 15.9 / 16 | 15.7 / 0 | 15.9 / 3 | 17.4 / 7 | 19.5 / 16 | 21.8 / 24 | 21.6 / 50 | ✓ |
| 37.1 / 70 | 16.8 / 38 | 15.7 / 19 | 16.6 / 16 | 15.3 / 11 | 15.2 / 0 | 15.9 / 10 | 15.4 / 24 | 16.4 / 39 | 18.8 / 40 | 20.4 / 61 | ✓ |

"A" line

Left - W. or N.  Right - S. or E.

42+65.89 P.C.

43+49.71 CC

| | | | |
|---|---|---|---|
| 6.53 | 24.82 | 3.59 | 19.29 |

44+20

+32 N. end bridge

+37

+82 - 4" C.I. water pipe - bottom 10' E. of ℄ conduit

45

+12 S. end bridge

| | | | |
|---|---|---|---|
| T.P. | 0.86 | 21.58 | 4.10 | 20.72 |

+13

+19

46

+39

47

+96

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 23.4 / 60 | 23.8 / 35 | 18.5 / 17 | 16.6 / 15 | 15.6 / 0 | 15.1 / 10 | 15.3 / 50 | 16.3 / 68 | 18.3 / 70 | 21.1 / 100 | | | ✓ |
| 30.0 / 59 | 29.5 / 37 | 23.7 / 30 | 20.4 / 22 | 19.0 / 13 | 16.4 / 13 | 14.8 / 0 | 13.5 / 8 | 15.8 / 38 | 14.6 / 40 | 13.6 / 50 | 14.6 / 62 | 21.9 / 100 | ✓ |
| 24.7 / 43 | 23.7 / 35 | 16.0 / 22 | 15.8 / 6 | 15.3 / 0 | 14.2 / 3 | 12.4 / 3 | 12.4 / 10 | 14.1 / 16 | 14.0 / 29 | 13.3 / 42 | 15.3 / 47 | 17.8 / 56 | 19.3 / 72 | 21.4 / 85 | ✓ |
| 23.5 / 40 | 22.7 / 12 | 19.5 / 0 | 16.1 / 6 | 12.2 / 6 | 13.3 / 18 | 12.5 / 33.5 | 21.7.8 / 35 | 21.4 / 70 | | | | | | | ✓ |
| 22.4 / 0 | | | | | | | | | | | | | | | ✓ |
| 18.15 | | | | | | | | | | | | | | | ✓ |
| 21.9 / 40 | 21.4 / 20 | 21.2 / 0 | 21.3 / 4 | 12.5 / 5 | 12.1 / 18 | 12.5 / 33.0 | 21.7 / 35 | 20.1 / 40 | 20.0 / 60 | | | | | | ✓ |
| 22.1 / 44 | 20.9 / 31 | 19.2 / 9 | 19.8 / 0 | 21.3 / 4 | 12.6 / 5.5 | 21.8 / 18 | 12.3 / 31 | 14.1 / 33 | 20.9 / 34.5 | 20.3 / 41 | 20.2 / 60 | | | | ✓ |
| 18.5 / 41 | 19.8 / 60 | | | | | | | | | | | | | | ✓ |
| 22.5 / 45 | 18.6 / 35 | 17.5 / 8 | 15.4 / 0 | 12.1 / 9 | 11.6 / 26 | 15.2 / 40 | 17.2 / 40 | 17.4 / 55 | | | | | | | ✓ |
| 19.2 / 45 | 15.4 / 35 | 14.2 / 3 | 13.4 / 0 | 12.9 / 7 | 12.4 / 10 | 10.6 / 25 | 13.3 / 30 | 13.8 / 40 | | | | | | | ✓ |
| 19.3 / 40 | 18.5 / 32 | 14.0 / 17 | 13.6 / 7 | 12.7 / 0 | 10.9 / 8 | 10.5 / 24 | 12.9 / 30 | 12.9 / 40 | | | | | | | ✓ |
| 18.1 / 41 | 16.8 / 28 | 16.2 / 16 | 14.7 / 13 | 12.4 / 0 | 12.4 / 5 | 10.0 / 8 | 10.4 / 27 | 11.9 / 35 | 12.2 / 40 | | | | | | ✓ |
| 14.9 / 40 | 13.4 / 27 | 11.8 / 22 | 11.1 / 10 | 9.6 / 0 | 8.8 / 3 | 8.8 / 15 | 11.4 / 25 | 13.3 / 32 | 13.3 / 40 | | | | | | ✓ |

21.58

| | | | | |
|---|---|---|---|---|
| TP | 2.21 | 16.87 | 6.92 | 14.66 |
| | | | 2.92 | 13.95 ✓ 13.95 BM |

48+12 $\frac{5.6}{}$ = N. end bridge

+62.65 4" Kalamein pipe - bottom

+93 $\frac{6.5}{}$ So " "

49 + 04

+38

50

| | | | | |
|---|---|---|---|---|
| TP | 5.45 | 12.67 | 9.65 | 7.22 |

51

52

+20

+34 $\frac{29.0}{}$ Ctr 'L' St

+38 $\frac{30.0}{}$

+43 $\frac{1.0}{}$

+51

"A" line

Left = West No. Right = East or S.

15.4 = Top bridge

$\frac{14.5}{40}$ $\frac{14.3}{28}$ $\frac{14.4}{17}$ $\frac{13.9}{15}$ $\frac{9.7}{5}$ $\frac{9.7}{0}$ $\frac{8.6}{2}$ $\frac{8.3}{12.5}$ $\frac{14.6}{14}$ $\frac{15.1}{20}$ $\frac{14.2}{40}$ ✓

12.14

14.9 = Top bridge

$\frac{13.8}{40}$ $\frac{14.1}{15}$ $\frac{10.6}{14}$ $\frac{9.3}{10}$ $\frac{8.6}{5}$ $\frac{8.6}{0}$ $\frac{7.7}{2}$ $\frac{7.5}{10}$ $\frac{9.2}{14}$ $\frac{13.7}{15}$ $\frac{12.7}{23}$ $\frac{13.1}{40}$ ✓

$\frac{13.9}{40}$ $\frac{14.1}{28}$ $\frac{12.5}{17}$ $\frac{9.2}{8}$ $\frac{7.8}{0}$ $\frac{7.3}{9}$ $\frac{9.8}{15}$ $\frac{10.8}{30}$ $\frac{11.0}{40}$ ✓

$\frac{11.7}{40}$ $\frac{10.4}{20}$ $\frac{9.9}{11}$ $\frac{8.9}{5}$ $\frac{8.7}{2}$ $\frac{7.4}{1}$ $\frac{7.3}{0}$ $\frac{7.5}{8}$ $\frac{9.9}{18}$ $\frac{9.5}{29}$ $\frac{9.9}{40}$ ✓

$\frac{10.6}{40}$ $\frac{9.0}{26}$ $\frac{8.5}{6}$ $\frac{7.7}{0}$ $\frac{7.1}{3}$ $\frac{7.0}{12}$ $\frac{9.0}{19}$ $\frac{9.2}{32}$ $\frac{9.5}{40}$ ✓

POSTED

$\frac{13.0}{40}$ $\frac{8.3}{27}$ $\frac{7.9}{9}$ $\frac{6.6}{0}$ $\frac{6.5}{11}$ $\frac{8.6}{24}$ $\frac{8.7}{40}$ ✓

$\frac{6.7}{40}$ $\frac{5.9}{22}$ $\frac{6.0}{12}$ $\frac{7.5}{0}$ $\frac{7.8}{18}$ $\frac{8.2}{40}$ ✓

$\frac{6.6}{40}$ $\frac{5.7}{28}$ $\frac{6.3}{0}$ $\frac{6.4}{20}$ $\frac{6.9}{40}$ ✓

$\frac{7.7}{50}$ $\frac{7.3}{40}$ $\frac{6.9}{31}$ $\frac{5.9}{8}$ $\frac{6.7}{0}$ $\frac{8.3}{16}$ $\frac{8.5}{40}$ ✓

$\frac{10.5}{60}$ $\frac{10.45}{46}$ Top rail $\frac{7.3}{44}$ $\frac{6.0}{34}$ $\frac{5.9}{27}$ $\frac{5.1}{14}$ $\frac{6.7}{7}$ $\frac{10.5}{5}$ Top rail $\frac{10.53}{0}$ = Top rail

$\frac{10.62}{40}$ = Top rail - 40 ft ✓

$\frac{10.5}{60}$ $\frac{10.45}{46}$ Top rail $\frac{7.3}{44}$ $\frac{6.0}{34}$ $\frac{5.9}{27}$ $\frac{5.1}{14}$ $\frac{6.7}{7}$ $\frac{10.5}{5}$ Top rail $\frac{10.53}{0}$ $\frac{10.62}{40}$ Top rail ✓

$\frac{9.3}{70}$ $\frac{8.0}{54}$ $\frac{6.5}{39}$ $\frac{5.7}{24}$ $\frac{6.6}{4}$ $\frac{6.8}{30}$ $\frac{7.0}{40}$ ✓

12.67

53

54

TP 7.21 11.35 8.53 4.14

55+00 59. P.C.

+34 62 = C.C.

+58 64 = P.T.

+77 X section taken parallel to "N" 54 51°0'

+81 18 N. end bridge - X sect taken along end bridge △51°
53+69.24 = 2" W.I. gaspipe - top
56+37.18 = N. rail car track
+43 48 30 " " " } "N" 54

+83 24 S. end bridge X sect. taken along end bridge △51°

TP 6.76 8.92 9.19 2.16

+83 24 X Sect. taken along end of bridge

57

+50

58

TP 4.25 6.92 6.21 2.71

"A" line

Left W Right E

9.1/40 8.2/19 4.3/16 5.5/0 6.2/27 7.8/33 8.3/40 ✓

7.8/66 6.1/40 4.9/19 4.4/0 4.2/7 6.3/28 6.7/40 ✓

5.3/53 4.8/30 3.2/12 3.5/0 5.9/14 8.4/40 ✓

4.7/64 4.1/25 1.8/23 3.1/19 3.2/0 5.3/12 6.1/34 6.2/47 ✓

5.6/70 4.1/19 2.0/16 2.7/0 7.6/18 6.6/55 ✓

4.7/66 4.2/40 3.8/12 1.6/0 ✓

6.9 = Top bridge

6.3/53 7.1/21 3.7/20 1.7/0 4.4/12 6.9/13 6.3/46 6.7/70. ✓
+.48
7.02 ✓

7.01 ✓

7.0 = Top bridge

5.0/53 5.1/35 7.0 2.3/22 2.3/0 1.7/22 2.3/30 7.1/32 6.9/57 ✓

5.0/53 5.0/35 4.9/3 2.3/2 2.3/0 1.7/22 2.3/30 6.0/35 6.9/57 ✓

4.9/17 4.4/2 3.6/0 1.9/5 1.5/23 3.6/34 6.5/36 5.5/55 5.5/64 ✓

4.5/50 3.3/15 2.1/6. 1.3/0 1.7/19 4.5/33 4.3/60 ✓

3.8/50 3.6/16 0.9/0 2.4/10 3.9/25 3.8/50 ✓

"A" line

Left W  Right E

58+50

59+11.70 = B.C.

+49.33 = C.C

+79.27 = E.C.

60

T.P  3.92  6.51  7.37  2.59

+69.41 = N. rail S.O. & E

+74.20 S.  "  "

+84.63 = N.  "  C.B.L

+89.61 S.  "  "  "

61

62

+54.37 = N. rail N.C.& O.

+61.62 = C.L.  "  "  "

+68.17 = S.  rail N.C.& O.

T.P  2.27  3.67  5.11  1.40

+8.3

POSTED

141
3.67

63

+29

+36

+70 47. P.C

+85. Top bulkhead

+85

+89

+92

64 +05 05. CC

+39 34. EC

65

66

67 +08

68

TP 1.99 2.35 3.31 0.36 Nail in bulkhead

69

A line

Left - W Right - E

-0.2 -0.7 -0.6 2.7 2.2 -3.4 -2.5 -6.6 -6.7 0.7 ✓
70 42 0 11 29 39 63 68 70 100

-0.6 0.2 2.5 1.8 -3.0 -3.4 -0.8 -0.6 -0.9 ✓
0 17 28 44 50 68 72 74 100

-0.2 0.2 2.3 2.3 -0.4 -3.0 -3.7 -0.9 -0.7 -0.8 -0.9 ✓
0 27 33 38 38 50 67 72 74 74 100

0.3 0.5 -0.3 1.4 Top bulkhead -2.7 -3.5 -1.1 1.4 Top bhd -1.5 -1.4 ✓
80 80 0 11 15 41 46 47 57 61

1.5 ✓
-0.2 ✓
-0.5 ✓
-2.5 ✓

Top bhd -1.4 -0.3 -2.9 -3.3 -3.3 -1.8 1.4 Top bhd ✓
9.5 9.5 4 0 17 23 23

Top bhd. 1.4 -0.5 -0.8 -3.3 -3.6 -3.2 -0.5 0.0 1.4 Top bhd ✓
14.7 14.7 12 10 0 9 12 14.7 14.7

bhd. 1.4 -0.8 -1.1 -4.0 -4.4 -4.1 -3.7 -0.9 -0.5 1.4 bhd ✓
14.7 14.7 13 10 0 2 9 13 14.7 14.7

bhd. 1.3 -0.8 -1.2 -4.1 -4.3 -3.9 -2.0 -1.5 1.3 bhd ✓
14.7 14.7 13 10 0 10 13 14.7 14.7

1.3 bhd. -4.3 13 bhd -4.3 -5.0 -4.4 1.3 bhd -4.4 1.3 bhd ✓
21 21 14.7 14.7 0 14.7 14.7 21 21

bhd -1.3 -4.6 -4.9 -4.7 1.3 bhd ✓
21 21 0 21 21

1.3 bhd -5.2 -5.6 -1.6 -5.7 -5.0 ✓
21 21 10 0 1 21

2.85

70

71

72

+13.33 No rail

+18 21 Sc "

73

6.94 -4.59 3pk in Sc. pile 18th bent from W end of bridge

A line

Left

Right

1.3 / 21 Rip Bulkhead -5.2 / 21

-5.9 / 0 -6.8 / 21 1.3 / 21 Bhd.

1.4 / -1 Bhd. -7.4 / 21 -6.4 / 8 -6.0 / 0 -6.3 / 21 -1.3 / 21 Bhd.

-7.2

1.90

1.91

-7.0

POSTED

Cross-Section of 15th St. Conduit "B" line

26+57.2° "A" line = 26+57.2° "B" line

0.79 43.63 42.845 Bm poly N.W. cor.

26+57.2°

27

+12

+60

+74

+74

+75 No. end bridge

28+17.62 No rail
+22.32 So. } So. Park & E. Side Ry.

+55 - So. end bridge

+55.5°

+62

+77

T.P. 6.58 39.89 10.32 33.31

29

+45

"B" line

53

Left West or No. Right So or E.

42.9/51 41.9/20 35.4/8 35.1/0 34.3/11 33.2/14 33.2/24 34.7/28

43.1/55 42.0/36 36.4/24 34.2/19 34.0/8 33.6/3 32.9/6 32.9/19 33.5/45 33.6/26 33.6/35

43.2/55 42.3/37 41.2/34 36.2/34 34.6/24 33.5/2 33.2/0

41.8/31 33.1/31 31.8/26 31.2/11 31.9/3 33.3/2 33.8/3 36.9/3 40.0/12 41.0/26 41.3/40

36.0

42.9

42.8/0 43.3/25

42.67

42.66

30.9/23 31.1/17 32.2/14 35.0/1 42.2/1 42.1/0 42.4/12 42.5/31

37.8

39.6/36 34.2/36 31.8/33 30.7/23 31.1/17 33.0/15 37.6/0 41.9/13 42.0/31

40.9/60 40.6/67 35.0/55 33.9/42 31.1/32 30.7/21 32.2/15 37.0/7 38.3/0 38.9/9 40.9/15 40.9/28 40.5/37

33.3/45 32.4/43 31.1/38 30.7/32 33.6/14 34.3/10 37.7/0 38.1/6 39.2/13 39.7/26

32.9/55 32.1/43 30.5/39 30.9/24 35.7/14 37.1/6 38.9/10 39.4/25

POSTED

| | | | | | | |
|---|---|---|---|---|---|---|
| | | | | | | |
| | | | | | | |
| | | | | | | |

N.1
34.47

+84 32 - N. rail - N. track
+99 32 - S. " - S. " } S.D.E.Ry Co.

36+43 97 - S. line 'H' 54.

37

| | | | | |
|---|---|---|---|---|
| T.P. | 2.14 | 29.00 | 7.61 | 26.86 |

+87

38+05

39

40

+23 42 - S.L. 'I' 54.

+34

41

+73

+80

'B' line



Left: W. or N. Right: S. or E.

29.80

29.77

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| 29.7 / 55 | 29.5 / 41 ck | 27.1 / 41 | 29.5 / 15 | 29.0 / 0 | 28.7 / 11 | 29.1 / 11 ck | 28.9 / 25 |
| | 26.2 / 55 | 26.9 / 23 | 27.6 / 0 | 27.7 / 9 | 28.4 / 25 | | |
| 24.9 / 55 | 25.3 / 40 | 26.1 / 17 | 26.9 / 0 | 26.7 / 11 | 27.2 / 25 | | |
| 27.3 / 55 | 27.5 / 43 | 26.6 / 38 | 26.9 / 20 | 27.2 / 0 | 26.7 / 11 | 27.3 / 11 ck | 27.5 / 26 |
| 26.0 / 55 | 25.6 / 40 | 25.8 / 15 | 26.7 / 0 | 25.6 / 11 | 26.0 / 11 ck | 26.3 / 25 | |
| 25.0 / 55 | 25.5 / 20 | 25.2 / 0 | 23.8 / 10 | 26.0 / 26 | | | |
| 25.7 / 55 | 26.0 / 41 ck | 24.0 / 41 | 24.4 / 20 | 24.7 / 0 | 25.0 / 11 ck | 26.2 / 25 | |
| 22.4 / 55 | 23.0 / 43 | 23.7 / 37 | 23.5 / 32 | 24.2 / 16 | 24.6 / 0 | 24.1 / 9 | 24.8 / 10 | 25.1 / 26 |
| | 21.4 / 55 | 21.4 / 35 | 21.2 / 17 | 21.8 / 0 | 22.4 / 6 | 22.7 / 12 | 24.2 / 25 |
| | | | | 20.8 / 0 | 21.0 / 8 | 23.1 / 13 | 23.6 / 25 |
| | | | | 20.7 / 0 | 20.6 / 9 | 21.2 / 17 | 21.5 / 25 |

| | | | | |
|---|---|---|---|---|
| | | N.T. 29.00 | | |
| +2 | | | | |
| TP | 1.73 | 23.69 | 7.06 | 21.94 ~ 21.96 BM. |
| +3 | | | | |
| +23 [illegible] No line "J" St | | | | |
| +26 | | | | |
| +4 | | | | |
| +46 | | | | |
| +5 | | | | |
| +6 | | | | |
| +7 | | | | |
| +8 | | | | |
| T 85 | | | | |
| T 69 | | | | |
| +83 [illegible] St. "K" St. | | | | |
| +90 | | | | |

"B" line

56

Left - W or No  Right - So or E

| | | | | | |
|---|---|---|---|---|---|
| 20.2 / 55 | 20.6 / 22 | 20.5 / 0 | 20.4 / 14 | 20.6 / 25 | ✓ |
| 19.7 / 55 | 20.1 / 17 | 20.3 / 0 | 20.5 / 12 | 21.0 / 25 | ✓ |
| 20.3 / 55 | 20.4 / 43 | 21.2 / 23 | 21.5 / 0 | 21.7 / 12 | 21.9 / 25 | ✓ |
| 22.2 / 55 | 21.1 / 35 | 21.7 / 29 | 21.6 / 0 | 22.2 / 25 | ✓ |
| 21.2 / 55 | 21.1 / 41 | 20.4 / 41 | 20.5 / 20 | 20.8 / 0 | 21.2 / 25 | ✓ |
| 18.0 / 55 | 18.1 / 36 | 19.6 / 23 | 20.5 / 0 | 21.7 / 25 | ✓ |
| 17.4 / 55 | 17.7 / 42 | 19.6 / 26 | 21.1 / 13 | 21.2 / 0 | 22.0 / 25 | ✓ |
| 16.1 / 55 | 16.5 / 31 | 19.3 / 14 | 19.6 / 0 | 20.4 / 10 | 21.1 / 25 | ✓ |
| 16.5 / 55 | 16.4 / 41 | 16.2 / 30 | 17.3 / 16 | 17.6 / 0 | 17.8 / 10 | 18.5 / 25 | ✓ |
| 16.7 / 55 | 16.4 / 20 | 17.0 / 0 | 17.2 / 11 | 17.5 / 25 | ✓ |
| 16.7 / 55 | 17.2 / 0 | 18.6 / 25 | ✓ |
| 15.9 / 55 | 17.0 / 0 | 17.7 / 25 | ✓ |
| 16.7 / 55 | 16.5 / 41 | 16.1 / 41 | 17.2 / 0 | 18.0 / 11 | 18.3 / 25 | ✓ |
| 15.5 / 55 | 16.6 / 20 | 17.2 / 0 | 17.9 / 11 | 19.3 / 25 | ✓ |

POSTED

"B" line

Left: W or N. Right: E or N.

28.69

| | | | | |
|---|---|---|---|---|
| TP | 2.75 | 20.30 | 6.14 | 17.55 |
| 48 | | | | |
| +85 | | | | |
| 49+20 | | | | |
| 50 | | | | |
| +80 | | | | |
| +85 | | | | |
| 51 | | | | |
| +10 | | | | |
| +45 | | | | |
| 52 | | | | |
| TP | 3.15 | 12.36 | 11.09 | 9.21 |
| 53 | | | | |
| 54 | | | | |

| | | | | | | |
|---|---|---|---|---|---|---|
| 15.3 / 55 | 15.9 / 40 | 16.9 / 16 | 18.1 / 0 | 18.7 / 11 | 20.0 / 25 | ✓ |
| 14.3 / 55 | 14.9 / 43 | 15.5 / 26 | 16.9 / 0 | 17.9 / 25 | | ✓ |
| 14.4 / 55 | 15.7 / 27 | 17.7 / 11 | 18.3 / 0 | 19.3 / 15 | 19.7 / 25 | ✓ |
| 12.5 / 55 | 13.3 / 40 | 14.0 / 9 | 16.2 / 0 | 18.3 / 25 | | ✓ |
| 14.3 / 55 | 13.5 / 40 | 13.9 / 20 | 15.2 / 0 | 15.8 / 11 | 17.1 / 25 | ✓ |
| 14.1 / 55 | 14.3 / 30 | 14.0 / 17 | 14.8 / 0 | | | ✓ |
| 13.8 / 55 | 14.4 / 14.0 | 15.0 / 0 | 15.8 / 25 | | | ✓ |
| 13.5 / 55 | 14.7 / 20 | 15.6 / 0 | 16.2 / 25 | | | ✓ |
| 13.5 / 55 | 13.5 / 23 | 14.2 / 0 | 14.3 / 25 | | | ✓ |
| 10.2 / 55 | 9.7 / 53 | 9.3 / 40 | 10.9 / 17 | 11.2 / 0 | 11.9 / 21 | 12.7 / 25 | ✓ |
| 7.8 / 55 | 7.7 / 26 | 8.4 / 20 | 9.0 / 0 | 10.0 / 15 | 10.3 / 25 | | ✓ |
| 6.5 / 55 | 6.6 / 0 | 7.0 / 13 | 7.7 / 25 | | | | ✓ |

HI
12.36

+60

+66

T.P. 2.43 8.64 6.15 6.21

55

+01.11 N. rail } S.D.E.R.Y
+05.1 - 50 }

+28

+44

+51

56

57

+47

+58

T.P 4.85 11.09 2.40 6.24

58+07 47 P.C

+52 ℄ N. rail siding 50 CCE station tangent X sect at right angles to ton.

"B" line

Left W. of N. Right - So or E.

6.3/55 6.7/26 7.1/0 7.4/9 8.2/16 8.7/25 ✓

8.3/55 77/40 8.5/18 77/0 73/5 8.5/11 8.7/25 ✓

8.1/55 8.1/0 8.2/25 ✓

8.17 ~

8.17 ✓

7.2/55 7.1/44 7.9/14 7.4/0 6.8/12 7.2/25 ✓

8.1/55 7.8/48 7.2/31 7.5/8 6.5/0 6.2/7 7.8/12 8.1/25 ✓

4.2/55 4.5/30 5.4/0 4.8/25 ✓

3.6/55 4.0/0 4.1/25 ✓

3.0/55 2.9/21 3.4/0 3.6/25 ✓

3.8/55 2.6/24 2.9/19 3.7/0 3.8/18 3.4/21 3.6/25 ✓

4.0/55 2.6/34 3.0/15 5.0/9 5.7/0 5.1/20 4.0/25 ✓

3.9/55 3.4/37 2.6/20 2.8/20 5.4/10 5.7/0 5.7/25 ✓

3.5/55 4.6/19 5.7/0 Top rail on tan. 6.4/25 Top rail

N1
1609

58+66 - Sta. on tan. X sect. at right angles to tan.

+71 " " " " " "

+73 Lt. Top No rail S.D.C.T.E. Sta on tan.

+76.5 Lt. Ctr. Track S.D.C.T.E. Sta on tan. X sect at right angles to tan

+81 " " " " " "

+90.5 Ctr Track C.B.L. " " " " "

+93.2 Top So rail C.B.L. on Tan.

+95 Sta on tan X sect at right angles to tan.

59+07.1 P.I. X sect. taken at right angles to No. R.S. Tan.

+07+1. P.C. X sect taken to hit center of Curve

59+64.50 E.C.

60

T.P 2.44 8.27 5.26 5.88

"B" 1,172

Left - W or No. Right - E or So.

1.7 / 10 — 3.3 / 5.5 — 4.6 / 31 — 5.8 / 0 Tan — 6.5 / 25

5.7 / 100 — 6.0 / 50 — 6.3 / 32 — 6.4 / 0 — 6.5 / 25

6.72 / 60 — 7.22 / 0

6.1 / 100 — 6.5 / 60 — 6.7 / 30 — 7.1 / 0 — 7.3 / 25

5.7 / 100 — 5.9 / 65 — 5.9 / 30 — 6.2 / 0 Tan — 6.3 / 25

6.1 / 100 — 6.4 / 65 — 6.6 / 30 — 7.1 / 0 — 7.3 / 25

6.62 / 60 — 7.34 / 0

5.3 / 100 — 6.1 / 55 — 6.4 / 30 — 6.8 / 0 Tan — 6.9 / 25

2.7 / 100 — 2.5 / 55 — 2.6 / 30 — 2.8 / 0 P.I. — 3.1 / 25

3.63 / 71 Sor rail S.M.P.G. — 3.8 / 41 — L.O. / 53 — 4.5 / +81 Top No rail S.D.C.T.E. — 6.5 / +1.38 C.L. Comp. Curve — 6.84 / +1.1 Top Sor rail S.D.C.T.E. — 5.9 / 35 — 7.03 / 27.2 Top No rail C.B.L. — 7.18 / 20.2 Top Sor rail C.B.L. — 2.8 / 0 P.I. — 2.5 / 2.5

6.31 / 29.6 Top So. rail S.D.C.T.E. — 5.5 / 23 — 6.1 / 17 — 6.37 / 14.7 Top So. rail C.B.L. — 5.3 / 13 — 2.2 / 6 — 2.2 / 0 — 2.5 / 17 — 2.1 / 40

6.03 / 29.9 Top So. rail S.D.C.T.E. — 5.2 / 25 — 5.8 / 18 — 6.0 / 15.3 Top So rail C.B.L. — 5.1 / 13 — 2.1 / 7 — 2.2 / 0 — 2.4 / 17 — 1.9 / 40

Ht.
8.37

61+12.9 - Δ

+93

+91

62

1P 2.23 5.50 5:00 3.27 4.66' Top 3.37 Bm

+70.46 Int with 18 line of North Ave

63 +10

+25 Sta on tan x Seat at right angles to tan

+40 " " " " " "

+6.1 68 - C.C. Sta on curve x Seat on radial line

+73 - Sta on tan - x Seat at R.A. to tan

+82

64+05.66 - P.T.

65

"B" line

Left - W or No Right - So or E

5.21' Tip Surveil SDCTE 4.1 / 26 — 4.9 / 19 — 5.13' Tip Surveil CBL 4.4 / 12 — 1.6 / 7 — 1.8 / 0 — 4.8 / 16 — 0.5 / 58 — 3.8 / 65 — 3.8 / 75 ✓

3.9 / 27 — 4.6 / 20 — 3.9 / 15 — 1.6 / 9 — 1.65 / 0 — 3.4 / 65 — 3.3 / 21 — 2.3 / 21 — 3.2 / 60 ✓

3.8 / 27 — 4.7 / 20 — 3.9 / 16 — 2.2 / 9 — 2.1 / 2 — 3.1 / 0 — 2.8 / 14 — 2.3 / 15 — 3.7 / 50 ✓

3.7 / 27 — 4.6 / 20 — 4.71' Tip Surveil CBL 4.0 / 17.6 — 2.7 / 14 — 2.7 / 11 — 2.4 / 0 — 3.2 / 8 — 4.0 ✓

4.34' Tip Surveil SDCTE 4.7 / 33.1 — 4.9 / 28 — 4.4' Tip Surveil CBL 3.1 / 21 — 2.5 / 18.6 — 3.0 / 0 — 3.1 / 15 — 1.1 / 29 — -0.5 / 35 — 6.2 ✓ ✓

4.22 / 33.7 — Tip Surveil SDCTE 4.3 / 28 — 4.13 / 11.9 — Tip Surveil CBL 3.4 / 0 — 2.0 / 13 — -0.7 / 36 — -0.7 / 66 ✓

3.9 / 28 — 3.8 / 21 — 3.3 / 13 — 0.2 / 0

3.9 / 26 — 3.8 / 21 — 3.1 / 17 — 0.3 / 10 — 0.1 / 0

4.2' Surveil SDCTE 4.0 / 49 — 4.0 / 32 — Tip Surveil CBL 3.8 / 29 — 1.2 / 10 — 0.4 / 0.CC. — -0.7 / 60 ✓✓

3.7 / 50 — 3.7 / 25 — 1.3 / 9 — 0.7 / 0 Tan — 0.0 / 20 — -0.7 / 40

3.7 / 64 — 2.9 / 45 — 0.1 / 32 — -0.7 / 26 — 0.8 / 14 — 0.4 / 0 Tan — -0.8 / 60

2.3 / 100 — 2.9 / 81 — 0.7 / 72 — 0.7 / 46 — -0.7 / 0 — -0.8 / 60 ✓✓

0.5 / 100 — -0.1 / 64 — 0.3 / 42 — -0.7 / 0 — -0.8 / 12 — -0.8 / 47 — 1.7 / 64 — 1.7 / 69 — -0.7 / 79 — -1.1 / 100 ✓

POSTED

M1
5.50

+43

+56

+67

66

TP 1.35 4.33 2.52 2.98 -3.0/100

+26

+25 3° built head Top

+35

+52

+59

+60 3° No rail N.C.70.

+65 3½ 30° + + + .

+61

+70

+76

B line

Left W or N. Right So or E

0.7/100 -0.5/50 -0.9/5 -0.4/0 2.0/11 2.0/18 -0.5/31 -0.8/47 -1.1/100 ✓✓

0.7/100 0.0/64 -0.7/19 1.7/3 1.9/0 2.0/3 -0.2/14 -0.7/29 -1.1/100 ✓✓

1.0/100 0.3/66 -0.3/31 1.5/20 1.7/12 -0.1/0 -0.6/18 -0.9/54 -1.1/100 ✓✓

-3.1/95 0.3/88 1.1/80 1.3/57 1.6/50 0.4/44 0.1/0 -0.4/40 -1.1/100 ✓✓

2.4/100 -3.2/83 -3.4/61 -2.5/20 -0.6/46 -1.2/0 -1.1/28 -1.1/100 ✓✓

2.93

-0.7/95 2.5/91 2.7/75 2.1/56 -3.4/40 -3.0/1 -2.3/0 -1.3/8 -0.9/10 -0.4/44 -1.0/100 ✓

0.6/— -0.3/76 2.7/57 2.6/39 1.4/16 -3.0/10 -3.6/0 -3.8/10 -0.8/14 -2.1/26 -0.8/67 -0.9/115 ✓

-0.5/100 -0.8/65 2.6/46 2.5/15 -0.7/14 -2.7/10 -3.5/0 -4.0/12 -0.2/16 0.8/18 1.6/29 1.3/54 0.7/79 0.7/100 ✓

2.56

2.94

-0.7/100 -0.5/71 -0.5/44 2.6/32 2.0/16 -1.0/14 -2.6/9 -3.2/0 -3.9/12 -1.7/16 2.5/17 2.5/61 2.4/100 ✓✓

-0.7/100 -0.7/88 0.0/37 1.3/16 Top blkd. -1.1/14 -2.7/9 -3.3/0 -4.0/12 -1.7/15 2.2/17 2.3/40 2.2/100 ✓

-0.5/100 -0.5/51 -0.7/21 1.3/147 Top blkd. -1.0/14.7 -2.5/11 -3.1/0 -3.9/11 -1.8/15 1.4/15 Top blkd. 2.5/29 2.3/77 2.3/100 ✓

"B" line

Left: W or No. Right: See E

-0.3 / 65 | 0.6 / 21 | -1.3 / 16 | 1.3 / 14.7 | -0.8 (Top of Hd.) / 14.7 | -2.6 / 11 | -3.3 / 0 | -3.6 / 11 | -1.8 / 14.7 | 1.4 / 14.7 | 0.8 (Top of Hd.) / 1.6 | -1.1 / 20 | -1.3 / 53 | -1.7 / 100 ✓

1.3 / 14.7 | -0.6 (Top of Hd.) / 14.7 | -2.7 / 11 | -3.3 / 0 | -3.5 / 11 | -1.7 / 14.7 | 1.3 / 14.7 | Top of Hd. ✓

1.3 / 14.7 | -0.4 (Top of Hd.) / 14.7 | -0.7 / 10 | -3.0 / 10 | -3.7 / 0 | -3.3 / 10 | -0.5 / 13 | -0.4 / 14.7 | 1.3 / 14.7 | Top of Hd ✓

433

+ P I

- -0.2 / 10

67

+43 67 - 64+06 81 on "A" line - PI of 10° R curve

# Cross - Section of 28th St. Conduit

7/30/08 { Davis, Donnan, Williams.

Left. W or N.

Right. E or S.

℄

| | | | | |
|---|---|---|---|---|
| | 5.37 | 69.29 | | 63.92-8M 2.67M |
| | 8.08 | 73.45 | 3.92 | 65.37 |
| | 11.84 | 83.61 | 1.68 | 71.77 |
| | 7.10 | 86.28 | 4.43 | 79.18 |
| 0+00 | | | | |
| +30 | | | | |
| 1 | | | | |
| +60 | | | | |
| 2 | | | | |
| +62 | | | | |
| +67 | | | | |
| +73 | | | | |
| +78 | | | | |
| 3 | | | | |
| | 3.60 | 82.78 | 7.10 | 79.18 |
| +50 | | | | |
| 4 | | | | |
| +64 | | | | |
| 5 | | | | |
| +60 | | | | |
| 6 | | | | |
| 7 | | | | |
| | 1.63 | 77.79 | 4.62 | 76.16 |
| 8 | | | | |
| +49 | | | | |

℄

141
77.79

+52

+66

+68

+89.5 Norail

+92 · Ctr. M St. Car Track

+94.5 · 50. rail

9. +17

+19

+32

+36

+77

10

+37

+75

11

2.31 72.55 7.65 70.24

+21

+97.5 PC

12 +47 Sta on tan. X sect at right angles to tan

+59 " " " " " " " "

+89.2 · Norail Sta on tan

+71.5 · Ctr Track } S.D.C&E Ry.

+74.6 · S. rail } Sta on tan

+78 " " " " " " " "

+83.95 · Norail C.B.L.

28th St line

64

Left. W or N. ℄ Right S. or E

73.4/50 73.6/25 73.7/0 74.0/30 74.3/60

73.2/50 73.0/27 73.7/0 73.8/25 73.9/50

72.2/50 72.6/25 72.5/0 72.8/25 72.6/50

73.18

72.7/50 73.1/0 73.5/50

73.21

71.3/50 71.7/18 71.7/0 72.0/32 71.9/50

72.4/50 72.8/0 73.2/50

72.4/50 72.7/0 73.2/50

72.0/50 71.1/28 71.0/0 71.6/24 70.0/50

71.2/50 70.0/35 70.0/25 70.4/0 71.5/26 71.8/50

70.0/50 69.6/39 69.9/13 71.1/0 72.1/15 71.4/41 71.5/50

69.2/50 69.0/22 69.2/0 69.7/18 71.1/72 70.5/60

68.4/50 68.6/26 69.0/17 68.9/0 69.9/50

69.5/50 68.8/32 69.7/0 70.0/20 70.9/60

69.3/50 69.1/37 70.2/0 70.6/20 70.4/50

68.4/50 69.5/38 69.0/22 69.0/0 69.4/20 69.7/50

66.0/100 66.4/77 67.0/62 68.0/28 68.3/0 69.2/30

65.3/100 65.9/37 66.3/0 66.9/30

Top rail = 66.98/100 67.24/50 67.38/30 67.55/0-Tan

66.9/100 67.7/50 67.4/0 67.6/30

Top rail = 67.02/100 67.26/50 67.51/0

67.0/100 66.7/90 66.5/32 66.6/0 66.9/30

Top rail = 67.52/100 67.79/50 68.11/0

POSTED

72.55

+86.45 Ctr Track } Sta on tan
+88.95 So. rail } C.B.L.
+92 " " "
+96.45 R.T. " " " X Sect at right angles to No. So. tan
+96.45 X Sect taken to hit Cen. of Curve 67.6/90 67.2/69 66.1/63 66.6/49 66.6/45 66.7/40.77 67.44/38.4
13+5.32 R.T.
14
15
16
2.82 68.80 6.57 65.98
17
+13
+16
+30
+55
+82
+83
+96
18
+55.85 = R.C.
19
+32
+36
TP 2.16 65.01 5.95 62.85 Hub P.R.

2nd St line

Left Wor No. Right So or E

67.5/100 67.6/50 68.0/0 Tan 68.0/30
Top rail = 67.62/100 67.92/50 68.17/0
66.6/100 66.9/50 67.4/6 67.7/30
64.5/100 64.8/87 65.2/93 65.3/17 66.0/0-RT. 66.4/20
67.8/34 67.39/31.05 Top Rail 66.4/2.5 Top Rail Sec 66.05/17.5 Top Rail 66.0/14 Top Rail 67.12/10.6 Top Rail 67.6/5 Top Rail C.B.L. 66.0/0-P.I.
67.02/22.5 Top Rail 66.6/2.0 67.2/16 67.4/10 67.22/7.5 Top Rail Sec 66.6/4 64.5/0 65.3/5 65.7/27 67.4/33 66.8/60
64.73/22.5 Top R. 66.3/18 67.1/10 67.37/7.5 Top R. 66.4/4 64.5/0 65.7/5 65.7/13 66.3/22 66.1/35 66.5/50
64.78/22.5 Top R. 65.3/17 66.7/10 66.87/7.0 Top R. 65.7/4 64.5/0 64.6/12 61.2/44
65.67/22.5 R. 64.6/17 66.0/10 66.25/7.5 R. 65.7/4 64.4/0 65.3/5 65.5/29 66.4/31 66.5/42
64.88/22.5 Top R. 64.9/17 65.4/10 65.64/7.5 R. 64.6/4 63.2/0 63.6/4 64.1/15 63.9/29 64.4/31 65.6/50
63.3/0 64.2/4 64.2/15 64.5/50
63.6/0 64.5/4 65.0/17 64.5/50
63.9/0 65.0/64.2 Ctr 65.25 Ctr/64.5 Center
Top rail 64.57/22.5 64.7/17 65.4/10 65.36/7.6 Top Rail 65.0/4 64.7/0 64.8/50
63.7/0 63.9/25 64.2/50
64.9/0 64.6/25 64.5/50
64.3/0 64.8/50
Top R. 64.30/22.5 63.4/17 65.0/10 65.15/7.5 Top R. 64.3/4 63.6/0 63.0/5 63.2/20 64.4/25 64.6/50
Top R. 64.06/22.5 63.2/17 64.4/10 64.73/7.5 R. 63.8/4 62.4/0 63.2/2.2 63.7/28 63.9/50
Top R. 64.285/22.8 63.7/18 64.2/9.5 64.45/7 R. 63.9/4 61.7/0 61.4/2 61.4/30 62.4/50
63.0/0 61.5/15 60.8/50
63.0/0 61.5/15 60.8/50

28th St line

Left Work

Right Street

20

+89.19 P.R.

21

22

+75 · E end bridge

+84

+90 W

23

+22.53 · R.T.

+55

24

25

26

27

28

29

+50

+83 · E end bridge

+97

30 +04 · W

+05.50

+16

+49

31

Daniel
Denman
Williams

61.37

| | | | | |
|---|---|---|---|---|
| +29 | 3.07 | 56.79 | 7.65 | 53.72 |
| +54 | | | | |
| +82 | | | | |
| +89 | | | | |
| 32 | | | | |
| +33 | | | | |
| +40 | | | | |
| 33 | | | | |
| +35 | | | | |
| +70 | | | | |
| +75 | | | | |
| 34 | | | | |
| +50 | | | | |
| 35 | | | | |
| | 2.49 | 53.34 | 5.94 | 50.85 |
| +62 | | | | |
| +68 | | | | |
| +78 18° PC. | | | | |
| +92 Sta on tan. X sect at right angles to tan. | | | | |
| 36 +11 30° RI. X sect. taken to hit Cen. of curve | | | | |
| +43 07° PT. | | | | |
| +55 | | | | |
| 37 | | | | |
| | 2.91 | 51.88 | 4.37 | 48.97 |
| +18 | | | | |

50.77 : R
36.9

Left Wall No

Right Soar E

50.0
100

537 0 | 537 8 | 532.6 23 | 530 28 | 49.6 32 | 49.0 37 | 49.2 45 | 50.1 51 ✓

53.5 0 | 52.6 12 | 50.5 37 | 49.7 42 | 48.3 44 | 49.6 50 | 49.5 100 ✓

52.5 0 | 52.1 9 | 51.0 41 | 49.6 57 | 48.8 64 | 47.6 66 | 48.5 68 | 49.2 100 ✓

52.9 0 | 52.5 5 | 53.5 15 | 53.9 24 | 53.8 42 | 50.7 53 | 49.0 67 | 48.0 68 | 48.1 72 ✓

Top R. 53.13 22.5 | 53.9 17 | 53.7 10 | 53.79 7.5 | Top R. 53.6 4 | 53.6 0 | 53.7 24 | 53.8 42 | 50.2 64 | 49.1 79 | 48.6 91 | 47.8 98 | 49.1 100 ✓ | 48.8 92 | 48.8 100

Top R. 53.61 22.5 | 53.9 17 | 53.0 10 | 53.16 7.5 | Top R. 52.8 4 | 52.6 0 | 51.9 30 | 48.9 46 | 48.1 100 | 46.1 120 ✓

52.6 0 | 51.4 32 | 48.4 46 | 47.4 52 | 47.6 100 | 46.2 125 ✓

52.6 0 | 51.9 15 | 48.2 30 | 46.8 31 | 46.7 65 | 46.8 100 | 45.6 116 ✓

52.6 0 | 51.6 16 | 48.5 27 | 46.9 28 | 44.9 50 | 46.6 100 | 48.7 109 | 46.8 110 ✓

Top R. 52.86 22.5 | 53.2 17 | 53.5 10 | 53.73 7.5 | Top R. 53.4 4 | 52.2 0 | 51.6 11 | 44.5 28 | 44.1 31 | 45.8 32 | 46.3 41 | 46.9 50 ✓

51.6 0 | 51.8 8 | 49.6 14 | 43.6 24 | 47.6 44 | 48.8 59 | 48.9 72 | 46.1 100 ✓

Top R. 51.01 22.5 | 51.2 17 | 51.5 10 | 51.68 7.5 | Top R. 50.8 4 | 50.7 0 | 50.6 8 | 44.0 23 | 48.0 36 | 43.7 41 | 44.7 45 | 44.3 61 | 45.3 84 | 47.1 98 | 52.0 112 ✓

49.5 0 | 49.3 8 | 48.0 18 | 46.2 29 | 44.3 31 | 42.4 36 | 42.1 48 | 42.7 53 | 46.3 58 | 51.0 68 | 50.8 78 ✓

48.4 0 | 45.6 27 | 43.7 28 | 43.3 35 | 42.5 105 | 50.8 115 | 50.7 92 | 50.3 80 ✓

49.1 0 | 47.9 6 | 46.0 22 | 44.1 23 | 43.3 35 | 50.5 42 | 50.5 47 | 50.1 55 | 49.0 64 | 49.7 64 | 50.5 58 ✓

48.1 0 | 46.8 16 | 44.1 19 | 44.7 25 | 42.0 25 | 50.2 42 | 50.2 45 | 50.0 48 | 50.1 61 | 50.15 50 ✓

Top R. 51.17 23.8 | 49.7 18 | 52.4 10 | 50.13 7.5 | Top R. 49.7 4 | 47.8 0 | 47.4 2 | 46.0 18 | 50.2 27 | 42.5 27 | 42.5 50 | 52.0 50 | 50.4 54 ✓

Top R. 53.88 36 | 49.6 30 | 50.2 21 | 50.25 15.9 | Top R. 49.9 14 | 46.9 6 | 46.7 0 | 45.0 8 | 48.8 7.5 | 49.2 2.95 | 42.4 2.95 | 42.5 44 | 52.0 44 | 50.0 70 ✓

49.6 33 | 50.1 25 | 50.39 Top R. 22.3 | 49.7 19 | 48.1 14 | 47.4 6 | 49.2 0 | 49.3 18 | 41.6 18 | 41.6 41 | 40.7 41 | 49.7 70 ✓

49.4 45 | 50.0 33 | 49.1 0 | 48.3 7.4 | 47.5 7.4 | 41.6 30.5 | 49.7 30.5 | 49.7 54 | 47.2 71 | 46.1 100 ✓

48.7

28th St line

Left = W or N.  Right S or E

+20
+32
+39
+46
+52
38
+15
+47
8.16  48.60  11.44  40.44
+57
+63
+66
39
+50
40
+39
+56
+65
+68
T.C.  9.70  51.04  7.26  41.34
+74.6 end of culvert - E
+75.83 end culvert - Ctr.
+77.06 " " W.
+84
+93

end wing wall - for
bottom of end wing wall
bottom culvert
top
top + bottom
top
bottom
top end wing wall

51.04

41

+09

+11

+42

+69

+71

+87

42+02.25 · End culvert - E.

+04.00 · " " C.

+06.75 · " " IX/

+11.40 · " Wingwall "

+17

+22

+34

+39

+61

+66

4.04 | 43.93 | 11.15 | 39.89

3.30 | 43.19 | 4.04 | 39.89

+75.14 · P.C.

+79 - Sta on tan.

+3+04 " " "

+32.65 - P.I. x Sect taken to but Cen. of Curve

+48 Sta on tan - x sect at right angles to tan

+67 " " " " " " " "

49.3 / 100

48.0 / 100 | 47.9 / 88

47.0 / 63

42.7 / 46

38.9 / 45

46.7 / 84

47.4 / 85

8 / 3 / 0 } Days Damaged Wt. Marks

28th St line

Left - W'll No. | Right - E or So.

47.9 / 100 | 47.7 / 87 | 44.3 / 57 | 43.6 / 31 | 49.9 / 13 | 49.9 / 0

49.7 / 0

48.8 / 0

48.5 / 84 | 49.2 / 81 | 49.2 / 58 | 48.4 / 51 | 48.9 / 25 | 49.5 / 0 | 49.0 / 4.2 | 49.7 / 4.4 | 50.1 / 7.1 | 37.9 / 11.1 | 44.1 / 14.9

48.5 / 0

49.2 / 0

49.4 | 48.5 / 125 | 47.7 / 122 | 48.5 / 100 | 49.0 / 73 | 46.2 / 28 | 49.0 / 25 | 49.2 / 0 | 38.6 / 39 | 36.1 / 75 | 35.5 / 100 | 36.3 / 123 | 40.8 / 135

34.43 · bottom culvert. | 39.58 · Top culvert. / 2

34.12 · Top / 34.60 bottom

39.60 · Top / 2 | 37.47 = bottom / 2 | 37.0 / 0 | 34.7 / 7 | 36.3 · Top end E wing wall / 7 | 35.1 / 11

36.4 · Top end wing wall / 2 | 33.8 / 2 | 33.9 / 0 | 34.2 / 8 | 33.9 / 18 | 35.5 / 19 | 35.2 / 34 | 36.3 / 3

37.7 / 15 | 34.0 / 13 | 33.4 / 0 | 33.1 / 2 | 35.1 / 23 | 34.4 / 31 | 36.1 / 39 | 37.5 / 56

48.6 | 49.0 / 41 | 41.3 / 38 | 38.8 / 28 | 36.7 / 17 | 34.1 / 10 | 33.1 / 0 | 33.5 / 26

49.0 / 65 | 41.9 / 40 | 37.7 / 26 | 35.7 / 9 | 33.0 / 0 | 32.5 / 10 | 32.6 / 28 | 34.7 / 48 | 36.8 / 49 | 40.0 / 70

34.7 / 0 | 34.4 / 14 | 32.4 / 16 | 33.2 / 25 | 33.0 / 26 | 33.6 / 36 | 36.2 / 52 | 37.9 / 53 | 39.7 / 68

47.9 / 61 | 40.1 / 36 | 34.6 / 19 | 34.1 / 0 | 32.1 / 3 | 31.9 / 12 | 33.7 / 13 | 34.9 / 30 | 41.0 / 70 | 42.6 / 71 | 43.5 / 80

34.2 / 19 | 34.0 / 3 | 31.8 / 0 | 31.7 / 6 | 34.0 / 13 | 35.1 / 30

POSTED

33.8 / 21 | 33.9 / 11 | 31.6 / 7 | 31.7 / 0 | 33.6 / 6 | 34.4 / 11 | 35.0 / 28

47.7 / 64 | 41.2 / 38 | 33.7 / 21 | 33.8 / 12 | 31.6 / 10 | 31.7 / 3 | 33.3 / 4 | 34.0 / 7 | 34.9 / 26 | 39.0 / 45 | 40.5 / 60

42.7 / 46 | 38.8 / 36 | 33.2 / 23 | 31.1 / 22 | 31.1 / 17 | 32.6 / 12 | 34.2 / 0 | 34.7 / 24 | 39.3 / 46 | 41.7 / 56 | 44.9 / 65

38.9 / 45 | 32.7 / 25 | 30.4 / 24 | 30.9 / 19 | 33.2 / 14 | 33.6 / 9.77+C.C. | 33.8 / 0 PI | 34.1 / 10 | 36.0 / 20 | 40.1 / 34 | 42.5 / 46

38.8 / 45 | 34.3 / 30 | 33.0 / 21 | 30.6 / 20 | 30.3 / 14 | 32.0 / 1 | 33.2 / 0 | 34.0 / 11 | 35.9 / 19 | 36.1 / 28 | 41.8 / 60

41.0 / 68 | 39.6 / 45 | 36.0 / 34 | 33.8 / 25 | 32.8 / 10 | 30.2 / 0 | 32.9 / 10 | 34.7 / 22 | 37.9 / 34 | 41.5 / 56

+3.19

+83 Sta on tan x sect at right angles to tan

+87 13 = P.I. 8.57 45.65 6.11 37.08

+88 74 = Top 6" Sewer pipe

44

+13

+14

+22

T29 8.79 45.87 6.57 37.08

+32

+47

+51

+55

+60

+67

+88

6.12 40.22 11.97 34.10

45

+18

+27

+40

+52

46

+43

+53

+54

28th St line

Left Wer No. 2 Right 6 or E

46.0 / 70 | 39.4 / 48 | 37.9 / 41 | 34.1 / 24 | 32.9 / 10 | 37.6 / 0 | 30.9 / 5 | 30.4 / 13 | 32.6 / 15 | 34.8 / 17 | 36.0 / 36 | 39.6 / 49 | 41.2 / 67

45.9 / 62 | 40.0 / 46 | 37.6 / 36 | 33.9 / 17 | 32.6 / 0 | 31.8 / 8 | 30.4 / 10 | 30.4 / 17 | 32.7 / 23 | 35.7 / 32 | 36.5 / 41 | 38.8 / 46 | 40.2 / 65

36.98

46.2 / 70 | 46.3 / 52 | 37.9 / 15 | 35.5 / 0 | 32.9 / 12 | 31.4 / 13 | 30.1 / 17 | 30.4 / 23 | 34.9 / 30 | 35.2 / 36 | 37.0 / 40 | 39.9 / 72

41.9 / 45.5

46.0 / 70 | 45.7 / 15 | 45.5 / 0 | 45.5 / 1 | 40.1 / 1 | 33.7 / 14 | 31.4 / 16 | 32.5 / 26 | 31.3 / 26 | 34.3 / 37 | 36.3 / 55 | 37.7 / 73

45.7 / 74 | 45.1 / 44 | 45.1 / 34 | 45.5 / 2.8 | 40.1 / 2.8 | 40.1 / 0

45.5 / 75 | 44.5 / 49 | 42.4 / 31 | 45.6 / 14

45.1 / 84 | 43.6 / 60 | 42.9 / 37 | 38.8 / 21 | 45.2 / 8 | 38.7 / 8 | 34.4 / 0 | 29.7 / 2 | 30.4 / 18 | 29.3 / 21 | 31.1 / 27 | 34.4 / 35 | 39.7 / 35 | 39.9 / 39 | 45.3 / 39 | 38.1 / 62 | 40.0 / 88 | 41.4 / 100

45.1 / 71 | 42.6 / 53 | 40.1 / 40 | 36.3 / 31 | 33.8 / 22 | 32.5 / 11 | 31.1 / 0

42.5 / 61 | 42.4 / 44 | 37.4 / 31 | 32.4 / 19 | 30.5 / 0 | 30.1 / 3 | 28.5 / 6 | 29.6 / 11 | 36.1 / 24 | 40.8 / 31 | 45.4 / 31 | 43.2 / 72 | 40.9 / 92 | 41.7 / 112

30.2 / 0 | 29.5 / 4 | 29.2 / 8 | 35.1 / 16 | 38.6 / 24 | 46.2 / 49

28.7 / 0

43.9 / 60 | 42.2 / 40 | 36.0 / 26 | 31.1 / 15 | 29.0 / 9 | 29.0 / 3 | 30.4 / 0 | 30.7 / 9 | 36.0 / 41 | 45.0 / 74 | 44.3 / 107

40.5 / 32 | 37.5 / 28 | 34.0 / 23 | 32.6 / 21 | 29.2 / 16 | 30.7 / 7 | 31.3 / 0

41.3 / 60 | 40.7 / 34 | 36.5 / 21 | 28.4 / 10 | 27.9 / 11 | 29.1 / 9 | 30.7 / 4 | 34.3 / 0 | 31.2 / 33 | 33.0 / 69 | 39.2 / 100

29.8 / 0

28.0 / 0

41.2 / 62 | 40.2 / 47 | 36.7 / 18 | 27.4 / 0 | 27.7 / 4 | 29.8 / 7 | 30.9 / 25 | 31.8 / 47 | 33.8 / 81 | 43.1 / 98 | 43.1 / 110

31.6 / 0

39.3 / 45 | 36.4 / 17 | 33.9 / 0 | 29.9 / 18 | 29.5 / 29 | 26.8 / 36 | 26.8 / 40 | 28.6 / 21 | 29.8 / 51 | 35.4 / 66 | 38.6 / 80 | 39.0 / 82 | 39.1 / 100

41.9 / 75 | 35.3 / 45 | 34.7 / 39 | 33.6 / 25 | 34.0 / 9 | 32.8 / 0 | 32.5 / 23 | 31.6 / 34 | 35.4 / 43 | 35.8 / 64 | 35.1 / 60 | 37.5 / 100

33.5 / 0

34.9 / 0

28th St line

Left: W.W. No. Right: Bridge E

40.22

+62

47+29

+34

+44

48

6.52 35.76 10.98 29.24

+35

+42

+61

+90

+95

49

+14

+15

+25

+30

+36

+43

+50

+77

50

+19

+28

+45.15 P.C.

7.62 31.49 11.89 23.87

28th St line

Left Wall N.

Right Side of E

POSTED

22.91

+ 32

+ 53

+ 91.98 P.C.

55+10 Sta on tan X sect taken at right angles to tan.

+46 " " " " " " " "

71.98 = PI X sect taken to hit Cen. of Curve

+71.98 " " at right angles to tan ahead.

56+16 Sta on tan X sect at right angles to tan.

+32 " " " " " " "

+26.82 - PT

+70

+78

57 PC 5.36 19.88 8.39 14.52

+73.22 PC.

58+07.59 C.C. X sect taken on radial line

+42.45 = PT

Elev. of bottom N. & H. see sketch P31.

" " S.H. Omitted.

+97

+98

59+25

+35

60. 7.81 21.22 6.47 13.41

+13 - Head culvert

2.02 14.54 8.70 12.625 12.52 8.97 16.7 N.

No rail - N. Track X sect taken along rail.

28th St line

Left W. or No. Right So. or E.

22.3 / 78 — 21.8 / 63 — 17.7 / 19 — 17.7 / 8 — 15.9 / 0 — 16.0 / 4 — 17.0 / 7 — 17.9 / 52 — 17.1 / 85 ✓

17.9 / 76 — 17.2 / 11 — 15.8 / 0 — 15.5 / 6 — 16.9 / 10 — 18.3 / 71 — 20.4 / 91 ✓

16.7 / 59 — 16.9 / 0 — 16.9 / 2 — 15.3 / 7 — 15.3 / 12 — 16.5 / 13 — 18.5 / 75 — 21.7 / 96 ✓

16.0 / 60 — 16.8 / 0 — 16.6 / 6 — 15.9 / 10 — 15.9 / 16 — 16.3 / 17 — 16.7 / 29 — 18.9 / 42 — 19.9 / 80 — 22.1 / 95 ✓

16.0 / 57 — 14.8 / 38 — 15.9 / 0 — 14.9 / 5 — 14.5 / 13 — 16.2 / 15 — 16.7 / 41 — 20.3 / 55 — 21.1 / 71 — 23.3 / 83 ✓

15.5 / 73 — 16.8 / 49 — 16.3 / 36 — 14.7 / 38 rec. — 14.7 / 15 — 15.7 / 10 — 15.7 / 0 P.I. — 16.3 / 19 — 15.8 / 45 — 20.7 / 60 ✓

16.7 / 0 P.I. — 15.5 / 21 — 15.9 / 44 — 16.1 / 67 ✓

14.6 / 0 — 15.5 / 5 — 14.0 / 20 — 15.9 / 45 — 15.3 / 57 ✓

16.0 / 60 — 15.5 / 11 — 14.3 / 10 — 13.7 / 4 — 14.3 / 0 — 15.0 / 4 — 16.3 / 10 — 16.6 / 11 — 19.6 / 60 ✓

16.0 / 60 — 15.5 / 17 — 14.9 / 10 — 14.4 / 7 — 13.1 / 6 — 13.3 / 0 — 14.2 / 2 — 15.8 / 10 — 17.7 / 11 — 18.0 / 60 ✓

13.7 / 0 — 15.3 / 10 — 17.5 / 11 — 18.0 / 60 ✓

12.9 / 0 — 14.4 / 7 — 14.5 / 60 ✓

14.6 / 60 — 14.5 / 10 — 14.9 / 9 — 13.4 / 4 — 12.7 / 3 — 12.3 / 0 — 13.5 / 2 — 14.0 / 4 — 14.7 / 14 — 13.9 / 60 ✓

15.5 / 45 — 14.9 / 20 — 14.2 / 10 — 14.0 / 7 — 12.5 / 3 — 11.7 / 1 — 11.0 / 0 — 11.4 / 1 — 13.0 / 2 — 14.5 / 6 — 13.8 / 60 ✓

17.4 / 30 — 16.2 / 15 — 15.0 / 10 — 11.0 / 5 — 12.1 / 00.0 — 13.7 / 4 — 14.6 / 5 — 13.2 / 60 ✓

17.5 / 60 — 15.4 / 11 — 15.2 / 9 — 11.9 / 7 — 11.1 / 5 — 11.0 / 0 — 12.0 / 4 — 14.8 / 6 — 15.4 / 8 — 13.7 / 45 ✓

8.01 ✓

20.5 / 30 — 19.5 / 30 — 15.5 / 13 — 15.0 / 9 — 11.9 / 8 — 10.7 / 0 — 10.9 / 4 — 12.4 / 4 — 13.9 / 8 — 12.7 / 45 ✓

20.5 / 60 — 19.5 / 30 — 19.5 / 13 — 15.5 / 12 — 16.0 / 9 — 11.9 / 6 — 10.2 / 0 ✓

19.2 / 60 — 18.7 / 12 — 14.7 / 14 — 14.2 / 8 — 10.9 / 7 — 10.3 / 6 — 10.4 / 0 ✓

19.0 / 59 — 18.6 / 43 — 15.3 / 32 — 13.5 / 8 — 10.9 / 7 — 10.1 / 0 ✓

20.5 / 60 — 20.4 / 70 — 16.0 / 57 — 14.2 / 25 — 12.2 / 5 — 10.6 / 0 — 9.6 / 2 — 9.5 / 8 — 8.9 / 13 — 10.2 / 18 — 10.2 / 27 — 12.8 / 32 — 13.0 / 45 ✓

20.0 / 90 — 19.8 / 78 — 15.7 / 64 — 14.8 / 34 — 12.9 / 14 — 11.9 / 0 — 11.0 / 3 — 10.3 / 7 — 9.4 / 8 — 9.4 / 18 — 11.9 / 18 — 13.2 / 22 — 12.6 / 40 ✓

11.11 / 40 — 11.53 / 0 — 12.00 / 40 ✓

1454

So rail of No track X sect taken along r

No " " 50 " " " "

50 " " " " " "

61+82 35 PC

+92 22 - C.C.

62+01 68 E.C.

+12 40 = 5 end culvert

+73

+76 2 PC No x sect.

+81 + 5 sta on tan X sect at right angles to tan

+88 " " " " " " " "

+96 " " " " " " " "

63+13 " " 4.70 " 12.44 6.80 " " 7.74

+16 " " " " " " " "

+26 28 PI X sect taken to hit Con of curve

+62 5 sta on tan

+73 " " "

+55 24 = E.C. 5 sta on curve.

6.4

+48 28 P.C

+66 27 - C.C.

+83 57 = P.T

4.32 8.17 8.59 3.85

+98 29 - PC

28th 54 line 5 10 08 { Davis Dannan Williams Dangs

Left W.C. No Right 50 or E

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | | 11.04 / 40 | | 11.57 / 0 | | 11.92 / 40 | | ✓ |
| | | | | 10.99 / 40 | | 11.37 / 0 | | 11.73 / 40 | | ✓ |
| | | | | 10.94 / 40 | | 11.28 / 0 | | 11.68 / 40 | | ✓ |
| | | 10.3 / 40 | 8.8 / 12 | 9.5 / 12 | | 9.3 / 0 | | 9.3 / 38 | | ✓ |
| | | 9.6 / 40 | 8.5 / 2 | 9.1 / 2 | | 9.0 / 0 | | 9.4 / 31 | | ✓ |
| | | | 8.6 / 35 | 8.8 / 16 | | 8.4 / 0 | | 9.6 / 30 | | ✓ |
| | | 8.2 / 25 | 8.2 / 11 | 8.7 / 11 | | 5.3 / 0 | 5.3 / 1 | 8.1 / 1 | 9.4 / 30 | ✓ |
| | 6.4 / 53 | 6.6 / 42 | 8.3 / 33 | 8.0 / 12 | 8.0 / 12 | 8.1 / 7 | 5.6 / 0 | 6.5 / 4 | 7.1 / 4 | 6.8 / 40 | ✓ |
| | 6.8 / 52 | 6.4 / 41 | 7.6 / 34 | 7.8 / 31.5 | 7.6 / 33 | 8.0 / 9 | 5.5 / 0 | 6.5 / 4.5 | 7.1 / 4.5 | 6.6 / 40 | ✓ |
| 6.3 / 37 | 6.2 / 42 | 6.3 / 32 | 6.4 / 32 | 8.0 / 10.5 | 7.5 / 10 | 8.5 / 10 | 8.7 / 4 | 5.3 / 0 | 6.3 / 5.5 | 6.8 / 5.5 | 6.5 / 40 | ✓ |
| 6.7 / 61 | 6.4 / 42 | 6.8 / 43 | 6.9 / 37 | 8.0 / 30 | 7.7 / 30 | 7.5 / 11 | 5.3 / 0 | | | | | ✓ |
| | | | | | | | 4.9 / 0 | 6.2 / 6.5 | 6.5 / 6.5 | 6.7 / 40 | | ✓ |
| | | | | | | | 4.9 / 0 | | | 5.3 / 40 | | ✓ |
| 6.3 / 52 | 6.0 / 46 | 6.2 / 42 | 7.7 / 40 | | 7.0 / 20.7 sc | 6.5 / 11 | 5.0 / 0 PI | | | | | ✓ |
| | | | | | | | 6.7 / 0 | | | | | ✓ |
| | | | | 6.5 / 40 | 6.4 / 10 | 3.6 / 10 | 3.4 / 0 | | | | | ✓ |
| | | | | 6.1 / 40 | 6.2 / 8 | 4.3 / 7 | 3.6 / 0 | 3.6 / 4 | 5.7 / 10 | 5.6 / 50 | | ✓ |
| | | | | 4.8 / 37 | 4.6 / 6 | 3.2 / 3 | 3.0 / 0 | 3.3 / 2 | 4.2 / 4 | 5.0 / 9 | 4.4 / 55 | ✓ |
| | | | | | 4.4 / 50 | 4.4 / 7 | 3.5 / 0 | 2.9 / 2 | 2.9 / 5 | 4.0 / 8 | 3.5 / 55 | ✓ |
| | | | | | 3.7 / 50 | | 4.2 / 0 | 3.0 / 3 | 3.0 / 9 | 4.0 / 12 | 3.5 / 50 | ✓ |
| | | | | | 3.3 / 50 | 3.8 / 4 | 5.1 / 0 | 5.1 / 1 | 3.4 / 1 | 3.0 / 8 | 3.5 / 50 | ✓ |
| | | | | | | | | | | | | ✓ |
| | | | | | 3.3 / 50 | 3.6 / 5 | 4.4 / 1 | 3.0 / 1 | 3.0 / 0 | 3.1 / 3 | 3.5 / 7 | 3.5 / 50 | ✓ |

8.17

65+28.45 = O.C.

+67.82 P.T.

66+08.38 P.C.

+47.16 C.C.

+86.94 P.T.

67+36.84 - P.T. on B line = Sta 59+64.50

6.12 13.25 1.04 7.13

7.4 12.51 E 12.52 E

28th St Line

Left-West N. Right-South E

| | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | 3.3 / 50 | 3.3 / 0 | 3.3 / 2 | 4.3 / 5 | 3.6 / 9 | 3.0 / 14 | 3.2 / 25 | 4.7 / 30 | 3.2 / 50 ✓ |
| | | 2.8 / 55 | 3.1 / 45 | 3.0 / 22 | 3.6 / 20 | 2.6 / 0 | 2.8 / 2 | 4.2 / 5 | 3.4 / 6 | 3.3 / 35 | 3.3 / 50 | | ✓ |
| W | 2.6 / 56 | 3.8 / 47 | 2.8 / 41 | 2.9 / 14 | 3.1 / 7 | 2.7 / 0 | 2.8 / 4 | 3.5 / 8 | 2.9 / 11 | 3.2 / 50 | E | | ✓ |
| SW. | | 2.4 / 56 | 3.6 / 47 | 2.8 / 40 | 2.4 / 15 | 2.8 / 0 | 2.7 / 2.0 | 2.0 / 39 | 2.46 Rail / 39.9 | 2.3 / 56 | N.E | | ✓ ✓ |
| No | | 6.3 / 26 | 6.71 Rail / 15.3 | 6.2 / 13 | 2.8 / 5 | 2.8 / 0 | 2.4 / 4 | 3.4 / 36 | 2.8 / 41 | 2.8 / 60 | So | | ✓ |
| | 6.02 / 29.9 | 5.6 / 25 | 5.8 / 18 | 6.0 Top Rail / 15.3 | 5.1 / 12 | 3.1 / 7 | 2.2 / 0 | 2.5 / 17 | 1.9 / 40 | | 30 | | ✓ |

Cross-Section of "5" line from 61+92.5 to 64+67-28 ft

0+00-61+92.5-28 ft Min 0.78 13.30 12.0-2

+53 Ch. Gutr.

+63

+67

1

2

+102 = 64+67-28 ft. Line

X/o 5o

9.6 / 25 — 8.5 / 0 — 9.0 / 1 — 8.5 / 25 ✓

7.6 Gutr / 8.2 Ch / 25 — 7.4 Gutr / 8.0 Ch / 0 — 7.3 Gutr / 7.9 Ch / 8 — 8.3 / 9 — 8.2 / 25 ✓

8.4 / 25 — 8.2 / 0 — 8.1 / 7 — 8.7 / 15 — 8.1 / 25 ✓

6.3 / 25 — 6.5 / 0 — 6.5 / 7 — 8.5 / 7 — 8.1 / 25 ✓

5.7 / 25 — 5.7 / 0 — 5.7 / 7 — 6.5 / 7 — 6.7 / 25 ✓

3.8 / 25 — 3.5 / 0 — 3.8 / 9 — 2.9 / 11 — 3.1 / 16 — 4.0 / 19 — 4.2 / 25 ✓

3.6 / 25 — 4.0 / 5 — 4.0 / 6 — 2.9 / 8 — 3.0 / 12 — 3.1 / 16 — 3.7 / 25 ✓


G 54
PC 31+01.24
PT. 32+39.66
52°57'
77.65'
PC 33+17.31
PC
PT. 34+24.25
10.0'K
PT
R 150'
T 56.08
L 107.34
E 10.14
Δ 41°00'
H 54
PC 36+32.34
3828.77 old mt.
R 150'
T. 74.71
L. 138.62
E 17.57
Δ 52°57'

Change in alignment of Switzer Creek Conduit.



depth trp. to invert = 4 28

3 30

15 82

6 44

4 21

~~3 91~~

4 16

~~4 03~~

4 28

12.52.

9 38

11 61

~~11 91~~

11 66

~~11 79~~

11 54



Em. N.E. 16 + N.

Great Wand.

~~Gr. at E.~~

~~Gr. at E.~~

Gr at E

15.87
.65
6.17
.25
6.42

589
55
644

216
108
5.36
8

5.36
4.49
.87

96

.87
12
1044

44
8
352

10 44
10 7/16

| | | | |
|---|---|---|---|
| | | | 10.00 |
| 5 41 | 15 41 | 4 80 | 10 61 |
| | | 6 53 | 8 88 |
| | | 5 58 | 9 83 |
| | | 5 36 | 10 05 |

X Curb on W

" " E

W Cb at Rt Ang.

℄

E

9 65

55+7878
53+52,65
37+26 18
32 42
58,55

46.71 22
43+8713
2484 09

48+5562
46+7122
1848 4 2

50+96 02
46+7122
3,44 8 2

50+45.15
16 02
28.13

54+9198
524+2475
2+6723

54+9198
54+2060
71,88

2672 3
5
2721 23

57+7883
56+2692
1+4641

61+8235
58+4245
3+3990
10 24
50 19

Return to City Engineers Office
City Hall, San Diego, Cal.

*able showing the difference of latitude and departure in running 80 chains at any course from 1 to 60 minutes.*

| UTES. | LKS. | MINUTES. | LKS. | MINUTES. | LKS. |
|---|---|---|---|---|---|
| | 2⅓ | 21 | 49 | 41 | 95⅔ |
| | 4⅔ | 22 | 51⅓ | 42 | 98 |
| | 7 | 23 | 53⅔ | 43 | 100⅓ |
| | 9⅓ | 24 | 56 | 44 | 102⅔ |
| | 11⅔ | 25 | 58⅓ | 45 | 105 |
| | 14 | 26 | 60⅔ | 46 | 107⅓ |
| | 16⅓ | 27 | 63 | 47 | 109⅔ |
| | 18⅔ | 28 | 65⅓ | 48 | 112 |
| | 21 | 29 | 67⅔ | 49 | 114⅓ |
| | 23⅓ | 30 | 70 | 50 | 116⅔ |
| | 25⅔ | 31 | 72⅓ | 51 | 119 |
| | 28 | 32 | 74⅔ | 52 | 121⅓ |
| | 30⅓ | 33 | 77 | 53 | 123⅔ |
| | 32⅔ | 34 | 79⅓ | 54 | 126 |
| | 35 | 35 | 81⅔ | 55 | 128⅓ |
| | 37⅓ | 36 | 84 | 56 | 130⅓ |
| | 39⅔ | 37 | 86⅓ | 57 | 133 |
| | 42 | 38 | 88⅔ | 58 | 135⅓ |
| | 44⅓ | 39 | 91 | 59 | 137⅔ |
| | 46⅔ | 40 | 93⅓ | 60 | 140 |

## TABLE FOR RUNNING ON SLOPES.

*following table the first column shows the angle, the second the number of links to be added to a chain on the slopes, to make one chain, horizontal measurement.*

| E | COR. IN LINKS | ANGLE | COR. IN LINKS | ANGLE | COR. IN LINKS | ANGLE | COR. IN LINKS |
|---|---|---|---|---|---|---|---|
| | | ° | | ° | | ° | |
| | 0.24 | 11 | 1.88 | 18 | 5.14 | 25 | 10.54 |
| | 0.38 | 12 | 2.24 | 19 | 5.76 | 26 | 11.26 |
| | 0.55 | 13 | 2.63 | 20 | 6.42 | 27 | 12.24 |
| | 0.76 | 14 | 3.06 | 21 | 7.11 | 28 | 13.37 |
| | 0.98 | 15 | 3.53 | 22 | 7.85 | 29 | 14.34 |
| | 1.24 | 16 | 4.02 | 23 | 8.64 | 30 | 15.47 |
| | 1.55 | 17 | 4.56 | 24 | 9.47 | 35 | 22.07 |