550
F. B.

## TRAVERSE TABLE FOR TRANSIT BOOK.

From 1° to 90° for a distance of 100.

| Degrees. | DEGREES. | | ¼ DEGREE. | | ½ DEGREE. | | ¾ DEGREE. | | Degrees. |
|---|---|---|---|---|---|---|---|---|---|
| | Lat. | Dep. | Lat. | Dep. | Lat. | Dep. | Lat. | Dep. | |
| 0 | | | 100.00 | 0.44 | 100.00 | 0.87 | 99.99 | 1.31 | 89 |
| 1 | 99.98 | 1.75 | 99.98 | 2.18 | 99.97 | 2.62 | 99.95 | 3.05 | 88 |
| 2 | 99.94 | 3.49 | 99.93 | 3.93 | 99.91 | 4.36 | 99.88 | 4.80 | 87 |
| 3 | 99.86 | 5.23 | 99.85 | 5.67 | 99.81 | 6.10 | 99.79 | 6.54 | 86 |
| 4 | 99.76 | 6.98 | 99.73 | 7.41 | 99.69 | 7.85 | 99.66 | 8.28 | 85 |
| 5 | 99.62 | 8.72 | 99.58 | 9.15 | 99.54 | 9.58 | 99.50 | 10.02 | 84 |
| 6 | 99.45 | 10.45 | 99.41 | 10.89 | 99.36 | 11.32 | 99.31 | 11.75 | 83 |
| 7 | 99.25 | 12.19 | 99.20 | 12.62 | 99.14 | 13.05 | 99.09 | 13.49 | 82 |
| 8 | 99.03 | 13.92 | 98.97 | 14.35 | 98.90 | 14.78 | 98.84 | 15.21 | 81 |
| 9 | 98.77 | 15.64 | 98.70 | 16.07 | 98.63 | 16.50 | 98.56 | 16.93 | 80 |
| 10 | 98.48 | 17.36 | 98.40 | 17.79 | 98.33 | 18.22 | 98.25 | 18.65 | 79 |
| 11 | 98.16 | 19.08 | 98.08 | 19.51 | 97.99 | 19.94 | 97.90 | 20.36 | 78 |
| 12 | 97.81 | 20.79 | 97.72 | 21.22 | 97.63 | 21.64 | 97.53 | 22.07 | 77 |
| 13 | 97.44 | 22.50 | 97.34 | 22.92 | 97.24 | 23.34 | 97.13 | 23.77 | 76 |
| 14 | 97.03 | 24.19 | 96.92 | 24.62 | 96.81 | 25.04 | 96.70 | 25.46 | 75 |
| 15 | 96.59 | 25.88 | 96.48 | 26.30 | 96.36 | 26.72 | 96.25 | 27.14 | 74 |
| 16 | 96.13 | 27.56 | 96.00 | 27.98 | 95.88 | 28.40 | 95.76 | 28.82 | 73 |
| 17 | 95.63 | 29.24 | 95.50 | 29.65 | 95.37 | 30.07 | 95.24 | 30.49 | 72 |
| 18 | 95.11 | 30.90 | 94.97 | 31.32 | 94.83 | 31.73 | 94.69 | 32.14 | 71 |
| 19 | 94.55 | 32.56 | 94.41 | 32.97 | 94.26 | 33.38 | 94.12 | 33.79 | 70 |
| 20 | 93.97 | 34.20 | 93.82 | 34.61 | 93.67 | 35.02 | 93.51 | 35.43 | 69 |
| 21 | 93.36 | 35.84 | 93.20 | 36.24 | 93.04 | 36.65 | 92.88 | 37.06 | 68 |
| 22 | 92.72 | 37.46 | 92.55 | 37.86 | 92.39 | 38.27 | 92.22 | 38.67 | 67 |
| 23 | 92.05 | 39.07 | 91.88 | 39.47 | 91.71 | 39.87 | 91.53 | 40.27 | 66 |
| 24 | 91.35 | 40.67 | 91.18 | 41.07 | 91.00 | 41.47 | 90.81 | 41.87 | 65 |
| 25 | 90.63 | 42.26 | 90.45 | 42.66 | 90.26 | 43.05 | 90.07 | 43.44 | 64 |
| 26 | 89.88 | 43.84 | 89.69 | 44.23 | 89.49 | 44.62 | 89.30 | 45.01 | 63 |
| 27 | 89.10 | 45.40 | 88.90 | 45.79 | 88.70 | 46.17 | 88.50 | 46.56 | 62 |
| 28 | 88.29 | 46.95 | 88.09 | 47.33 | 87.88 | 47.72 | 87.67 | 48.10 | 61 |
| 29 | 87.46 | 48.48 | 87.25 | 48.86 | 87.04 | 49.24 | 86.82 | 49.62 | 60 |
| 30 | 86.60 | 50.00 | 86.38 | 50.38 | 86.16 | 50.75 | 85.94 | 51.13 | 59 |
| 31 | 85.72 | 51.50 | 85.49 | 51.88 | 85.26 | 52.25 | 85.04 | 52.62 | 58 |
| 32 | 84.80 | 52.99 | 84.57 | 53.36 | 84.34 | 53.73 | 84.10 | 54.10 | 57 |
| 33 | 83.87 | 54.46 | 83.63 | 54.83 | 83.39 | 55.19 | 83.15 | 55.56 | 56 |
| 34 | 82.90 | 55.92 | 82.66 | 56.28 | 82.41 | 56.64 | 82.16 | 57.00 | 55 |
| 35 | 81.92 | 57.36 | 81.66 | 57.71 | 81.41 | 58.07 | 81.16 | 58.42 | 54 |
| 36 | 80.90 | 58.78 | 80.64 | 59.13 | 80.39 | 59.48 | 80.13 | 59.83 | 53 |
| 37 | 79.86 | 60.18 | 79.60 | 60.53 | 79.34 | 60.88 | 79.07 | 61.22 | 52 |
| 38 | 78.80 | 61.57 | 78.53 | 61.91 | 78.26 | 62.25 | 77.99 | 62.59 | 51 |
| 39 | 77.71 | 62.93 | 77.44 | 63.27 | 77.16 | 63.61 | 76.88 | 63.94 | 50 |
| 40 | 76.60 | 64.28 | 76.32 | 64.61 | 76.04 | 64.94 | 75.76 | 65.28 | 49 |
| 41 | 75.47 | 65.61 | 75.18 | 65.93 | 74.90 | 66.26 | 74.61 | 66.59 | 48 |
| 42 | 74.31 | 66.91 | 74.02 | 67.24 | 73.73 | 67.56 | 73.43 | 67.88 | 47 |
| 43 | 73.14 | 68.20 | 72.84 | 68.52 | 72.54 | 68.84 | 72.24 | 69.15 | 46 |
| 44 | 71.93 | 69.47 | 71.63 | 69.78 | 71.33 | 70.09 | 71.02 | 70.40 | 45 |
| 45 | 70.71 | 70.71 | | | | | | | |
| Degrees. | Dep. | Lat. | Dep. | Lat. | Dep. | Lat. | Dep. | Lat. | Degrees. |
| | DEGREES | | ¾ DEGREE. | | ½ DEGREE. | | ¼ DEGREE. | | |

Published by H. S. Crocker Company, Stationers, Drawing Materials, Mathematical Instruments, etc., San Francisco.

Crocker Quality

# FIELD BOOK

No._____

MANUFACTURED BY

H. S. CROCKER CO.

SAN FRANCISCO AND SACRAMENTO
CALIFORNIA

FROM
LORINGS BOOK STORE
San Diego, Cal.

1.72
17.34

0+20
C 25
E 15

13.94 BM
4.19
18.13 HI.
3.80
14.33 TP
4.65
21.78 HI.

17.35
4.43

J

28.00 B.M. N.W. C. plg

34.93 B.M. S.W. 8 plg.



R.6.30 B.M. SW. D p/q




D
ST.
ST.
26.5
27.0
24.0
25.0
UNION
E
ST.
24.0
25.0

19.47 B.M. SW.F. plg. 2465 HH. 19.50



15.51 B.M. S.W.G. plg. 16.5 17.0 17.5 18.0 18.5 19.0 19.5
5.27 4.77 4.34 3.77 3.27 2.77 2.27

curb stakes

C. RC
21.77 HI
20.37 H.I.

16.17 / 4.20 — 15.83 / 4.54

19.47 (3. WF BM)
6 SHP 18.83 / 24.56 / 5.72

19.47
2.51
21.98 H.I.

| | | | | | |
|---|---|---|---|---|---|
| 18.08 | 2.62 | 2.50 | 2.68 | 3.01 |
| 2.90 | 19.36 | 19.48 | 19.28 | 19.07 |
| 5.65 | 4.80 | 5.31 | 5.46 | 4.85 |
| 16.43 | 16.60 | 16.67 | 16.50 | 16.12 |

F

ST.

5

ST.

19.5

17.0

16.5

15.5

16.0

G

ST.



10.93 SW. H. p/g.

15.61 / 2.12 / 17.73 M

2.49 / 15.14 — 2.12 / 15.61 — 1.93 / 15.74 — 1.95 / 15.66 — 2.20 / 15.43 — 2.02 / 10.61 — 6.46 / 11.17

11.38 / 6.26 — 11.62 / 6.01 — 11.39 / 6.24 — 10.93 / 6.70 — 4.46 / 4.54 — 4.31 / 4.70

15.61 13M SW G.

4.86 / 20.37 M — 14.93 / 5.54 — 15.17 / 5.20

G

ST 6

+0.01 / 15.13 — -0.06 / 15.12 — -0.02 / 15.78 — -0.02 / 15.70 — +0.02 / 15.54 — 15.17 / 07L

15.5

16.0

ST.

11.37 — 10.61 — 10.93 — 11.39 — 11.62 — 11.62 — 11.38 — 11.17 — 11.87

11.0

PAVING STOPS HERE

11.50

H

ST.

UNION

11.0

11.50

20.405 B.M. N.W. C plg

20.93 B.M. SW. B plg

B

ST.

PAVE TO HERE

21.0

22.5

ST.

20.5

21.5

C

ST

COLUMBIA

16.19 B.M. SW.D. plg



14.46 SW. E plq



12.47 B.M. SW. F plg

17.67 HI

14.46 B.M.
3.27
17.73 HI

12.47
5.31
18.78 HI

E ST

11




F ST.



9.35 B.M. SW. G plg 11.77 M. 1.59 / 10.18 2.25 / 9.52 17.87 M. 4.7° / 13.17

12.47 / 0.22 / 12.69 M

12.15 / 3.00 — 12.69 / 2.67 — 13.02 / 2.56 — 13.14 / 2.64 — 13.05

10.47 / 5.32 — 10.15 / 5.0 — 10.61 / 10.08 — 10.37 / 5.0 — 9.92 / 5.77




G
ST
13
9.5
9.74
7.98
7.22
6.47
5.71
5.50
5.00 5.26 5.62 5.80 5.78 5.59 5.41
5.50
PAVING STOPS HERE
H
ST.
COLUMBIA

NJ. 100.00

3.81 / 96.19 — 3.65 — 3.37 / 96.63 — 3.33 — 406 — 3.80 / 96.20 — 377 — 4 77 — 4.43 — 371 / 346 / 6.25 — 4 15 — 3 77



16.44 BM. SW India

2.95
18.79 M

1650 4.20 | 1375 5.29 | 1250 6.29

1644 BM-
83
17.26 M

1250 4.76 | 1350 8.76 | 1450 2.76 | 1550 1.76 | 1650 0.76 | Curb Sta. Nos. 11 West

1644
2.87
16.25

7.83
7.42

1583 4.56 | 1617 4.52 | 1637 4.02 | 1645 3.84

1644 Bm
391
20.39

1183 5.43 | 1217 5.09 | 1237 4.89 | 1241 4.81

6.62 12.09 | 7.05 12.66 | 6.76 12.94 | 6.32 13.29 | 5.86 13.86 | 5.52 14.19

16.44
3.27
19.71 M
14.14
3.57
17.26

10.83
3.85

12.00
7.71

16.44
2.17
18.61 M

16.00 4.65 | 12.17 6.39 | 16.35 2.30 | 16.40 3.15 | 16.45 2.10 | 12.45 6.10 | 12.42 6.13 | 12.33 6.20

12.50
7.67

16.44
3.67
20.11 M

INDIA ST. 15 ST.

16.50 | 16.0 | 16.50 | 16.0 | 16.50 | 16.0

12.50 | 14.0 | 12.50 | 12.0 | 12.50 | 12.0

Point Limits

PAVE TO HERE

ARCTIC ST.

11.50 | 11.0 | 11.50 | 11.0

B.


COLUMBIA ST.
16
INDIA ST
B


20.93 BM. S.W. Columbia pl.
20.93
4.78
25.71 HH
26.46
3.64
30.10 HH
26.46
2.39
28.85 HH
20.93
4.55
25.48 HH
2093
4.78
25.71 HH


STATE
17
28.0
22.5
26.5
22.5
35.5
24.0
21.5
1½' above 1½' below
COLUMBIA ST
21.0
21.0
26.5
20.5


UNION
ST.
STATE
ST.
ST.
B

34.93 B.M. S.W. Union plg
40.29

35.47
35.32

35.93 Bm
40.43
34.33
40.10

35.50
3.81
39.31 Ht.

35.38 35.89 36.05 34.77 35.36 35.66 34.32
3.93 3.45 4.26 4.64 3.96 3.76 4.98

34.93
4.67
39.60 Ht.

34.73 34.33 34.79 34.45 34.21 35.17 35.39 35.47
4.73 5.17 5.21 5.26 5.29 5.38 4.21 4.03

35.53 35.38 34.77 34.70 34.62 34.54 34.47 34.87
3.96 4.18 4.93 4.80 4.88 4.96 5.03 4.63

35.10
4.56

35.67 35.17
4.29 4.79

35.53 35.51 35.38 35.50 35.17
4.41 4.46 4.58 4.79

34.93
5.07
39.90 Ht.

35.51 35.51 35.38 35.65 35.69 36.05 36.01 35.64
4.46 4.49 4.62 40.15 Ht 4.48 4.10 4.14 4.27

40.00 Ht

4.76 4.11 4.04 4.06 35.80 35.90 35
35.24 35.89 35.16 35.94 4.20 4.10

35.60 35.85 35.64 35.80 35.72 35.53 35.89 36.--
4.16 4.15 4.36 4.10 4.28 4.47 4.11 4.00

34.93
4.41
40.34 Ht

35.86 35.46 35.68 35.90 35.64 36.66 35.77
4.11 4.50 4.32 4.10 4.38 4.40

36.62 35.60
4.82 4.74

35.60 BM. 36.10 35.97 35.85 35.72 35.60
4.63 4.03 4.14 4.25 4.41 4.53
40.13 Ht.

FRONT

19

47.0

36.5

42.2

36.0

35.5

31.5

35.97

35.72

29.0

35.0

UNION

36.00

ST.

42.2

36.0

35.0

28.0


FIRST
ST
20
35.50 S.W. Front p/g.
47.31
38.30 B.M.
40.37
40.26 M.
40.77 M.
40.30 M.
41.17 M.
40.83 M.
FRONT
ST.
PIPE
48.0
47.5
47.0
37.7
36.5
37.0
35.5
35.0
32.5
31.5

36.93 B.M. S.W. First plg.



40.44 — B.M. S.W. 2nd & B

No. B.M. at 2nd & B. B.M. at 2nd & C. N.W. 38.43

40.40
6.30
46.70 M.
50 W
6.67
47.11 M

.675
39.75
3.96
43.86

3.46

6.07
41.04

41.43 41.33

40 W
6.33
46.77 M.
40.44 B.M.
6.83
47.27 M

5.52 5.16 5.02 2.76 2.30 2.53 2.01 5 0 2
41.25 41.67 41.76 44.51 44.47 44.25 43.86

5.88 5.87 5.72 5.57 3.44 3.09 2.89 2.81
41.39 41.56 41.53 41.68 43.80 44.18 44.08

3.53
44.53

1.93
45.13

40 W
6.67
47.06 M

38.83 43.15 44.47
5.05 3.76 4.44

40 W
6.47
46.91 M

THIRD ST.

22

57.0 44.5 42.0

55.0 42.0

44.5 42.0

41.5 39.5

SECOND ST.

58.0 41.0

40.5 38.5

B

HH.32 B.M. N.W Third. blg.




FIFTH
ST
FOURTH
ST
24
54.5
50.5
54.0
50.0
50.5
50.0
48.0
48.0
B

54.66 B.M. N.W. Fifth p/g

58.43 NW 6th Plg.



58.43 B.M. N.W. Sixth plg

61.36 B.M. S.E. 7th



23.97 B.M. N.W. C p/q

26.46 B.M. S.W. B p/q



21.75 B.M. SW. D.p/g -



18.47 B.M. S.W.E plg.



16.00 B.M. S.W. F plg

1847 BM. S.W.E



13.49 B.M. S.W.G. p/q

16.00 BM. S.W.E.

| | R. | 4 | 5 | Gt. |
|---|---|---|---|---|
| 16.41 | 4.64 | 4.78 | 4.96 | 5.22 |
| 19.41 HI | 14.77 | 14.63 | 14.45 | 14.19 |
| | 1.89 | 2.94 | 3.16 | 3.42 |
| | 16.66 | 16.57 | 16.35 | 16.13 |

| | | | | | |
|---|---|---|---|---|---|
| 16.00 | 3.59 | 3.15 | 3.17 | | |
| 3.17 | 15.58 | 14.02 | 13.02 | | |
| 19.17 HI | 15.75 | 16.04 | 16.43 | 16.36 | 16.40 |
| 16.00 | 3.40 | 3.11 | 2.92 | 2.79 | 2.75 |
| 3.16 | 14.90 | 14.97 | 14.78 | 14.67 | 14.90 |
| 19.16 HI | 4.25 | 4.28 | 4.37 | 4.53 | 4.76 |
| | 15.75 | 16.04 | 16.43 | 16.36 | 16.40 |
| 16.00 | 4.14 | 3.86 | 3.46 | 3.52 | 3.49 |
| 3.89 | 14.40 | 14.62 | 14.78 | 14.87 | 14.90 |
| 19.89 HI | 5.49 | 5.27 | 5.11 | 5.02 | 4.99 |
| 16.00 | 16.20 | 16.00 | 15.70 | 15.42 | 15.10 |
| 4.97 | 4.69 | 4.97 | 5.17 | 5.47 | 5.77 |
| 20.87 HI | .17 | .17 | .17 | .17 | .17 |
| | 4.92 | 5.02 | 5.34 | 5.64 | 5.94 |



8.465 B.M. S.W.H plg

13.49 BM
1.74
15.23 HH

1.48 2.03 6.84 8.71 6.13 9.10 9.51 9.92 10.32 10.72
13.75 13.20 3.37 6.50 9.10 6.12 5.72 0.81 4.91 4.50

11.14 11.54 11.94 12.36 12.76 1.80 1.62 1.36
4.09 3.69 3.29 2.87 2.47 13.43 13.60 13.87

8.91 9.03 9.07
6.32 6.20 6.16

13.49
1.90
15.39 HH

2.11 1.93 1.78 1.70 1.71 7.17 6.34
13.28 13.46 13.61 13.69 13.68 8.22 9.11

9.07 8.04 6.93 8.76 8.53
6.32 6.45 6.46 6.68 6.86

13.49
3.08
16.57 HH

13.43 13.20 13.20 13.05 12.86
3.24 3.27 3.37 3.52 3.73

9.07 8.04 8.93 8.76 8.53
7.50 7.53 7.64 7.81 8.04

13.49
3.28
16.77 HH

12.95 12.10 11.75 10.40 9.50
3.82 4.67 5.02 6.37 7.22
.17 .17 .17 .17 .17
3.99 4.84 5.19 6.54 7.39

G

35

13.5

8.5

14.0

9.0

13.37 13.48 13.72 13.76 13.68 13.53 13.17
13.84 13.06 13.20 13.30 13.33

12.76 12.36 11.96 11.54 11.14 10.73 10.32 9.95 9.51 9.10

8.22 8.53 8.76 8.93 9.04 9.07 9.12 9.07 9.03 8.91 8.70 9.42

H ST

STATE


31.46 B.M. N.W. C. p/q
35.50 B.M. S.W. B p/q.
B
ST
35
ST.
35.5
35.5
31.5
32.5
C
ST.
FRONT
31.5
32.5

29.34 B.M. S.W. D. p/g



27.01 B.M. S.W. E p/g

4.95
31.96

27.01 B.M.
5.91
32.96

27.01 B.M.
5.93
32.94

2904 B.M.
5.57
34.85

27.00
.66
26.34
5.68
27.50
3.46

2750
5.44
2883
6.02

2768 2790 2850
5.26 5.02 4.94
2915 2959 2925 2967 2929 2984
5.70 5.26 5.40 5.48 5.52 5.85

2850
4.96
2750
4.96

D ST.

29.5 28.0

30.0 28.0

E ST.

27.0 27.0

FRONT

18.49 B.M. S.W. F plg

5 1 5
2 3 , 6 4 4 5

1850 6 6 1784 5 8 6

1900 6 6 1834 5 3 8

2701 B.M. 5 0 2 3 2 4 4 1 8 5 9 5 1 5

1849 5 4 5 2394

2701 5 7 8 2 2 , 1 9

1833 1858 1889 1900
5 3 1 5 3 6 5 0 5 4 9 4

2633 2658 2689 2700
5 8 6 5 7 1 5 3 0 5 1 9



16.43 B.M. S.W. G p/q

9 34
20.77½

16.43
5'2.5
21.68

7P.6 | 16.50 | 17.50
15.54 | 1.46
4.83 | 3.92.

16.83 | 17.08 | 17.39 | 17.50
4.83 | 4.60 | 4.29 | 4.18

18.49
4.50
22.99

1783 | 1808 | 1839 | 1850
5.16 | 4.94 | 4.60 | 4.49



12.46 B.M. S.W. H p/g
4 78
17.24

12.50
16
12.84
5.40

1643 Bm G
5.30
21,73

1588 16.04 1639 16.50
4.98 5.01 5.34 5.23

12.46
4.63
17.09

12.16 12.41 12.72 12.83
4.93 4.68 4.37 4.26



34.93 B.M. S.W. B. plg
5.65
40.58 M1.

35.84
4.74

34.93
7.64
42.57 M1

36.08 36.40 36.51 41.77 42.09 42.20
6.49 6.17 6.06 0.80 0.48 0.37



42.38
~~41.84~~ B.M. N.W.A plg.

ASH



40.97 B.M. N.W. Ash p/g

7.74

48.71 HI

40.50 41.83

8.21 6.88

40.97 BM. 40.80 42.16

57.0 5.83 4.51

46.67 HI

41.00 40.89 40.67 40.40

4.56 4.67 4.89 5.16

40.97 42.07 42.39 42.50 40.45 40.57 40.51 40.38

4.59 3.49 3.17 3.06 5.11 5.04 5.20 5.23

46.56 HI

41.73 41.83 40.57 40.28 41.78

3.83 3.73 4.99 5.28 3.78

40.96 41.66 42.09 42.26 42.16

4.60 3.90 3.47 3.30 3.40






49.42 BM N.W Union Beech

56.95
6.3
57.28 M1

Front & Beech N.W Pig.

7.86 49.42 8.08 50.17 7.11 50.30 6.98 50.38 6.90 50.27 7.03 49.91 7.37 49.35 7.93

49.42 Bm
6.08
55.50 M1

6.82 48.68 5.36 50.14 53.33 3.17 52.83 2.67

49.42
6.04
54.46 M1

49.42
6.83
56.25 M1

64.02 BM
1.97
65.99
9.32
5.74
55.16 M1

CEDAR

63.30 63.68 63.39 63.50 63.59 63.48 63.33

59.0 63.0 64.0 54.0

53.33 53.53 53.74 53.76 53.54 53.13 52.83 53.50

49.86 49.39 50.11 50.58 50.66 50.48 49.50 51.0

BEECH

49.50 49.39 49.08 49.83 49.00 49.35 49.91 50.45 50.38 50.30 50.17 51.00 50.89 50.58 50.38

UNION ST

49.50 51.0 41.0 42.50

64.02 B.M. N.Y. CEDAR dig

DATE



68.99 B.M. S.W. DATE p/g

ELM



Location of Outside edge of outside rail of Curve at 2nd & Winder Sts

Ang A = 1°52'
" B 35° 34'
" C 32° 40'
" D 33° 05'



Location of Track at Tide & Kurtz & Intersection of Kurtz & Witherby.



7/19 13 Davis Hancock Herrick

Location of outside edge of outside rail of Curve at Kurtz & Tide



Location of outer edge of inside rail of Curve at Rosecrans & Lytton Sts

7/19/13 Davis Hancock Horrior



Location of Turnout
on Tide St $\frac{E}{18}$ $\frac{}{13}$ { Davis / Hancock / Horner.




Measurements from gague on main line to outside of rail on turnout - Use same measurements for other end.

Levels Over ℄ of Tio ST from the N.W. Line of Kurtz St to the SoEnd of Lyttom ST

33' offset Staioning

| | | | | |
|---|---|---|---|---|
| | 1.10 | 5.73 | 4.63 | spk NE Kurtz |
| 0.0 = W.L. KURTZ ST PRODUCED | | 4.1 | 1.63 | |
| + 09 = Ctr 2.5 x 4.0 CONC. CULVERT | | | | |
| + 50 | | 4.2 | 1.5 | |
| 1 + 00 | | 4.5 | 1.2 | |
| 1 + 25 = 15" SHEETPIPE ON SO. Elev. on bottom = 6.11 − 0.68 | | | | |
| 1 + 39 = 15" " " " No. " " = 6.17 − 0.44 | | | | 1.13 |
| 1 + 50 | | 4.4 | 1.3 | |
| 1 + 98 = Ctr 2.5 x 4.0 CONC. CULV. | | | | |
| 2 + 00 | | 4.6 | 1.1 | |
| 2 + 50 | | 4.5 | 1.2 | |
| 3 + 00 | | 4.8 | 0.9 | |
| 3 + 50 | | 4.8 | 0.9 | |
| 4 + 00 | | 4.9 | 0.8 | |
| + 50 | | 5.0 | 0.7 | |
| 5 | | 5.0 | 0.7 | |
| + 50 | | 5.1 | 0.6 | |
| 6 | | 5.3 | 0.4 | |
| + 50 | | 5.2 | 0.5 | |
| 7 | | 5.3 | 0.4 | |
| + 50 | | 5.4 | 0.3 | |
| 8 | | 5.4 | 0.3 | |
| + 50 | | 5.4 | 0.3 | |
| 9 | | 5.3 | 0.4 | |
| T.P. | 5.30 | 5.78 | 5.25 | 0.48 |
| + 50 | | 5.3 | 0.5 | |
| 10 | | 5.3 | 0.5 | |

5.78

| | | |
|---|---|---|
| + 50 | 5.1 | 0.7 |
| 11 | 5.1 | 0.7 |
| + 50 | 4.8 | 1.0 |
| 12 | 4.8 | 1.0 |
| + 50 | 4.8 | 1.0 |
| 13 | 4.8 | 1.0 |
| + 50 | 4.7 | 1.1 |
| 14 | 4.7 | 1.1 |
| + 50 | 4.6 | 1.2 |
| 15 | 4.5 | 1.3 |
| + 50 | 4.5 | 1.3 |
| 16 | 4.43 (w) | 1.33 |
| + 50 | 4.4 | 1.4 |
| 17 | 4.3 | 1.5 |
| + 50 | 4.4 | 1.4 |
| + 67 = Ctr 2.5 x 4.0 CONC. CULVERT. { ELEV BOTTOM " " | INLET = Rod 9.67 − 3.87 | |
| | OUTLET = F.S. 8.99 − 4.21 | |
| 18 | 4.5 | 1.3 |
| + 50 | 4.6 | 1.2 |
| 19 | 4.6 | 1.2 |
| T.P. 3.60 4.85 | 4.53 | 1.25 |
| + 50 | 3.8 | 1.1 |
| 20 | 3.9 | 1.0 |
| + 50 | 4.0 | 0.9 |
| 21 | 4.1 | 0.8 |
| + 50 | 4.2 | 0.7 |
| 22 | 4.2 | 0.7 |
| + 50 | 4.4 | 0.5 |

H.85

| | | | | |
|---|---|---|---|---|
| 23 | | | 4.6 | 0.3 |
| +50 | | | 4.7 | 0.2 |
| 24 | | | 4.7 | 0.2 |
| +50 | | | 4.6 | 0.3 |
| 25 | | | 4.5 | 0.4 |
| +50 | | | 4.5 | 0.4 |
| 26 | | | 4.4 | 0.5 |
| +50 | | | 4.4 | 0.5 |
| 27 | | | 4.3 | 0.6 |
| +50 | | | 4.1 | 0.8 |
| 28 | | | 4.0 | 0.9 |
| +50 | | | 4.0 | 0.9 |
| 29 | | | 4.0 | 0.9 |
| +50 | | | 4.0 | 0.9 |
| 30 | | | 3.9 | 1.0 |
| T.P. | 5.06 | 6.12 | 3.79 | 1.06 |
| +50 | | | 5.1 | 1.0 |
| 31 | | | 5.1 | 1.0 |
| +50 | | | 5.0 | 1.1 |
| 32 | | | 4.9 | 1.2 |
| +50 | | | 4.9 | 1.2 |
| 33 | | | 4.7 | 1.4 |
| +38 = Ctr 2.5'x4.0' Conc Culv. | | | Elev bottom Inlet = Rod 10.64 | −4.52 |
| | | | Outlet = 11.15 | −5.03 |
| +50 | | | 4.6 | 1.5 |
| 34 | | | 4.6 | 1.5 |
| +50 | | | 4.3 | 1.8 |
| 35 | | | 4.5 | 1.6 |

| | | | | |
|---|---|---|---|---|
| +50 | | 6.12 | 4.5 | 1.6 |
| 36 | | | 4.7 | 1.4 |
| +50 | | | 4.7 | 1.4 |
| 37 | | | 4.8 | 1.3 |
| +50 | | | 5.0 | 1.1 |
| 38 | | | 5.0 | 1.1 |
| +50 | | | 5.2 | 0.9 |
| 39 | | | 5.3 | 0.8 |
| +50 | | | 5.4 | 0.7 |
| 40 | | | 5.4 | 0.7 |
| T.P. | 4.53 | 5.27 | 5.38 | 0.74 |
| +50 | | | 4.6 | 0.7 |
| 41 | | | 4.7 | 0.6 |
| +50 | | | 4.7 | 0.6 |
| 42 | | | 4.8 | 0.5 |
| +50 | | | 4.9 | 0.4 |
| 43 | | | 4.9 | 0.4 |
| +50 | | | 4.8 | 0.5 |
| 44 | | | 4.6 | 0.7 |
| +50 | | | 4.6 | 0.7 |
| 45 | | | 4.5 | 0.8 |
| +50 | | | 4.3 | 1.0 |
| 46 | | | 4.1 | 1.2 |
| +50 | | | 4.0 | 1.3 |
| 47 | | | 3.9 | 1.4 |
| +50 | | | 3.7 | 1.6 |
| 48 | | | 3.6 | 1.7 |
| +50 | | | 3.5 | 1.8 |

527

48+70 = Ctr 8'x5' conc. culv { Elev. bottom Inlet. = RP 11.10 − 3.83 / outlet = 12.15 − 6.88

48+92 = Inter. ℄ Tide & ℄ Lytton 3.4 1.9

T.P. 3.24 5.07 3.44 1.83 (1.21)

T.P. 2.86 2.21 Spike in pole

49+27 ± = Int ℄ Tide St & W.L. Line Lytton St.

ok




17.40
revised
6.85

ARCTIC ST

ST

LEVELS ON ℄ CHALMERS ST. 17.40
FROM W.L. INDIA. ST TO ℄ CALIFORNIA ST.

56

| | | | | | |
|---|---|---|---|---|---|
| | | | | | cpk S.W. India & Chalmers |
| | 3.41 | 70.46 | | | 67.05 |
| | 4.37 | | | | 6600 cut SW Bnd |
| 00 = W.L. India St | | | H.H | | 66.10 |
| +50 | | | 8.2 | | 62.3 |
| 1 | | | 11.7 | | 58.8 |
| T.P. | 1.40 | 59.02 | 12.84 | | 57.62 |
| +50 | | | 3.4 | | 55.6 |
| 2.00 = E.L. Arctic St | | | 6.4 | | 52.6 |
| ℄ Arctic St | | | 8.4 | | 50.6 |
| W.L. Arctic St | | | 11.2 | | 47.8 |
| E. Rail La Jolla Ry | | | 12.23 | | 46.79 |
| W " " " | | | 12.39 | | 46.63 |
| T.P. | 0.42 | 46.40 | 13.04 | | 43.98 |
| +50 | | | 0.6 | | 45.80 |
| 1700 | | | 2.1 | | 44.30 |
| +50 | | | 6.0 | | 40.40 |
| ℄ = E.L. California St | | | 8.6 | | 37.8 |
| ℄ " " | | | 10.9 | | 35.5 |

LEVELS ON ℄ CALIFORNIA ST
FROM ℄ CHALMERS ST TO ℄ HANCOCK ST

| | | | | |
|---|---|---|---|---|
| ℄ CHALMERS ST | | | 10.9 | 35.5 |
| W.L. " " | | | 10.9 | 35.5 |
| T.P. | 12.26 | 47.72 | 10.94 | 35.46 |
| 50' No | | | 9.5 | 38.2 |
| 100 " | | | 8.4 | 39.3 |

47.72

| | | |
|---|---|---|
| 150' No | 7.1 | 40.6 |
| 200' No | 5.7 | 42.0 |
| 250' No. | 4.8 | 42.9 |
| No = ℄ HANCOCK ST PRODUCED | 4.9 | 42.8 |

LEVELS ON ℄ HANCOCK ST FROM ℄ CALIFORNIA ST PRODUCED TO ℄ WINDER ST

| | | |
|---|---|---|
| ℄ CALIFORNIA ST + ℄ HANCOCK | 4.9 | 42.8 |
| 50' No | 4.7 | 43.0 |
| 100' No. | 4.9 | 42.8 |
| = ℄ WINDER ST. | 4.9 | 42.8 |

LOCATION OF CURVE AT INDIA & WINDERS STS

10/14/13

Eugene Sturdevant Moore




58



6th & B N.W. Pfg. 58.43

79.03 NE A Nail in Ct



·7902 BM Nail in Curb N.E Ash





18.36 13M. N.E. Beech Top Hydt



126.99 Bm NE Cedar Nail in Ch.



142.17 S.W. 6th Ave Date



NW. Cor Univ Ave & Park Blvd R.R Spk pole 315.83
N.E Cor " " " " -Wall - pigtt 316.905
" Lincoln NE Pig 332.386 Lincoln NE Spk pole 332.73



Polk 339.79 N.E. Spk Polo

66

Polk Ave.

BLVD.

PARK

Lincoln.

Ave

339.79 N.E Polk Spk Pole

344.13 4ft
3.8
340.33 TP
341.78 RH
339.79
4.59
344.38 RH
39.79
7.39
47.16 RH

3.15
4.03
39.73
5.65
39.87
4.51
4.03
6.43

7.75
41.43
37.93
6.45
37.51
6.80
40.70
3.68
5.87
41.29
40.58
6.51



BLVD.

Polk Ave

Polk Ave.

Centre St.

PARK

341.4
40.73 gutter
5.193 R to PL
60.65
341.0
27.05
38.3
339.0
37.93
39.73
339.4
33.40
27.08
R 22
62

343.22 Tacks 7' Line on R Blvd int with Univ Blvd.
at int of E.L. Univ Blvd with W.L. Park Blvd.
339.79 NE Polk Spk Pole 41.83 Bolt 14 of S.E Howard



NW El Cajon & Park Blvd 34286 Plug in Curb.

41.83 Bm
405
45.88
591
39.97 TR.
7.68
47.65 MT
479
4286
42.17
4.38
47.70 MT

40.09 / 5.88
40.26 / 5.64
40.18 / 5.40
40.72 / 5.16
40.96 / 6.69
40.61 / 7.04
40.41 / 7.44
39.09 / 8.65
41.83 / 570 / 47.53 MT
39.50 / 8.03
41.90 / 5.63
41.71 / 5.82
42.30 / 43.23
42.17 / 5.53
40.46 / 7.24
39.50 / 8.20

Bench at NW El Cajon used as 342.74 for paving no of El Cajon

343.0

Univ. Blvd.

El Cajon Ave

Park Blvd.

Howard Ave.

39.17
39.50
340.0
340.21
340.61
340.96
340.72
340.50
340.24
340.0
39.50
340.0
42.17
N Bench 40.00
343.0
41.90 Bench
41.71 Bench
39.50
340.0

6570 Nail Ct. S W 6th A

79.03 " " NE 6th A

65.71
7.93
73.64 NT
73.27
.37 TP
73.64 NT
89.09

7.80
67.83
6570.
8.85
74.55 NT

6775
7.88
6779
6.76
6782
6.73
77.62
1.99
77.63
1.92

3.06

4th 5th

79.0 78.17 75.83 76.50

73.40 77.57 77.63 77.82 77.75 70.43 71.10

Paving 1st 100
for Ohio Savings Co.
W. H. Davis

67.75 67.82 67.79 67.52 65.79

67.80 64.97 64.75 65.03 65.70

6th St

3P0.9 ER
371.90 WR
371.75 CR

Levels over tracks and W. Cb. at Univ. Blvd

| Sta | East Rail Rod | East Rail Elev | West Rail Rod | West Rail Elev | West Curb Rod | West Curb Elev |
|---|---|---|---|---|---|---|
| | | 5.88 | | H.I. 49.10 | | 343.22 |
| Sta E. Cb Univ. Blvd | | | | | 6.13 | 42.97 = E. Cb. |
| 0+00 (632 Inhot NL Campus on W. | 4.85 | 44.25 | 4.87 | 44.23 | 5.40 | 43.70 |
| +25 | 4.90 | 44.20 | 4.87 | 44.23 | 5.45 | 43.65 |
| +50 | 5.02 | 44.07 | 4.90 | 44.20 | 5.52 | 43.58 |
| +75 | 5.07 | 44.03 | 4.97 | 44.12 | 5.53 | 43.57 |
| 1 | 4.98 | 44.12 | 5.01 | 44.09 | 5.65 | 43.45 |
| +25 | 5.04 | 44.06 | 5.06 | 44.04 | 5.53 | 43.57 |
| +50 | 5.01 | 44.09 | 5.06 | 44.04 | 5.80 | 43.30 |
| +75 | 5.07 | 44.03 | 5.06 | 44.04 | 5.87 | 43.23 |
| 2 | 5.12 | 43.98 | 5.10 | 44.00 | 5.92 | 43.18 |
| +25 | 5.15 | 43.95 | 5.17 | 43.93 | 5.97 | 43.13 |
| +50 | 5.30 | 43.80 | 5.39 | 43.71 | 5.97 | 43.13 |
| +75 | 5.51 | 43.56 | 5.61 | 43.49 | 6.03 | 43.07 |
| 3 | 5.76 | 43.34 | 5.75 | 43.35 | 6.17 | 42.93 |
| +25 | 6.33 | 42.77 | 6.12 | 42.98 | 6.25 | 42.85 |
| +50 | 6.98 | 42.12 | 6.88 | 42.22 | | |
| No. #L. El Cajon +51.75 | | | | | 6.25 | 42.85 |
| " " +71.90 | | | 7.43 | 41.67 | | |
| " " +80.95 | 7.61 | 41.49 | | | | |

Elevations on Cable Slot along 41st St. Cedar to 15th

| Sta | | | | |
|---|---|---|---|---|
| | | NH 166.36 | | ℄ 64.96 BM. Top N |
| | So. line Fir | | 5.0 ± | G 61.50 61.34 |
| 0+00 | 1.34 | NH 139.28 | | 137.94 ℄ Elm (N) |
| | No. line Elm | | 1.35 | G 38.00 37.93 |
| +50 | So. " " | | 4.55 | G 35.00 34.73 |
| +75 | T.P. | 0.54 | NH 137.42 | 17.41 176.88 |
| 1 | No. line Date | | 5.40 | G 27.50 22.02 |
| +25 | So. " " | | 7.08 | 20.50 20.34 |
| +50 | T.P. | 0.47 | NH 115.93 | 11.76 ~~115.46~~ |
| +75 | No. line Cedar | | 5.81 | G 110.75 110.62 |
| 2 | So. " | | 7.30 | G 108.75 108.63 |
| 3 | | | | |

10.50 / 5.55 / 1605 NT

Bm S.E. Arctic Plgab.

5.17 / 10.38 — 5.17 / 10.88 — 8.50 / 7.55 — 10.70 / 5.25 — 7.86 / 8.19

10.50 / 5.06 / 16.16 NT — 5.06 / 11.10 — 11.10 / 5.04 — 10.88 / 5.28 — 10.70 / 5.46

12.00 Sta. C.

Grade for 8" pipe for 20' No. of N.E. Cor Arctic Bndy to connect with pipe in No. gutr. line of Bndy.



29.63 Bm SW 4th F Plg rt.



79.4°

79.47 Bm n/w 5m3 ASL

70.406 3.W 2d p19



#950

Ditch

H+D 19 L

796 ↓

Monhart a S.W. 63.43

68.29 S.E.

2+18.2 pl. line



550

...d by H. S. CROCKER COMPANY, Stationers, Drawing ...s, and Mathematical Instruments, San Francisco.

*Table showing the difference of latitude and departure in running 80 chains at any course from 1 to 60 minutes.*

| MINUTES. | LKS. | MINUTES. | LKS. | MINUTES. | LKS. |
|---|---|---|---|---|---|
| 1 | 2⅓ | 21 | 49 | 41 | 95⅔ |
| 2 | 4⅔ | 22 | 51⅓ | 42 | 98 |
| 3 | 7 | 23 | 53⅔ | 43 | 100⅓ |
| 4 | 9⅓ | 24 | 56 | 44 | 102⅔ |
| 5 | 11⅔ | 25 | 58⅓ | 45 | 105 |
| 6 | 14 | 26 | 60⅔ | 46 | 107⅓ |
| 7 | 16⅓ | 27 | 63 | 47 | 109⅔ |
| 8 | 18⅔ | 28 | 65⅓ | 48 | 112 |
| 9 | 21 | 29 | 67⅔ | 49 | 114⅓ |
| 10 | 23⅓ | 30 | 70 | 50 | 116⅔ |
| 11 | 25⅔ | 31 | 72⅓ | 51 | 119 |
| 12 | 28 | 32 | 74⅔ | 52 | 121⅓ |
| 13 | 30⅓ | 33 | 77 | 53 | 123⅔ |
| 14 | 32⅔ | 34 | 79⅓ | 54 | 126 |
| 15 | 35 | 35 | 81⅔ | 55 | 128⅓ |
| 16 | 37⅓ | 36 | 84 | 56 | 130⅓ |
| 17 | 39⅔ | 37 | 86⅓ | 57 | 133 |
| 18 | 42 | 38 | 88⅔ | 58 | 135⅓ |
| 19 | 44⅓ | 39 | 91 | 59 | 137⅔ |
| 20 | 46⅔ | 40 | 93⅓ | 60 | 140 |

## TABLE FOR RUNNING ON SLOPES.

*In the following table the first column shows the angle, the second the number of links to be added to a chain on the slopes, to make one chain, horizontal measurement.*

| ANGLE | COR. IN LINKS | ANGLE | COR. IN LINKS | ANGLE | COR. IN LINKS | ANGLE | COR. IN LINKS |
|---|---|---|---|---|---|---|---|
| ° | | ° | | ° | | ° | |
| 4 | 0.24 | 11 | 1.88 | 18 | 5.14 | 25 | 10.54 |
| 5 | 0.38 | 12 | 2.24 | 19 | 5.76 | 26 | 11.26 |
| 6 | 0.55 | 13 | 2.63 | 20 | 6.42 | 27 | 12.24 |
| 7 | 0.76 | 14 | 3.06 | 21 | 7.11 | 28 | 13.37 |
| 8 | 0.98 | 15 | 3.53 | 22 | 7.85 | 29 | 14.34 |
| 9 | 1.24 | 16 | 4.02 | 23 | 8.64 | 30 | 15.47 |
| 10 | 1.55 | 17 | 4.56 | 24 | 9.47 | 35 | 22.07 |