
DIETZGEN
ENGINEERS'
LEVEL BOOK
No. 410
Miscelaneous
Nov 1921 To
F.B. 586

EUGENE DIETZGEN CO.

DRAWING MATERIALS, MATHEMATICAL and
SURVEYING INSTRUMENTS

Chicago New York San Francisco New Orleans Pittsburg Toronto

Distances from Center of Roadway for Cross-Sectioning
Roadway 16 feet wide. Side Slopes 1 on 1.
For Single Track Embankment.

H	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	H
0	8.0	8.1	8.2	8.3	8.4	8.5	8.6	8.7	8.8	8.9	0
1	9.0	9.1	9.2	9.3	9.4	9.5	9.6	9.7	9.8	9.9	1
2	10.0	10.1	10.2	10.3	10.4	10.5	10.6	10.7	10.8	10.9	2
3	11.0	11.1	11.2	11.3	11.4	11.5	11.6	11.7	11.8	11.9	3
4	12.0	12.1	12.2	12.3	12.4	12.5	12.6	12.7	12.8	12.9	4
5	13.0	13.1	13.2	13.3	13.4	13.5	13.6	13.7	13.8	13.9	5
6	14.0	14.1	14.2	14.3	14.4	14.5	14.6	14.7	14.8	14.9	6
7	15.0	15.1	15.2	15.3	15.4	15.5	15.6	15.7	15.8	15.9	7
8	16.0	16.1	16.2	16.3	16.4	16.5	16.6	16.7	16.8	16.9	8
9	17.0	17.1	17.2	17.3	17.4	17.5	17.6	17.7	17.8	17.9	9
10	18.0	18.1	18.2	18.3	18.4	18.5	18.6	18.7	18.8	18.9	10
11	19.0	19.1	19.2	19.3	19.4	19.5	19.6	19.7	19.8	19.9	11
12	20.0	20.1	20.2	20.3	20.4	20.5	20.6	20.7	20.8	20.9	12
13	21.0	21.1	21.2	21.3	21.4	21.5	21.6	21.7	21.8	21.9	13
14	22.0	22.1	22.2	22.3	22.4	22.5	22.6	22.7	22.8	22.9	14
15	23.0	23.1	23.2	23.3	23.4	23.5	23.6	23.7	23.8	23.9	15
16	24.0	24.1	24.2	24.3	24.4	24.5	24.6	24.7	24.8	24.9	16
17	25.0	25.1	25.2	25.3	25.4	25.5	25.6	25.7	25.8	25.9	17
18	26.0	26.1	26.2	26.3	26.4	26.5	26.6	26.7	26.8	26.9	18
19	27.0	27.1	27.2	27.3	27.4	27.5	27.6	27.7	27.8	27.9	19
20	28.0	28.1	28.2	28.3	28.4	28.5	28.6	28.7	28.8	28.9	20
21	29.0	29.1	29.2	29.3	29.4	29.5	29.6	29.7	29.8	29.9	21
22	30.0	30.1	30.2	30.3	30.4	30.5	30.6	30.7	30.8	30.9	22
23	31.0	31.1	31.2	31.3	31.4	31.5	31.6	31.7	31.8	31.9	23
24	32.0	32.1	32.2	32.3	32.4	32.5	32.6	32.7	32.8	32.9	24
25	33.0	33.1	33.2	33.3	33.4	33.5	33.6	33.7	33.8	33.9	25
26	34.0	34.1	34.2	34.3	34.4	34.5	34.6	34.7	34.8	34.9	26
27	35.0	35.1	35.2	35.3	35.4	35.5	35.6	35.7	35.8	35.9	27
28	36.0	36.1	36.2	36.3	36.4	36.5	36.6	36.7	36.8	36.9	28
29	37.0	37.1	37.2	37.3	37.4	37.5	37.6	37.7	37.8	37.9	29
30	38.0	38.1	38.2	38.3	38.4	38.5	38.6	38.7	38.8	38.9	30
31	39.0	39.1	39.2	39.3	39.4	39.5	39.6	39.7	39.8	39.9	31
32	40.0	40.1	40.2	40.3	40.4	40.5	40.6	40.7	40.8	40.9	32
33	41.0	41.1	41.2	41.3	41.4	41.5	41.6	41.7	41.8	41.9	33
34	42.0	42.1	42.2	42.3	42.4	42.5	42.6	42.7	42.8	42.9	34
35	43.0	43.1	43.2	43.3	43.4	43.5	43.6	43.7	43.8	43.9	35
36	44.0	44.1	44.2	44.3	44.4	44.5	44.6	44.7	44.8	44.9	36
37	45.0	45.1	45.2	45.3	45.4	45.5	45.6	45.7	45.8	45.9	37
38	46.0	46.1	46.2	46.3	46.4	46.5	46.6	46.7	46.8	46.9	38
39	47.0	47.1	47.2	47.3	47.4	47.5	47.6	47.7	47.8	47.9	39
40	48.0	48.1	48.2	48.3	48.4	48.5	48.6	48.7	48.8	48.9	40

Example—If point is 22.6 ft. above grade, how far should it be from center line to be a slope stake point? Ans. from Table 30.6. For same slopes but other widths of roadbed, correct above figures by one-half difference in width of roadbed; thus in example above, for 20 ft. roadbed distance will be 30.6+(20—16)÷2 or 2 ft. added to 30.6 =32.6. For slopes of 1 on 1½ see inside of back cover.

Copyright, 1914, by Eugene Dietzgen Co.

DIGITIZED BY GOOGLE

F.B. 586

Front St.	Palm to Quince	4 - 7
Tie cross-section	Front St	35 - 38
Alley Blk. 60 Univ. Hts	Monroe to Madison Ohio - Illinois	8 - 11
Palm	Kettner to Pacific sketch	12 - 19
Vine	Calif. to Pacific sketch. (13)	20 - 23
Maple	32 to 33 sketch	25 - 32
Oil Road proposed	Columbia South to Sassafrass	34
Narragansett Ave.	Warrington & Catalina	38 - 40
Final Paving Measurement's on Alley Blk 72 Ocean Beach		41
Alley Blk 106 Univ. Hts		50 - 55
Dupont	Catalina to Bow sketch	56 - 64
Silvergate	Dupont to Charles	65 - 71
BORN.	Dupont to Dudley	72 - 75

Topog. Quince St Front Block 349 & 350

					N.W. BP Redwood + 2 rods
BM	0.94	266.47		265.53	
TP	0.85	254.33	12.99	253.48	
BM			8.87	245.46	SE Top F Hyd Redwood + 1st Fire
TP	2.11	243.63	12.81	241.52	
Top Curb	W.L. 1st Fire	East ℄	1.77	241.86	
TP	1.06	232.48	12.21	231.42	
2+20	Base Line		3.43	229.05	on Stub
1+60	" "		7.48	225.00	on Stob
1+18.74	Base Line		11.58	220.90	on Hub
1+60	225 W of ℄		12.93	219.55	on Stob

April 19-46
S. Sloan
Wright
Waddell



Grades - Euclid N. of Klauber

Smale / Chisholm 11-10-21 1

	+	HI	−	Elev.
BM	1.99	42.62		340.63
TP			5.26	37.36
✓	10.68	48.04		37.36
2+00				
" +50				
3				
+50				
4				
+50				
5				
TP			3.81	44.23
✓	3.26	47.49		44.23
5+50				
6+00				

82/2

BP - N. W. Univ. & Euclid

W/S	Grade	Cut	E/S	Grade	Cut
10.68 / 37.36	38.33	F 0.97	—		
7.25 / 40.79	38.60	G - 2.19	11.44 / 36.60	38.60	F 2.00
6.24 / 41.80	38.87	✓ 2.93	8.42 / 39.62	38.87	G 0.75
5.23 / 42.81	39.14	✓ 3.67	6.67 / 41.37	39.14	✓ 2.23
4.54 / 43.50	39.41	✓ 4.09	5.69 / 42.35	39.41	✓ 2.94
3.74 / 44.30	39.68	✓ 4.62	4.54 / 43.50	39.68	✓ 3.82
3.81 / 44.23	39.96	✓ 4.27	3.88 / 44.16	39.96	✓ 4.20
4.38 / 43.11	40.23	✓ 2.88	3.43 / 44.06	40.23	✓ 3.83
5.21 / 42.28	40.5	✓ 1.78	3.81 / 43.68	40.50	✓ 3.18

Curb Grades Daley Ave Diagram

Univ. to Klauber

	West	M	M	East
0+00 SL Univ	346.8			347.2
2+40	338.4 X 4/4=1/16=		1/4=1/16=.035 1/2=1/4=.13 3/4=9/16=.30	X339.4
A°	337.0+.4=	M=+.4	M=+.52	338.0+.52=
2+80	337.4 X			X338.52
40'				
3+20	337.2 X			X338.3
N.L. Klauber 6+00	338.6			339.7
S.L. Klauber	338.0			339.0

Stake Lots

Block	Lots
5	48
	47
	46
	45

DEC 23 1921

DEC 23 1921 31+034

DEC 23 1921 29+30

DEC 23 1921 55 25-6-7-8

DEC 23 1921 Return

Lots	Block
11-12	
15-16	54
17-18	
21-22-23-24	54

DEC 23 1921

DEC 23 1921

DEC 23 1921

DEC 23 1921

Ford
Smale
Chisholm
Nov 12-21

SW Stakes Daley

Sta	+	HI	−	Elev	
BM				338.03	52/19
NE Klauber Daley	6.32	344.35	4.65	339.70	
BM				338.03	52/19
NW Klauber Daley	6.66	344.69	6.09	338.6	
				338.03	
NE Klauber Daley	6.15	344.18	4.48	339.70	
				338.03	
N.W. Klauber Daley	5.71	343.74	5.14	338.60	
330' N of NL Klauber NL Daley			6.34	337.40	
				338.03	
330' N of NL Klauber E L Daley	6.70	344.73	6.21	338.52	
			5.03	339.70	
BM				338.03	52/19
	5.41	343.44	4.84	338.60	M=4

B.P. SW Klauber Daley

P

N/S Klaub

11-28-21

Front St. Cross Section
Palm St to Quince St.

BM	1.10	249.39		248.29	HE BP Palm & 1st
TP	0.52	237.39	12.52	236.87	
TP	1.59	226.85	12.13	225.26	
		0+0 = N.L. Palm St.			
F Cb Top			3.00	223.85	✓
Gutter			3.77	223.08	✓
+2.5 = W.L. Conc Gutter			3.85	223.00	
¼ on Pav			3.90	222.95	
½ " "			4.17	222.68	✓
¼ " "			4.61	222.24	
Gutter " "			5.21	221.64	✓
Cb Top			4.52	222.33	✓
+10			4.5	222.3	
W			6.1	220.7	
		0+50			
W			9.0	217.8	
C			8.0	218.8	
¼			7.5	219.3	
½			7.3	219.5	

Reduced - plot 11-2-39 - Profile #351 CB Hough

80' Wide
20' C&S
10' ½

Indexed
C.S.K.

Oct 31-39
Sisson
Northern

4



		226.85	
¼		7.0	219.8
+7.5 = Wly Con Gutter		7.24	219.61
Gutter		7.19	219.66 ✓
E Cb Top		6.92	220.43 ✓
	0+75		
E Cb Top		8.14	218.71
Gutter		9.03	217.82
+2.5 = Wly Con Gutter		8.99	217.76
¼		8.8	218.0
℄		8.7	218.1
¼		8.2	218.6
Cb		9.6	217.2
W		11.7	215.1
+5		12.3	214.5
	1+0		
-10		15.2	211.6
W		14.9	211.9
Cb		12.3	214.5
¼		9.6	217.2

		226.85	
℄		10.3	216.5
¼		10.5	216.3
+7.5 = Wly Con Gutter		10.68	216.17
Gutter		10.74	216.11 ✓
E Cb Top		9.90	216.95 ✓
TP	1.28	216.33	11.80 215.05
	1+25		
E Cb Top		1.11	215.22 ✓
Gutter		1.95	214.38 ✓
+2.5 = Wly Con Gutter		1.89	214.44
¼		1.8	214.5
℄		1.6	214.7
¼		1.4	214.9
Cb		5.2	211.1
W		8.6	207.7
+15		9.6	206.7
	1+50		
-20		17.5	198.8 Tb ~~208.8~~
W		13.5	202.8

216.33

Cb	9.6	206.7
¼	3.6	212.7
℄	3.5	212.8
¼	3.6	212.7
+7.5 = N'ly Conc Gutter	3.68	212.65
Gutter	3.69	212.64
E Cb Top	3.86	213.47
1775		
E Cb Top	4.67	211.66
Gutter	5.53	210.80
+2.5 = N'ly Conc Gutter	5.42	210.91
¼	5.6	210.7
℄	5.2	211.1
+7	5.6	210.7
¼	7.1	209.2
Cb	13.0	203.3
W	20.3	196.0
+25	30.3	186.1

216.33

270

-85	43.3	173.0
W	26.8	189.5
Cb	19.0	197.3
¼	12.9	203.4
℄	7.0	209.3
¼	7.2	209.1
+7.5 = N'ly Conc Gutter	7.12	209.21
Gutter	7.18	209.15
E Cb Top	6.84	209.99
2+25 = N'ly End Cb & Walk on East		
E Cb Top	8.30	208.03
Gutter	9.11	207.22
+2.5 = N'ly Conc Gutter	9.11	207.22
¼	8.8	207.5
℄	8.3	208.0
¼	16.0	200.3
Cb	23.2	193.1
W	35.5	180.8

		216.83			
+45			58.3	163.0	
	2+50				
-50			62.0	154.3	2+39 = NW End Conc Drive 9.42
W			42.6	173.7	
cb			28.8	187.5	
¼			20.2	196.1	
℄			12.0	204.3	
¼			9.4	206.9	
cb			9.2	207.1	
E = Sly 6' Conc Dr.			8.85	207.48	✓
TP	3.86	211.63	8.56	207.77	
TP	3.18	208.74	11.07	200.56	
	2+75				
E			0.0	203.7	
cb			8.3	195.4	
¼			8.5	195.2	
℄			9.2	194.5	
¼			13.2	190.5	
cb			18.0	185.7	

	208.74			
W		38.0	170.7	
+15		40.8	162.9	
+55		44.0	159.7	
	3+0 = S.L. Quince			
-50		34.0	169.7	
-25		35.0	168.7	
W		42.2	161.5	
cb		30.5	173.2	
¼		26.2	177.5	
℄		23.0	180.7	
¼		18.6	185.1	
cb		16.0	187.7	
E		10.0	193.7	

Alley Block 60 Univ Hgts. Cross Section
Between Ohio & Illinois From
Monroe to Madison

Indexed C.S.K.

0.0 + 31.39 Sinsq Northern

BM	6.91	392.91		386.00	S.E.B.P. Madison & 3rd St
TP	3.82	393.51	3.22	389.69	
	0 - 14 = SCb of Madison				
W	on Par		4.46	389.05	
Z	" "		4.53	388.98	
E	" "		4.40	389.11	
	0 + 0 = SL Madison				
E	Top Cb		3.92	389.59	
Gutter	on Par		4.22	389.29	
Z	" "		4.18	389.33	
Gutter	" "		4.05	389.46	
W	Top Cb		3.82	389.69	
	0 + 22				
W			4.2	389.3	
Z			4.0	389.5	
E			3.8	389.7	
+5 = Z	Garage N Ent Conc Floor		3.50	390.01	

Reduced Plat on Profile 2251 11-2-39 CBH



89351

0+50

E		4.2	389.3
℄		4.2	389.3
W		4.7	388.8

1+00

W		4.9	388.6
+0.5' = W/y Post Pole			
℄		4.6	388.9
E		4.7	388.8

1+34

-3.5 = ℄ Garage Dirt Floor		4.5	389.0
E		4.5	389.0
℄		4.8	388.7
W		5.1	388.4

1+65

W		5.5	388.0
℄		5.3	388.2
E		5.3	388.2

89351

1+79

-4.5 = N/y Do Garage Conc Floor		4.65	388.86
E		5.1	388.4
℄		5.4	388.1
W		5.7	387.8

1+98

W		5.4	388.1
℄		5.4	388.1
E		5.1	388.4
+4.5 = S/y Do Garage Conc Floor		4.62	388.89

1+99

0.6' E of W.L = Post Pole

2+0 - N/y 4 Garages on W

E		5.1	388.4
℄		5.4	388.1
W = N/y 4 Car Garage on Conc Apron		5.56	387.95
+2' = Garage Floor		5.49	388.02

	393.51		
2+37 = S1y 4 Garages			
-2' = Garage Floor Conc	5.43	388.08	✓
W on Conc Apron	5.62	387.89	✓
℄	5.41	388.10	
E	5.5	388.0	
2+76			
0.8' E of W.L. = Pav Pole			
2+87			
E	5.9	387.6	
℄	5.8	387.7	
W	5.9	387.6	
+1.7 = ℄ Garage Dirt Floor	5.7	387.8	✓
3+09			
W	6.2	387.3	
℄	5.9	387.6	
E	5.8	387.7	
+0.7' = Conc Apron	5.73	387.78	✓
+6.7 = Garage Floor Conc	5.63	387.88	✓

	393.51		
TP	4.25	392.01	5.75	387.76	
3+34					
E = ℄ 3' Conc Gutter			4.69	387.32	✓
℄			4.5	387.5	
W			4.4	387.6	
3+62.7 = NCb Walton Pl. on W					
W Top Cb			4.81	387.20	✓
Gutter on Pav.			5.07	386.94	✓
℄			4.9	387.1	
E			4.7	387.3	
3+73 = N1y Conc Drive on E					
E			4.92	387.59	✓
3+74.5 = ℄ Walton on W					
W on Pav			5.01	387.00	✓
3+86.3 NSCb Walton Pl on W					
E on Conc. Drive			4.48	387.53	✓
℄			4.7	387.3	
W Gutter			5.29	386.72	✓
W Top Cb			4.92	387.09	✓

	392.01						392.01			
	3+89				TP	4.92	391.50	5.43	386.58	
1.0' E of W.L = Power Pole					TP	2.82	386.61	7.71	383.79	
	4+30				BM			7.64	378.97	S.E. BP Monrock 30 ft 378.95
W		4.9	387.1							
℄		4.7	387.3							
E		4.7	387.3							
+12 = ℄ Garage		4.6	387.4	✓						
	4+59									
E		4.9	387.1							
℄		4.7	387.3							
W = W℄ Do. Garage Conc Floor		4.77	387.24							
	4+68									
E		4.7	387.3							
+13 = ℄ Garage 1st Floor		4.6	387.4	✓						
	4+74.3									
E		4.9	387.1							
℄		5.0	387.0							
+93 = W℄ Bm Blk										
W = S℄ Do. Garage Conc Floor		4.90	387.11	✓						

X Sec Palm 80 wide 1-25-40
Ker. to Pac. 14 c66
18 1/4

INDEXED
E.F.B.

12

S.E.BP	1.5 ✓	59.01 ✓	57.49	Palm & Ker.
	0-12 w c6 Ker.			E.C. Pacific
				63.47
S c6		2.54	56.47	
S par gut		3.20	55.81	
c6 "		3.10	55.91	
1/4 "		3.01	56.00	
c "		2.96	56.05	
1/4 "		2.81	56.20	
c6 "		2.74	56.27	
N " gut		2.69	56.32	
N c6		2.05	56.96	
	0+0			
N c		1.8	57.2	
N + 14.7		2.20	56.81	
gut par		2.90	56.11	
1/4 "		2.41	56.40	
c "		2.46	56.35	
1/4 "		2.87	56.14	



59.01

S gut	par		3.41	55.60
S cb			-.74	56.25
S			2.5	56.5
	0+1.5	S+12	12" P.P	
	0+15			
S			2.8	56.2
cb			4.5	54.5
1/4			3.7	55.3
C			3.7	55.3
1/4			4.1	54.9
cb			3.4	55.6
N			2.1	56.9
	0+35			
N			2.9	56.1
1/4			5.7	53.3
1/4			7.0	52.0
cb			6.4	52.6
1/4			7.4	51.6
C			7.5	51.5
1/4			7.5	51.5



5901

c6	8.0	51.0	
+1½	6.0	53.0	
S	3.1	55.9	
0+50			
S	5.2	53.8	
+3	9.1	49.9	
c6	9.7	49.3	
1/c	10.2	48.8	
c	10.0	49.0	
1/c	10.6	48.4	
c6	9.5	49.5	
+1½	9.4	49.6	
N	6.2	52.8	
+1	OUTS are Top of Cut 4.6	54.4	
0+96	S+12 12" P.P.		
1+00			
-1	10.0	49.0	
N	3.1	45.9	
+6	14.5	42.5	
c6	14.7	42.3	

5901

1/c	17.3	41.7	
c	18.3	40.7	
1/c	18.3	40.7	
c6	18.0	41.0	
+10	17.4	41.6	
S	14.3	47.7	
T.P. 1.12	47.25	12.88	46.13
1+50			
-1	5.5	41.8	
S	7.5	39.8	
+2	10.3	37.0	
+4	13.0	34.3	
c6	13.1	34.2	
1/4	14.3	33.0	
c	13.6	33.7	
1/c	13.2	34.1	
c6	13.2	34.1	
+9	12.2	35.1	

		47.25 ✓			
cb + 13			9.9	37.4	
N			5.7	41.6	
+ 1			4.0	43.3	
T.P.	0.09	34.59 ✓	12.75 ✓	34.50	
T.P.	1.01	33.31 ✓	2.29	32.30	Nail in Pole
	1 + 75				
- 1			+ 8.0	41.1	
N			+ 6.1	39.4	
+ 4			+ 1.7	35.0	
+ 9			0.3	33.0	
cb			0.5	32.8	
1/4			2.2	31.1	
C			3.2	30.1	
1/4			3.4	29.9	
cb			2.1	31.2	
+ 2	14"	P.P.			
+ 7			2.1	31.2	
+ 12			+ 1.1	34.4	

		38.31 ✓		
S		+ 4.1	37.4	
+ 1		+ 5.5	38.8	
	1 + 86			
- 1		+ 3.7	37.0	
S		+ 2.4	35.7	
+ 6		3.0	30.3	
cb		3.8	29.5	
1/4		3.1	30.2	
C		3.2	30.1	
1/4		2.9	30.4	
+ 7		1.0	32.3	
+ 10		+ 1.7	35.0	
cb		+ 3.4	36.7	
N		+ 5.6	38.9	
	2 + 00.49 = EL Coll 4			
N		+ 6.0	39.3	
cb		+ 5.7	39.0	
+ 4		+ 5.7	39.0	
+ 8		1.0	32.3	
1/4		2.4	30.9	

33.31

C	3.8	29.5
1/4	4.9	28.4
C6	3.8	29.5
+9	2.0	31.3
S	+3.2	36.5
2+05		
S	0.3	33.0
+2	1.6	31.7
C6	2.1	31.2
+5	2.2	31.1
1/4	5.8	27.5
+9	2.0	31.3
C	1.9	31.4
1/4	1.4	31.9
C6	0.0	33.3
N	2.5	30.8
2+16		
N	6.4	26.9
C6	6.5	26.8
1/4	6.7	26.6

33.31

C	6.9	26.4
1/4	6.8	26.5
C6	6.8	26.5
S	6.8	26.5
2+24.09 = E rails		
S E rail	5.88	27.43
S E	6.2	27.1
S W "	6.04	27.27
C " "	5.70	27.61
C E	5.9	27.41
C E "	5.53	27.78
N " "	5.20	28.11
N E	5.7	27.61
N W "	5.39	27.92
2+32		
N	7.0	26.3
C6	7.0	26.3
1/4	7.2	26.1
C	7.3	26.0
1/4	7.4	25.9

33.31

c6	7.6	25.7	
9	7.8	25.5	
2 +38			
5	4.0	29.3	
c6	4.0	29.3	
1/4	4.7	28.6	
c	4.6	28.7	
1/4	4.1	29.2	
c6	4.4	28.9	
N	4.7	28.6	
+7 & Blk. Signal			
2 +75.49 WL Call			
-10	5.2	28.1	
N	5.4	27.9	
c6	5.8	27.5	
1/4	5.9	27.4	
c	6.2	27.1	
1/2	6.2	27.1	
c6	6.6	26.7	
+9	6.9	26.4	

33.31

5	4.9	28.4
2 +79		
5	5.0	28.3
+5	7.1	26.2
c6	6.9	26.4
1/4	6.7	26.6
c	6.3	27.0
1/4	7.0	26.3
c6	6.3	27.0
+11	5.9	27.4
N	8.6	24.7
+10	13.0	20.3
3 +00		
-10	13.8	19.5
N	9.8	23.5
+2	8.6	24.7
c6	8.6	24.7
1/4	9.6	23.7
c	9.3	24.0
1/4	9.5	23.8

		33.31		
c6			8.6	24.7
+7			10.3	23.0
S			6.0	27.3
3+05	14" P.P.	S +1N		
T.P.	0.98	21.68	17.41	20.70
3+40				
S			2.7	19.0
c6			2.8	18.9
1/4			2.8	18.9
c			2.7	19.0
1/4			2.9	18.8
c6			3.5	18.2
+6			3.5	18.2
+10			4.4	15.3
N			4.5	15.2
+7	SE Cor Span Stucco Bldg.		6.3	15.4

	27.68		
3+47			
-7 & 9' opening		6.57	15.11 Con. El. of Sp.
N		6.6	15.1 Stucco Co.
c6		6.7	15.0
1/4		6.3	15.4
c		6.3	15.4
1/4		6.6	15.1
c6		6.5	15.2
S		6.8	14.9
3+96	15" PP	S +11.8	
3+98	12" "	N +9.5	
4+07.30	& Span on & Path		
S & rail		6.70	14.98
S &		7.1	14.6
S W "		6.48	15.00
C " "		6.98	14.70
C &		7.1	14.6
C E "		6.93	14.75
N " "		7.34	14.34
N E		7.8	13.9
N W "		7.44	14.24

℄ +18 S +10 Sta. R.R. xing Post			
℄ +37			
N		7.5	14.2
cb		7.3	14.4
1/℄		7.2	14.5
C		7.3	14.4
1/℄		7.2	14.5
cb		7.2	14.5
+6.6 12" P.P. Guy Pole			
S		6.8	14.9
℄ +76.21 E.C. Pacific			
S		6.7	15.0
+10.7 Top cb end		6.93	14.75
" out Pav		7.61	14.07
cb	"	7.60	14.08
1/℄	"	7.59	14.09
C	"	7.73	13.95
1/N	"	7.95	13.73
cb	"	8.19	13.49

cb +3.2 Pav.		8.26	13.42	
cb + 4.7 out Pav		8.10	13.58	
" " ~~Top cb. end~~ cont. sdw.		8.10	13.58	
N Conc. drive		7.59	14.09	
8' West E cb Pacific				
N-17 Top cb		7.28	13.80	cb end
" out		8.44	13.24	beg. cont. S dw. of Drive 1x to 0.1 Sta.
N "		8.23	13.45	
C Pav		7.93	13.75	
S "		7.41	14.07	
S Top cb.		7.04	14.64	
B.P. Front of Lindberg Field Bldg		9.46	12.22	12.22 0.0N

1-25-40

Xsec Vine St. 80 wide
Calif. to Pacific 14' CGS
18' ½
See Sketch p 13
" FB 1258-40

SEBD	7.53	42.11		39.58	Vine + Kct.
T.P.	0.76	30.14	12.73	29.38	

0+00 W.L. Calif to North

S		7.6	22.5
c6		7.0	23.1
1/4		8.2	21.9
C		8.5	21.6
1/4		9.3	20.8
c6		8.3	21.8
N		7.0	23.1

0+06.88 = 90° with SW Cor.

N		7.6	22.5
c6		7.5	22.6
1/4		7.5	22.6
C		7.6	22.5

Notes Reduced + Plotted on Profile #713 1-27-40 GBM

30.14

INDEXED EFB

20

1/4			7.6	22.5
c6			7.1	23.0
S			7.5	22.6
	0+08.93	Int. ℄ Vine	℄ R.R.	
S	E rail		6.99	23.15
S	W "		7.13	23.01
C	W "		7.17	22.97
C	E "		7.00	23.14
N	" "		7.03	23.11
N	W "		7.23	22.91
	0+14			
N			8.0	22.1
c6			8.1	22.0
1/4			8.1	22.0
C			7.9	22.2
1/4			7.8	22.3
c6			7.8	22.3
S			7.8	22.3
T.P.	0+41	18.20	12.35	17.79

1820 ✓

0+80			
-10		1.8	16.4
S		1.7	16.5
c6		1.7	16.5
1/4		1.6	16.6
C		1.4	16.8
1/4		1.1	17.1
c6		0.9	17.3
N		0.7	17.5
0+84			
-10		0.6	17.6
N		2.0	16.2
c6		2.0	16.2
1/4		2.1	16.1
C		2.1	16.1
1/4		2.1	16.1
c6		2.3	15.9
+3	12" R.P.		
S		2.4	15.8
+10		2.5	15.7

1820 ✓

0+73			
-10		4.4	11.8
S		4.9	13.3
c6		3.9	14.3
1/4		3.7	14.5
C		3.6	14.6
1/4		3.3	14.9
c6		3.2	15.0
N		3.2	15.0
+10		3.0	15.2
0+90			
-10		3.5	14.7
N		3.7	14.5
c6		3.7	14.5
1/4		3.7	14.5
C		4.0	14.2
1/4		4.8	13.4
c6		6.0	12.2
S		6.3	11.9
+10		6.4	11.8

18.20

1+09			
-10		4.5	11.7
S		4.4	11.8
cb		4.3	11.9
1/4		4.0	12.2
C		3.6	12.6
1/4		3.9	13.3
cb		3.8	13.8
N		3.8	13.8
+10		3.8	13.8
1+21.09 - MHT Sardine			
-10		3.9	13.3
N		3.9	13.3
cb		4.0	13.2
1/4		4.0	12.2
C		4.2	12.0
1/4		4.4	11.8
cb		4.5	11.7
S		4.6	11.6
+10		4.6	11.6

18.20

1+50			
S		7.0	11.2
cb		6.9	11.3
1/4		6.8	11.4
C		6.8	11.4
1/4		6.7	11.5
cb		6.8	11.4
N		6.9	11.3
1+72	S + 11.7	14" P.P.	
2+00			
N		7.7	10.5
cb		7.6	10.6
1/4		7.3	10.9
C		7.2	11.0
1/4		7.1	11.1
cb		7.0	11.2
S		7.0	11.2
2+43.3	end Pav. at Pac.		
S		7.7	10.5
cb	Top end	7.73	10.47

S qut pav		8.2N	9.98
1/4	"	7.9N	10.28
c	"	7.75	10 45
1/4	"	7.9N	10 28
qut	"	8.20	10.00
N cb Top end		7.55	10 65.
N		7.8	10.4
C.T. N+53.70. Int. Evine & El. Pac.			
N		7.9	10.3
+10 cb		7.88	10.32
" qut Pav		8.45	9.75
cb	"	8.38	9.82
1/4	"	8.25	9.95
c C.T.	"	8.19	10.01
1/4	"	8.27	9 93
cb	"	8.46	9.74
+4 qut	"	8.49	9.71
cb Top		8.01	10.19
S		8.1	10.1

E cb Pac				
S Top cb		8.21		9.99
S qut pav		8.76		9 44
c "		8.45		9 75
N+c "		8.43		9 57
" Top cb. P.C.		8.03		10 17
T.P.	3.45	13.45	8.20	10.00
T.P.	5.70	11.65	8.50	8.95
NEBP Pac. & Harmsby		8.60	10.05	10.00

Cross Section Maple St 32nd St to 33rd St

BM	1.59	302.70	301.11	SW. BP Maple & 32nd
		FCb 32nd St		
S	Cb Top	2.91	299.79	
S	Gutter on Paving	3.94	299.26	
Cb	" "	3.70	299.00	
¼	" "	4.14	298.56	
½	" "	4.56	298.14	
¼	" "	5.04	297.66	
Cb	" "	5.75	296.95	
H	" "	6.36	296.34	
H	Cb Top	5.60	297.10	
		0+0 = FL 32nd St		
H		5.37	297.33	
½	= Sly Conc Walk	5.38	297.32	
Cb	Top	5.42	297.28	
Gutter on Paving		5.96	296.74	
¼	" "	5.12	297.58	
½	" "	4.37	298.33	
¼	" "	3.93	298.77	

Reduced & Plotted By H.M. Cole 7/15/40 Profile 620

INDEXED EFB



Sd 43.4 Sisson Northern Moore

225

	302.70		
Gutter on Paving		3.67	299.03
CL Top		2.94	299.76
S of Conc Walk		2.8	299.9
	0+35		
S		1.2	301.5
+2		2.8	299.9
+5		3.4	299.3
CL		3.9	298.8
¼		4.3	298.4
½		4.8	297.9
¼		5.2	297.5
CL		5.5	297.2
+4 = S/y Conc Walk		5.40	297.30
	0+50		
N +6 = S/y Conc Walk		5.45	297.25
CL		5.5	297.2
¼		5.5	297.2
½		5.1	297.6
¼		4.8	297.9

	302.70		
+8		4.7	298.0
CL		4.4	298.3
+4		4.0	298.7
+7		3.3	299.4
S		+1.5	304.2
	0+70		
S		0.9	301.8
+1		3.0	299.7
+7		4.6	298.1
CL		4.8	297.9
+4		5.2	297.5
¼		5.0	297.7
½		5.1	297.6
¼		5.6	297.1
CL		5.8	296.9
+4 S/y Conc Walk		5.51	297.19
	1+0		
N +6 = S/y Conc Walk		5.63	297.07
CL		6.1	296.6
¼		6.0	296.7

		302.70		
℄		5.5	297.2	
1/4		5.5	297.2	
+7		5.4	297.3	
Cb		5.2	297.5	
+6		4.4	298.3	
S		3.9	299.8	
TP	2.92	300.10	5.52	297.18
		1+01		
-11.6	= Wly Do Garage Conc Floor		0.65	299.45
-0.8'	= N Wly Conc Apron		2.09	298.01
S			2.1	298.0
SCb			2.7	297.4
		1+17		
-11.6	= Ely Do. Garage C.F.		0.67	299.43
-0.2'	= N Ely Conc Apron		2.42	297.68
S			2.5	297.6
SCb			3.0	297.1
		1+25		
S			0.3	299.8

		300.10		
+6			2.7	297.4
Cb			3.1	297.0
+5			3.6	296.5
1/4			3.3	296.8
℄			3.3	296.8
1/4			3.7	296.4
Cb			3.7	296.4
+4 = Sly Conc Walk			3.51	296.59
		1+50		
N+6 = Sly Walk			3.99	296.11
Cb			4.2	295.9
+3			4.4	295.7
1/4			4.2	295.9
℄			3.9	296.2
1/4			3.8	296.3
+5			4.0	296.1
Cb			3.6	296.5
+7			3.0	297.1
S			1.7	298.4

Maple St.

300.10

270

S	4.0	2961
Cb	4.4	2957
+2	4.9	2952
¼	5.0	2951
½	5.1	2950
¼	5.2	2949
Cb	5.2	2949
+4 = S/y Conc Walk	4.84	29526
27046 on N		
27085 on S = W/y Edge Paving Bancroft		
N 76 = S/y Conc Walk	4.90	29520
Cb Top	4.99	29511
Gutter on Paving	5.54	29456
¼ " "	5.28	29482
½ " "	5.10	29500
¼ " "	5.10	29500
Gutter " "	5.29	29481
Cb Top	4.62	29548
S	4.3	2958

300.10

W Cb Bancroft

S Cb Top	4.57	29553
S Gutter on Paving	5.26	29484
Cb " "	5.38	29472
¼ " "	5.44	29466
½ " "	5.55	29455
¼ " "	5.69	29441
Cb " "	5.73	29437
N Gutter " "	5.82	29428
N Cb Top	5.15	29495

E Cb Bancroft

W Cb Top	6.15	29395
Gutter on Paving	6.77	29333
Cb " "	6.48	29362
¼ " "	6.09	29401
½ " "	5.88	29422
¼ " "	5.86	29424
Cb " "	6.00	29410
S Gutter " "	6.05	29405

	300.10		
S Cb Top	5.68	294.42	
0+01.5 ∩ S Cb 0+08.6 " N Cb = Fly Edgr. Paving			
S ∩ Conc Walk	5.45	294.65	
Cb Top	5.87	294.23	
Gutter ∩ Paving	6.48	293.62	
¼ " "	6.18	293.92	
½ " "	6.06	294.04	
¼ " "	6.35	293.75	
Gutter " "	6.84	293.26	
Cb Top	6.21	293.89	
N	5.9	294.2	
	0+25		
N	7.2	292.9	
+½	8.1	292.0	
Cb	7.7	292.4	
¼	7.3	292.8	
½	7.1	293.0	
¼	7.1	293.0	
Cb	7.0	293.1	

	300.10		
S	7.0	293.1	
	0+50		
S	8.4	291.7	
Cb	9.0	291.1	
¼	9.5	290.6	
½	9.3	290.8	
¼	10.0	290.1	
Cb	10.2	289.9	
+7	9.8	290.3	
N	8.6	291.5	
	0+75		
N	11.0	289.1	
+5	11.6	288.5	
Cb	11.6	288.5	
¼	11.4	288.7	
½	11.1	289.0	
¼	10.9	289.2	
Cb	10.8	289.3	
+5	9.9	290.2	

Maple St.

	300.10			
S		9.7	290.4	
	0+92			
N = S Wly Conc Apron		11.71	288.39	
N - 18 : Wly Do Garage C.F.		11.28	288.82	
	1+09			
S		11.5	288.6	
Cb		11.8	288.3	
¼		12.1	288.0	
Δ		12.4	287.7	
¼		12.7	287.4	
Cb		12.9	287.2	
N		12.7	287.4	
N = S Ely Conc Apron		12.32	287.78	
+18 : Ely Do Garage C.F.		11.23	288.87	
	1+22			
S - 13.3 = Δ Conc Apron		10.99	289.11	
S - 17.3 = Δ Do Garage Conc Floor		10.88	289.22	
TP	1.27	289.21	12.16	287.94

	289.21		
	1+34		
-16.4 = S Wly Do Garage Conc Floor	3.64	285.57	
-6.3 = S Wly Conc Apron	3.68	285.53	
N	3.8	285.4	
Cb	3.5	285.7	
¼	3.8	285.4	
Δ	3.6	285.6	
¼	3.3	285.9	
+6	3.2	286.0	
Cb	2.4	286.8	
+6	1.4	287.8	
S	1.3	287.9	
	1+50		
N -16.4 = S Ely Do Garage C.F.	3.65	285.56	
N -6.3 = S Wly Conc Apron	3.94	285.27	
	1+75		
S	2.7	286.5	
Cb	4.7	284.5	
+5	5.7	283.5	

	2+89.21		
¼	6.0	28 3 2	
½	6.3	28 2 9	
¼	6.4	28 2 8	
Cb	6.2	28 3 0	
N	6.2	28 3 0	
	2+0		
N	8.0	28 1 2	
Cb	8.2	28 1 0	
¼	8.5	28 0 7	
½	8.3	28 0 9	
¼	8.0	28 1 2	
Cb	6.5	28 2 7	
+5	6.1	28 3 1	
S	4.2	28 5 0	
	2+10 = N ¼ Imp. on 33rd St.		
S	5.6	28 3 6	
+4	7.3	28 1 9	
Cb	7.7	28 1 5	
+1.8 = Back Rolled Cb Top	8.73	28 0 48	

	2+89.21		
Gutter on Paving	9.07	280.14	
¼ " "	9.01	280 20	
½ " "	9.10	280 11	
¼ " "	9.27	279 94	
Cb " "	9.57	279 64	
+1.8 " "	9.58	279 63	
+1.8 = Back Rolled Cb Top	9.25	279 96	
+6.8 = N ½ (conc) walk	92	280 0	
N	8.8	280 4	
	2+31 = N Cb 33rd St		
-11 = Cb BC	8.76	280 45	
Gutter on Pav	9.02	280 19	
N " "	9.37	279 84	
Cb " "	9.68	279 53	
¼ " "	9.80	279 41	
½ " "	9.80	279 41	
¼ " "	9.79	279 42	
Cb " "	9.75	279 46	
S " "	9.85	279 36	

		289.21			
+10 = Gutter on Pav			9.43	279.78	
+10 = CL BC Top			8.67	280.54	
TP	10.90	299.40	0.71	288.50	
TP	529	302.74	1.95	297.45	S.W. B.P. MAP/4482 301.11
BM			1.62	301.12	

Proposed Oiled Road
Columbia St South of Sassafras

INDEXED
EPB

Sept 6-40
Sissa
Northern
N Moore



RC Cross Section Front St
Palm St North
See Sketch Page 4

BM	5.86	228.19	222.33	Top Curb N L Palm N Cb Front St Page 9
		N W Return		
N End Cb: N L Palm		5.86	222 33	
Gutter		6.51	221. 68	
	9.22 SW			
Cb Top		6.00	222 19	
Gutter		6.61	221.58	
	18.45 SW			
Cb Top		6.25	221 94	
Gutter		6.90	221 29	
	27.67 SW			
Cb Top		6.57	221 62	
Gutter		7.21	221 98	
	36.9 SW = W Cb E C			
Cb Top		6.87	221.32	
Gutter		7.61	220 58	
	N E Return			
N Cb = N L Palm		4.84	223 85	
Gutter		5.13	223 06	

INDEXED
EFB

Nov 23-40
S. 1507
Northern
W Moore

	228.19		
	9.47 SE		
Cb Top		4.47	223 72
Gutter		5.20	222 99
	18.95 SE		
Cb Top		4.40	223 79
Gutter		5.10	223 09
	28.42 SE		
Cb Top		4.25	223.94
Gutter		4.93	223.26
	37.90 SE = E Cb E C.		
Cb Top		4.00	224.19
Gutter		4.65	223 54
	0-25 = N Cb L. of Palm St.		
E Cb on Paving		5.38	222 81
Δ " "		6.09	222 10
W Cb. " "		6.85	221 34
	0+0		
W		6.9	221.3
Cb Top		5.86	222.33

Red. 9.4 Jobs Corrected.
11-25-40
B.M.

228.19		
Gutter	6.51	221.68
¼	5.94	222.25
℄	5.52	222.67
¼	5.26	222.93
Gutter	5.13	223.06
ECb Top	4.34	223.85
0+50		
ECb Top	7.77	220.42
Gutter	8.54	219.65
¼	8.4	219.8
℄	8.5	219.7
¼	8.7	219.5
+5 = Wly Oil Pox	8.9	219.3
Cb	9.5	218.7
W	10.1	218.1
+9 = Ely House	10.1	218.1
0+70		
16.6 E of ℄ = Wly Power Pole		

228.19		
0+75		
-10	12.7	214.5
W	11.0	217.2
Cb	9.5	218.7
+5	9.4	218.8
+8 = Wly Oil Pox	10.3	217.9
¼	10.2	218.0
℄	10.1	218.1
¼	10.1	218.1
Gutter	10.25	217.84
ECb Top	9.49	218.70
1+0		
ECb Top	11.23	216.96
Gutter	12.07	216.12
¼	11.8	216.4
℄	11.7	216.5
¼ = Wly Oil Pox	11.7	216.5
+2	11.0	217.2
Cb	11.6	216.6

		228.19		
+5			12.1	216.1
TP	1.80	217.66	12.33	215.86
+10			4.0	213.7
W			5.6	212.1
+10			6.3	211.4
	1+25			
-15			11.0	206.7
W			10.0	207.7
+10			8.4	209.3
Cb			6.8	210.9
+4			6.1	211.6
¼			2.8	214.9
+1 = W by Oil Pan			3.2	214.5
½			3.0	214.7
¼			3.1	214.6
Gutter			3.26	214.40
FCb			2.43	215.23

	217.66		
1+50			
FCb Top	4.19		213.47
Gutter	5.00		212.66
¼	4.9		212.8
½	4.9		212.8
+7 = W by Oil	5.0		212.7
¼	4.9		212.8
Cb	10.9		206.8
W	15.0		202.7
-20	19.0		198.7
1+75			
FCb Top	6.00		211.66
Gutter	6.85		210.81
¼	6.8		210.9
½	6.8		210.9
+3 = W by Oil Pan	6.8		210.9
+8	6.4		211.3
¼	8.3		209.4

Rest of Sec Same

Proposed Widening of Narragansett Ave. to 80' Bet. Warrington & Catalina

Moore Osborne Hale 1-7-44.

Indexed L.M.

1+49.59 P.R.C. 10° 38.5

1+75	8° 57.2	Δ = 21° 17' 02" Rt.
1+00	7° 09.7	R = 400
0+75	5° 22.3	T = 75.16
0+50	3° 34.8	L = 148.59
0+25	1° 47.4	d = 4.2972° Cal. 8-7-51
0+00	B.C. = ℄ STA.	

EXISTING IMPMT. on Narragansett
Width 44'
Curbs 8'
Roadway 30' 6" Curb face
regular crown

See P 42 for X Sec.



5+78.33 P.R.C. 32°23'21"

+50 30°15.6

5 26°29.5 Δ = 64°47'42" Rt.

+50 22°43.3 / D.R = 380

T = 241.13

4 18°57.1 L = 429.74

+50 15°11.0 Long chord = 407.23 bal 8-7.5'

3 11°24.8 d = 4.53'

+50 7°38.6

2+00 3°52.5

1+48.59 P.R.C.

P.R.C. Ld. C.T.

P.R.C. Ld. C.T.

8+62.38 = E/L 7' Line Catalina

8+48.50 E.C. N0°47.0 Ld. C.T.

8	17° 03.14	
+50	13° 12.36	Δ = 41° 34' Rt
		ER = 372.4
7	9° 21.58	T = 141.34 ✓
		L = 270.17
+50	5° 30.8'	d = 4.62' on 8-75'
6+00	1° 49.0 N	

5+78.33 PRC



Final Meas. of alley Blk 72 Ocean Beach

Moore
Osborne
1-7-41.

0+00	19.90		
0+50	18.80	19.35 × 50.0	967.50
0+50	18.80		
0+64.9	19.60	19.20 × 14.9	286.08
0+649	19.60		
0+65	20.00	19.80 × 0.1	1.98
0+65	20.00		
1+00	19.90	19.95 × 35.0	698.25
1+00	19.90		
2+00	20.00	19.95 × 100.0	1995.00
2+00	20.00		
2+50	19.80	19.90 × 50.0	995.00
2+50	19.60		
2+51	20.00	19.90 × 1.0	19.90
2+51	20.00		
4+25.3	20.00	20.00 × 174.3	3486.00
			8449.71



Bacon

Indexed
L.M.

alley

Paved

41

4+25.3 —— 20 ——

2+51
2+50
20
19.8

2+44 2.7 × 3.5
iron grate

2+00 20

1+00 19.9 1.5

0+65 20.0
0+64.9 19.5

this Paid by P.O.
May be

0+50 18.8

0+00 9.95 9.95 3

60.56 ft

10 10

Bacon ST.

Moore
Osborne
Sommermeyer

1-28-11

Xsec Proposed align.
Narragansett 80' wide
West of Warrington
to Catalina Blvd

Indexed
L.M.

422

			LT	℄	RT
0+75			220.0 / 1.0 / 40	216.8 / 4.2 / 14	216.30 / 4.73 / 6.2 / C6
				216.11 / 4.9	216.35 / 4.68 / 24.7 / C6
					216.5 / 4.2 / 31
					217.2 / 3.8 / 34
					217.2 / 3.8 / 40
0+50			219.6 / 1.4 / 40	216.7 / 4.3 / 10	216.48 / 4.55 / 2.9 / C6
					216.08 / 4.95
					216.54 / 4.79 / 28.2 / C6
					216.8 / 4.2 / 40
0+00 ℄ T.P.	Ld+C.T.	4.54	~1.03	4.17	216.49 Ld. C.T. IN PAV.
			~1.03		
0+25			219.9 / 0.8 / 40	217.2 / 3.5 / 10	216.61 / 4.05 / 1.0 / C6
					216.09 / 4.57
					216.59 / 4.07 / 29.5 / C6
					216.9 / 3.8 / 40
0+00	B.C. RT	℄ Sta.			
			219.6 / 1.1 / 40	216.91 / 3.75 / 6.4 / C6	216.49 / 4.17
					216.59 / 4.07 / 30 / C6
					216.8 / 3.9 / 40
T.P.	12.91	~0.891	0.17	196.00	
				220.66	
TP	12.76	196.17	0.53	183.41	
T.P.	12.78	183.94	0.41	171.16	
T.P.	12.79	171.57	0.17	158.78	
T.P.	13.10	158.95	0.27	145.85	
NEBP	12.93	146.12		133.19 Chatsworth Narragansett	
T.P.	12.69	220.66	0.94	207.97 Narragansett La Cresta	
NW Ld plug			3.74	205.17	
		208.91			

	LT		℄		RT	
3+00	211.5 9.5 40	210.0 11.0 19	209.88 11.15 12 C6	209.80 11.23	209.98 11.05 18.7 C6	211.2 9.8 40
2+50		215.8 5.2 40	214.38 6.65 26.5 C6	213.77 7.26	214.03 7.00 4.6 C6	214.0 7.0 20
2+00	216.1 4.9 20	215.69 5.34 31.4 C6	215.66 5.37 1.50 C6	215.69 5.34 SDW	215.4 5.6 25	213.3 7.7 40
+48.59 P.R.C.	217.8 3.7 40	216.9 4.1 28	215.95 5.08 24.8 C6	215.77 5.26	216.01 5.02 4.3 C6	215.5 5.5 40
1+25	219.4 1.6 40	216.6 4.4 25	216.07 4.96 17.7 C6	216.01 5.02	216.11 4.92 13.4 C6	216.2 4.8 19
1+00	219.5 1.5 40	216.6 4.4 20	216.22 4.81 11.1 C6	216.09 4.94	216.25 4.78 19.8 C6	216.4 4.6 24
221.03			221.03			

217.2 215.3
3.8 5.7
22 40

217.5 216.3
3.5 4.7
28 40

5+00							
4+50							
4+38.5		W c6 Redondo ℄ N.L regular crown 6" curb face					
4+08.84	= INT. E c6 Redondo ℄ N.L.						
4+00							
T.P.	0.21	201.14	13.08	201.93			
3+50							
T.P. T.P.	0.54	215.01	6.56	214.47			
		221.03					

	LT.		℄		RT.	
191.8	188.6	188.64	189.29	189.66	190.2	194.9
10.3 / 40	13.5 / 27	13.50 / 21 c6	12.85	12.48 / 9.5 c6	11.9 / 18	7.7 / 40
197.6	194.8	194.84	194.81	194.95	196.2	
4.5 / 40	7.3 / 20	7.30 / 11.6 c6	7.33	7.19 / 21.1 c6	5.9 / 40	
			196.73	196.65	196.72	196.75 176.78
			5.71 / 40	5.49 / 45	5.42 / 50 c6	5.39 / 55 5.36 / 60
			197.95	197.54	197.18	197.18 197.18
			4.19 / 40	4.60 / 45	4.96 / 50 c6	4.96 / 55 4.96 / 60
202.1	199.9	199.12	198.79	198.99	198.8	
0.0 / 40	2.2 / 15	3.07 / 4.15 c6	3.35	3.15 / 20.3 c6	3.3 / 40	
		207.14				
207.0	204.3	204.12	203.91	204.53	205.2	
8.0 / 40	10.7 / 12	10.89 / 11.7 c6	11.10	10.48 / 26 c6	9.8 / 40	
		215.01				

6+50				
T.P.	0.33	178.02	12.99	177.69
6+35.45	SL Narr + WC6 Redondo			
6+00				
5+78.33	PRC			
5+54.4	S.L. Narr. + E C6 Redondo			
5+50				
T.P.	1.62	190.68	13.08	189.06
		202.14		

	Lt.		&		Rt.
176.9	176.57	176.03	176.06	175.4	173.7
11 / 40	1.45 / 32.5 C6	1.99 / 2.3 C6	1.96 Sdw	2.6 / 20	4.3 / 40

178.02

178.94	178.64	178.35	178.03	177.79
11.74 / 60 C6	12.04 / 55 C6	12.33 / 50 C6	12.65 / 45 C6	12.99 / 40 C6

180.04	180.10	180.32	180.36	179.9	
10.64 / 50 Pav	10.58 / 40 Pav	10.36 / 2.8 C6	10.32 Sdw	12.8 / 40	

180.89	181.21	181.42	181.49	181.7	179.9
9.79 / 50 Pav	9.47 / 40 Pav	9.26 / 2.3 C6	9.19 Sdw	9.0 / 10	10.8 / 40

181.70	181.84	182.20	182.58	182.94
8.98 / 60 C6	8.84 / 55	8.48 / 50	8.10 / 45	7.74 / 40 C6

183.22	183.31	183.36	183.83	186.1	185.9	
7.46 / 40 Sdw	7.37 / 37.5 C6	7.32	6.85 / 0.5 C6	4.6 / 20	4.8 / 40	

190.68

check to BMBP Narragansett Catalina	8.10	157.46	157.52			
			0.06			
T.P.	0.40	145.56	0.30	145.16		
8+42.38 = E 7' Line Catalina Blvd.						
E.L. Catalina Blvd						
+48.50 E.C.						
8						
T.P.	0.30	165.46	12.8L	165.16		
7+50						
7+00						
	178.0N					

	Lt		℄		Rt	
156.14	155.96	155.41	155.05	154.24	154.67	154.68
9.3N	9.50	10.05	10.41	11.2N	10.79	10.78
40	27	27		26.7	36.7	40
Sdw	C6	9.47		9.47	C8	Sdw
	156.3	155.91	155.49	154.99	155.0	
	9.2N	9.55	9.97	10.47	10.5	
	40	21.2		27.6	40	
		C6		C6		
157.3	156.7	156.54	155.99	155.46	155.3	155.7
7.2N	8.8	8.9N	9.47	10.0	10.2N	9.8
40	25	16.8		23.3	30	40
		C6		C6		
163.0	161.2	160.92	160.28	159.84	160.3	161.2
2.5	4.3	4.5N	5.18	5.6N	5.2N	4.3
40	25	18.3		12	20	40
		C6		C6		
			165.46			
	167.7	166.15	165.28	165.36	164.8	164.4
	10.3	11.87	12.74	12.6L	13.2N	13.6
	40	25		5.2	20	40
		C6		C6		
	172.2	171.38	170.46	170.92	169.9	168.8
	5.8	6.6N	7.56	7.10	8.1	9.2N
	40	29.5		0.44	20	40
		C6		C6		
			178.0N			

Moore
Osborne
Sumner
4-n3-W1.

Survey — Washed out — Fill

Arizona
~~Oregon~~ N. of adams

W side

S.E.B.P.	5.38	390.09		384.91	adams Idaho
SW BP			6.34	383.95	adams Oregon
T.P.	1.97	385.17	7.09	383.20	
SW IBP adams Hamilton	=380.05	Brass Plug out only Lead	5.20	379.97	
T.P.	5.55	382.68	8.04	377.13	



Levels on Washout
West side Arizona
N. of

Indexed
4/1

0+14 = wk Arizona Oregon

0+10 w/edge

0+0 ~

Cvr 6 = 0+0

0+0 gutter

00 — 10 = C.L. Pav.

38 x 68

| | | |

0+75	Toe of Fill			
0+55				
0+43				
0+40				
T.P	0.16	358.03	17.7N	357.87
0+30				
T.P	0.47	370.59	17.7L	369.9N
0+18				
		387.68		

LT | ℄ | RT

LT		℄		RT
335.7		335.6		336.6
22.1 / 5		22.4		21.4 / 4
348.2		345.0	344.6	347.4	347.3	347.3
9.8 / 10		13.0 / 7	13.4 / 4	10.6 / 2	10.7	10.7 / 7
356.0		354.2	351.2	355.6	357.0	357.0
2.0 / 20		3.8 / 7	6.8 / 5	2.4	1.0 / 4	1.0 / 8
358.7		357.8	351.6	352.0	358.6	358.4
+0.7 / 20		0.2 / 6	6.4 / 3	6.0	+0.6 / 4	+0.4 / 10
			358.03			
		364.6	364.4	358.0	363.3	363.6
		6.0 / 12	6.2 / 6	12.6	7.3 / 4	7.0 / 10
378.98		374.95	372.48	366.68	370.59	376.08	377.96
3.7 / 50		7.7 / 18	10.2 / 10	16.0 / 2	16.1	6.6 / 14	4.7 / 35
					387.68		

Moore Osborne S'Meyer 4-23-41.

X sec. of N & S alley 20' wide Blk 10C U.H.

SEBP	2.47	379.70	377.23	Meade Oregon
	0-14 = Sc6 Meade			
E	Pav.	5.1 ±	374.56	
W	"	5.3 ±	374.38	
	0+00 S.L. Meade			
W	cb beg. Eugenia Hedge	4.80	374.90	Planted 1' back
W	pav	4.86	374.84	
C	"	4.97	374.73	
E	on old header	4.87	374.83	
E	cb	4.56	375.14	
	0+04			
E	± 6" Cypress Tree			
	0+19			
E-1.4	& 1.4 Brick Chimney	3.3	376.4	ground
E		3.3	376.4	
C		3.7	376.0	

Indexed LM

Meade

Ave

H.C. Pav.

7' 7' 4.5'

C.J.

0+00

139.90

139.90

R 3' reverse pav.

10 10

Hamilton

Oregon

3715

Sump

to drain Property here

small wooden drain

3'

4+49.70

10' alley Conc. Pav.

3'

Chisel Cross

		379.70			
W			4.0	375.7	5' width × 1.5
+2.3	Brick Chimney		4.2	375.5	
	0 + 42				
E +0.5	beg. Wooden slat fence				
	0 + 44				
W −1.3	℄ 3' Conc. walk		4.7	375.53	
W			4.2	375.5	
C			3.8	375.9	
E			3.8	375.9	
+5			3.9	375.6	
	0 + 50				
W +0.2	beg. 6d. Fence				
	0 + 94				
W +2.6	14" P.P.				
	1 + 00				
−5			4.7	375.0	
E +0.2	end slat Fence		4.3	375.4	
C			4.5	375.2	
+9.9	" 6d. "		4.6	375.1	
W +5			4.6	375.1	

51

51

		379.70			
T.P.	4.74	380.05	4.39	375.31	
	1 + 03				
E −6.3	N end 4 car gar.		4.60	375.4	Fl. El. according to Carpenter Gar. is under Const.
	1 + 20				
−5			5.2	374.8	
W			5.2	374.8	
C			4.9	375.1	
E			5.2	374.8	
	1 + 40				
E −6.2	S end 4 car gar.		4.55	375.50	Fl. El.
	1 + 50				
−5			5.1	374.9	
E −1.1	beg. picket fence				
E			5.2	374.8	
C			4.6	375.4	
W			5.1	374.9	
+1.3	beg. Picket fence				
+10			5.4	374.6	

Get Apron and Floor

38005

	1+65			
-5		5.0	375.0	
W		5.0	375.0	
C		4.3	375.7	
E		4.3	375.7	
+20	Low spot	5.3	374.7	
	1+85			
-20		5.2	374.8	
E		5.2	374.8	
C		4.8	375.2	
W		5.0	375.0	
+5		5.0	375.0	
	1+94			
W +2.6	9" P.P			
	2+03			
-5		5.1	374.9	
-1.2	end Picket Fence			
W		5.0	375.0	
C		4.9	375.1	
E		5.1	374.9	

38005

P2

E +1	Picket Fence			
+20		5.3	374.7	
	2+15			
W		5.0	375.0	
-7.8	E Sin gar.	4.83	375.22	Cem.
	2+29			
W -13	beg. Picket Fence			
	2+50			
E -20		5.7	374.3	
E -1	Picket Fence			
E		5.6	374.4	
C		5.7	374.3	
W		5.4	374.6	
+1	end Picket Fence beg wire "			
+5		5.2	374.8	
	2+80			
-5		5.2	374.8	
W		5.2	374.8	
C		5.7	374.3	
E		5.9	374.1	
+5		5.9	374.1	Try to
+30	Straw Berry Patch	6.1	373.9	drain this

	3+00			
-30	Strawberries	6.4	373.6	draw this
-7		6.5	373.5	
E -0,3	end Piket fence			
E	beg. Lat. fence on line	6.1	373.9	
C		6.0	374.0	
W		5.7	374.3	
+0.6	end wire fence			
+5		5.7	374.3	
	3+07			
W +1.0	beg. Cypress Hedge			
	3+15			
-10		5.9	374.1	
W		6.0	374.0	
+2		5.8	374.2	
C		5.8	374.2	
+7		5.9	374.1	
+7	Swamp of weed drain	6.7	373.3	
E		5.8	374.2	
+20		5.9	374.1	

	3+17			
E -0,7	end Lat. fence			
E -0,5	NW Cor house	5.8	374.2	ground
"	floor El.	3.9	376.1	
"	Bot. Conc. fd.	6.4	373.6	
	3+25			
E -0.5	Cor. House			W to end Cypress Hedge
E -1.6	to N end porch			
	3+27			
E +0,3	6" Tree			
	3+34			
W +0.1	12" P.P.			
	3+40			
E -1.6	SW Cor Porch			
T.P.	5.0 W	379.71	5.36	374.69
	3+50			
-10		5.6	374.1	
E		5.2	374.5	

Nail in pole West side

		379.71			
C			4.9	374.8	
W			5.4	374.3	
+15			5.6	374.1	
	3+65				
-10			5.5	374.2	
W			5.4	374.3	
C			5.5	374.2	
E			5.3	374.4	
+10			5.3	374.4	
	3+85				
E +0.5	NW Cor. Bd. shed				
	3+99				
E +0.3	SW Cor. "	"			
" "	beg. wire fence				
	4+00				
-10			5.1	374.6	
E			5.2	374.5	
C			5.0	374.7	
W			4.9	374.8	

	379.71			
W +0.7 beg. picket fence				
+10		5.1	374.6	
	4+15			
W +2.6 12" p.p.			Note!	2.6 in alley
	4+20			
W -0.9 end picket fence				
	4+25			
W -3.7 E. edge gar.		4.8	374.9	S/y entrance on 10' alley
W		4.5	375.2	
C		5.0	374.7	
E		5.0	374.7	
+10		5.0	374.7	
	4+43			
-10		4.9	374.8	
E		4.6	375.1	
C		4.8	374.9	
W		4.8	374.9	
+3.7 against gar.		5.3	374.4	
	4+49.70	N.L. E+W 10' alley		
W-5 pav.		6.7	373.44	

4+48.2 = End wire fence 0.5 in alley

		379.71			
W	pav		6.75	373.46	
C	"		6.30	373.41	
E	"		5.99	373.72	
+5	"		5.90	373.81	
	E INT. of alleys on M.H.				
E of S.M.H			6.31	373.40	
T.P.	3.47	377.98	10.20	369.51	
SEBP			7.00	370.98	371.07
Meade & Hamilton					
	Brass Plugs Taken out & Kids in both B.M.'s				
T.P.	7.19	378.17	7.00	370.98	
check to orig. B.M.			0.95	377.22	377.23

C. Moore
G. Farrow
7-23-41

Add. Notes for New Garage Blk 10 L.U.H.

55

					Meade Oregon
SEBP	4.93	380.16		377.23	
T.P.	4.07	379.96	4.27	375.89	
	1+03				
E-0.3	NL Cem. apron		5.34	374.62	
E-6.3	" 4 Car gar. Cem. floor		4.53	375.43	
	1+21.5				
E-0.25	E Cem. apron		5.48	374.48	
E-6.25	" garage		4.57	375.39	
	1+40				
E-0.2	SL Cem apron		5.57	374.39	
E-6.2	" garage Cem.		4.49	375.47	

Cross Section Dupont St.
Catalina to Box

Indexed
LM

Box

Dudley

Existing Curb

Charles

Dudley

Magnolia

Box

Pt. Line 2

Existing 16" Conc Culvert

Silvergate

Warner

Dupont

Catalina Blvd

Sewer
Sisson
Northern
W Moore
Albin

Wire Fence
Metal Posts

8" Conc Wall

Cross Section Dupont St
Catalina to Bay

See Sketch Page 56

Reduced & Plotted 6-20-41 GBH

0+83	= ℄ 10. Conc Drive on Rt			
0+50				
0+25				
0+0	= ℄ Catalina			
0-16				
0-40	= ℄ Catalina on Paving			
BM	8.07	303.97	295.90	Mon 20 N Nly Cor Catalina & DuPont

57

Lt-N ✓ ℄ Rt 5 ✓

	301.0	301.0	301.0	300.7	301.29	301.98
	3.0 / 25	3.0 / 15	3.0	2.8 / 15	2.68 / 20 Rt=Nly Conc Dr-Way	1.99 / 25 on Dr.
	300.4	300.2	300.0	299.7	299.7	300.7
	4.6 / 25	4.8 / 15	4.0	4.3 / 15	4.3 / 20	3.3 / 25
	299.8	299.2	298.7	298.7	298.6	300.1
	4.3 / 25	4.8 / 15	5.3	5.3 / 15	5.4 / 20	3.9 / 25
299.4	299.3	297.6	296.8	297.2	297.5	297.7	299.6
4.6 / 25	4.7 / 20	6.4 / 15	7.2 / 10	6.8	6.5 / 15	6.3 / 20	4.4 / 15
		296.1		296.6		297.1	
		7.9 / 15		7.4		6.9 / 15	
	296.22	296.65		297.05	297.40	297.70	
	7.75 / 50	7.32 / 25		6.92	6.57 / 25	6.27 / 50	

303.97 ✓

3+0	24.3 Lt of Z = Sly 1.5x1.5 Brick Pilaster ✓			
2+50				
2+24.3 =	24.3 Lt of Z = Sly 1.5x1.5 Brick Pilaster ✓			
2+28	21.2 Rt of Z = Sly 24" Cyperconcrete ✓			
2+0				
1+50				
TP	7.17	310.76	0.38	303.59
1+27 =	23.5 Conc walk on Rt			
1+0				
		303.97		

Lt			Z		Rt	
307.3	307.4	307.2	307.2	307.2	308.5	308.7
3.5 / 25	3.4 / 20	3.6 / 15	3.6	3.6 / 15	2.3 / 20	2.1 / 25
305.8	306.3	305.7	305.9	305.9	307.1	307.5
5.0 / 25	4.5 / 20	5.1 / 15	4.9	4.9 / 15	3.7 / 20	3.3 / 25
304.6	305.1	304.4	304.5	304.4	304.6	305.8	306.1
6.2 / 25	5.7 / 20	6.4 / 15	6.3	6.4 / 15	6.2 / 18	5.0 / 20	4.7 / 25
303.2	303.3	303.6	302.8	303.0	302.8	303.0	304.0
7.6 / 35	7.5 / 25	7.2 / 20	8.0 / 15	7.8	8.0 / 15	7.8 / 20	6.8 / 25
			310.76 ✓				
					302.85	303.50
					1.12 / 21 = Rt Conc Walk	0.47 / 25 = Top of Conc Wall
301.4	301.6	301.3	301.5	301.4	301.6	302.7
2.6 / 35	2.4 / 25	2.7 / 15	2.5	2.6 / 15	2.4 / 20	1.3 / 25
			306.97			

Dupont

5+21	19.6 Rt of ℄ = Sly 10" Pepper Tree	✓		
5+02	19.8 Rt of ℄ = Sly 12" Pepper Tree	✓		
5+0				
4+82	20' Rt of ℄ = Sly 10" Pepper Tree	✓		
4+71	= ℄ 7' Conc Drive on Rt			
4+64	23.7 Rt of ℄ = Nly 1x1 Conc Post	✓		
4+50				
4+21	17' Rt of ℄ = ℄ 2' 12" Fac Trees	✓		
4+0	16.2 Rt of ℄ = ℄ 12" Fac Tree	✓		
3+91	17' Rt of ℄ = ℄ 3' 8" Fac Trees	✓		
3+83	21.3 Lt of ℄ = Sly 1.5x1.5 Brick Pilaster	✓		
TP	5.67	315.33	1.10	309.66
3+50				
		310.76		

59

	Lt	℄	Rt	
	310.3	310.4	309.9	310.0
	5.0	4.9	5.4	5.3
	25	20	15	
				311.41
				3.95
				23.5 = NLy Conc Drive
	310.2	310.3	310.4	310.5
	5.1	5.0	4.9	4.8
	25	25	15	
	309.5	309.7	309.7	310.0
	5.8	5.6	5.6	5.3
	25	25	15	
				315.33 ✓
	308.5	308.9	308.4	308.5
	2.3	1.9	2.4	2.3
	25	20	15	
				310.76

	Lt	℄	Rt	
	310.1	311.1	310.9	310.9
	5.2	4.2	4.4	4.4
	10	13	15	25
	311.85			
	3.48			
	30 conc.			
	310.6	311.0	311.6	
	4.7	4.3	3.7	
	12	15	25	
	309.7	310.5	310.9	
	5.6	4.8	4.4	
	12	15	25	
	308.6	309.4	309.6	
	2.2	1.4	1.2	
	15	20	25	

7+01 = Ely Conc Dr. on Lt

7+0

6+90 = Wly Conc Dr on Lt

6+65 25.0 Lt of ℄ = Sly 1.5×1.5 Brick Pilaster ✓

6+50

TP 0.85 304.89 11.29 304.04

6+0

5+65 25' Lt of ℄ = Sly 1.5×1.5 Brick Pilaster ✓

5+62 20' Rt of ℄ = Sly 6" Pepper Tree ✓

5+50

5+42 19.5 Rt of ℄ = Sly 6" Pepper Tree ✓

8/5/33

Lt.	℄	Rt
300.95		
3.94		
25-Sly Conc		
301.09	301.2	301.3
3.80	3.7	3.6
25-Conc Drive	15	
301.62		
3.27		
25-Sly Conc Drive		
303.7	303.9	303.9
1.2	1.0	1.0
25-Base & Hdg Brick Wall	15	
304.89 !		
306.2	306.4	306.2
9.1	8.9	9.1
25-Base & Hdg Brick Wall	10	15
307.8	308.3	308.5
7.5	7.0	6.8
35	25	20
		8/15/33

301.2	301.3	301.6	301.9	302.5
3.7	3.6	3.3	3.0	2.4
15		15	20	25

303.9	303.9	303.9	304.7	305.3
1.0	1.0	1.0	0.2	+0.4
15		10	15	25

306.4	306.2	306.3	306.3	307.3	307.7
8.9	9.1	9.0	9.0	8.0	7.6
10	15		10	15	25

308.3	308.5	308.3	308.3	308.3	309.6	310.0
7.0	6.8	7.0	7.0	7.0	5.7	5.3
25	20	15		10	15	25

8/15/33

Dupont

8+69 22.5 Rt of ℄ = Double Pepperidge 8" Diam ✓

8+64.40 = ℄ Silvergate

TP	0.18	293.38	11.69	293.20
8+50				
8+0				
7+80 = ℄ 10' Flag Stone Walk on Rt				
7+50				
7+19 = ℄ 15 Brick Drive on Rt				

304.89

61

Lt	℄	Rt	
292.3	291.0	291.4	292.1
1.1 / 25	2.4 / 20	2.0 / 15	1.3
293.38 ✓			
293.2	292.7	292.5	293.1
11.7 / 25	12.2 / 19	12.4 / 15	11.8
296.7	295.3	295.5	296.0
8.7 / 25	9.6 / 18	9.4 / 15	8.9
298.14			
6.75 / 25 = ℄ 10' Flag Stone Walk			
298.4	298.3	298.5	298.4
6.25 / 25	6.6 / 15	6.4	6.5 / 10
301.41			301.79
3.48 / 25 = ℄ 14' Brick Drive			3.10 / 38 on Brick Dr.
304.89			

Lt	Rt	
293.3	293.4	293.6
1.1 / 25	0.0 / 20	+0.2 / 25
293.7	294.4	
11.2 / 15	10.5 / 25 = Base Rock Wall	
296.4	297.1	
8.5 / 15	7.8 / 25 = Base Rock Wall	
298.9	299.9	
6.0 / 15	5.0 / 25 = Base Rock Wall	

Surface

		Lt		℄		Rt
2+50		278.9 278.9	279.1 279.0	278.1	280.4 280.4	280.4
		5.5 5.5	5.3 5.1	6.3	4.0 4.0	4.0
		10 30	20	7	10 20	30
2+00		280.7 281.1	280.9 280.7	279.0	282.1 282.0	282.2
		3.7 3.3	3.5 3.7	4.4	2.3 2.4	2.2
		40 30	20	7	10 20	30
TP	1.88	284.38	10.88	282.50	284.38 V	
1+50		282.6 283.1	282.4 282.8	282.4	282.0 284.0	283.8 284.1
		10.8 10.3	11.0 10.6	11.0	11.4 9.4	9.6 9.3
		40 30	25 20		10 12	20 30
1+00		285.2 284.7	285.0 285.0	284.8	284.3 286.0	285.9 286.1
		8.2 8.7	8.4 8.4	8.6	9.1 7.4	7.5 7.3
		30 25	20 10		10 12	20 30
0+50		287.0 287.1	286.9 287.1	287.3	287.0 286.3	285.5 288.1 288.3
		6.4 6.3	6.5 6.3	6.1	6.4 7.1	4.9 5.3 5.1
		40 30	25 20	10	10	12 20 30
0+0 = F.L. Silvergate						
BM		284	290.54		2 Moo Silvergate +Dupont From West	
	293.38					
		289.2 289.4	288.7 288.7	289.2	289.3 290.6	290.6 291.1
		4.2 4.0	4.7 4.7	4.2	4.1 2.8	3.8 3.3
		30 20	25 20		12 14	20 30 W.L. Wire Fence
			293.38			

Dupont

4+85.75	℄ 10" Conc Culvert			
4+50				
TP	3.50	276.47	11.41	272.97
4+0				
3+50				
3+0				
		284.38		

℄		RT
	270.31	271.17
	6.16	5.30
	32" Conc Culvert	3.1 = 10 lot 10" Conc Culv Flow Line
271.8	272.3	272.8	271.9	271.8	272.4	272.4	274.40
4.7	4.2	3.7	4.6	4.7	4.1	4.1	2.07
40	30	20		10	20	30	30 = Top Wall
		376.47					
274.0	273.5	273.7	273.4	273.4	273.6	273.5	275.73
10.4	10.9	10.6	11.0	11.0	10.8	10.9	8.65
40	30	20		10	20	30	30 = Top Wall
275.0	274.8	275.3	275.2	274.9	276.6	276.2	276.6	277.12
9.4	9.6	9.1	9.2	9.5	7.8	8.2	7.8	7.24
40	30	20		7	10	20	30	30 = Top Wall
277.0	277.1	277.2	277.1	276.4	278.7	278.6	278.5
7.4	6.7	7.2	7.3	8.0	5.7	5.8	5.9
40	30	20		7	10	20	30
		284.38					

BM		5.50	270.97	Nail Pole SW Pole Dupont & Bow
6+38.28	= E.L Bow From N = P.L.			
6+17.5	= Ely Wire Fence on Rt			
6+06.28	= ℄ Bow From N			
5+76.28	= W.L. Bow From N			
5+50				
5+0				
		276.47		

Lt		℄		Rt		
		268.4				
		8.1 30				
	268.5	268.7	269.3	269.7	270.0	272.2
	8.0 20	7.8	7.2 20	6.8 30	6.5 50	4.3 100
268.8	268.8	268.8	269.0	269.5	270.2	273.1
7.9 30	7.7 20	7.7	7.5 20	7.0 30	6.3 50	3.8 100
269.0	269.0	268.7	269.3	269.8		
7.5 30	7.5 20	7.8	7.2 20	6.7 30		
269.3	269.1	269.3	269.9	270.3	271.3	271.6
7.3 10	7.4 30	7.2 20	6.6	6.2 10	5.2 20	4.9 30
271.1	269.5	270.2	271.2	271.3	271.5	272.6
5.4 10	7.0 30	6.3 20	5.3	5.2 10	5.0 20	3.9 30
271.4	271.2	271.5	271.6	272.0	272.8	272.7	272.91
5.1 10	5.3 30	5.0 20	4.9	4.5 10	3.7 20	3.8 30	3.56 50 = Top Wall
			276.47			

Cross Section Silvergate Ave
Dupont to Charles

Indexed LM

See Sketch Page 56

1+87 21.8 Rt of ℄ = Ely Tel Pole = 25.3 Lt of ℄ = W½ Post Pole

1+50

1+0

0+66.77 = N.L. Dupont From E

Plot.

0+50 = N.L. Dupont From W 30.2 Lt of ℄ = Sly Picket Fence

0+25 = ℄ Dupont From West

0+0 = S.L. Dupont From West

BM. 6.88 294.42 290.54

2.5 Mon Silvergate & Dupont From W Page 69

Survey-41

65

Lt = W		℄		Rt = E			
291.4	290.6	289.5	289.4	288.6	289.1	288.5	288.1
3.0 30	3.8 20	4.9 18	5.0	5.8 20	5.3 22	5.9 30	6.3 40
291.7	291.7	289.8	289.5	289.9	289.8	289.1	288.4
3.7 30	3.7 20	4.6 18	4.9	5.5 20	4.6 28	5.3 30	6.0 40
291.6	291.7	290.1	289.8	288.9	289.3		
3.8 30	3.8 20	4.3 18	4.6	5.5 20	5.1 30		
	292.7	290.5	290.2	289.4	288.9		
	2.8 30	3.9 20	4.2	5.0 20	5.5 30		
	292.1	291.6	290.7	289.4	290.7		
	2.3 30	2.8 20	3.7	5.0 20	3.7 30		
293.9	293.5	291.8	291.4	291.7	291.7	291.0	
0.5 30	0.9 23	2.6 20	3.0	3.3 15	2.7 20	3.4 30	

294.42 ✓

3+55	21.8 Rt of Z = Fly Tel. Pole			✓
3+50	= S.L. Warner			
3+36	25.3 Lt of Z = N/y Power Pole			✓
3+0				
TP	8.40	297.68	5.14	289.28
2+50				
2+06				
2+0				
1+89	30.2 Lt of Z = N/y Picket Fence			✓
	294.42			

Lt.		Z		Rt.			
292.1	291.0	289.9	289.5	288.9	289.4	288.2	287.6
5.6 / 30	6.7 / 20	7.8 / 15	8.2	8.8 / 19	8.3 / 20	9.5 / 30	10.1 / 40
291.9	290.9	289.5	289.3	288.6	288.9	287.9	287.5
5.8 / 30	6.8 / 20	8.2 / 17	8.4	9.1 / 20	8.8 / 21	9.8 / 30	10.2 / 40
			297.68 ✓				
291.6	290.8	289.6	289.1	288.3	288.7	288.0	287.6
5.8 / 30	6.6 / 20	4.8 / 17	5.3	6.1 / 18	5.7 / 20	6.4 / 30	6.8 / 40
		289.58					
		4.84					
		3.8+3.8 = 7.6 as M.H.					
291.1	290.1	289.6	289.2	288.6	288.6	288.2	287.7
5.3 / 30	4.3 / 20	4.8 / 17	5.2	5.8 / 20	5.8 / 22	6.2 / 30	6.7 / 40
			294.42				

Silver gate

6+03 28.7 Lt of ℄ = Ely 24" Cypress Tree ✓

6+0

5+66 29.0 Lt of ℄ = Ely 24" Cypress Tree ✓

5+50

5+36 21.7 Rt of ℄ = Ely Anchor Bolt 26.0 Lt of ℄ = N'ly Pole ✓ ✓

5+23 21.7 Rt of ℄ = Ely Tel Pole

5+0

4+50

4+15 29.3 Lt of ℄ = Ely 24" Cypress Tree ✓

4+0 = N'L Warner

3+75 = ℄ Warner

29768

Lt.		℄		Rt.			
296.4	295.6	293.6	293.0	292.5	293.1	292.7	291.8
1.6 / 30	3.1 / 20	4.1 / 15	4.7	5.2 / 18	4.6 / 20	5.0 / 30	5.9 / 40
294.7	293.5	292.9	292.2	291.5	292.9	291.7	290.9
3.0 / 30	4.2 / 20	4.8 / 14	5.5	6.2 / 18	4.8 / 20	6.0 / 30	6.8 / 40
294.5	293.3	291.7	291.4	290.7	291.7	290.8	290.4
3.2 / 30	4.4 / 20	6.0 / 15	6.3	7.0 / 20	6.0 / 22	6.9 / 30	7.3 / 40
293.6	292.5	290.9	290.6	290.0	290.5	289.7	288.9
4.1 / 30	5.2 / 20	6.8 / 16	7.1	7.7 / 20	7.2 / 22	8.0 / 30	8.8 / 40
292.5	291.9	290.5	290.0	289.3	289.7	288.2	288.0
5.2 / 30	5.8 / 20	7.2 / 17	7.7	8.4 / 18	8.0 / 20	9.5 / 30	9.7 / 40
	291.6	290.7	289.8	289.2	289.5	288.4	287.7
	6.1 / 30	7.0 / 20	7.9	8.5 / 19	8.2 / 20	9.3 / 30	10.0 / 40

29768

7+30

7+25 = ℄ Dudley

7+01 20.7 Rt = Ely Tel Pole ✓

7+0 = S.L. Dudley From Wart

TP	6.42	301.52	2.58	295.10	
6+92	26.4 Lt of ℄ = Wly Power Pole				✓
6+85	28.8 Lt of ℄ = Ely 24" Cypress Tree				✓
6+50					
6+33	28.8 Lt of ℄ = Ely 24" Cypress Tree				✓
BM		409	293.59	B.P. Ecb Sl. Magnolia 18" Pine & Silverado 293.60	
6+18	= Sly Cb on Rt				
6+16	30.7 Rt of ℄ = Sly Wire Fence				✓

297.68

Lt		℄		Rt	
299.4	298.5	296.1	295.6	295.6	295.13	294.6
3.1 30	3.0 20	5.4 16	6.9 19	6.9 19	6.39 19	6.9 30
297.6		296.6	295.5	294.6	295.09	294.5
3.9 30		4.9 20	6.0	6.9 19	6.43 19	7.0 30
298.6	297.3	295.7	295.1	294.2	294.78	294.2
2.9 30	4.4 20	5.8 16	6.4	7.3 19.1	6.74 19.1 Cb	7.3 30
			30.52 ✓			
297.4	296.5	294.5	294.0	293.3	294.01	293.7	293.0
0.3 30	1.2 20	3.2 16	3.7	4.4 19	3.67 19 Cb	4.0 30	4.7 40
296.7	295.4	293.9	293.4	292.8	293.57	293.0	292.0
1.0 30	2.2 20	3.8 16	4.3	4.9 19 Gutter	4.11 19.5 Cb	4.7 30	5.7 40
			297.68				

Silvergate

Plot 6 - 1941 C.H.

	Lt	℄	Rt
8+53 = Conc Walk + Steps out	299.79 / 1.73 / 30 = Mt. Walk	299.01 / 2.51 / 21.2 Top Steps	297.51 / 4.01 / 17.4 = ℄ Bot. Conc Stp
8+45.35 = ℄ Dudley	299.7 / 1.8 / 30	298.8 / 2.7 / 20	296.7 / 4.8 / 16 — 296.4 / 5.1 — 295.5 / 6.0 / 19 — 295.1 / 6.4 / 30
8+28.85 = SCb Dudley From East	299.7 / 1.8 / 30	299.1 / 2.4 / 20	296.7 / 4.8 / 16 — 296.4 / 5.1 — 295.5 / 6.0 / 19 — 295.3 / 6.2 / 30 — 296.11 / 5.4 / 30 = Cb — 292.39 / 9.13 / 80 = Cb
8+15.35 = SL Dudley From East	299.9 / 1.6 / 30	299.1 / 2.4 / 20	296.7 / 4.8 / 16 — 296.4 / 5.1 — 295.5 / 6.0 / 19 — 296.42 / 5.10 / 19 — 295.8 / 5.7 / 30
8+0	299.8 / 1.7 / 30	299.1 / 2.4 / 20	296.7 / 4.8 / 16 — 296.3 / 5.2 — 295.2 / 6.8 / 19 — 296.13 / 5.89 / 19 — 295.4 / 6.1 / 30
7+50 = NL Dudley 31.4 Lt of ℄ = SL Tile wall ✓	299.3 / 8.2 / 30	298.7 / 2.8 / 20	296.3 / 5.7 / 16 — 295.7 / 5.8 — 294.8 / 6.7 / 19 = Gut. — 295.32 / 6.30 / 19 = Cb — 294.8 / 6.7 / 30

301.52

301.52

9+99 20.5 Rt of Z = Ely Tel Pole ✓

9+78 = Z 5' Conc Step on Lt

9+50

9+10

9+0

8+90 30.8 Lt of Z = Wly Tile Wall ✓

8+88 21.3 Rt of Z = Ely Tel Pole 23.2 Lt of Z = Wly Pow Pole ✓

8+25.35 = NL Dudley From E

8+61.85 = NCL Dudley

30.52

Lt		Z		Rt	
297.62	296.35				
3.90	5.17				
26.2 = Z 5' Top Conc Step	20.2 = Z 6' Step Top Bot Step				
298.4	298.4	296.9	295.3	295.1	294.1	294.69	297.5
6.1 30	6.1 20	4.6 20	6.2 17	6.4	7.4 19	6.83 19	7.0 30
298.8	298.6	296.7	295.8				
4.7 30	4.9 20	4.8 20	5.7				
297.9	297.0	296.4	295.9	294.9	295.61	295.3	
5.6 30	4.5 20	5.1 15	5.6	6.6 19	5.91 19	6.2 30	
299.3	298.6	296.7	296.2	295.1	296.02	295.7	
3.7 30	4.9 20	4.8 16	5.3	6.4 19 = 6w Ht	5.50 19 cb	5.8 30	
299.5	298.8	296.8	296.3	295.4	295.2	296.01	292.08
3.0 30	3.7 20	4.7 16	5.2	6.1 19	6.3 30	5.51 30 cb	9.44 86 cb

30.52

Silvergate

						Lt	℄	Rt
BM			7.92	292.68	BP Fcb Silvergate ℄ Magnolia Part 29350			
BM	8.90	301.60		292.70	BP Fcb Silvergate ℄ Charles			
11+0 = ℄ Charles From W						292.5 9.0 30	291.9 9.6 20	291.2 10.3
BM			8.90	292.62	BP Fcb Silvergate ℄ Charles 29370			
10+76 = N End Cb on Rt						293.9 7.6 30	293.0 8.5 20	291.9 9.6
10+50 = ℄ Charles From W						294.1 7.4 30	293.5 8.0 20	292.8 8.7
10+20						297.2 4.3 30	296.7 4.8 25	293.9 7.6 20
10+18	25.8 Lt of ℄ = Wly Power Pole							
10+0						297.5 4.0 30	297.3 4.2 25	295.1 6.4 26
		301.52						

	Lt	℄	Rt
	292.5 9.0 30	291.9 9.6 20	291.2 10.3
	293.9 7.6 30	293.0 8.5 20	291.9 9.6
	294.1 7.4 30	293.5 8.0 20	292.8 8.7
	297.2 4.3 30	296.7 4.8 25	293.9 7.6 20
	297.5 4.0 30	297.3 4.2 25	295.1 6.4 26

	Lt	℄	Rt
	291.0 10.5 19	290.8 10.7 30	
	292.1 9.4 1875	292.65 8.87 1875	291.5 10.0 30 1875 End Curb
	292.4 9.1 19	292.90 8.62 19	292.8 8.7 30
	293.9 7.9		
	294.2 7.3 18	294.1 7.4	293.1 8.4 19 Gutter

	Lt	℄	Rt
	293.1 8.4 19 Gutter	293.77 7.75 19 Cb	293.8 7.7 30

301.52

Cross Section Bow Ave
Dupont to Dudley

Indexed
LM

See Sketch Page 61

2+40	= Existing Corg Iron Culvert			✓
2+47	29.8 Rt of ℄ = Wly 2 Board Fence			✓
2+0				
1+95	20.8 Lt of ℄ = Wly Power Pole			✓
1+50				
1+0				
0+50				
0+07	31 Rt of ℄ = Sly 2 Board Fence			✓
0+0	= N.L. Dupont			
BM	124	27231	27097	Sw Nail Pole Dupont Bow P64

Sarge 16 7272

Lt. = W ℄ Rt. E

262.61 264.55

9.60 7.66
17 = Outlet 14" 24.5 = Inlet 8" Corg Iron Culvert
Corg Iron Culvert

263.7	264.8	265.0	266.8	266.5	266.1	265.8	267.2	266.9
8.5 45	7.4 30	7.2 20	5.4 17	5.7	6.1 20	6.4 26	5.0 30	5.3 40
267.4	267.1	268.6	267.0	267.2	266.4	266.5	267.7	267.1
4.8 40	5.1 30	3.6 20	5.2 17	5.0	5.8 20	5.7 26	4.5 30	5.1 40
269.5	269.1	268.3	267.5	267.8	267.2	267.1	267.8	267.2
3.7 40	3.1 30	3.9 20	4.7 18	4.4	5.0 20	5.1 27	4.4 30	5.0 40
269.6	269.7	269.6	268.3	268.1	267.9	267.7	268.2	267.0
3.6 40	3.5 30	3.6 23	3.9 20	4.1	4.3 20	4.5 28	4.0 30	5.2 40
	269.1	269.2	268.9	268.5	268.3			
	3.1 30	3.0 25	3.3	3.7 20	3.9 30			

272.31

Box Arc.

4+50				
TP	0.82	261.60	11.43	260.78
4+12	28.0	Rt of ℄ = ℄ 1" Stand Pipe as Hyd		
4+0				
	31.5	Rt of ℄ = Ely Power Pole		
3+64	22.4	Lt of ℄ = Wly Power Pole		
3+50				
3+0				
2+75				
2+50				
		272.21		

Lt.			℄			Rt	
250.1	251.5	252.2	252.8	254.7	254.8	256.1	261.4
11.5 50	10.1 30	9.1 20	8.8 8	6.9	6.8 20	5.5 24	0.2 30
			261.60				
252.6	256.3	256.8	255.7	258.7	259.0	260.5	264.5
19.6 55	15.9 35	15.4 20	16.5 15	13.5	13.2 20	11.7 24	7.7 30
256.7	257.7	258.9	259.0	260.5	260.9	261.7	266.0
15.5 45	14.5 30	13.3 20	13.2 20	11.7	11.3 20	10.5 25	6.2 30
257.6	259.6	260.2	266.4	263.4	262.7	262.9	266.2
14.6 50	12.6 30	12.0 20	5.8 10	8.8	9.5 20	9.3 24	6.0 30
258.7	261.1	261.6	263.6	264.2	264.6	265.5	266.6
13.5 50	11.1 30	10.6 20	8.6 6	8.0	7.6 20	6.7 30	5.6 40 07 Dirt Drive
261.3	262.1	263.2	266.1	265.5	265.2	266.1	266.6	267.3
10.9 40	10.1 30	9.0 20	6.1 10	6.7	7.0 20	6.1 25	5.6 30	4.9 40
			272.21				

Box Arc

7+48.5 = S.L. Dudley From West					
7+0					
6+50					
6+0					
BM			8.00	249.93	Mon. Well Cap PL 172
TP	2-09	251.98	11.76	249.84	
5+48.6		40' Rt of ℄ = Ely 18" Cypress Tree			✓
5+0					
		261.60			

	Lt		℄		Rt		
	232.9	232.9	233.2	236.0	238.1	239.8	241.3	241.0
	19.0 47	19.0 30	18.7 20	15.9	13.8 20	12.1 30	10.6 10	10.9 60
	236.2	236.4	237.0	238.7	240.6	242.0	243.7	243.6
	15.7 50	15.5 30	14.9 30	13.2	11.3 20	9.9 30	8.2 40	8.3 60
	237.9	238.1	238.7	239.3	240.5	242.6	243.1	246.2	246.9
	14.0 50	13.8 30	13.2 20	12.6 30	11.4	9.3 20	8.8 30	5.7 40	5.0 60
	241.1	241.7	241.9	244.4	245.3	247.2	248.7	247.7	250.6
	10.8 50	10.2 30	10.0 20	7.5 5	8.6	4.7 20	3.2 30	4.2 40	1.3 60
				251.93					
	243.1	243.6	244.8	246.6	248.0	249.4	249.6	252.1	254.0
	18.5 50	18.0 30	16.8 20	15.0	13.6 8	12.2 13	12.0 30	9.5 40	7.6 60
	247.6	249.4	249.9	250.8	251.8	251.8	252.4	255.1
	14.0 50	12.2 30	11.7 20	10.8 5	9.8 5	9.8 20	9.2 40	6.5 30
				261.60				

BM			2.04	298.59	BPF Cb of Si Kurrgati SL Magnolia Pat L 298.60
TP	12.05	295.63	2.61	283.58	
TP	11.49	286.22	0.21	274.73	
TP	11.44	274.94	0.20	263.50	
TP	12.28	263.70 251.93	0.51	251.42	

H
0
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40

r line to
idths of
example
.9 =43.9.

Table IX.—Calculation of Earthwork.

Width	HEIGHT														
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
1	.02	.04	.06	.07	.09	.11	.13	.15	.17	.18	.20	.22	.24	.26	.28
2	.04	.07	.11	.15	.18	.22	.26	.30	.33	.37	.41	.44	.48	.52	.56
3	.06	.11	.17	.22	.28	.33	.39	.44	.50	.56	.61	.67	.72	.78	.83
4	.07	.15	.22	.30	.37	.44	.52	.59	.67	.74	.81	.89	.96	1.04	1.11
5	.09	.19	.28	.37	.46	.56	.65	.74	.83	.93	1.02	1.11	1.20	1.30	1.39
6	.11	.22	.33	.44	.56	.67	.78	.89	1.00	1.11	1.22	1.33	1.44	1.55	1.67
7	.13	.26	.39	.52	.65	.78	.91	1.04	1.16	1.30	1.42	1.55	1.68	1.81	1.94
8	.15	.30	.44	.59	.74	.89	1.04	1.19	1.33	1.48	1.63	1.78	1.92	2.08	2.22
9	.17	.33	.50	.67	.83	1.00	1.17	1.33	1.50	1.67	1.83	2.00	2.17	2.33	2.50
10	.18	.37	.56	.74	.93	1.11	1.30	1.48	1.67	1.85	2.04	2.22	2.41	2.59	2.78
11	.20	.41	.61	.82	1.02	1.22	1.43	1.63	1.83	2.04	2.24	2.44	2.65	2.85	3.06
12	.22	.44	.67	.89	1.11	1.33	1.56	1.78	2.00	2.22	2.44	2.67	2.89	3.11	3.33
13	.24	.48	.72	.96	1.20	1.44	1.68	1.92	2.16	2.41	2.65	2.89	3.13	3.37	3.61
14	.26	.52	.78	1.04	1.30	1.55	1.81	2.08	2.33	2.59	2.85	3.11	3.37	3.65	3.89
15	.28	.56	.83	1.11	1.39	1.67	1.94	2.22	2.50	2.78	3.06	3.33	3.61	3.89	4.17
16	.30	.59	.89	1.18	1.48	1.78	2.07	2.37	2.67	2.96	3.26	3.56	3.85	4.15	4.44
17	.31	.63	.94	1.26	1.57	1.89	2.20	2.52	2.83	3.15	3.46	3.78	4.09	4.41	4.72
18	.33	.67	1.00	1.33	1.67	2.00	2.33	2.67	3.00	3.33	3.67	4.00	4.33	4.67	5.00
19	.35	.70	1.06	1.41	1.76	2.11	2.46	2.82	3.17	3.52	3.87	4.22	4.57	4.92	5.28
20	.37	.74	1.11	1.48	1.85	2.22	2.59	2.96	3.33	3.70	4.07	4.44	4.81	5.18	5.56
21	.39	.78	1.17	1.55	1.94	2.33	2.72	3.11	3.50	3.89	4.28	4.67	5.06	5.44	5.33
22	.41	.81	1.22	1.63	2.04	2.44	2.85	3.26	3.67	4.07	4.48	4.89	5.30	5.70	6.11
23	.43	.85	1.28	1.70	2.13	2.56	2.98	3.41	3.83	4.26	4.68	5.11	5.54	5.96	6.39
24	.44	.89	1.33	1.78	2.22	2.67	3.11	3.56	4.00	4.44	4.89	5.33	5.78	6.22	6.67
25	.46	.92	1.39	1.85	2.31	2.78	3.24	3.70	4.17	4.63	5.09	5.56	6.02	6.48	6.94
26	.48	.96	1.44	1.92	2.41	2.89	3.37	3.85	4.33	4.82	5.30	5.78	6.26	6.74	7.24
27	.50	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
28	.52	1.04	1.55	2.07	2.59	3.11	3.63	4.15	4.67	5.18	5.70	6.22	6.74	7.26	7.78
29	.54	1.07	1.61	2.15	2.68	3.22	3.76	4.30	4.83	5.37	5.91	6.44	6.98	7.52	8.06
30	.56	1.11	1.67	2.22	2.78	3.33	3.89	4.44	5.00	5.55	6.11	6.67	7.22	7.78	8.33
31	.57	1.15	1.72	2.30	2.87	3.44	4.02	4.59	5.17	5.74	6.32	6.89	7.46	8.04	8.61
32	.59	1.18	1.78	2.37	2.96	3.56	4.15	4.74	5.33	5.92	6.52	7.11	7.70	8.30	8.89
33	.61	1.22	1.83	2.44	3.05	3.67	4.28	4.89	5.50	6.11	6.72	7.33	7.94	8.55	9.17
34	.63	1.26	1.89	2.52	3.15	3.78	4.40	5.04	5.67	6.29	6.93	7.56	8.18	8.81	9.44
35	.65	1.30	1.94	2.59	3.24	3.89	4.53	5.18	5.83	6.48	7.13	7.78	8.42	9.08	9.72
36	.67	1.33	2.00	2.67	3.33	4.00	4.66	5.33	6.00	6.67	7.33	8.00	8.67	9.33	10.00
37	.68	1.37	2.06	2.74	3.42	4.11	4.79	5.48	6.17	6.85	7.54	8.22	8.91	9.59	10.28
38	.70	1.41	2.11	2.82	3.52	4.22	4.92	5.63	6.33	7.03	7.74	8.44	9.15	9.85	10.56
39	.72	1.44	2.17	2.89	3.61	4.33	5.05	5.78	6.50	7.22	7.95	8.67	9.39	10.11	10.83
40	.74	1.48	2.22	2.96	3.70	4.44	5.18	5.92	6.67	7.41	8.15	8.89	9.63	10.37	11.11

Table gives cu. yds. in 1 ft. of a triangle of given width and height. Corrections for tenths of width are one tenth the values found under each height considering the widths from 1 to 9 as tenths and similarly the corrections for tenths of height are one tenth the figures opposite width considering the heights from 1 to 9 as tenths. Thus if w =16.2 and h =5.3, cu. yds. =1.48+.028+.089 =1.597 cu. yds. or practically 160 cu. yds. per 100 ft. If w exceeds 40 ft., use one half and multiply result by 2, if both w and h are large use one half of each and multiply result by 4. Any cross-section may be divided into triangles by the following rule. To the triangle of the sum of the outside cuts (or fills) =h, and ½ the roadbed =w, add the triangles formed by taking the distance out to each break in turn (=w's) by the difference between the cuts (or fills) on each side of it (=h's) always subtracting the outer from the inner.

Distances from Center of Roadway for Cross-Sectioning.

Roadway 16 feet wide. Side Slopes 1 on 1½.

For Single Track Embankment.

H	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	H
0	8.0	8.2	8.3	8.5	8.6	8.8	8.9	9.1	9.2	9.4	0
1	9.5	9.7	9.8	10.0	10.1	10.3	10.4	10.6	10.7	10.9	1
2	11.0	11.2	11.3	11.5	11.6	11.8	11.9	12.1	12.2	12.4	2
3	12.5	12.7	12.8	13.0	13.1	13.3	13.4	13.6	13.7	13.9	3
4	14.0	14.2	14.3	14.5	14.6	14.8	14.9	15.1	15.2	15.4	4
5	15.5	15.7	15.8	16.0	16.1	16.3	16.4	16.6	16.7	16.9	5
6	17.0	17.2	17.3	17.5	17.6	17.8	17.9	18.1	18.2	18.4	6
7	18.5	18.7	18.8	19.0	19.1	19.3	19.4	19.6	19.7	19.9	7
8	20.0	20.2	20.3	20.5	20.6	20.8	20.9	21.1	21.2	21.4	8
9	21.5	21.7	21.8	22.0	22.1	22.3	22.4	22.6	22.7	22.9	9
10	23.0	23.2	23.3	23.5	23.6	23.8	23.9	24.1	24.2	24.4	10
11	24.5	24.7	24.8	25.0	25.1	25.3	25.4	25.6	25.7	25.9	11
12	26.0	25.2	26.3	26.5	26.6	26.8	26.9	27.1	27.2	27.4	12
13	27.5	27.7	27.8	28.0	28.1	28.3	28.4	28.6	28.7	28.9	13
14	29.0	29.2	29.3	29.5	29.6	29.8	29.9	30.1	30.2	30.4	14
15	30.5	30.7	30.8	31.0	31.1	31.3	31.4	31.6	31.7	31.9	15
16	32.0	32.2	32.3	32.5	32.6	32.8	32.9	33.1	33.2	33.4	16
17	33.5	33.7	33.8	34.0	34.1	34.3	34.4	34.6	34.7	34.9	17
18	35.0	35.2	35.3	35.5	35.6	35.8	35.9	36.1	36.2	36.4	18
19	36.5	36.7	36.8	37.0	37.1	37.3	37.4	37.6	37.7	37.9	19
20	38.0	38.2	38.3	38.5	38.6	38.8	38.9	39.1	39.2	39.4	20
21	39.5	39.7	39.8	40.0	40.1	40.3	40.4	40.6	40.7	40.9	21
22	41.0	41.2	41.3	41.5	41.6	41.8	41.9	42.1	42.2	42.4	22
23	42.5	42.7	42.8	43.0	43.1	43.3	43.4	43.6	43.7	43.9	23
24	44.0	44.2	44.3	44.5	44.6	44.8	44.9	45.1	45.2	45.4	24
25	45.5	45.7	45.8	46.0	46.1	46.3	46.4	46.6	46.7	46.9	25
26	47.0	47.2	47.3	47.5	47.6	47.8	47.9	48.1	48.2	48.4	26
27	48.5	48.7	48.8	49.0	49.1	49.3	49.4	49.6	49.7	49.9	27
28	50.0	50.2	50.3	50.5	50.6	50.8	50.9	51.1	51.2	51.4	28
29	51.5	51.7	51.8	52.0	52.1	52.3	52.4	52.6	52.7	52.9	29
30	53.0	53.2	53.3	53.5	53.6	53.8	53.9	54.1	54.2	54.4	30
31	54.5	54.7	54.8	55.0	55.1	55.3	55.4	55.6	55.7	55.9	31
32	56.0	56.2	56.3	56.5	56.6	56.8	56.9	57.1	57.2	57.4	32
33	57.5	57.7	57.8	58.0	58.1	58.3	58.4	58.6	58.7	58.9	33
34	59.0	59.2	59.3	59.5	59.6	59.8	59.9	60.1	60.2	60.4	34
35	60.5	60.7	60.8	61.0	61.1	61.3	61.4	61.6	61.7	61.9	35
36	62.0	62.2	62.3	62.5	62.6	62.8	62.9	63.1	63.2	63.4	36
37	63.5	63.7	63.8	64.0	64.1	64.3	64.4	64.6	64.7	64.9	37
38	65.0	65.2	65.3	65.5	65.6	65.8	65.9	66.1	66.2	66.4	38
39	66.5	66.7	66.8	67.0	67.1	67.3	67.4	67.6	67.7	67.9	39
40	68.0	68.2	68.3	68.5	68.6	68.8	68.9	69.1	69.2	69.4	40

Example—If point is 22.6 ft. above grade, how far should it be from center line to be a slope stake point? Ans. from Table 41.9. For same slopes but other widths of roadbed correct above figures by one-half difference in width of roadbed; thus in example above for 20 ft. roadbed distance will be 41.9+(20—16)÷2 or 2 ft. added to 41.9 =43.9. For slopes of 1 on 1 see inside of front cover.

Copyright, 1914, by Eugene Dietzgen Co.