B-27

ENGINEER'S

LEVEL BOOK

No. 4105

EUGENE DIETZGEN CO.

DRAWING MATERIALS, MATHEMATICAL and SURVEYING INSTRUMENTS

Chicago New York San Francisco New Orleans Pittsburg Toronto

Distances from Center of Roadway for Cross-Sectioning
Roadway 16 feet wide. Side Slopes 1 on 1.
For Single Track Embankment.

H	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	H
0	8.0	8.1	8.2	8.3	8.4	8.5	8.6	8.7	8.8	8.9	0
1	9.0	9.1	9.2	9.3	9.4	9.5	9.6	9.7	9.8	9.9	1
2	10.0	10.1	10.2	10.3	10.4	10.5	10.6	10.7	10.8	10.9	2
3	11.0	11.1	11.2	11.3	11.4	11.5	11.6	11.7	11.8	11.9	3
4	12.0	12.1	12.2	12.3	12.4	12.5	12.6	12.7	12.8	12.9	4
5	13.0	13.1	13.2	13.3	13.4	13.5	13.6	13.7	13.8	13.9	5
6	14.0	14.1	14.2	14.3	14.4	14.5	14.6	14.7	14.8	14.9	6
7	15.0	15.1	15.2	15.3	15.4	15.5	15.6	15.7	15.8	15.9	7
8	16.0	16.1	16.2	16.3	16.4	16.5	16.6	16.7	16.8	16.9	8
9	17.0	17.1	17.2	17.3	17.4	17.5	17.6	17.7	17.8	17.9	9
10	18.0	18.1	18.2	18.3	18.4	18.5	18.6	18.7	18.8	18.9	10
11	19.0	19.1	19.2	19.3	19.4	19.5	19.6	19.7	19.8	19.9	11
12	20.0	20.1	20.2	20.3	20.4	20.5	20.6	20.7	20.8	20.9	12
13	21.0	21.1	21.2	21.3	21.4	21.5	21.6	21.7	21.8	21.9	13
14	22.0	22.1	22.2	22.3	22.4	22.5	22.6	22.7	22.8	22.9	14
15	23.0	23.1	23.2	23.3	23.4	23.5	23.6	23.7	23.8	23.9	15
16	24.0	24.1	24.2	24.3	24.4	24.5	24.6	24.7	24.8	24.9	16
17	25.0	25.1	25.2	25.3	25.4	25.5	25.6	25.7	25.8	25.9	17
18	26.0	26.1	26.2	26.3	26.4	26.5	26.6	26.7	26.8	26.9	18
19	27.0	27.1	27.2	27.3	27.4	27.5	27.6	27.7	27.8	27.9	19
20	28.0	28.1	28.2	28.3	28.4	28.5	28.6	28.7	28.8	28.9	20
21	29.0	29.1	29.2	29.3	29.4	29.5	29.6	29.7	29.8	29.9	21
22	30.0	30.1	30.2	30.3	30.4	30.5	30.6	30.7	30.8	30.9	22
23	31.0	31.1	31.2	31.3	31.4	31.5	31.6	31.7	31.8	31.9	23
24	32.0	32.1	32.2	32.3	32.4	32.5	32.6	32.7	32.8	32.9	24
25	33.0	33.1	33.2	33.3	33.4	33.5	33.6	33.7	33.8	33.9	25
26	34.0	34.1	34.2	34.3	34.4	34.5	34.6	34.7	34.8	34.9	26
27	35.0	35.1	35.2	35.3	35.4	35.5	35.6	35.7	35.8	35.9	27
28	36.0	36.1	36.2	36.3	36.4	36.5	36.6	36.7	36.8	36.9	28
29	37.0	37.1	37.2	37.3	37.4	37.5	37.6	37.7	37.8	37.9	29
30	38.0	38.1	38.2	38.3	38.4	38.5	38.6	38.7	38.8	38.9	30
31	39.0	39.1	39.2	39.3	39.4	39.5	39.6	39.7	39.8	39.9	31
32	40.0	40.1	40.2	40.3	40.4	40.5	40.6	40.7	40.8	40.9	32
33	41.0	41.1	41.2	41.3	41.4	41.5	41.6	41.7	41.8	41.9	33
34	42.0	42.1	42.2	42.3	42.4	42.5	42.6	42.7	42.8	42.9	34
35	43.0	43.1	43.2	43.3	43.4	43.5	43.6	43.7	43.8	43.9	35
36	44.0	44.1	44.2	44.3	44.4	44.5	44.6	44.7	44.8	44.9	36
37	45.0	45.1	45.2	45.3	45.4	45.5	45.6	45.7	45.8	45.9	37
38	46.0	46.1	46.2	46.3	46.4	46.5	46.6	46.7	46.8	46.9	38
39	47.0	47.1	47.2	47.3	47.4	47.5	47.6	47.7	47.8	47.9	39
40	48.0	48.1	48.2	48.3	48.4	48.5	48.6	48.7	48.8	48.9	40

Example—If point is 22.6 ft. above grade, how far should it be from center line to be a slope stake point? Ans. from Table 30.6. For same slopes but other widths of roadbed, correct above figures by one-half difference in width of roadbed; thus in example above, for 20 ft. roadbed distance will be 30.6+(20—16)÷2 or 2 ft. added to 30.6 =32.6. For slopes of 1 on 1½ see inside of back cover.

Copyright, 1914, by Eugene Dietzgen Co.

B-27

This Field Book is manufactured of a High Grade 50% Rag Paper having a WATER RESISTING SURFACE, and is sewed with Bing Special Enamel Waterproof thread.

Made in U. S. A.

Indexed

2018 Cypress	3
4464 Jewell	4
3615 Noell	5
Tennyson, Wells to Cat. Blvd } one Job	15
Alicia " " } one Job	11
Arastadero " " } one Job	
Lot 101 Blvd Gardens - Mariana 1294	77
Garrison & Scott 5-76	30
Garrison N Side East of Raccoon	33
N. Side Tourmaline - East of Mission Blvd	34
4052 Tennyson	35
Marcey 29th to 30th	36
66 Stakes Lot 1 +34 M.d.	37
" " Lot 10 37 Pt. Loma Hts	38
3020 Univ Ave.	40
Lots 3-4 - Blk 6 Roseville Hts	42
Marlin Drive	57
Curbs - Noyes & Garnet, Lot 21 Blk - 206 - S.B.	76

Hendricks Stake 72' Curb & Sidewalk
Hardin Ohio & Monroe East Side
Smith
Worren
Aug 11, 1947
HYD # 2018.

INDEXED
AUG 8 1951

2

Sta	+	HI	−	Elev Rails	Elev Grade	Fills

INDEXED

50' Curb & Walk at

2018 Cypress 8-26-47

W.O. # 21018

Sommermeyer
Wilmore
Sherman
LaMore

SWBP
Florida & Cypress

	160	237.60	—	236.00
	1.89	227.06	12.43	225.17

0+90 — 224.93 — 2.13 ✓

1+00 — 224.20 — 2.86 — 2.46 — C0.40 on drive

1+40 — 221.75 — 5.31 ✓

Florida & Cypress

stakes 2' North
Curb face
chisel x 2' No. of
1+00

1+40

+ 1+00

224.93 — 0+90

20' — 20' — 20' — 20'

0+00 = old line Florida
20'06
R.

Conc. Pav.
Florida St.

Hoard
Beggs Curb grades for 5' walk
Greer
Roberts Lots 21 - 28 Blk 217 Pac. Beach
9-30-47
4+64 Jewell
W.O. 21018

N/W BP	10.12	61.96		51.84	Jewell Grand
T.P.	9.49	70.49	0.96	61.00	
Sw. Top of	Garnet Jewell		1.9 V	68.55	
0+74	Curb grade			63.80	
				4.69 V	
1+20	"	"		64.92	
				5.57 V	

Stakes set 2' back Curb



LOT 21-28 BLK. 217 ADD. Pacific Beach
OWNER Pac. Beach Pres. Church
CONTR. L. C. Ardersen Co.
PERMIT NO. 1471

AUG 9 1951

Lots 1-2 + 11-12
Blk 194 Middle town
(3615 Noell St)

W.O. 21018

Check Exist. Curb Elev.

N.E.B.P. Noell & La Jolla — 74.15

La Jolla
74.93
.92
71.01 = 0.09 High

Moore St.
50.92
8.20
42.72 = 0.09 High

Met these grades.

14.3%

0.78
74.93
12.57
62.36
.82
63.18
12.70
50.48
0.44
50.92

0+00	+50	1+00	1+50	1+97.9
1463	74.63	63.10	63.10 ↑	
71.01	63.86	56.71	49.56	42.72
3.62	10.77	6.39	13.54	
3.61	8.77	2.39	9.54	
IN.	C 2.00	C 4.00	C 6.00	

74.15
.48
74.63 ↑
12.27
62.36
.74
63.10 ↑
12.62
50.48
4.73
55.21 ↑
12.49
42.72 = End Cl. Moore St.

La Jolla — 9'W + 16'N. Tack
curb in 10' Rad. Ret. Met
Prof. Gr. 70.94

0+00 — 71.02

Sommermeyer
W Moore
E Sherman
10-3-47
W.O.#

0+50 — 63.86

1+04 — 56.71

Noell

1+50 — 49.56

1+97.2 — 4.N. / 11.N. — Profile Grade 42.63

7' Tack.
10' Rad. Curb Ret. in Met

Moore

Curb Grades - 5th & Kalmia

10-15-47

J. Osborne

W.O. 21018

Permit # 1511

Grades - P-7





Curb Grades - 5th + Kalmia - Sketch - P. 6

6.49 246.36 239.87 S.W. 5th & Kalmia

stakes = Nails - 3' out

		Rod	stake Ext. Top	Grade	
0-56.4	= Meet Ext. cb.		36.71	36.77	
0-06		6.17	40.19	40.72	F 0.53
0+00	W.L.	5.77	40.59	41.04	F 0.45
0+04	= P.C.	5.76	40.60	41.15	F 0.55
0+12.8	= ℄	5.87	40.49	41.27	F 0.78
0+19.7	= E.C.	5.58	40.78	41.33	F 0.55
0+23.7	= N.L.	5.52	40.84	41.37	F 0.53
0+33.7		5.37	40.99	41.55	F 0.56
0+81.3	= Meet Ext. cb.		42.71 Ext. Top.	42.53	

changed grade of Return to give proper curb face - OK By A. Brems


Encl.
20' cbs
c.t.
5+25
R=20
Ingraham
7.5
119'
0+02.5
0+00
12.5
R=20
17.5
0+00
c.t.


Pacific Beach Dr.
Mon.
Bldg.
1+00
Fortuna st
Fd. Mon. under Pave

Curb Grades - Ingraham + Fortuna

W.O. 21018

10-17-47

7.0

	4.24	50.35	46.11 Grade	℄ L+T. Ingraham + Pac. Beach
0+00 = N.L. Fortuna				
0+02.5 = P.C.				
0+50		5.26	45.09	
1 ~		5.16	45.19	
+50		5.07	45.28	
2 ~		4.97	45.38	
+50		4.88	45.47	
3 ~		4.78	45.57	
+50		4.69	45.66	

	Rod		Grade	
4 ~	4.59		45.76	
+50	4.50		45.85	
5 ~	4.40	390	45.95	= C 0.50
S.L. Pacific				
5+25 = P.C.	4.35	395	46.00	C 0.40
℄ Ret.	4.25		46.10	
E.C.	4.10		46.25	
	4.42	49.26	5.51	44.84 = ℄ t ℄ Ingraham + Fortuna
N.E. Ret.				
P.C. Ingraham	4.26		45.00	
1/4	4.30		44.96	

Ret. Cont.		49.26			
℄		4.37		44.89	
3/4		4.47		44.79	
P.C. = Fortuna = 0+00		4.64		44.62	
0+40		5.85	5.45	43.41	C 0.40
6+78.5 = Brk.		7.01		42.25	
1+06.5		7.49	7.35	41.77	
3 @ 2	+41.5			41.17	
	+76.5			40.57	

Grade Changed.

Curb Grades, Alicia Dr.
Wells to Cor. Blvd

W.O. 21018

Moore
Begg
Greer
Roberts
10-28-47

2+80

2+60

2+50 Beg. on North O.K.

2+45 Beg. on South.

T.A	6.41	142.92	0.46	136.51 = 12-2-47.	
T.P.	7.68	144.91	0.11	137.23	

1+00 end on North

0+50 Beg. on North

B.M. Mon.	12.23	136.97		124.74	12-2-47.
0+00 = W.L. Wells					
New Mon Alicia Wells 1743-11	12.60	137.34		124.74	

5

3.38 ✓ 139.54 — 138.94 ✓ — 3.98 / 1.98 / C 2.0

curb →

~~139.XX~~ ✓ — 138.83 ✓ — 4.09 / 3.09 / C 1.0
F.S. 7 / 2.07 / C 3.4 — C 2.08 / 4.15 / C 1.93

they do not own this lot

138.63 ✓ — 4.29 / 3.29 / C 1.0
C 6.28 / 4.35 / C 1.93
C6 & Walk NOT PUTIN

~~3.78~~ ~~139.14~~ ✓ —
5.77 / 1.47 / C 4.3

131.13

131.13 ✓ — 5.84 ✓ / 4.84 ✓ / C 1.00
C 6.21 / 3.57 / C 2.64

Note!
Stakes 2' Back of C&G
12-2-47.

1283.1 ✓ — 8.66 ✓
9.03 / 6.84 / C 2.17

12.831

Alicia C6 grados

4+50					
.T.P.	0.44	131.26	12.10	130.82 ← 12-2-47	
T.P.	0.63	133.83	11.71	133.20	
4+00	E y C				
180					
160					
140					
120					
3+00		132.92	12-2-47		
		129.91			

5

1.68 ✓	129.58		128.98	2.28 ✓
	4.25		4.85	
	3.65		3.55	
	C 0.6		C 1.3	
8.87 ✓	134.05		133.45	9.47 ✓
	10.8 C		11.4 C	
	9.7 C		7.9 C	
	C 1.1		C 3.5	
7.23 ✓	135.69		135.09	7.83 ✓
	9.22		9.82	
	7.82		7.8	
	C 1.4		C 2.0	
5.87 ✓	137.05		136.45	6.47 ✓
4.81 ✓	138.11		137.51	5.41 ✓
	C.8		7.4	
	4.4		5.2	
	C 2.4		C 2.2	
4.03 ✓	138.89		138.28	4.64 ✓
3.5 C ✓	139.3 C		138.75	4.17 ✓
	5.55		6.16	
	1.65		3.10	
	C 3.9		C 3.06	

N 12

Alicia Dr.

6+80							108.81	10.67
6+60							110.29 12.14 9.60 C 2.50	9.19
6+45 end on South					7.32	112.16 10.27 7.77 C 2.5	—	
6+40 P.V.C. ✓					6.90	112.58 9.85 7.25 C 2.6	111.98 10.05 6.85 C 3.6	7.50
6+00					3.32	116.16 6.27 3.92 C 2.35	115.56 6.87 2.87 C 4.0	3.92
T.P.	0.76 ~~0.68~~	119.48 ~~119.40~~	12.54	118.72	12-2-47			
T.P.	0.77	122.43	12.17	121.66				
5+50					10.63	120.63 13.2 13.7 0.0	120.03 13.80 12.0 C 1.8	11.23
5+00					6.16	125.10 8.73 8.03 C 0.7	124.50 9.33 7.53 C 1.8	6.76
		131.26	= 12-2-47					
		133.83						

N. Side

Alicia Dr.

7+00	check grades 1-14-x8			107.49 9.45 9.40 C 0.05
6+80				108.81 8.13 8.07 C 0.06
6+60				110.29 2.65 1.60 C 0.05 = 06
End S. Side 6+45		112.16 4.78		
6+40 = P.V.C.		112.58 4.36		111.98 4.96 4.9x
	2.95	116.94		108.99 C 0.02
Check to BM F. Hyd			10x8	109.00 108.99
check to	Top F.H.	Cat. Blvd Alicia	3.27	109.00 108.99 0.01
7+00 end on North				
		114.8 = 12-2-47.		
T.P.	2.88	112.27 122.43	13.04	109.39

S x1

8.5 - 1 x 2 x 14

107.49 11.99
4.78
2.85
C 1.9

Curb grades S. side
Tennyson Betw. Wells & Cat. Blvd.

W/O 3.018

5+60					S 130.69			
					124.23	6.46 ✓		
5+40					125.16 ✓ (5.44, 2.44, C 3.0)	5.53 ✓		
5+20					125.85	4.84 ✓ (130.69)	106.92	BM
							1.57	
							118.49	
							1.14	
							117.35	TP
							10.90	
5+00	PVC.				126.30 ✓ (4.3, 2.7, C 2.1)	4.39 ✓	128.25	
							1.80	
							126.45	TP
							4.24	
							130.69	HI
4+80					126.50 ✓ (4.1, 2.0, C 2.1)	4.19 ✓		
4+50	Beg. on S.				126.60 ✓ (4.0, 1.8, C 2.2)	130.69	HI	
	00 = W.L Wells					126.60		
						4.09 ✓		

T.P.	11.39	130.61	0.06	119.22
SW Mon.	12.30	118.28		106.92 ✓
Tennyson & Wells				

7+50					11920			
					106.90 ✓	12.30 ✓		
					12.4			
					10.5			
					C 1.9			
							130 69	
							12 63	
7+00					11920			
					117.98 ✓	7.22 ✓	118 06 TP	
					7.3		1 14	
					C 2.2 ✓		119.20 HI	
							12.29	
							106.91 TP	
							091	
6+70					11920			
					115.02 ✓	4.18 ✓	107.82 HI	
	0.67	119.30			4.3			
T.P.			11.98	118.63	C 2.3			
					130 69			
6+40	E.C.				118.06 ✓	12.63		
					12.5 ✓			
					9.9 ✓			
					C 2.6			
					130 69			
6+20					119.97 ✓	10.72 ✓		
					10.63			
					7.63			
					C 3.0			
6					121.63	9.06 ✓		
5+80				130 69				
				130 61 8	123.05 ✓	130 69		
		13061			7.55	7.64 ✓		
					4.05			
					C 3.5			

+ HI − EI

c3-m1-14-48

check curb grade

8+00 0.88 101.84

13.19 102.72 89.53

8.12 89.54 89.53

T.P. 1.33 97.71 1.88 96.38

8+05.25 = End of on S.

8+00

0.97 108.26

119.30 12.01 107.29

40 − 1 x 2 x 14

20 2 x 2 x 14

89.53 82 29

curb end 1743 22

Tennyson Catalina

107.82 ✓ 101.30 6.52 ✓

6.96 4.91

5.32 1.61

c 1.64

107.82 101.84 5.98 ✓

107.82H
1.76
97.06
1.20
98.26
8.44
89.82

107.82
10.76
97.06
1.68
98.74
9.21
89.53

Point

Tennyson Catalina

Curb grades
Atascadero Dr
Wells to Cor. Blvd.
WO 2108

0+50	= end on S & Beg. on N.				
+40	4.22	159.72	155.50	11-14-47 PM	
+20					
0+00	W/L Wells = Beg. on S.				
11-14-47	3.26	158.76	155.50		
SWLy Con. Mon. Atascadero + Wells	4.89	160.39	155.50		

S

3.00 ✓	155.72	
	3.67	
	1.33	
	C 2.3	
3.18 ✓	155.54	
	3.85	
	+ 1.65	
	C 2.2	
3.79 ✓	155.93	
	4.46	
	2.56	
	C 1.9	
4.52 ✓	155.20	
	5.19	
	4.89	
	C 0.3	

N

	155.13	
	4.26	2.63 ✓
	4.92	
	F 0.66	
—		
—		
—		

155.20
155.30 / 4.42 ✓
R.10 — — — 155.63
SW. Cor Atascadero & Wells

1+60				4.47	15525 5.14 3.44 C 1.7	—	
1+50	= end on N.			~~4.07~~ Not set	~~15565~~ 4.74 3.0 C 1.7	15505 5.34 2.34 C 3.0	3.71
1+40				3.67	15605 4.34 2.44 C 1.9	15545 4.94 2.44 C 2.5	3.31
1+20				3.09	15663 3.76 1.94 C 1.8	15603 4.36 2.26 C 2.1	2.73
1+00	Beg. on S.			2.76	15696 3.43 1.1 C 2.33	15636 4.03 2.13 C 0.9	2.10
0+80				—	—	15647 3.92 4.38 F .46	2.29
0+60		15977 PM 15876		—	—	15631 4.08 4.32 F .24	2.45
		16039					

							S			N		
3+50						7.37	140.70			140.10	6.43	
							7.8			8.4		
							6.4			6.8		
							C 1.4			C 1.6		
3 T.P.	0.87	148.07	12.52	147.20	P.M.	1.7	144.81	3.26		144.21	2.32	
T.P.	0.76	146.53	12.99	145.77	11-14-47	0.7	3.69			4.29		
T.P.	1.1 C	148.50	.1305	147.34	A.M.	C 1.0	3.29			2.89		
							C 0.4			C 1.4		
2+50	Beg. on N.					10.80	148.92			148.32	10.46	
							11.47			12.07		
							10.57			8.77		
							C 0.9			C 3.3		
2+20	E.V.C.					8.34	151.38			—		
							9.01					
							8.01					
							C 1.0					
2+00						6.82	152.90			—		
							7.49					
							7.09					
							C 0.4					
		154.72 = P.M.										
1+86		158.76	11-14-47.			5.54	154.18			—		
							C 2.1					
		160.39					4.9					
							C 1.3					

Catalina & Atasco dem.

Check to SEB-10			8.55	116.86	116.84
T.P.	1.24'	125.41	12.55	124.17	

5+50 end on North

5+00 = End on South

T.P. PM 4+50	0.75	135.84	12.98	135.09	
T.P.	0.41	133.86	13.08	133.45	11-14-47
	1.07	136.73			
T.P.			12.80	135.70	

T.P. PM 4+00

14807 PM.
14653 11-14-47

14850

85 - 2 x 2 x 14

—				123.67	10.19
				13.05	
				10.85	
				C 2.2	
7.46	12838		8.0	127.78	6.08
	8.34			8.94	
	8.04			7.84	
	F 0.3			C 1.1	
3.36	13248			131.88	1.98
	4.24			4.84	
	0.0			3.94	
				C 0.9	
11.48	13659			135.99	10.54
	11.91			12.51	
	19.2			11.5	
	C 2.7			C 1.0	

Walker
Hendricks
Becker
Johnson
12-30-47

CURB GRADES

HAWK ST.

Indexed
SB

1+49.85		6.14	253.30	253.30
1+20		5.84	253.60	253.60
0+95		5.59	253.85	253.85
0+70		5.34	254.10	254.10
0+45		5.09	254.35	254.35
0+20 = Brk		4.84	254.60	254.60
0+00 = S. Line	Sutter	A84 St	254.60	254.60
	4.89	259.44		254.55

Cuts offsets.

2' Lt. of cb
"
"
"
"
"
"



B.M. on South edge Side Walk
East Line Hawk
FB 1768
59

Plotted. TPS 6/11 McQ

Curb Stakes

Moore Bogg Green Roberts 1-15-48

Lot 5 Blk 28 Montemar Ridge

W.O. 21018

Sw. A. Bolt on Curb	2.78	44.41	41.63	Rose crown Lytton 1775-17
T.P.	1.36	33.94	11.83	32.58
T.P.	1.58	22.72	12.80	21.14
		8.79	14.53	14.33
		1775-26		0.20 / 0.17

15.36 / 7.36 — 16.33 / 6.39 — 17.30 / 5.42

10' sdwalk
Stakes 3' Back curb line and set to grade



Curbgrades N.E. Cor.
Garnet & Jewell
W.O. 21018

Moore
Bagg
Green
Roberts
1-19-47.

SEBP Garnet Ingraham	7,16	6976		62.60
T.P.	6.72	7V.09	2.39	67.37

States set 3' back

0+32.5 = E.C. #2 — 68.36 / 5.73

0+50 — 68.55

1+00 — 69.10

1+35 = ℄ old alley now closed — 69.50





Void

Not Rt. Cor

Next Page



Lot 20 / 217 P.P.

Curb grades

SW Cor of

Garnet & Jewell

MOORE W.O. 21018

1-19-48.

H.I. P24 ← 7409

7409
5.55
18.55

SL. Garnet
0+00 Ex. cb. bird — 18.55 ← P.V.

0+50 — 17.33 / 6.76

1+00 — 16.11 / 7.98

1+24.48 - NL alley — 15.56 / 8.53 ✓

BLK. IS 1.04 Short

STAKED 2' back

LOT 20 BLK. 217 ADD. Pacific Beach
OWNER L. C. Anderson Co.
CONTR.
PERMIT NO. 1705

Lot 181

Stake 99.3 curb on Littlefield

Moore
Begg
Roberts
1-30-48

W.O. 21018

T.P.	F.B.			
1821-32	0.51	37.82		37.31 ✓
T.P.	37.6	33.45	8.10	= 29.72

25.50 = 27.39 29.28 32.75

7.90

25.58

0.57

32.96

0.21 H ✓

Top Ex c6
2' W of EC.

25.65 = 27.50 29.34

7.83 ✓ 5.98 ✓ V.I. ✓

Bay. Pk. V.L.

26



W.O. 21018

Curb stakes on N.S. Atascadero Dr

Lot 65 Catalina Villas

SW Mon Wells Atascadero

	4.75	160.25	155.50
0+00 = W/L Wells		EVC	
	2+00	2+20	2+50
	152.30	150.78	148.32
	7.95	9.47	11.93

Lot 86 Cat. Villas

0+00 W/L Wells

BM SW Mon. 7.6 N 114.54 106.9 N Tennyson Wells P.18

0+50	1+00	
109.03	111.76	
5.51	N 1.78	
4.51	1.90	
C 1.0	C 0.88	

INDEXED Oct 11 1951

LOT 65-84-86 BLK. 37 ADD. Pt Loma Hts. Catalina Villas

OWNER

CONTR.

PERMIT NO.

2-3-48

W.O. 21018

27

Lot 84 Cat Villas

BM T.P.	12.00	136.7 N		124.74	P.11
	8.9 N	144.22	1.44	135.30	

W/L Wells = 0+00

5' INT

2+55	2+60	2+80	3+00	3+05	
138.73	138.83	138.9 N	138.75	138.63	
5.49	5.39	5.28	5.47		
			5.53		
			0.06 Low	C.B. Cond	

Permit said Blk 38 error Should Lot 13 Pt. Loma Hts 37 was set. P.11

0+50	1+00		
13 C.74			
~~128.9~~	~~131.74~~		
128.31	131.13		See P.11
8.43	5.61		
	5.11		
	C 0.50		

LOT 13 BLK 37 ADD. Point Loma Heights

OWNER

CONTR.

PERMIT NO.

Curb Grades Lot F Block 35 N.C.T. San Diego
North Side G.St. 100' East of Pacific Hwy

BM	5.50	8.46	2.96	S.P.R.R. Spike in Root

Feb 5-48
S. Olson
Allen
Smith
Johnson
No. 2 of 18

5' Stakes offset 5' Back of Face of Curb

LOT Por. F BLK. 35 ADD. N.S.D.
OWNER Santa Fe Railway
CONTR. Triple Construction Co.
PERMIT NO. 1770



W.O. 21018

2-16-48

J.O. 29

INDEXED
AUG 9 1951

Stake - 150.5' of Curb on Chalcedony for Lot 51 - W. of Academy St.

	2.56	128.59		126.03	S.E. 7' ct. Chalcedony + Lamont
	2.29	118.41	12.47	116.12	
			Rods 6.88	Grade	
0+00 = Meet Exit. cb.			11.53	111.54	
0+24.55			5.62 12.79	11.79	C 1.00
+49.11			5.37 13.04	12.04	C 1.00
+69.11			6.12 12.29	12.29	
+89.11			5.77 12.64	12.64	
1+09.11			5.32 13.09	13.09	
+29.11			4.78 13.63	13.63	
1+50.5 = end.			4.08 14.33	14.33	

LOT 51 BLK. 1 ADD. Pacific Beach
OWNER Milton P. Sessions
CONTR. Griffith Co.
PERMIT NO. 17886



curb grades Sly. side

of Garrison, Roseerans & Scott

B.M. W.O. 21018 1776-37

SW BP. 3.71 6.46 2.75

Rosecrans

Garrison

0+00 ~~2.31~~ 2.20 This is the Curb

~~4.14~~ 4.26

Moore

Begg

0+50 Gacer 2.06

Roberts 11.40

4-1-48

1+00 1.92

4.54

1+50 1.78

4.68

2+00 1.64

4.82

2+48 P.S. Curb 1.50

4.96



Garrison

INDEXED 30

AUG 8 1951



Fenelon

Walker Side Walk Grades
Hendricks on Broadway Between
Becker 7th & 6th
Williams
4-19-48

LOT G & H BLK. 34 ADD. Horton's
OWNER Thearle Music Co.
CONTR. M. H. Golden Constr.
PERMIT NO. 2028

RECEIVED
AUG 8 1951

6th Ave



Curb Grades Alg Garrison St.
Between Roseerans & Sco H Sts.

BM	4.65	7.40		2.75	SMBP Roseerans & Garrison

INDEXED AUG 8 1951

May 5-48
Sisson
Smith
Allen
Sobinson

W.O. 21018.

2 Stakes 1' Back of Face of Curb

LOT 5½ 1-2 BLK. 62 ADD. Roseville
OWNER J. Walton
CONTR. J. F. Araiza
PERMIT NO. 2035

LOT 3-4-5 BLK. 62 ADD. Roseville
OWNER Clark, McCormick, Machado
CONTR. J. F. Araiza.
PERMIT NO. 940



B.M.	11.46	14.80		3.34	S.W. 1" Disk Ingelow & Rosecrans
		= exist. cb.		4.80	
S.L. Ingelow				10.00	10.00
14'				4.65	
				10.15	10.15
12.68'					
P.C. 43' Rad.		25' S. of S.L. = 0+00		4.50	
				10.30	10.30
+25				4.40	
				10.40	10.40
+50				4.30	
				10.50	10.50
0+75 = Lot line				4.20	
				10.60	10.60

INDEXED

Curb. Stakes on Lot 12 - Block 74 - Roseville

7-14-48

7.0.

#2503

W.O. 21018

Locust st



LOT 12 BLK. 17 ADD. Roseville

OWNER Scott King

CONTR. Travelodge Corp.

PERMIT NO. 2267

Stake 57$ cl. N. side Tourmaline

Stakes 3' Back of Ch. face

7-15-48

W.O.# 21018

Sommermeyer
McCoy
Melton

N.W.B.P. Sapphire + Mission Blvd. 98.54
1.54
100.08
8.52
91.56
3.72
95.28

0+00
6.68

LOT 2-4 BLK. 3 ADD. Ocean Villa
OWNER Alvidson
CONTR. Callahan Bros.
PERMIT NO. 2229

East of Mission Blvd.



Lot. 1 Blk 35 Pt. Loma Hgts

4-23-48
W.O. 21018

Sommermeyer
McCoy
W. Moore
Melton.

S.W. Mon. Wells & Tennyson 106.92
11.66
118.58
0.42
118.16
11.77
129.93

S. 5' inc Tennyson
Set B.M. W.L. San Clemente 3.29 126.64

129.93
11.77
118.16
0.66
118.82
11.70
106.92 ✓ orig B.M.

LOT 1 BLK. 35 ADD. Point Loma Heights
OWNER Howard Close
CONTR. J. F. Araiza
PERMIT NO. 2259

Fd. 2" pipe
17 A 2
16

INDEXED
AUG 8 1951

35

Set lead & disk

25' 30'

Sublina

Fd. nail

Fd. 1/2"

San Clemente →

125.60
A.J 3

125.75
4.18

125.00
4.93

20' Cl. Rad.

0-10

125.50
4.43

123.42
6.51

0-50

2

Tennyson

5 3/4%

125.50
106.00
3.75 19.50 .052
19 75
750
750

106.00
10'
105.45

Fd. nail

Stake 380' of 7' curb on N. side Marcey 29th toward 30th

Moore & Gay Bench 7-27-48

BM			6.75	68.46	68.45
TP	4.61	75.21	4.95	70.60	
3+80	Rec'd as			71.62	
				3.93	
+50			71.50		
			4.05		
3				71.32	
				4.23	
+50			71.13		
			4.42		
2				70.94	
				4.61	
TP	4.79	75.55	4.34	70.76	
+50			70.76		
			4.34		
1				70.57	
				4.53	
0+50			70.39		
			4.71		
0+00 E.L. 29th				70.20	
				4.90	
NW BP Logan 29th	4.55	(75.10)		70.45	

W.O. 21018

INDEXED
AUG 8 1951



Curb stakes

Lot 1 Middletown
234

1+00		Not Set	2.04
0+80	Break	Not set	2.10
0+66	end Job		2.01 ✓
			4.84 ✓
0+13	c6 end		1.66
			5.19 ✓
			5.19
			0.0
0+00	Ely Pacific		

B.M.
SW 7" C.T. 5.37 6.85 1.53
Bonding
Kurtz
1675-X9

W.O. 21018

Moore
Bc99
Bunch
8-2-X8

INDEXED
AUG 8 1951



LOT 1 BLK. 234 ADD. Middletown
OWNER Wright Refrigeration
CONTR. A. S. Anderson
PERMIT NO. 3173

INDEXED
AUG 8 1951

Curb stakes

Lot 10 Blk 37 Pt Loma Hts.

W.O. 21018

Moore
Beggs
Burch 8-2-48

+60			138.83
	on Curb		3.22
			3.28
			0.06 Low
+40			138.43
			3.62
			3.22
			C 0.40
+20			137.71
			4.31
			3.31
			C 1.00
2+00	P.V.C.		136.76
			5.29
			4.29
			C 1.00

0+00 = W.L. Wells

T.P.	5.99	(142.05)	1.32	136.06
	12.64	137.38		+0.09
B.M. Mon.	~~12.67~~	~~137.41~~		136.74

N.W. Wells + Alicia.

INDEXED
AUG 8 1951

Hardin
Oakley
Decker
Duncan
8-13-48

Curb Grades

Grand To Alley E. side Ingraham
W.O. 21018

B.M. N.E. B.P. Grand & Ingraham

	5.33	61.18	55.85	
	Stakes 3' Back Curb face			
1+24.65	4.00	57.18	58.06	F 0.88
1+18.65	PC 4.00	57.18	57.90	F 0.72
0+93	4.24	56.94	57.47	F 0.53
0+64	4.52	56.66	56.93	F 0.27
0+31	5.17	56.01	56.39	F 0.38
0+00	N. Line of	Grand	Ave.	Meet 55.85



INDEXED
W.K.
OCT 19 1948

Curb Stakes 3020 Univ Ave.

10-1A-48

W.O. 21018

Sommermeyer
McCoy
Allen
Jones

Stakes on 3' offset line

Meet Exist ol.		Alley Rot. B.C.	E.C.	Alley & Prop.
0+00	0+40 ℄	0+80		
5.37	94.98	95.35	95.38	95.49
94.62 = EL	5.01	4.64	4.62	4.50
Meet ol.	×		4.65	×
			F0.03	
Pave				
0+80				
5.32				
94.68 = EL				

Set 0.67 curb face

Assume 99.99 - π

℄ Univ. Ave.



2-21-45 State Cb Lots 4&D Block J Plumosa Park
Hendricks
Bramby
Greer
Rorer
WO# 21018

INDEXED
AUG 8 1951

Meet Ex Cb		7.77	143.24	143.24
#1		7.86	143.15	144.06
#2		6.55	144.46	144.88
#3 PRC		6.13	144.88	145.70
#4		5.28	145.73	146.34
#5		3.72	147.29	146.98
Meet Ex Cb		3.38	147.63	147.63
	0.66	151.01		150.35

SE. curb Villa Dr & Elliott 41



Meet	
F 0.91	
F 0.42	
F 0.82	
F 0.61	
C 0.31	
Meet	

LOT 4&D BLK. J ADD. Plumosa Park
OWNER Ralph Krause
CONTR. Triangle Contractors
PERMIT NO. 3939

SEBP Villa Dr. & Elliot St.

Moore
3099
D. Sisson

Curb stakes 4-7-49.

Lots 3-4 Blk 6 Roseville Hts

W.O. 2018

SEBP	0.35	154.46	154.11	Trumbull Akron
1+25 Sly Lot 4		8.15	148.31	
2+39.92 Brk		8.66	147.80	
2+50		9.20	147.26	
End Top cb. Return NWly Cor. of Trumbull & Akron		2.33	154.13	154.20 = .07

INDEXED
AUG 8 1951

Blk 6

Sly Line Lot 4 Blk 2 +25

Trumbull

cb. R.18

5

7' Ld. C.T.

Akron.

Profile

Lot 3-4 Blk. 6 Add. Roseville Hts

Owner Baker

Contr. James J. Hill

Permit No. 4035

Curb Grades South Side Main St.
West of 28th St.

BM	0.69	40.82		40.13	X.N. B.P. 805 Main St 28th St
TP	1.49	30.19	12.12	28.70	

INDEXED

AUG 8 1951

PERMIT NO.
CONTR.
OWNER
LOT BLK. ADD.

LOT 1-2-3-4 BLK. 22 ADD. Reed & Hubbell
OWNER Tipton
CONTR. Raymond Arnold
PERMIT NO. 4059 4-13-49

April 19-49
H. Sisson
D. Smith
W Garber

W O 21018

(25.39) = Existing Curb

28th St.

Existing Curb + Walk



P. Smith III
C. Sommermeyer II
C. Allen
J. Rorer

Curb Stake 75' of walk North of Alley
1 of 12 Blk 3 La Mesa Colony

wo # 20007
10-10-49

Amherst St

INDEXED
W.K.
OCT 14 1949



BM 35.0 460.20 — 457.20 SW BP 657 ft El Cajon.

El Cajon Blvd.

D Smith III
C Sommermeyer
C Allen
J Rorer

Stake curb Return Kalmia
Kettner

wo # 20007
10-13-49
44



INDEXED
W.K
OCT 14 1949

LOT 12 BLK. 3 ADD. La Mesa Colony
OWNER W.D. Jeahke
CONTR. Al. Riley
PERMIT NO. 4475

TP	5.32	36.58	6.23	31.26	
BM	4.52	37.49		32.97	SE BP laurel Kettner

D Smith
D Hendricks
J Greer
F Bunch

wo# 20007

10-24-49

45

Stake curb + walks Estrella St.

Permit # 5373-5374.

btw. Orange + Trojan Ave.

Fd 7x7 tack NW cor Orange + Estrella

Fd 7x7 tack SE cor Trojan + Estrella

INDEXED

AUG 8 1951

LOT 11-12 BLK. 35 ADD. Fairmount

OWNER Quidart

CONTR. John Picone

PERMIT NO. 5373

LOT 28-42 BLK. 34 ADD. Fairmount

OWNER Greenwood - McNeally

CONTR. John Picone

PERMIT NO. 5374

					C6 Elv.	
				West side		2 18
	0+00	=		North of N line Orange	346 50	
	0+90		Begin c6 + walk		343 26	5 50 5 48 CO 02
	1+07 5				342 65	6 13 6 23 FO 10
	1+25		End c6 + walk		342 02	6 76 7 01 FO 25
	2+00		Begin c6 + walk		339 47	9 31 9 71 FO 40
	2+04 15				339 38	9 40 9 74 FO 34
	2+17 85		Top c6 inlet exist'g		339 17	9 61
	2+28 85		Top c6 inlet exist'g		339 09	9 69
	2+44 15				339 35	9 43 9 75 FO 32
	2+50		End c6 + walk		339 59	9 19 9 69 FO 50
BM	0 33	348 78	348 45	SE cor BP Church St & Orange + Estrella		

Permit # 5373-5374

East curb Estrella Lot 11+12

		cb Elv.	
3+50	Begin cb + walk	343.28	5.50 / 5.99 / FO 49
3+75		344.18	4.65 / 5.00 / FO 35
4+00	Connect existing cb	345.13	3.75 / 4.17 / FO 42
4+25		345.91	2.87
4+50	End walk	346.68	2.10

		cb elv.	3' BK cb face
3+50.15	North line Lot 10 existing cb	343.98	4.80 / 5.00 / 020 Low
3+28.65		343.13	5.65 / 5.79 / C006
3+07.15		342.29	6.49 / 6.49 / G
2+85.65		341.44	7.34 / 7.37 / FO03
2+64.15	BrK	340.60	8.18 / 8.56 / FO 38
2+50.15	End cb+walk South line Lot 12	340.04	8.74 / 9.03 / FO 29
2+30.75	North end Top cb inlet existing	339.52	
2+19.75	South end Top cb inlet existing	339.31	

HI 348.98

Stake Cbs Twiggs & Congress
Block 462 Lot 1

Sta	+	H.I	–	Elev. Stake	Elev. Gr.
CL Exist Cb 87' West of San Diego Ave			0.05	26.86	26.83
1+00			4.34	22.57	~~22.43~~ ~~21.83~~
0+75			4.61	22.30	~~22.22~~ ~~21.74~~
0+50			4.74	22.17	~~22.01~~ ~~21.66~~
0+25			4.94	21.97	~~21.81~~ ~~21.58~~
0+00 EC Cb			4.99	21.92	~~21.60~~ ~~21.50~~
#1 ℄ Curve			5.04	21.87	~~21.54~~ ~~21.44~~
1+50 EC 10' CbR			5.01	21.90	21.50.
1+25			4.40	22.51	22.12
1+05			3.90	23.01	22.62
0+85			3.29	23.62	23.12
0+65			2.61	24.30	23.62
0+45			2.38	24.53	24.12
0+25			1.91	25.00	24.62
0+00			0.97	25.94	25.25
T.P.	2.92	26.91	11.47	23.99	
B.M.	13.14	35.46			2232

LOT 1 BLK. 462 ADD. Old Town
OWNER D. y. Harbough
CONTR. Daniel E. Wipff.
PERMIT NO. 5438



12-6-49
Hendricks
Johnson
Greer
Cota
W.O.# 20007

Stake CB & Sidewalk
Lots 33 & 34 Block 230 Pacific Beach

INDEXED.
AUG 8 1951

Sta	+	H.I	−	Elev. Stake	Elev. Grade
2+00			1.68		19.08
1+75			1.94		18.82
1+50			2.21	18.55	18.52
0+00			3.72	17.04	17.00
BM	9.01	20.76			11.75



12-27-49 Stake Cb's Lot 1 Block 210 Pacific Beach
Hendricks
Johnson
Cote
WO# 20007

INDEXED
AUG 8 1951

LOT 1 BLK. 210 ADD. Pacific Beach
OWNER Harry Muns
CONTR. Frank G. Real & Co.
PERMIT NO. 100310



0+50	End		6.16		33.75	Pendelton 54
0+25			5.48		34.43	
0+00	East Line Pendelton	4.81	4.81	35.17	35.10	Ex. Cb
BM	4.81	39.91			35.10	(Ex Cb 0+00 used as B.M.)
TP	3.65	39.98	9.46	36.33		
BM	0.69	45.79			45.10	NWBP Garnet & Olney

Stake Curb along Lot 40' Block 202
Pac Beach - 6-21-50 - 70.
4579
W.O. 20007
N.W. 7' ct. Garnett & Ingraham 63.26
see Plan 7016-L for Elev.
N.L. Garnet.

6'N=		Grade	
P.C. 20' Rad = 0+00	63.21	63.32	
+30	63.70	63.74 (.70)	F 0.04
+60	64.08	64.16 (.08)	F 0.08
+90	64.20	64.58 (.20)	F 0.38
1+19 = end.	64.90	64.98 (.90)	F 0.08

LOT 40 BLK. 202 ADD. Pacific Beach
OWNER Safeway Stores, Inc.
CONTR. Morena Bros.
PERMIT NO. 2642

IMPROVED
AUG 8 1951



INDEXED APR 26 1951

Johnson
Cota
Greer
Crawford
W.O. 20007
8-7-50

Stakes for 50' Sidewalk
South Side Tourmaline St.
West of Mission Blvd

				1.18	98.54
T.P.	8.63	99.72		3.02	91.09
				6' from CB outside edge Sidewalk Grade	
	Curb Elev	Rod	Stake Elev.	Elev	Cuts or Fill
0+65 =	85.88	8.49	85.62	85.34	FO.32
0+50 =	End 86.24 Sidewalk	8.24	85.87	86.30	FO.43
0+25	86.84	7.24	86.87	86.90	FO.03
0+10 =	87.20 Brk.	6.79	87.32	87.26	CO.06
0+00 =	87.30 West Line Mission Blvd				
T.P.	5.02	94.11		10.96	89.09
B.M.	1.51	100.05			98.54

98.54 = N.W.B.P. Sapphire & Mission Blvd



N.W.B.P. Sapphire & Mission Blvd

9-6-50
Hendricks
Cota
Greer
Bunch
WO# 20007

Stake Cb Lots 10, 11, 12, & 13
Blk 11, New Roseville

INDEXED
AUG 8 1951

Stg.	+	H.I.	—	Elev. Stake	Elev. Grade

LOT 4-5 BLK. 11 ADD. New Roseville
OWNER Marie Tillman
CONTR. Al Riley
PERMIT NO. 4826

1+00			7.45	18.00	17.50
0+70			6.25	19.20	18.70
0+50			5.45	20.00	19.50
0+25			4.45	21.00	20.50
0+00			4.03	21.42	21.50
TP	4.03	25.45	7.86	21.42	
BM.	1.46	29.28			27.82

52

LOT 10-13 BLK. 11 ADD. New Roseville
OWNER Paul Conner
CONTR. Al Riley
PERMIT NO. 4823

Rosecrans



NW 4 BP Bessemer & Rosecrans

Cont. P-54

Walker Pope Rasmussen 11-28-50

Exist cb = 2701 Blk

Exist cb 17.66

50'

5.5

1948 = 7

Exist cb

-7.5 25'

-10-

Exist cb = 2+50

cb. Grade 17.74

Stake 17.82 C 0.08

2+00

16.34 = curb

16.96 = Stake

C 0.62

1+60

1+57

cb = 16.02

16.34

C 0.32

10'

10'

14.94 = curb

15.54 = Stake

C 0.60

1+20

1+17

cb = 14.53

Stake = 14.63

C 0.10

13.54 = curb

14.79 = Stake

C 1.25

0+80

0+77

cb = 13.04

Stake = 13.21

C 0.17

Talbot St

12.31 = curb

13.23 = Stake

C 0.92

0+45

0+42

cb = 11.74

12.01 = Stake

C 0.27

11.59 = cb

12.57

C 1.07

0+22 Brk

0+22 = Brk

cb = 11.0 = Brk

11.37

C 0.37

11.01 = cb

Stake = 12.21

C 1.20

0+10

0+03

0+00

13'

7'

cb. 10.22

0.00

0+00

10.66

11.88

C 1.23

0+00

10' cb R

7'

0+00

0+10

0+22

17'

7.0'

Exist cb 9.90

cb

10.45

11.79

C 1.34

Set Cop Disc. in Lead Plg

Fd. Conc. Mon.

Set Bar & Tag on Mon

Plan 652.5+

cb = 10.38

11.46

C 1.08

curb = 10.22

11.32

cb = 10.10

11.34

C 1.25

Brk

2.75 = B.M. Rosecrans & Garrison

1.52 chk Disc. SW. Garrison & Scott

T.P. 0.58

T.P. 2.75

T.P. 7.49

T.P. 11.23 chk curb Upshur See sketch

LOT 19-20 BLK. 9 ADD. New Rosedale

OWNER R. B. Moseley

CONTR. C. L. Riley

PERMIT NO. 4824

10'

Exist Curb

7'

11.23

10'

49

11'

Upshur St.

70'

Conc. Paving

Exist Curb

7

Fd. Conc. Mon.

0.51%

11.00

10.33

11.15

C 0.82

0.5%

Cont. from P-53

Rosecrans Street



LOT 17-18 BLK. 9 ADD. New Roseville
OWNER G.R. Wood
CONTR. Al Riley
PERMIT NO. 4825

LOT 17-18 BLK. 9 ADD. New Roseville
OWNER J. E. Conn
CONTR. Al Riley
PERMIT NO. 4828

12-8-50

Grade stakes for cbs. 11th. st. South line
Market st. = 0+00. South to 1+50 (on West.)

1+50 meet exist. cb.	40.75 Exist.
1+25 end drive	41.13 40.85 F - 0.28
0+85 begin drive	41.75 41.46 F - 0.29
0+50 end drive	42.29 41.99 F - 0.30
0+10 begin driveway	42.91 Elev. Grade 42.60 Elev. stake F - 0.31
0+00 (So. line Market st.)	43.06 Exist.

Direct Elev. Rod.

B.M. Elev. = 38.47 N.W.B.P. Island & 11th.

X-25-51 Stake C&S Block 126
Hendricks Lot 4 La Playa Sub
Allen
Shepard
Bruner
HO #20007

INDEXED
APR 26 1951

LOT 4 BLK. 126 ADD. La Playa
OWNER Ernest Montero
CONTR. Silver Strand Constr.
PERMIT NO. 37244

		Elev. Stake	Elev. C&S
0+75		C1.32	60.38
0+50		61.14	60.25
0+25		61.21	60.12
0+00 ℄ Line Kellog		60.05	60.00
BM			59.58



MERLIN DRIVE

CURB GRADES

Walker Pope Clark Huffman 5-22-51

Lots - 1-7 Blk 1; 1-12 - Blk 2;

" 1-20 Blk 3

Used:- Sub Map 2692. W.O. 20007

Alignment = Page 67-72

℄ Station	def	
0+88	1°31.4'	
0+62	1°04.4'	℄ R = 1654.4'
		Δ = 15°48'24"
		L = 456.4'
		def. per ft = 1.039'
0+36	0°37.4'	

0+17.56 = C.B.C. Rt. on Rt. 21'R 0°18.5'

~~0+10~~ 0+16.40 = B.C. 0°17.06

0+00 = B.C. Rt. K.L. Kenwood

(N.W. & N.E. Returns on P-66)

12.12 222.14 210.02

Lt. ℄ Rt. 57

Top cb Subgrade = Oiled finish Top cb.

= 0.33 below Future Paving

With 0.25' crown per inst. — Roder.

INDEXED

AUG 8 1951

C 0.10'				F 0.01
218.44	17.94'	18.12	18.46	218.96
218.54'				218.95'
3.60				3.19

C 0.93'				C 0.22'
216.46	13.96'	16.14	16.48	216.98
217.39'				217.20'
4.75				4.24

C 0.52'			Gut	C 0.24'
214.48	13.98'	Sub 14.16	14.50'	215.00
215.00 V				215.24
7.14				6.90

C 0.87		Fan 13.03	Gut	C 0.21
212.99 = cb	Gut 12.49'	12.71 Sub.	13.08	213.58 = cb
213.86	Stakes			213.79

222.14

BM SW Top cb GH Book 274-7

Kenwood & Merlin Drive

Merlin Drive Curb Grades

North of Kenwood

2+40		4°09.34			
2+20		3°48.56			
2+00		3°27.78			
1+80		3°07			
1+60		2°46.22			
1+40 P.V.C.		2°25.44			
T.P.	12.20	234.04	0.30	221.84	
1+14		1°58.43			
		222.14			

Lots 1-20 in Block 3
1-12 in "2"
1-7 Blk. "1" Amended Hills
Owner C. J. & Ida Smyth
Cameron Bros.
Permit No. 40625 - 40626

Lt.		℄		Rt.
T.P. Ch. F 0.03			Gut.	Top Ch. C 0.13
228.86	28.36		228.86	229.36
228.83				229.49
5.21				4.55
C 0.09				C 0.22
227.77	27.27	27.44	27.77	228.27
227.86				228.49
6.18				5.55
F 0.13				C 0.37
226.57	26.07		26.57	227.07
226.44				227.44
7.60				6.60
C 0.04				C 0.36
225.28	24.78		25.28	225.78
225.32				226.14
8.72				7.90
C 0.07				C 0.32
223.90	23.40	23.87	23.90	224.40
223.97				224.72
10.07				9.32
C 0.15				C 0.39
222.42	21.92		22.42	222.92
222.57				223.31
11.47				10.73
		234.04		
220.55 T.P.				
C 0.14				F 0.14
220.42	19.92	20.10	20.44	220.94
220.56				220.80
1.58				1.34
		222.14		

58

T.P. 228.61

Melin Drive Curb Grades

3+80		6°34.96'		
3+60		6°14.18		
3+40		5°53.40		
T.P.	8.43	242.22	0.25	233.79
3+20		5°32.62		
3+00		5°11.84		
2+80		4°51.06		
2+60 = EVC		4°30.14'		
		234.04		

Lt. Top cb		℄		Rt. cb
C 0.15				C 0.25
235.65	35.15		35.65	236.15
235.80				236.40
6.42				5.82
C 0.14				C 0.24
234.68	34.18		34.68	235.18
234.82				235.42
7.40				7.00
C 0.22				C 0.29
233.71	33.21	33.38	33.71	234.21
233.93				234.50
8.29		242.22		7.72
C 0.14				C 0.24
232.74	32.24		32.74	233.24
232.88				233.48
1.16				0.56
C 0.30				F 0.37
231.78	31.28		31.78	232.28
232.08				231.91
1.96				2.13
C 0.48				C 0.30
230.82	30.32	30.49	30.82	231.32
231.30				231.62
2.74				2.42
F 0.09				C 0.14
229.86	29.96		29.86	230.36
229.77				230.50
4.27				3.54
		234.04		

Merlin Drive - Curb Grades

					Lt.	℄	Rt	
								F.L. Gutter
5+00		0°48.5'			C 0.05 241.48 241.53 9.34	40.98 v. 41.18 = Sub.		C 0.42 241.48 41.90
4+75		0°20.5			C 0.17 240.27 240.44 v 10.43	cb Gut. 39.77		C 0.46 240.27 40.73
Spike in Pole 4+40 on Lt. T.P.	9.14	250.87	0 49	241.73		250.87		
4+57.86 = End Curb on Rt.					C 0.02 239.43 239.45 2.77 239.45 2.77	38.93 v	39.10 = Sub.	F 0.06 v 239.93 239.87 2.35	239.43 v
4+36.41 = PCC		7°54.2							
4+40		7°37.3'			C 0.23 v 238.56 238.79 3.43	38.06 v		C 0.04 239.06 239.10 3.12	238.56 v
4+20		7°16.52			F 0.04 v 237.57 237.55 4.67	37.09 v		C 0.21 238.09 238.30 v 3.92	237.57 v
4+00		6°55.74			C 0.10 v 236.62 236.72 5.50	36.12	36.29 v	36.62	C 0.18 237.12 237.30 4.92
		242.22				242.22			

236.06 T.P.

Merlin Drive Curb Grades

Grd. 27X-12

Chk Stake Lot #19

0.02
247.55
330 247.57

		C 5.14	C 2.48	C 1.37
6+34.86 Meas.	3°16.67'	242.25	245.43	247.37
~~6+35.61=P.I.C. Rel.~~	~~3°17.6~~	247.39	247.91	248.74
		3.48	2.96	2.13
		#4	#3	#2
		E.C. on Broadway		
6+25	3°05.92'			
6+00	2°38.35'			
5+75	2°10.78'			
5+50	1°43.2			
5+25	1°15.64'			
	250.87			

	Lt Gutter	Rt. Elev. Gutter
C 0.68	F 0.46	Gut.
248.11	248.04=cb	247.54 247.71=Sub.
248.79	247.58	248.04
208	3.29	48.53
#1		C 0.49
	F 0.49	Gut.
	247.56=cb	247.06' 247.56
	247.07'	48.10
	3.80	C 0.54
	C 0.21	C 0.69
	246.34	245.84' 246.01=Sub. 246.34=Gut.
	246.55'	47.03
	4.32	
	C 0.27	C 0.67
	245.13	44.63' 245.13
	245.40	45.92
	5.47	244.55=TP
	F 0.01	C 0.64
	243.91	43.41' 43.58=Sub. 243.91
	243.90	44.55
	6.97	
	F 0.09	C 0.49
	242.70	42.20' 242.70
	242.61	43.19
	8.26	
	250.87	

℄ Street. ℄ Station			Elev. Stakes	West side El. Curb
1+00	1°44'	5.23	256.16	256.38
0+75	1°18'	6.19	255.20	255.40
0+50	0°52'	7.25	254.14	254.43
			℄R=1654.4	
			Δ=11°31'43"	
			℄L=332.89	
0+25	0°26'	7.95	253.44	253.45
		8.60	252.79	252.97

0+00=B.C. = P.R.C. curb R on Lt.=N.W. Cor. Brooklyn

T.P.	11.53	261.39	1.01	249.86	Spk. in Pole on Lt. 6+00
		250.87			

	Lt. Cut.	℄	Rt. Cut.
F 0.22	255.88	56.0 = Sub.	C 0.77 / 257.15 / 256.38
F 0.20	259.90		C 0.92 / 256.32 / 255.40 — 256.32 T.P.
F 0.29	253.93	54.1 = Sub.	C 0.78 / 255.21 / 254.43 = Cut. — 254.2
F 0.01	252.95		C 0.69 / 253.45 = Cut. / 254.14 = Sub. / 252.41 — C 0.62 = Cut.
C 0.32	251.27		



Curb Grades – Merlin Drive on northerly side

℄ Merlin Stations					Elev. North curb
4+60.68		3°23.86'	6.69	272.05	271.41
4+40.68		2°51.96'	7.89	270.85	270.45
4+20.68		2°20.06'	9.12	269.62	269.48
4+00.68		1°48.16'	9.98	268.76	268.52
3+80.68		1°16.26'	10.54	268.20	267.60
3+60.68		0°44.36'	11.95	266.79	266.68
3+40.68		0°12.46'	12.85	265.89	265.80
3+32.89		0°00			
3+3289-PCC	5°45.93		13.36	265.38	265.46
T.P.	12.96	278.74			
3+25	5°38'		7.53	265.78	265.15
3+00	5°12'		9.34	263.97	264.18
2+75	4°46'		10.19	263.12	263.20
2+50	4°20		11.09	262.22	262.23
T.P.	12.07	273.31			
2+25	3°54'		0.15	261.24	261.25
2+00	3°28'		1.05	260.34	260.28
1+75	3°02'		2.03	259.36	259.30
1+50	2°36'		3.03	258.36	258.33
1+25	2°10'		4.27	257.12	257.35
		261.39			

	Lt. Gut.	℄ Subgrade	Rt. Gut.	
			C 0.48	271.89 TP
			71.89	
C 0.64	270.91		271.41	
			C 0.45	
C 0.40	269.95		70.90	
			270.45	
			C 0.49	
C 0.14	268.98	69.15	69.97	
			269.48	
			C 0.32	
C 0.24	268.02		68.84	
			268.52	
			C 0.31	20.27 Lt.
C 0.60	267.10		67.91	19.73 Rt.
			267.60	
			C 0.49	
C 0.11	266.18	66.35	67.17	
			266.68	
			C 0.56	
C 009	265.30		66.36	
			265.80	
				7.91 Lt.
				7.69 Rt.
			C 0.55	
F 0.08	264.96		66.01	
			265.46	
			C 0.55	
C 0.63	264.65		65.70	
			265.15	
			C 0.68	
F 0.21	263.68	Sub. 63.85	64.86	
			264.18	263.92 TP
			C 0.72	
F 0.08	262.70		63.92	
			263.20	
			C 0.56	
F 0.01	261.73	Sub. 61.90	62.78	
			262.23	
			C 0.65	
F 0.01	260.75		61.90	
			261.25	
			C 0.60	
C 0.06	259.78	59.75 Sub.	60.88	
			260.28	
			C 0.61	
C 0.06	258.80		59.91	
			259.30	
			C 0.75	
C 0.03	257.83	Sub. 58.00	59.68	
			258.33	
			C 0.58	
F 0.23	256.85		57.93	
			257.35	

Merlin Drive

Stations = 25' South of N Line	Curb Grades		Elev. North Curb	Lt Gut		Rt Gut	
						C 3.34 286.32	
7+20.38 = Brk		6.91	283.73	282.98	C 0.75	283.00 = Fin.	282.98
6+91.23		8.15	282.49	281.92	C 0.57	Sub = 81.98 281.91 = Fin.	C 1.02 283.14 282.65
6+62.08 = Brk.		9.48	281.16	280.86	C 0.30	280.90 = Fin.	C 1.04 281.98 280.24
6+54.67 = E.C.	8°33.5'	9.90	280.74	280.70	C 0.04	280.65 Fin.	C 1.04 281.64 = Stake 280.60
6+45.68	8°19.12'	10.35	280.29	280.24	C 0.05	Sub. 79.71	C 0.87 81.11 280.24
6+25.68	7°47.22'	11.33	279.31	279.40	F 0.09	278.90	C 0.50 79.90 279.40
6+05.68	7°15.32'	11.86	278.78	278.51	C 0.27	278.01	C 0.53 79.10 278.51
T.P. 12.67	2.90 64						C 0.57
5+85.68 PVC	6°43.42'	0.77	277.97	277.55	C 0.42	277.05	78.12 277.55
5+65.68	6°11.52'	1.42	277.32	276.58	C 0.74	276.08	C 0.64 77.22 276.58
5+48.32		2.58					C 0.67
P.R.C. 2' Alley Rt. on Merlin	5°43.75'		276.16	275.72	C 0.44	275.22	76.39 275.72
B.C. 2' R on NE Alley Rt.		2.58	276.16	275.64	C 0.52	275.14	
			276.66		C 0.94		
N.E. Prop on Alley		~~3.96~~	~~274.78~~	275.72	~~F 0.94~~	275.22	
			274.81				
NW Prop Alley		~~5.06~~	~~273.68~~	274.77	~~F 1.09~~ C 0.04	274.27	
NW E.C. 2' R on Alley		3.49	275.25	274.69	C 0.56	274.19	
		3.49	275.25				C 0.71 75.28
5+24.73 = P.R.C. 2' cb R Alley	5°06.46'			274.57	C 0.68	274.07	274.57
							C 0.78 74.12
5+00.68	4°27.66	4.96	273.78	273.34	C 0.44	272.84	273.34
4+80.68	3°55.75'	5.70	273.04	272.37	C 0.67	Sub. 72.04 271.87	C 0.64 73.01 272.37
	278.74						

28397 Pipe SE Iona

281.11 T.P.

Merlin Drive Curb Grades

		col	Elev. North Curb	Lt. Gutter		Rt. Gutter	
	Broadway		282.13				
Chk S.W. B.P. 60th	8.50	282.14					
25 N	8.74	281.80					
10' N	8.31	282.33					
E.C. on East cb	8.03	282.61	282.60	✓	282.10		
10 +86.03 B.C. 10' cb R	7.71	282.93	282.88	C 0.05	282.38 (34)		
10+64.6 = Exist. Pav.						284.32 = Exist. Pav.	
10+61.80 opp SW cor. 60th	7.45	283.19	283.38	F 0.19	282.88	C 3.27 87.31 284.24	
10+64.6 = Pav. on Rt.							C 3.79 2880 284.06
10+51.72 = B.C.	7.20	283.44	283.50	F 0.06	283.00	284.06 = 10+31.72	
10+31.72			283.82		283.32	283.61	7.85 → C 3.02
10+11.72 = Brk	6.41	284.23	284.13	C 0.10	283.63	C 4.79 89.33 284.83	
9+76.28	5.60	285.04	284.68	C 0.36	284.18	84.53	C 3.29 88.53 285.04
9+40.85 = E.V.C.	5.28	285.36	285.24	C 0.12	284.74		C 2.79 88.49 285.24
9+20.85	5.30	285.34	285.50	F 0.16	285.00	85.17	C 2.80 88.47 285.50
9+00.85	5.24	285.40	285.67	F 0.27	285.17		C 2.77 88.50 285.67
8+80.85 Vertex	5.27	285.37	285.73	F 0.36	285.23		C 2.79 88.47 285.73
8+60.85	5.30	285.34	285.68	F 0.34	285.18	85.35	C 3.14 88.68 285.68
8+40.85	5.68	284.96	285.54	F 0.58	285.04		C 3.66 88.96 285.54
8+20.85	5.62	285.02	285.30	F 0.28	284.80		285.30 3' Back
8+00.85	5.83	284.81	284.95	F 0.14	284.45	84.62	C 3.17 88.12 284.95 1' Back
7+80.85 = P.V.C.	5.97	284.67	284.50	C 0.17	284.00		C 3.26 87.76 284.50 2' Back
7+50.61 ✓	6.42	284.22	283.74	C 0.48	283.24	83.41	C 3.44 87.18 283.74 2' Back

2.9064

Merlin Drive - Curb Grades

4 = E.C. on Merlin		5.60	213.80	213.58	C 0.22
3	NE Return	6.09	213.31	212.74	C 0.57
2	NE Return	5.84	213.56	212.12	C 1.44
1	NE Return	3.87	215.53	211.77	C 3.76
B.C. on Kenwood		3.86	215.54	211.70	C 3.84
4 = E.C. on Merlin		5.53	213.87	212.99	C 0.88
3	NW Ret.	5.92	213.48	212.19	C 1.29
2	NW Ret.	5.56	213.84	211.38	C 2.46
1	NW Ret.	5.47	213.93	210.57	C 3.36
B.C. on Kenwood		5.58	213.82	209.76	C 4.06
	9.38	219.40		210.02	BM Top Ch.

Merlin Drive ~ Curbs | NDEVED
Alignment. ~~

AUG 8 1951

Walker
Pope
Clark
Huffman
6-1-51

Grades Page 57-65

Note: Stakes in Intersection set to Subgrade 0.33 below finish grades that are shown



Merlin Drive — Curbs
Alignment

Grades P-57-65



Merlin Drive - Curbs - Alignment



Merbis Drive ~ Curbs
Alignment



Merlin Drive ~ Curbs
Alignment



Merlin Drive ~ Curb Alignment

Grades P-57-65

LOT 1-20 BLK. 3 ADD. Emerald Hills
OWNER A.G. & H.W. SNYDER
CONTR. CAMERON BROS.
PERMIT NO. 40635

LOT 1-7 BLK. 1 ADD. Emerald Hills
OWNER A.G. & H.W. Snyder
CONTR. Cameron Bros.
PERMIT NO. 40636

LOT 1-12 BLK. 2 ADD. Emerald Hills
OWNER A.G. & H.W. SNY
CONTR. Cameron Bros.
PERMIT NO. 40633



INDEXED
AUG 8 1951

Merlin Drive
Paving Grades at Brooklyn Ave

Grades shown are Finish Paving.

Stakes set to Subgrade 0.33' below Elev. that are shown.

Mother
pope
clark
Huffman
6-14-51

(Grades from onion Profile by Remington)



Curb Grades - Returns

Beech & Felton

Walker
Pope
Clark
Huffman
8-7-51

W.O. 20008

(Plan 4184-B)

RECEIVED
AUG 8 1951





		Cl	F 0.52	F 0.32
	Exist=215.93	216.16	215.88	216.68
NW	B.C ~~216.00~~	216.08	216.40	217.00=F.C.
		.05		

		F 0.93	F 0.87	F 0.60
	Exist. Gr	214.97	215.03	215.90
SW	=215.00	215.40	215.90	216.50

BM 219.59

Roberts
cote
Moore
Patten
Aug 22, 1951
W.B. 20007

Grade Stakes Curb Lots 3 & 4 Blk 9
Seaman & Choate ADD.
Profile 1567 T.R. 9 pg 19

214.01

214.98 Stake

Nly End Lot 3

215.19 Stake

Lot 3 & 4

Blk

Sly End Lot 4 Exist

214.96

BM 219.49 NE BP 28th & Cedar

CURB GRADES - NOYES ST.

Between Ingraham & Felspar

Walker
Huffman
Kettle
10-3-51

INDEXED
Pews
OCT 4 1951

	Fill To Walk F. side	Elev. Back Walk	Elev. Stakes	Elev. Curb	Fill To Top Cb.
Prop line at Alley		63.61	63.43	64.05	F0.62
E.C. 3'R	F0.69	63.97	63.21	63.88	F0.67
1+21.85 = B.C. 3'R		63.90	63.21	63.81	F0.60
1+00	F0.74	63.62	62.88	63.48	F0.60
0+75	F0.53	63.29	62.76	63.11	F0.35
0+50	F0.60	62.96	62.36	62.74	F0.38
0+25	F0.62	62.63	62.01	62.37	F0.36
0+00 = N.K. Garnet		62.27 Exist Walk	61.76	62.00 61.90 = Exist cb	F0.24
S.W. & N.W. Cor. Garnet & Noyes office Record				62.02	



Clark
Shephard
Brunner
Bryson

5-1-52
W.O. 20007

Sidewalk Grades LOT 101
1294 - Morena Blvd

AS per F.B. 1048 - 1749
MAP Blvd. Gardens - 1505



RECEIVED
LAW
MAY 7 1952

Grades set for inside edge walk

Blvd. Gardens

77

Check: 20.98 = 21.00 = Elev Hub Sta. 14+03.94
℄ Viola + 17' W℄ Morena
Blvd. AS per F.B. 1791-28

LOT 101 BLK. — ADD. Blvd. Gardens
OWNER C. E. Briendenne
JOINER R. O. Phillips
PERMIT NO. 72469

0+77.76	21.11 Rod 21.32 Elev. F 0.21	
0+61.16	21.30 Rod 21.24 Elev. C 0.06	
0+44.56	21.16 Rod 21.15 Elev. C 0.01	
0+22.28	20.92 Rod 21.05 Elev. F 0.13	
0+00 =	20.93 Rod 20.94 Elev Frontedge WALK F 0.01	

Direct elev. Rod: 18.80 = ℄ ☐ Dorcas
℄ Morena Blvd.

DIETZGEN'S RAILROAD CURVE AND REDUCTION TABLES

Copyright, 1914, by Eugene Dietzgen Co., New York City



CURVE FORMULAS

Radius=R=$\frac{50}{\sin. D/2}$ (1) Degree of Curve=D and sin. $\frac{D}{2}=\frac{50}{R}$ (2)

Tangent=T=Rtan$\frac{\triangle}{2}$ (3) Length of Curve=L=100$\frac{\triangle}{D}$ (4)

Middle ordinate=M=R(1—cos. $\frac{\triangle}{2}$) (5)=Rvers $\frac{\triangle}{2}$ (6)

External=E=Ttan$\frac{\triangle}{4}$-(7)=R ÷ cos.$\frac{\triangle}{2}$—R(8)=Rexsec$\frac{\triangle}{2}$(9)

Long Chord=C=2 R sin.$\frac{\triangle}{2}$ (10) △=Central Angle

EXPLANATION AND USE OF TABLES

Stations.—Given P. I.=Sta. 161+60.35 to find Sta. of P. C. and P. T. △=62° 10′ D=8° 20′. From Table IV for 1° curve T=3454.1 and ÷8⅓=414.49 ft. From Table V correction=.36 or T=414.85 ft. P. C.=Sta. P.I.—T=157 +45.50. Also from (4) L=746.00 and P. T.=Sta. P. C.+L=164+91.50.

Offsets.—Tangent offsets vary (approximately) directly with D and with square of the distance. Thus tangent offset for Sta. 158 on above curve is 2.16 ft. found as follows. From Table III tangent offset for 100 ft.=7.27 ft. Distance=158—Sta. P. C.=54.50, hence offset=7.27 $(54.50 \div 100)^2$=2.16 ft. Also square of any distance divided by twice the radius equals (approximately) the distance from tangent to curve. Thus $(54.50)^2 \div (2 \times 688.26)$=2.16 ft.

Deflections.—Deflection angle=½ D for 100 ft., ¼ D for 50 ft., etc. For c ft.=(in minutes) .3 x C x D° or=defl. for 1 ft. from Table III x C. For Sta. 158 of above curve=.3 x 54.5 x 8⅓=136.2′ or 2° 16.2′, or=2.50 x 54.5=136.2′ from Table III. For Sta. 159 deflection angle=2° 16.2′ +8° 20′ ÷2=6° 26.2′, etc.

Externals.—May be found in similar manner to tangents. Thus E for curve above is 115.37. For from Table IV for 1° curve E=960.6 for 8° 20′=960.6 ÷8⅓=115.27 and from Table V correction=.10 or E=115.37 ft. Or suppose △=32° and E is measured and found to be 42 ft. What is D? From Table IV E=230.9 and ÷42=5.5 or D=5° 30′.

28203



DISTANCES FROM CENTER OF ROADWAY FOR CROSS-SECTIONING.

Roadway 16 feet wide. Side Slopes 1 on 1½

For Single Track Embankment.

H	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	H
0	8.0	8.2	8.3	8.5	8.6	8.8	8.9	9.1	9.2	9.4	0
1	9.5	9.7	9.8	10.0	10.1	10.3	10.4	10.6	10.7	10.9	1
2	11.0	11.2	11.3	11.5	11.6	11.8	11.9	12.1	12.2	12.4	2
3	12.5	12.7	12.8	13.0	13.1	13.3	13.4	13.6	13.7	13.9	3
4	14.0	14.2	14.3	14.5	14.6	14.8	14.9	15.1	15.2	15.4	4
5	15.5	15.7	15.8	16.0	16.1	16.3	16.4	16.6	16.7	16.9	5
6	17.0	17.2	17.3	17.5	17.6	17.8	17.9	18.1	18.2	18.4	6
7	18.5	18.7	18.8	19.0	19.1	19.3	19.4	19.6	19.7	19.9	7
8	20.0	20.2	20.3	20.5	20.6	20.8	20.9	21.1	21.2	21.4	8
9	21.5	21.7	21.8	22.0	22.1	22.3	22.4	22.6	22.7	22.9	9
10	23.0	23.2	23.3	23.5	23.6	23.8	23.9	24.1	24.2	24.4	10
11	24.5	24.7	24.8	25.0	25.1	25.3	25.4	25.6	25.7	25.9	11
12	26.0	26.2	26.3	26.5	26.6	26.8	26.9	27.1	27.2	27.4	12
13	27.5	27.7	27.8	28.0	28.1	28.3	28.4	28.6	28.7	28.9	13
14	29.0	29.2	29.3	29.5	29.6	29.8	29.9	30.1	30.2	30.4	14
15	30.5	30.7	30.8	31.0	31.1	31.3	31.4	31.6	31.7	31.9	15
16	32.0	32.2	32.3	32.5	32.6	32.8	32.9	33.1	33.2	33.4	16
17	33.5	33.7	33.8	34.0	34.1	34.3	34.4	34.6	34.7	34.9	17
18	35.0	35.2	35.3	35.5	35.6	35.8	35.9	36.1	36.2	36.4	18
19	36.5	36.7	36.8	37.0	37.1	37.3	37.4	37.6	37.7	37.9	19
20	38.0	38.2	38.3	38.5	38.6	38.8	38.9	39.1	39.2	39.4	20
21	39.5	39.7	39.8	40.0	40.1	40.3	40.4	40.6	40.7	40.9	21
22	41.0	41.2	41.3	41.5	41.6	41.8	41.9	42.1	42.2	42.4	22
23	42.5	42.7	42.8	43.0	43.1	43.3	43.4	43.6	43.7	43.9	23
24	44.0	44.2	44.3	44.5	44.6	44.8	44.9	45.1	45.2	45.4	24
25	45.5	45.7	45.8	46.0	46.1	46.3	46.4	46.6	46.7	46.9	25
26	47.0	47.2	47.3	47.5	47.6	47.8	47.9	48.1	48.2	48.4	26
27	48.5	48.7	48.8	49.0	49.1	49.3	49.4	49.6	49.7	49.9	27
28	50.0	50.2	50.3	50.5	50.6	50.8	50.9	51.1	51.2	51.4	28
29	51.5	51.7	51.8	52.0	52.1	52.3	52.4	52.6	52.7	52.9	29
30	53.0	53.2	53.3	53.5	53.6	53.8	53.9	54.1	54.2	54.4	30
31	54.5	54.7	54.8	55.0	55.1	55.3	55.4	55.6	55.7	55.9	31
32	56.0	56.2	56.3	56.5	56.6	56.8	56.9	57.1	57.2	57.4	32
33	57.5	57.7	57.8	58.0	58.1	58.3	58.4	58.6	58.7	58.9	33
34	59.0	59.2	59.3	59.5	59.6	59.8	59.9	60.1	60.2	60.4	34
35	60.5	60.7	60.8	61.0	61.1	61.3	61.4	61.6	61.7	61.9	35
36	62.0	62.2	62.3	62.5	62.6	62.8	62.9	63.1	63.2	63.4	36
37	63.5	63.7	63.8	64.0	64.1	64.3	64.4	64.6	64.7	64.9	37
38	65.0	65.2	65.3	65.5	65.6	65.8	65.9	66.1	66.2	66.4	38
39	66.5	66.7	66.8	67.0	67.1	67.3	67.4	67.6	67.7	67.9	39
40	68.0	68.2	68.3	68.5	68.6	68.8	68.9	69.1	69.2	69.4	40

Example—If point is 22.6 ft. above grade, how far should it be from center line to be a slope stake point? Ans. from Table 41.9. For same slopes but other widths of roadbed correct above figures by one-half difference in width of roadbed; thus in example above for 20 ft. roadbed distance will be 41.9+(20—16)÷2 or 2 ft. added to 41.9 = 43.9. For slopes of 1 on 1 see inside of front cover.

MADE IN U.S.A.