



NOTES:

1. SOLVENT WELD FITTINGS SHALL BE PVC SCHEDULE 40.
2. THREADED FITTINGS AND NIPPLES SHALL BE PVC SCHEDULE 80.
3. TEFLON TAPE SHALL BE USED ON THREADED CONNECTIONS.
4. CLOSE NIPPLES SHALL NOT BE USED.
5. AN ANTI-DRAIN VALVE SHALL BE INSTALLED UNDER ANY SPRINKLER HEAD THAT DOES NOT CONTAIN AN INTEGRAL ANTI-DRAIN VALVE.
6. LATERAL DEPTH SHALL BE 18" WHEN 12" POP-UP BODIES ARE USED.
7. MAINTAIN 3" MAXIMUM DISTANCE FROM POP-UP HEAD TO PAVEMENT OR CURB UNLESS OTHERWISE NOTED ON PLANS.

SHOW A NUMBER TO INDICATE TYPE HEAD

REVISION	BY	APPROVED	DATE
ORIGINAL*	RH	J. NAGELVOORT	01/12
REDRAFTED	CD	J. NAGELVOORT	09/18
UPDATED	AJ	J. NAGELVOORT	09/21

CITY OF SAN DIEGO – STANDARD DRAWING

**ROTOR, SPRAY, OR BUBBLER
POP-UP HEAD**

RECOMMENDED BY THE CITY
OF SAN DIEGO STANDARDS COMMITTEE

Alaine L. James 09/30/21
COORDINATOR R.C.E. 81047 DATE

DRAWING NUMBER **SDI-103**