



**NOTES:**

1. FOR BUBBLER LOCATION, REFER TO TREE PLANTING AND STAKING DRAWING.
2. EACH TREE SHALL HAVE A 2" POP-UP HEAD WITH BUBBLER NOZZLE **PER SDI-103**, AND A FIXED BUBBLER NOZZLE IN A PERFORATED PIPE.
3. THREADED FITTINGS AND NIPPLES SHALL BE PVC SCHEDULE 80.
4. SOLVENT WELD FITTINGS SHALL BE PVC SCHEDULE 40.
5. TEFLON TAPE SHALL BE USED ON THREADED CONNECTIONS.
6. CLOSE NIPPLES SHALL NOT BE USED.
7. ANTI-DRAIN VALVES SHALL BE INSTALLED UNDER ALL HEADS.

REVISION	BY	APPROVED	DATE	CITY OF SAN DIEGO – STANDARD DRAWING	RECOMMENDED BY THE CITY OF SAN DIEGO STANDARDS COMMITTEE
ORIGINAL*	RH	J. NAGELVOORT	01/12		<b>TREE BUBBLER TUBE</b>
REDRAFTED	CD	J. NAGELVOORT	0918	COORDINATOR R.C.E. 81047	
UPDATED	AJ	J. NAGELVOORT	0921	DATE	
					DRAWING NUMBER <b>SDI-104</b>