

NOTES:

- 1. ALL PIPES, NIPPLES, AND FITTINGS AFTER MALE ADAPTER SHALL BE RED BRASS.
- 2. VALVE AND CONTROLLER IDENTIFICATION SHALL BE LABELED OUTSIDE ON THE VALVE BOX LID AND TAGGED INSIDE THE BOX ON THE VALVE.
- 3. TEFLON TAPE SHALL BE USED ON THREADED CONNECTIONS.
- 4. BRASS COUPLING, GLOBE VALVE AND FITTINGS SHALL BE THE SAME SIZE AS THE LARGEST VALVE ON THE MANIFOLD. USE REDUCERS AS REQUIRED WHEN DOWNLINE VALVES ARE SMALLER.

UPDATED	AJ	J. NAGELVOORT	09/21	REMOTE CONTROL VALVE MANIFOLD ASSEMBLY WITH BRASS PIPE	Haine COORDINATO	- 17
		J. NAGELVOORT	09/18		Alaine	L James 09/30/21
ORIGINAL*	RH	J. NAGELVOORT	01/12	CITY OF SAN DIEGO – STANDARD DRAWING	OF SAN DIEGO STANDARDS COMMITTEE	
REVISION	BY	APPROVED	DATE	OITY OF CAN DIFOC CTANDARD PRAINING	RECOMMENDED BY THE CITY	