

NOTES:

- 1. ALL FOOTINGS SHALL BE 520-C-2500 CONCRETE.
- 2. THE FOLLOWING ITEMS SHALL BE FURNISHED AND INSTALLED ONLY WHEN SHOWN ON THE PLANS OR CALLED FOR IN THE SPECIAL PROVISIONS:

 A. BARBED WIRE
 - B. EXTENSION ARM
- 3. CHAIN LINK FENCE SHALL CONFORM TO THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION UNLESS SPECIFICALLY NOTED ON THIS DRAWING.
- 4. CHAIN LINK FENCE AND ALL FITTINGS SHALL BE 22 MIL PRESSURE-BONDED, OR 7 MIL THERMALLY-FUSED VINYL COATED, OVER 9 GAUGE ALUMINIZED STEEL CORE FABRIC, PRIOR TO COATING. POSTS AND RAILS SHALL BE GALVANIZED STEEL PVC VINYL BONDED, 10–14 MIL (COLOR SHALL MATCH FABRIC).
- 5. CHAIN LINK FABRIC SHALL HAVE KNUCKLED FINISH ON TOP EDGE.
- 6. THE FOLLOWING SHALL BE NOTED ON PLANS OR SPECIFICATIONS:

A. COLOR OF FENCE AND FITTINGS

- B. MATERIAL AND FITTING STEEL CLASS: 1 OR 1A
- C. WIRE CLASS: 1 OR 1A
- 7. SEE M-20 FOR ADDITIONAL DETAILS.

LEGEND ON PLANS

-x-o-x-x-o-x

		T				T DECOMMENDED DV	THE OTTY OF (AN DIEGO
\vdash	REVISION	BY	APPROVED	DATE	CITY OF SAN DIEGO – STANDARD DRAWING	RECOMMENDED BY THE CITY OF SAN DIEGO STANDARDS COMMITTEE		
	ORIGINAL		J.P. CASEY	06/92	CITI OF SAN BILGO - STANDARD BRAWING	CAtung	×20	
	UPDATE	KA	J. NAGELVOORT	01/12		COORDINATOR		11/20/2017 DATE
	UPDATE	НМ	J. NAGELVOORT	02/16	VINYL COATED CHAIN LINK FENCE	Section Williams The Financial States		- D/112
	UPDATE	НМ	J. NAGELVOORT	11/17	VIII CONTIDUINTI LITTE	DRAWING S	DM-112	
						NUMBER		