



NOTES:

1. IRREGULARITIES ON THE CONCRETE SURFACE OF THE EXISTING/PROPOSED SIDEWALK OR EXTENDED CURB, TO WHICH THE GEOMEMBRANE IS TO BE ATTACHED, SHALL BE REMOVED PRIOR TO INSTALLATION.
2. IF IRREGULARITIES (I.E., SHARP PROTRUSIONS EXCEEDING 1/2 INCH FROM SURFACE FACE) CAN NOT BE REMOVED FROM AN EXISTING SAW-CUT OR FORMED STRUCTURE, A PROTECTIVE GEOTEXTILE LAYER SHOULD BE PLACED BETWEEN THE SURFACE AND THE GEOMEMBRANE WITHIN VICINITY OF PROTRUSIONS.
3. REFER TO PLANS FOR VERTICAL DIMENSIONS OF BIOFILTRATION COMPONENTS.
4. SUBMIT GEOTEXTILE MANUFACTURER'S INSTALLATION RECOMMENDATIONS TO ENGINEER FOR APPROVAL.

REVISION	BY	APPROVED	DATE	CITY OF SAN DIEGO – STANDARD DRAWING	RECOMMENDED BY THE CITY OF SAN DIEGO STANDARDS COMMITTEE
ORIGINAL	CG	J.NAGELVOORT	06 /18		<i>Chung</i> 06/05/2018 COORDINATOR R.C.E. 56523 DATE
				VERTICAL PVC LINER ATTACHMENT	DRAWING NUMBER SDSW-104